

EventGrid

API Reference

Issue	01
Date	2025-12-18



Copyright © Huawei Cloud Computing Technologies Co., Ltd. 2025. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Cloud Computing Technologies Co., Ltd.

Trademarks and Permissions



HUAWEI and other Huawei trademarks are the property of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei Cloud and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Cloud Computing Technologies Co., Ltd.

Address: Huawei Cloud Data Center Jiaoxinggong Road
Qianzhong Avenue
Gui'an New District
Gui Zhou 550029
People's Republic of China

Website: <https://www.huaweicloud.com/intl/en-us/>

Contents

1 Before You Start.....

2 API Overview.....

3 Calling APIs.....

3.1 Making an API Request.....

3.2 Performing Authentication.....

3.3 Checking the Response.....

4 Getting Started.....

5 APIs.....

5.1 Event Subscription Management.....

5.1.1 Creating an Event Subscription.....

5.1.2 Obtaining the Event Subscription List.....

5.1.3 Updating an Event Subscription.....

5.1.4 Obtaining Event Subscription Details.....

5.1.5 Deleting an Event Subscription.....

5.1.6 Updating an Event Subscription Source.....

5.1.7 Creating an Event Subscription Target.....

5.1.8 Updating an Event Subscription Target.....

5.1.9 Obtaining Event Subscription Target Details.....

5.1.10 Deleting an Event Subscription Target.....

5.1.11 Enabling or Disabling Event Subscriptions.....

5.2 Event Channel Management.....

5.2.1 Creating a Custom Event Channel.....

5.2.2 Obtaining the Event Channel List.....

5.2.3 Updating a Custom Event Channel.....

5.2.4 Obtaining Event Channel Details.....

5.2.5 Deleting a Custom Event Channel.....

5.3 Event Management.....

5.3.1 Viewing Event Trace Details.....

5.3.2 Obtaining Sent Message Content.....

5.3.3 Obtaining the Event Trace List.....

5.3.4 Publishing an Event to an Event Channel.....

5.3.5 Publishing an Official Event to an Event Channel.....

1

3

5

5

8

9

11

12

12

12

27

35

49

56

58

61

72

83

89

91

93

93

97

100

103

105

107

107

111

112

115

118

5.3.6 Prechecking Event Publishing Status.....	122
5.4 Event Source Management.....	125
5.4.1 Creating a Custom Event Source.....	125
5.4.2 Obtaining the Event Source List.....	129
5.4.3 Updating a Custom Event Source.....	132
5.4.4 Obtaining Event Source Details.....	136
5.4.5 Deleting a Custom Event Source.....	139
5.5 Event Target Catalog Management.....	140
5.5.1 Obtaining the Event Target Catalog.....	140
5.6 Event Schema Management.....	143
5.6.1 Starting Automatic Event Schema Discovery.....	144
5.6.2 Creating a Custom Event Schema.....	146
5.6.3 Obtaining the Event Schema List.....	149
5.6.4 Updating a Custom Event Schema.....	152
5.6.5 Obtaining Event Schema Details.....	155
5.6.6 Deleting an Event Schema.....	157
5.6.7 Creating a Custom Event Schema Version.....	158
5.6.8 Obtaining the Event Schema Version List.....	161
5.6.9 Obtaining Event Schema Version Details.....	163
5.6.10 Deleting an Event Schema Version.....	165
5.7 Connection Management.....	166
5.7.1 Creating a Connection.....	166
5.7.2 Obtaining the Connection List.....	175
5.7.3 Updating a Connection.....	180
5.7.4 Obtaining Connection Details.....	187
5.7.5 Deleting a Connection.....	191
5.8 Service Agency Management.....	193
5.8.1 Obtaining the Service Agency List.....	193
5.8.2 Creating a Service Agency.....	195
5.9 Quota Management.....	196
5.9.1 Obtaining the Quota.....	196
5.10 API Version Management.....	199
5.10.1 Obtaining the API Version List.....	199
5.11 Trigger Management.....	201
5.11.1 Obtaining the EG Trigger of a Function.....	201
5.11.2 Obtaining the EG Trigger of a Function Flow.....	209
5.12 Endpoint Management.....	216
5.12.1 Updating an Endpoint.....	216
5.12.2 Deleting an Endpoint.....	219
5.12.3 Creating an Endpoint.....	220
5.12.4 Obtaining the Endpoint List.....	224
5.13 OBS Bucket Management.....	227

5.13.1 Obtaining the OBS Bucket List.....	227
5.13.2 Refurbishing OBS.....	230
5.14 Event Stream Management.....	238
5.14.1 Creating an Event Stream.....	238
5.14.2 Obtaining the Event Stream List.....	250
5.14.3 Updating an Event Stream.....	259
5.14.4 Obtaining Event Stream Details.....	270
5.14.5 Deleting an Event Stream.....	279
5.14.6 Starting/Stopping an Event Stream.....	280
5.15 Event Example Management.....	282
5.15.1 Obtaining the Event Example List.....	283
5.16 Professional Event Stream Job Management.....	285
5.16.1 Create a Professional Event Stream Job.....	285
5.16.2 Querying Professional Event Stream Jobs.....	301
5.16.3 Deleting a Professional Event Stream Job.....	310
5.16.4 Querying Details About a Professional Event Stream Job.....	312
5.16.5 Updating a Professional Event Stream Job.....	320
5.16.6 Performing Operations on a Professional Event Stream Job.....	336
5.16.7 Verifying Professional Event Stream Jobs.....	339
5.16.8 Querying the Synchronization Status of a Professional Event Job.....	344
5.17 Professional Event Stream Cluster Management.....	350
5.17.1 Querying AZs of a Professional Event Stream Cluster.....	350
5.17.2 Creating a Professional Event Stream Cluster.....	351
5.17.3 Querying the Professional Event Stream Clusters.....	355
5.17.4 Deleting a Professional Event Stream Cluster.....	358
5.17.5 Querying Details about a Professional Event Stream Cluster.....	360
5.17.6 Updating a Professional Event Stream Cluster.....	362
6 Permissions Policies and Supported Actions.....	366
7 Appendix.....	370
7.1 Status Codes.....	370
7.2 Error Codes.....	373
7.3 Obtaining a Project ID.....	376
7.4 Obtaining the Account Name and Account ID.....	377
8 Description.....	378

1 Before You Start

Welcome to EventGrid (EG)

EventGrid (EG) is a serverless event bus service for standard and centralized access of Huawei Cloud services and custom or SaaS applications. You can build a loosely coupled, distributed event-driven architecture to flexibly route events via CloudEvents.

This document provides API descriptions, syntax, parameters, and examples of EG.

EG supports Representational State Transfer (REST) APIs, allowing you to call APIs using HTTPS. For details about API calling, see [Calling APIs](#).

Constraints

- EG is continuously upgraded with new functions, and the existing APIs may be adjusted. For example, new response parameters may be added. To reduce the impact of API changes, EG is backward compatible with APIs when possible. However, when you use EG, you should accept and ignore unused parameters and parameter values in returned content (in JSON format).
- The number of EG resources that you can create is determined by your quotas. To increase your quotas, see [My Quotas](#).
- For more constraints, see API description.

Endpoints


An endpoint is the **request address** for calling an API. Endpoints vary depending on services and regions. For the endpoints of all services, see [Regions and Endpoints](#).

Concepts

- Account
An account is created upon successful registration and has full access permissions for all of its cloud services and resources. It can be used to reset user passwords and grant user permissions. The account is a payment entity and should not be used directly to perform routine management. For security purposes, create IAM users and grant them permissions for routine management.

- **User**
An IAM user is created using an account to use cloud services. Each IAM user has their own identity credentials (password and access keys).
The account name, username, and password will be required for API authentication.
- **Region**: A region is a geographic area in which cloud resources are deployed. Availability zones (AZs) in the same region can communicate with each other over an intranet, while AZs in different regions are isolated from each other. Deploying cloud resources in different regions can better suit certain user requirements or comply with local laws or regulations.
- **AZ**: An AZ contains one or more physical data centers. Each AZ has independent cooling, fire extinguishing, moisture-proof, and electricity facilities. Within an AZ, compute, network, storage, and other resources are logically divided into multiple clusters. AZs within a region are interconnected using high-speed optical fibers to allow you to build cross-AZ high-availability systems.
- **Project**
A project corresponds to a region. Projects are preset by the system and have physically isolated resources (including compute, storage, and network resources) across regions. Users can be granted permissions in a default project to access all resources in the region associated with the project. If you need more refined access control, create subprojects under a default project and create resources in subprojects. Then you can assign users the permissions required to access only the resources in the specific subprojects.

Figure 1-1 Project isolation model



- **Enterprise project**
Enterprise projects group and manage resources across regions. Resources in enterprise projects are logically isolated. An enterprise project can contain resources in multiple regions, and resources can be directly transferred between enterprise projects.
For details about how to obtain enterprise project IDs and features, see the [Enterprise Management User Guide](#).

2 API Overview

Table 2-1 describes the EG APIs.

Table 2-1 API overview

API	Description
Event Subscription Management	Create, update, delete, and enable/disable event subscriptions, query the event subscription list and details, and update event subscription sources. Create, update, delete, and query event subscription targets.
Event Channel Management	Create, update, and delete custom event channels, and query the event channel list and details.
Event Management	Publish an event to an event channel and precheck the event publishing status.
Event Source Management	Create, update, and delete custom event sources, and query the event source list and details.
Event Target Catalog Management	Query event target catalogs.
Connection Management	Create, update, and delete connections, and query the connection list and details.
Service Agency Management	Query and create service agencies.
Quota Management	Query quotas.
API Version Management	Obtain the API version list.
Trigger Management	Query the EG trigger of a function or a function flow.

API	Description
Endpoint Management	Update, delete, create, and query access endpoints.
OBS Bucket Management	Obtain the OBS bucket list.
Event Example Management	Obtain the event example list.

3 Calling APIs

3.1 Making an API Request

This section describes the structure of a REST API request, and uses the IAM API for [obtaining a user token](#) as an example to demonstrate how to call an API. The obtained token can then be used to authenticate the calling of other APIs.

Request URI

A request URI is in the following format:

{URI-scheme} :// {Endpoint} / {resource-path} ? {query-string}

Although a request URI is included in the request header, most programming languages or frameworks require the request URI to be transmitted separately.


- **URI-scheme:**
Protocol used to transmit requests. All APIs use **HTTPS**.
- **Endpoint:**
Domain name or IP address of the server bearing the REST service. The endpoint varies between services in different regions. It can be obtained from [Regions and Endpoints](#).
For example, the endpoint of IAM in the **CN-Hong Kong** region is **iam.ap-southeast-1.myhuaweicloud.com**.
- **resource-path:**
Access path of an API for performing a specified operation. Obtain the path from the URI of an API. For example, the **resource-path** of the API used to obtain a user token is **/v3/auth/tokens**.
- **query-string:**
Query parameter, which is optional. Ensure that a question mark (?) is included before each query parameter that is in the format of "*Parameter name=Parameter value*". For example, **?limit=10** indicates that a maximum of 10 data records will be displayed.

For example, to obtain an IAM token in the **CN North-Beijing1** region, obtain the endpoint of IAM (**iam.cn-north-1.myhuaweicloud.com**) for this region and the

resource-path (/v3/auth/tokens) in the URI of the API used to **obtain a user token**. Then, construct the URI as follows:

```
https://iam.cn-north-1.myhuaweicloud.com/v3/auth/tokens
```

Figure 3-1 Example URI



NOTE

To simplify the URI display, each API is provided only with a **resource-path** and a request method. The **URI-scheme** of all APIs is **HTTPS**, and the endpoints of all APIs in the same region are identical.

Request Methods

The HTTP protocol defines the following request methods that can be used to send a request to the server:

- **GET**: requests a server to return specified resources.
- **PUT**: requests a server to update specified resources.
- **POST**: requests a server to add resources or perform special operations.
- **DELETE**: requests a server to delete specified resources, for example, to delete an object.
- **HEAD**: requests a server resource header.
- **PATCH**: requests a server to update a part of a specified resource. If the resource does not exist, a new resource will be created.

For example, in the case of the API used to **obtain a user token**, the request method is **POST**. The request is as follows:

```
POST https://iam.ap-southeast-1.myhuaweicloud.com/v3/auth/tokens
```

Request Header

You can also add additional header fields to a request, such as the fields required by a specified URI or HTTP method. For example, to request for the authentication information, add **Content-Type**, which specifies the request body type.

Common request headers are as follows:

- **Content-Type**: specifies the request body type or format. This field is mandatory and its default value is **application/json**. Other values of this field will be provided for specific APIs if any.
- **X-Auth-Token**: specifies a user token only for token-based API authentication. The user token is a response to the API used to **obtain a user token**. This API is the only one that does not require authentication.

 NOTE

In addition to supporting token-based authentication, APIs also support authentication using access key ID/secret access key (AK/SK). During AK/SK authentication, an SDK is used to sign a request, and the **Authorization** (signature information) and **X-Sdk-Date** (time when the request is sent) header fields are automatically added to the request.

For details, see [AK/SK Authentication](#).

The API used to [obtain a user token](#) does not require authentication. Therefore, only the **Content-Type** field needs to be added to requests for calling the API. An example of such requests is as follows:

```
POST https://iam.ap-southeast-1.myhuaweicloud.com/v3/auth/tokens
Content-Type: application/json
```

Request Body

The body of a request is often sent in a structured format as specified in the **Content-Type** header field. The request body transfers content except the request header.

A request body varies between APIs. Some APIs do not require the request body, such as the APIs requested using the GET and DELETE methods.

In the case of the API used to [obtain a user token](#), the request parameters and parameter description can be obtained from the API request. The following provides an example request with a body included. Replace *username*, *domainname*, ******* (login password), and *xxxxxxxxxxxxxxxxxxxxxx* (project name) with the actual values (for example, **ap-southeast-1**). The project name can be obtained from [Regions and Endpoints](#).

 NOTE

The **scope** parameter specifies where a token takes effect. In the following example, the token takes effect only for the resources in a specified project. For more information about this API, see [Obtaining a User Token](#).

```
POST https://iam.ap-southeast-1.myhuaweicloud.com/v3/auth/tokens
Content-Type: application/json
```

```
{
  "auth": {
    "identity": {
      "methods": [
        "password"
      ],
      "password": {
        "user": {
          "name": "username",
          "password": "*****",
          "domain": {
            "name": "domainname"
          }
        }
      }
    },
    "scope": {
      "project": {
        "name": "xxxxxxxxxxxxxxxxxxxxxx"
      }
    }
  }
}
```

If all data required for the API request is available, you can send the request to call the API through curl, Postman, or coding. In the response to the API used to obtain a user token, **x-subject-token** is the desired user token. This token can then be used to authenticate the calling of other APIs.

3.2 Performing Authentication

You can use either of the following authentication methods when calling APIs:

- Token authentication: Requests are authenticated using tokens.
- AK/SK authentication: Requests are encrypted using an AK/SK. AK/SK authentication is recommended because it is more secure than token authentication.

Constraints

- AK/SK authentication supports API requests with a body not larger than 12 MB. For API requests with a larger body, token authentication is recommended.
- For AK/SK authentication, the signing SDK is only used for signing requests and is different from the SDKs provided by services.

Token Authentication

NOTE

A token is valid for 24 hours. If a token is required, the system caches the token to avoid frequent calling.

A token specifies temporary permissions in a computer system. During API authentication using a token, the token is added to request headers to get permissions for calling the API.

When calling an API to **obtain a user token**, you must set **auth.scope** in the request body to **project**.

```
{
  "auth": {
    "identity": {
      "methods": [
        "password"
      ],
      "password": {
        "user": {
          "name": "username",
          "password": "*****",
          "domain": {
            "name": "domainname"
          }
        }
      }
    },
    "scope": {
      "project": {
        "name": "xxxxxxx"
      }
    }
  }
}
```

After a token is obtained, the **X-Auth-Token** header field must be added to requests to specify the token when calling other APIs. For example, if the token is **ABCDEFJ....**, **X-Auth-Token: ABCDEFJ....** can be added to a request as follows:

```
POST https://iam.ap-southeast-1.myhuaweicloud.com/v3/auth/projects
Content-Type: application/json
X-Auth-Token: ABCDEFJ....
```

AK/SK Authentication

AK/SK is used to sign requests and the signature is then added to the request headers for authentication.

- AK: a unique identifier used in conjunction with an SK to sign requests cryptographically.
- SK: used with an AK to sign requests cryptographically. It identifies a request sender and prevents the request from being modified.

In AK/SK authentication, you can use an AK/SK to sign requests based on the signature algorithm or use the signing SDK to sign requests. For details about how to sign requests and use the signing SDK, see [API Request Signing Guide](#).

3.3 Checking the Response

Status Code

After sending a request, you will receive a response, including a status code, response header, and response body.

A status code is a group of digits, ranging from 1xx to 5xx. It indicates the status of a request. For more information, see [Status Codes](#).

If status code **201** is returned for the calling of the API for [obtaining a user token](#), the request is successful.

Response Headers

Similar to a request, a response also has a header, for example, **Content-Type**.

[Figure 3-2](#) shows the response header for the API of [obtaining a user token](#), in which **x-subject-token** is the desired user token. This token can then be used to authenticate the calling of other APIs.

Figure 3-2 Header fields of the response to the request for obtaining a user token

```
connection → keep-alive
content-type → application/json
date → Tue, 12 Feb 2019 06:52:13 GMT
server → Web Server
strict-transport-security → max-age=31536000; includeSubdomains;
transfer-encoding → chunked
via → proxy A
x-content-type-options → nosniff
x-download-options → noopen
x-frame-options → SAMEORIGIN
x-iam-trace-id → 218d45ab-d674-4995-af3a-2d0255ba41b5
x-subject-token → MIIYXQYJKoZIhvcNAQcCoIIYTCCEoCAQExDTALBgIghkgBZQMEAgEwgharBgkqhkiG9w0BBwGgghacBIIWmHsidG9rZW4iOansiZXhwaXJlc19hdCI6IjwMTktMDItMTNUMC
fj3KJs6YgKnPvNRbW2eZ5eb78SZOkqjACgklqO1wi4JIGzrpd18LGXK5bdfq4lqHCYb8P4NaY0NYejcAgz/VeFYtLWT1GSO0zxKZmlQHq82HBqHdgIZO9fuEbL5dMhdavj+33wEI
xHRCE9I87o+k9-
j+CMZSEB7bUGd5Uj6eRASXl1jipPEGA270g1FruooL6jgglFkNPQuFSOU8+uSsttVwRtNfsC+qTp22Rkd5MCqFGQ8LcuUxC3a+9CMBnOintWW7oeRUVhVpxk8pxiX1wTEboX-
RzT6MUbpvGw-oPNFYxJECKnoH3HRozv0vN--n5d6Nbxg==
x-xss-protection → 1; mode=block;
```

Response Body (Optional)

A response body is generally returned in a structured format corresponding to the **Content-Type** in the response header and is used to transfer content other than the response header.

The following is part of the response body for the API used to **obtain a user token**. The following shows part of the response body for the API to obtain a user token.

```
{
  "token": {
    "expires_at": "2019-02-13T06:52:13.855000Z",
    "methods": [
      "password"
    ],
    "catalog": [
      {
        "endpoints": [
          {
            "region_id": "XXXXXX",
            .....

```

If an error occurs during API calling, an error code and a message will be displayed. The following shows an error response body.

```
{
  "error_msg": "The format of message is error",
  "error_code": "AS.0001"
}
```

In the response body, **error_code** is an error code, and **error_msg** provides the information about the error.

4 Getting Started

Application Scenario

You can create a custom event source based on service requirements.

For details on how to call APIs, see [Calling APIs](#).

Prerequisites

- IAM endpoint obtained from [Regions and Endpoints](#).
- EG endpoint obtained from [Regions and Endpoints](#).

Creating an Event Source

Step 1 Create a custom channel by calling the [event channel creation](#) API.

```
POST https://{endpoint}/v1/{project_id}/channels
```

```
{
  "name" : "channel",
  "description" : "first channel"
}
```

- name: custom channel name.
- description: description of a custom channel.

Step 2 Create a custom event source by calling the [event source creation](#) API.

```
POST https://{endpoint}/v1/{project_id}/sources
```

```
{
  "name" : "first-source",
  "description" : "first event source",
  "channel_id" : "bd14144e-8f3c-43d6-bdfd-bf09b52c2b96"
}
```

- name: custom event source name.
- description: description of a custom event source.
- channel_id: Obtain the channel ID from the response of [Step 1](#).

----End

5 APIs

5.1 Event Subscription Management

5.1.1 Creating an Event Subscription

Function

This API is used to create an event subscription.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/subscriptions

Table 5-1 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-2 Query Parameters

Parameter	Mandatory	Type	Description
enterprise_project_id	No	String	ID of an enterprise project used for creating a subscription.

Request Parameters

Table 5-3 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-4 Request body parameters

Parameter	Mandatory	Type	Description
name	Yes	String	Name of the event subscription. The value must be unique under a tenant. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit.
description	No	String	Description of the event subscription.
channel_id	Yes	String	ID of the event channel to which the event subscription belongs.
sources	Yes	Array of SubscriptionSource objects	List of event subscription sources. Currently, only one event source can be subscribed to.
targets	Yes	Array of SubscriptionTarget objects	List of event subscription targets. At least one event target must be subscribed to.

Table 5-5 SubscriptionSource

Parameter	Mandatory	Type	Description
id	No	String	ID of the subscription source, which must be globally unique. If the subscription source with the specified ID exists, the subscription source is updated. Otherwise, the subscription source is created. If no ID is specified, the system automatically generates an ID when creating the subscription source. Only lowercase letters, digits, and hyphens (-) are allowed. It must start with a letter or digit.
name	Yes	String	Name of the event subscription source.
provider_type	Yes	String	Provider type of the event subscription source.
detail	No	Object	List of event subscription source parameters. The total length of this field after serialization cannot exceed 1024 bytes.
filter	Yes	Object	Filtering rule of the event subscription source. The total length of this field after serialization cannot exceed 2048 bytes.

Table 5-6 SubscriptionTarget

Parameter	Mandatory	Type	Description
id	No	String	Subscription target ID. The value must be globally unique. Only lowercase letters, digits, and hyphens (-) are allowed. It must start with a letter or digit. In the subscription update scenario, if the subscription target with the specified ID exists, the subscription target is updated. Otherwise, the subscription target is created. If no ID is specified, the system automatically generates an ID when creating the subscription target. If an ID is specified, the ID is used as the subscription target ID. This field is ignored when the subscription target is updated.
name	Yes	String	Name of the event subscription target.
provider_type	Yes	String	Provider type of the event subscription target.
connection_id	No	String	Connection ID used by the event subscription target.
detail	No	Object	List of event target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for function (urn, invoke_type, and agency_name), function flow (workflow_id and agency_name), and webhook (url) targets. An agency name must be specified for a function or function flow.
kafka_detail	No	KafkaTargetDetail object	List of Kafka event subscription target parameters. The total length of this field after serialization cannot exceed 1024 bytes.

Parameter	Mandatory	Type	Description
smn_detail	No	SmnTargetDetail object	List of SMN event target parameters for the subscription. The total length cannot exceed 1024 bytes after serialization.
eg_detail	No	EgTargetDetail object	List of EG event channel target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for EG channel event targets.
apigw_detail	No	ApigwTargetDetail object	List of APIGW URL target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for APIGW event targets.
retry_times	No	Integer	Number of retries.
transform	Yes	Transform object	Transform rule of the event subscription target.
dead_letter_queue	No	DeadLetterQueue object	List of dead letter queue parameters for the subscription.
rocketmq_detail	No	RocketmqTargetDetail object	Parameters for RocketMQ in event subscription.

Table 5-7 KafkaTargetDetail

Parameter	Mandatory	Type	Description
topic	Yes	String	Topic.
keyTransform	No	keyTransform object	Key value rule.

Table 5-8 keyTransform

Parameter	Mandatory	Type	Description
type	No	String	Type of the key value rule.

Parameter	Mandatory	Type	Description
value	No	String	Key value rule. This parameter is mandatory when type is VARIABLE or CONSTANT.
template	No	String	Key value rule template. This parameter is mandatory when type is VARIABLE.

Table 5-9 SmnTargetDetail

Parameter	Mandatory	Type	Description
urn	Yes	String	Specifies the topic URN.
agency_name	Yes	String	Agency name.
subject_transform	No	subject_transform object	Title rule.

Table 5-10 subject_transform

Parameter	Mandatory	Type	Description
type	Yes	String	Type of the title rule.
value	Yes	String	Title rule.
template	No	String	Title rule template. This parameter is mandatory when type is set to VARIABLE.

Table 5-11 EgTargetDetail

Parameter	Mandatory	Type	Description
target_project_id	Yes	String	Target project ID.
target_channel_id	Yes	String	Target channel ID.
target_region	Yes	String	Target region.
cross_region	No	Boolean	Indicates whether cross-region feature is enabled.
agency_name	Yes	String	Agency name.

Table 5-12 ApigwTargetDetail

Parameter	Mandatory	Type	Description
url	Yes	String	Target URL.
invocation_http_parameters	No	InvocationHttpParameters object	Parameters for invoking HTTP.

Table 5-13 InvocationHttpParameters

Parameter	Mandatory	Type	Description
header_parameters	No	Array of HeaderParameter objects	Object list.

Table 5-14 HeaderParameter

Parameter	Mandatory	Type	Description
is_value_secret	No	Boolean	Whether to encrypt the value.
key	No	String	Header key.
value	No	String	Header value.

Table 5-15 DeadLetterQueue

Parameter	Mandatory	Type	Description
type	Yes	String	Queue type.
instance_id	Yes	String	Instance ID.
connection_id	Yes	String	Connection ID.
topic	Yes	String	Topic.

Table 5-16 RocketmqTargetDetail

Parameter	Mandatory	Type	Description
topic	No	String	Topic name.
key_transform	No	Transform object	Transform rule.

Table 5-17 TransForm

Parameter	Mandatory	Type	Description
type	Yes	String	Type of the transform rule.
value	No	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	No	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Response Parameters

Status code: 200

Table 5-18 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-19 Response body parameters

Parameter	Type	Description
id	String	Subscription ID.
name	String	Subscription name.
description	String	Description of the subscription.
type	String	Subscription type.
status	String	Status.
channel_id	String	ID of the event channel.
channel_name	String	Name of the event channel.
used	Array of SubscriptionUsedInfo objects	Label information.
sources	Array of SubscriptionSourceInfo objects	List of subscription sources.
targets	Array of SubscriptionTargetInfo objects	List of subscription targets.
created_time	String	Time when the trigger is created.
updated_time	String	Time when the trigger is updated.

Table 5-20 SubscriptionUsedInfo

Parameter	Type	Description
resource_id	String	Associated resource ID.
owner	String	Management tenant account.
description	String	Description.

Table 5-21 SubscriptionSourceInfo

Parameter	Type	Description
id	String	ID of the event subscription source.
name	String	Name of the event subscription source.
provider_type	String	Provider type of the event subscription source.

Parameter	Type	Description
detail	Object	List of event subscription source parameters.
filter	Object	Filtering rule of the event subscription source.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.

Table 5-22 SubscriptionTargetInfo

Parameter	Type	Description
id	String	ID of the event subscription target.
name	String	Name of the event subscription target.
provider_type	String	Provider type of the event subscription target.
connection_id	String	Connection ID used by the event subscription target.
detail	Object	List of event subscription target parameters.
kafka_detail	KafkaTargetDetail object	List of Kafka event subscription target parameters. The total length of this field after serialization cannot exceed 1024 bytes.
smn_detail	SmnTargetDetail object	List of SMN event target parameters for the subscription. The total length cannot exceed 1024 bytes after serialization.
eg_detail	EgTargetDetail object	List of EG event channel target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for EG channel event targets.
apigw_detail	ApigwTargetDetail object	List of APIGW URL target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for APIGW event targets.

Parameter	Type	Description
retry_times	Integer	Number of retries.
transform	Transform object	Transform rule of the event subscription target.
dead_letter_queue	DeadLetterQueue object	List of dead letter queue parameters for the subscription.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.
rocketmq_detail	RocketmqTargetDetail object	Parameters for RocketMQ in event subscription.

Table 5-23 KafkaTargetDetail

Parameter	Type	Description
topic	String	Topic.
keyTransform	keyTransform object	Key value rule.

Table 5-24 keyTransform

Parameter	Type	Description
type	String	Type of the key value rule.
value	String	Key value rule. This parameter is mandatory when type is VARIABLE or CONSTANT.
template	String	Key value rule template. This parameter is mandatory when type is VARIABLE.

Table 5-25 SmnTargetDetail

Parameter	Type	Description
urn	String	Specifies the topic URN.
agency_name	String	Agency name.

Parameter	Type	Description
subject_transform	subject_transform object	Title rule.

Table 5-26 subject_transform

Parameter	Type	Description
type	String	Type of the title rule.
value	String	Title rule.
template	String	Title rule template. This parameter is mandatory when type is set to VARIABLE.

Table 5-27 EgTargetDetail

Parameter	Type	Description
target_project_id	String	Target project ID.
target_channel_id	String	Target channel ID.
target_region	String	Target region.
cross_region	Boolean	Indicates whether cross-region feature is enabled.
agency_name	String	Agency name.

Table 5-28 ApigwTargetDetail

Parameter	Type	Description
url	String	Target URL.
invocation_http_parameters	InvocationHttpParameters object	Parameters for invoking HTTP.

Table 5-29 InvocationHttpParameters

Parameter	Type	Description
header_parameters	Array of HeaderParameter objects	Object list.

Table 5-30 HeaderParameter

Parameter	Type	Description
is_value_secret	Boolean	Whether to encrypt the value.
key	String	Header key.
value	String	Header value.

Table 5-31 DeadLetterQueue

Parameter	Type	Description
type	String	Queue type.
instance_id	String	Instance ID.
connection_id	String	Connection ID.
topic	String	Topic.

Table 5-32 RocketmqTargetDetail

Parameter	Type	Description
topic	String	Topic name.
key_transform	Transform object	Transform rule.

Table 5-33 Transform

Parameter	Type	Description
type	String	Type of the transform rule.

Parameter	Type	Description
value	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Example Requests

Create an event subscription named test-subscription.

```
POST https://{endpoint}/v1/{project_id}/subscriptions
```

```
{
  "name": "test-subscription",
  "description": "this is a test subscription",
  "channel_id": "05649f9a-b324-4920-9c49-156d4cd2e546",
  "sources": [ {
    "id": "3a0eeff2-78a4-4122-dfge-7ty5e37f64er",
    "name": "HC.OBS",
    "provider_type": "OFFICIAL",
    "detail": {
      "name": "name"
    }
  },
  "filter": {
    "data": {
      "count": [ {
        "op": "NumberIn",
        "values": [ 1, 2 ]
      } ]
    }
  }
},
  "targets": [ {
    "id": "3a0eeff2-78a4-4122-dfge-7ty5e37f64er",
    "name": "WEBHOOK",
    "provider_type": "CUSTOM",
    "connection_id": "456eekj3-778u-4tyu-dfrt-er55e37f667t",
    "detail": {
      "url": "http://10.213.96.90:8080/t/nodeapp/trigger-hello-nodejs",

```

```
"agency_name" : "EG_TARGET_AGENCY",
"urn" : "urn:fss:cn-north-7:bac852160cc743158936edaab6dda813:function:default:gxtestjava:latest",
"invoke_type" : "ASYNC",
"workflow_id" : "86afc904-0019-46c8-baed-0225967c1b98"
},
"kafka_detail" : {
  "topic" : "8516d278-268a-4a8b-8766-9bf9b3302f43",
  "keyTransform" : {
    "type" : "NONE",
    "value" : "string",
    "template" : "string"
  }
},
"smn_detail" : {
  "urn" : "urn:smn:cn-north-7:bac852160cc743158936edaab6dda813:122",
  "agency_name" : "EG_SMN_PUBLISHER_AGENCY",
  "subject_transform" : {
    "type" : "VARIABLE",
    "value" : "string",
    "template" : "string"
  }
},
"eg_detail" : {
  "target_project_id" : "c5be311886934b7c8afb4f8970376130",
  "target_channel_id" : "10a79a30-bd4a-4955-a3ec-d62dc799347b",
  "target_region" : "cn-north-test",
  "cross_region" : false,
  "agency_name" : "EG_TARGET_AGENCY"
},
"apigw_detail" : {
  "url" : "https://dms.cn-north-4.myhuaweicloud.com/testaaa",
  "invocation_http_parameters" : {
    "header_parameters" : [ {
      "is_value_secret" : false,
      "key" : "test-key",
      "value" : "test-value"
    } ]
  }
},
"retry_times" : 16,
"transform" : {
  "type" : "VARIABLE",
  "value" : "{ \"contant_boolean\": true, \"contant_string\": \"constant\", \"variable_string\": \"$.data.string\", \"variable_json_object\": \"$.data.object\" }",
  "template" : "{ \"contant_boolean\": ${contant_boolean}, \"contant_string\": \"${contant_string!}\" \"default\" \"\" }\", \"variable_string\": \"${contant_boolean}\", \"variable_json_object\": \"${variable_json_object!}\" \"null\" }\" }"
},
"dead_letter_queue" : {
  "type" : "KAFKA",
  "instance_id" : "ff0e3f10-fcab-4c3a-84bb-cf5a8b6f7722",
  "connection_id" : "8516d278-268a-4a8b-8766-9bf9b3302f43",
  "topic" : "topic"
}
}
```

Example Responses

Status code: 200

Demo Information

```
{
  "id" : "23709d68-54d5-423b-a6be-03302e893152",
  "name" : "test-subscription",
  "description" : "this is a test subscription",
  "type" : "EVENT",
  "status" : "CREATED",
  "channel_id" : "05649f9a-b324-4920-9c49-156d4cd2e546",
}
```

```
"channel_name" : "channel006",
"used" : [ { } ],
"sources" : [ { } ],
"targets" : [ { } ],
"created_time" : "2021-12-09 09:00:00",
"updated_time" : "2021-12-09 09:00:00"
}
```

Status Codes

Status Code	Description
200	Demo Information

Error Codes

See [Error Codes](#).

5.1.2 Obtaining the Event Subscription List

Function

This API is used to obtain the event subscription list. An event channel can be specified.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/subscriptions

Table 5-34 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-35 Query Parameters

Parameter	Mandatory	Type	Description
channel_id	No	String	ID of the event channel.

Parameter	Mandatory	Type	Description
offset	No	Integer	Offset, which is the position where the query starts. The value must be greater than or equal to 0.
limit	No	Integer	Number of records displayed on each page. The value must be within the range [1, 1000].
sort	No	String	Sorting mode of the query results.
name	No	String	Name of the event subscription. It is used for exact match.
fuzzy_name	No	String	Name of the event subscription. It is used for fuzzy match.
connection_id	No	String	ID of the connection.
enterprise_project_id	No	String	ID of an enterprise project used for creating a subscription.

Request Parameters

Table 5-36 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-37 Response body parameters

Parameter	Type	Description
total	Integer	Total number of records.

Parameter	Type	Description
size	Integer	Number of records displayed on the current page.
items	Array of SubscriptionInfo objects	Object list.

Table 5-38 SubscriptionInfo

Parameter	Type	Description
id	String	Subscription ID.
name	String	Subscription name.
description	String	Description of the subscription.
type	String	Subscription type.
status	String	Status.
channel_id	String	ID of the event channel.
channel_name	String	Name of the event channel.
used	Array of SubscriptionUse- dInfo objects	Label information.
sources	Array of SubscriptionSour- ceInfo objects	List of subscription sources.
targets	Array of SubscriptionTar- getInfo objects	List of subscription targets.
created_time	String	Time when the trigger is created.
updated_time	String	Time when the trigger is updated.

Table 5-39 SubscriptionUsedInfo

Parameter	Type	Description
resource_id	String	Associated resource ID.
owner	String	Management tenant account.
description	String	Description.

Table 5-40 SubscriptionSourceInfo

Parameter	Type	Description
id	String	ID of the event subscription source.
name	String	Name of the event subscription source.
provider_type	String	Provider type of the event subscription source.
detail	Object	List of event subscription source parameters.
filter	Object	Filtering rule of the event subscription source.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.

Table 5-41 SubscriptionTargetInfo

Parameter	Type	Description
id	String	ID of the event subscription target.
name	String	Name of the event subscription target.
provider_type	String	Provider type of the event subscription target.
connection_id	String	Connection ID used by the event subscription target.
detail	Object	List of event subscription target parameters.
kafka_detail	KafkaTargetDetail object	List of Kafka event subscription target parameters. The total length of this field after serialization cannot exceed 1024 bytes.
smn_detail	SmnTargetDetail object	List of SMN event target parameters for the subscription. The total length cannot exceed 1024 bytes after serialization.

Parameter	Type	Description
eg_detail	EgTargetDetail object	List of EG event channel target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for EG channel event targets.
apigw_detail	ApigwTargetDetail object	List of APIGW URL target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for APIGW event targets.
retry_times	Integer	Number of retries.
transform	Transform object	Transform rule of the event subscription target.
dead_letter_queue	DeadLetterQueue object	List of dead letter queue parameters for the subscription.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.
rocketmq_detail	RocketmqTargetDetail object	Parameters for RocketMQ in event subscription.

Table 5-42 KafkaTargetDetail

Parameter	Type	Description
topic	String	Topic.
keyTransform	keyTransform object	Key value rule.

Table 5-43 keyTransform

Parameter	Type	Description
type	String	Type of the key value rule.
value	String	Key value rule. This parameter is mandatory when type is VARIABLE or CONSTANT.

Parameter	Type	Description
template	String	Key value rule template. This parameter is mandatory when type is VARIABLE.

Table 5-44 SmnTargetDetail

Parameter	Type	Description
urn	String	Specifies the topic URN.
agency_name	String	Agency name.
subject_transform	subject_transform object	Title rule.

Table 5-45 subject_transform

Parameter	Type	Description
type	String	Type of the title rule.
value	String	Title rule.
template	String	Title rule template. This parameter is mandatory when type is set to VARIABLE.

Table 5-46 EgTargetDetail

Parameter	Type	Description
target_project_id	String	Target project ID.
target_channel_id	String	Target channel ID.
target_region	String	Target region.
cross_region	Boolean	Indicates whether cross-region feature is enabled.
agency_name	String	Agency name.

Table 5-47 ApigwTargetDetail

Parameter	Type	Description
url	String	Target URL.
invocation_http_parameters	InvocationHttpParameters object	Parameters for invoking HTTP.

Table 5-48 InvocationHttpParameters

Parameter	Type	Description
header_parameters	Array of HeaderParameter objects	Object list.

Table 5-49 HeaderParameter

Parameter	Type	Description
is_value_secret	Boolean	Whether to encrypt the value.
key	String	Header key.
value	String	Header value.

Table 5-50 DeadLetterQueue

Parameter	Type	Description
type	String	Queue type.
instance_id	String	Instance ID.
connection_id	String	Connection ID.
topic	String	Topic.

Table 5-51 RocketmqTargetDetail

Parameter	Type	Description
topic	String	Topic name.
key_transform	Transform object	Transform rule.

Table 5-52 TransForm

Parameter	Type	Description
type	String	Type of the transform rule.
value	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Example Requests

Obtain the event subscription list.

```
GET https://{endpoint}/v1/{project_id}/subscriptions
```

Example Responses

Status code: 200

Operation successful.

```
{
  "total" : 1,
  "size" : 1,
  "items" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.1.3 Updating an Event Subscription

Function

This API is used to update an event subscription.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

PUT /v1/{project_id}/subscriptions/{subscription_id}

Table 5-53 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
subscription_id	Yes	String	ID of the event subscription.

Table 5-54 Query Parameters

Parameter	Mandatory	Type	Description
enterprise_project_id	No	String	ID of an enterprise project used for creating a subscription.

Request Parameters

Table 5-55 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-56 Request body parameters

Parameter	Mandatory	Type	Description
description	No	String	Description of the event subscription.
sources	No	Array of SubscriptionSource objects	List of event subscription sources. If this field exists, all subscription sources are updated.
targets	No	Array of SubscriptionTarget objects	List of event subscription targets. If this field exists, all subscription targets are updated.

Table 5-57 SubscriptionSource

Parameter	Mandatory	Type	Description
id	No	String	ID of the subscription source, which must be globally unique. If the subscription source with the specified ID exists, the subscription source is updated. Otherwise, the subscription source is created. If no ID is specified, the system automatically generates an ID when creating the subscription source. Only lowercase letters, digits, and hyphens (-) are allowed. It must start with a letter or digit.
name	Yes	String	Name of the event subscription source.
provider_type	Yes	String	Provider type of the event subscription source.
detail	No	Object	List of event subscription source parameters. The total length of this field after serialization cannot exceed 1024 bytes.

Parameter	Mandatory	Type	Description
filter	Yes	Object	Filtering rule of the event subscription source. The total length of this field after serialization cannot exceed 2048 bytes.

Table 5-58 SubscriptionTarget

Parameter	Mandatory	Type	Description
id	No	String	Subscription target ID. The value must be globally unique. Only lowercase letters, digits, and hyphens (-) are allowed. It must start with a letter or digit. In the subscription update scenario, if the subscription target with the specified ID exists, the subscription target is updated. Otherwise, the subscription target is created. If no ID is specified, the system automatically generates an ID when creating the subscription target. If an ID is specified, the ID is used as the subscription target ID. This field is ignored when the subscription target is updated.
name	Yes	String	Name of the event subscription target.
provider_type	Yes	String	Provider type of the event subscription target.
connection_id	No	String	Connection ID used by the event subscription target.

Parameter	Mandatory	Type	Description
detail	No	Object	List of event target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for function (urn, invoke_type, and agency_name), function flow (workflow_id and agency_name), and webhook (url) targets. An agency name must be specified for a function or function flow.
kafka_detail	No	KafkaTargetDetail object	List of Kafka event subscription target parameters. The total length of this field after serialization cannot exceed 1024 bytes.
smn_detail	No	SmnTargetDetail object	List of SMN event target parameters for the subscription. The total length cannot exceed 1024 bytes after serialization.
eg_detail	No	EgTargetDetail object	List of EG event channel target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for EG channel event targets.
apigw_detail	No	ApigwTargetDetail object	List of APIGW URL target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for APIGW event targets.
retry_times	No	Integer	Number of retries.
transform	Yes	Transform object	Transform rule of the event subscription target.
dead_letter_queue	No	DeadLetterQueue object	List of dead letter queue parameters for the subscription.

Parameter	Mandatory	Type	Description
rocketmq_detail	No	RocketmqTargetDetail object	Parameters for RocketMQ in event subscription.

Table 5-59 KafkaTargetDetail

Parameter	Mandatory	Type	Description
topic	Yes	String	Topic.
keyTransform	No	keyTransform object	Key value rule.

Table 5-60 keyTransform

Parameter	Mandatory	Type	Description
type	No	String	Type of the key value rule.
value	No	String	Key value rule. This parameter is mandatory when type is VARIABLE or CONSTANT.
template	No	String	Key value rule template. This parameter is mandatory when type is VARIABLE.

Table 5-61 SmnTargetDetail

Parameter	Mandatory	Type	Description
urn	Yes	String	Specifies the topic URN.
agency_name	Yes	String	Agency name.
subject_transform	No	subject_transform object	Title rule.

Table 5-62 subject_transform

Parameter	Mandatory	Type	Description
type	Yes	String	Type of the title rule.
value	Yes	String	Title rule.

Parameter	Mandatory	Type	Description
template	No	String	Title rule template. This parameter is mandatory when type is set to VARIABLE.

Table 5-63 EgTargetDetail

Parameter	Mandatory	Type	Description
target_project_id	Yes	String	Target project ID.
target_channel_id	Yes	String	Target channel ID.
target_region	Yes	String	Target region.
cross_region	No	Boolean	Indicates whether cross-region feature is enabled.
agency_name	Yes	String	Agency name.

Table 5-64 ApigwTargetDetail

Parameter	Mandatory	Type	Description
url	Yes	String	Target URL.
invocation_http_parameters	No	InvocationHttpParameters object	Parameters for invoking HTTP.

Table 5-65 InvocationHttpParameters

Parameter	Mandatory	Type	Description
header_parameters	No	Array of HeaderParameter objects	Object list.

Table 5-66 HeaderParameter

Parameter	Mandatory	Type	Description
is_value_secret	No	Boolean	Whether to encrypt the value.

Parameter	Mandatory	Type	Description
key	No	String	Header key.
value	No	String	Header value.

Table 5-67 DeadLetterQueue

Parameter	Mandatory	Type	Description
type	Yes	String	Queue type.
instance_id	Yes	String	Instance ID.
connection_id	Yes	String	Connection ID.
topic	Yes	String	Topic.

Table 5-68 RocketmqTargetDetail

Parameter	Mandatory	Type	Description
topic	No	String	Topic name.
key_transform	No	Transform object	Transform rule.

Table 5-69 Transform

Parameter	Mandatory	Type	Description
type	Yes	String	Type of the transform rule.

Parameter	Mandatory	Type	Description
value	No	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	No	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Response Parameters

Status code: 200

Table 5-70 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-71 Response body parameters

Parameter	Type	Description
id	String	Subscription ID.

Parameter	Type	Description
name	String	Subscription name.
description	String	Description of the subscription.
type	String	Subscription type.
status	String	Status.
channel_id	String	ID of the event channel.
channel_name	String	Name of the event channel.
used	Array of SubscriptionUsedInfo objects	Label information.
sources	Array of SubscriptionSourceInfo objects	List of subscription sources.
targets	Array of SubscriptionTargetInfo objects	List of subscription targets.
created_time	String	Time when the trigger is created.
updated_time	String	Time when the trigger is updated.

Table 5-72 SubscriptionUsedInfo

Parameter	Type	Description
resource_id	String	Associated resource ID.
owner	String	Management tenant account.
description	String	Description.

Table 5-73 SubscriptionSourceInfo

Parameter	Type	Description
id	String	ID of the event subscription source.
name	String	Name of the event subscription source.
provider_type	String	Provider type of the event subscription source.
detail	Object	List of event subscription source parameters.

Parameter	Type	Description
filter	Object	Filtering rule of the event subscription source.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.

Table 5-74 SubscriptionTargetInfo

Parameter	Type	Description
id	String	ID of the event subscription target.
name	String	Name of the event subscription target.
provider_type	String	Provider type of the event subscription target.
connection_id	String	Connection ID used by the event subscription target.
detail	Object	List of event subscription target parameters.
kafka_detail	KafkaTargetDetail object	List of Kafka event subscription target parameters. The total length of this field after serialization cannot exceed 1024 bytes.
smn_detail	SmnTargetDetail object	List of SMN event target parameters for the subscription. The total length cannot exceed 1024 bytes after serialization.
eg_detail	EgTargetDetail object	List of EG event channel target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for EG channel event targets.
apigw_detail	ApigwTargetDetail object	List of APIGW URL target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for APIGW event targets.
retry_times	Integer	Number of retries.

Parameter	Type	Description
transform	TransForm object	Transform rule of the event subscription target.
dead_letter_queue	DeadLetterQueue object	List of dead letter queue parameters for the subscription.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.
rocketmq_detail	RocketmqTargetDetail object	Parameters for RocketMQ in event subscription.

Table 5-75 KafkaTargetDetail

Parameter	Type	Description
topic	String	Topic.
keyTransform	keyTransform object	Key value rule.

Table 5-76 keyTransform

Parameter	Type	Description
type	String	Type of the key value rule.
value	String	Key value rule. This parameter is mandatory when type is VARIABLE or CONSTANT.
template	String	Key value rule template. This parameter is mandatory when type is VARIABLE.

Table 5-77 SmnTargetDetail

Parameter	Type	Description
urn	String	Specifies the topic URN.
agency_name	String	Agency name.
subject_transform	subject_transform object	Title rule.

Table 5-78 subject_transform

Parameter	Type	Description
type	String	Type of the title rule.
value	String	Title rule.
template	String	Title rule template. This parameter is mandatory when type is set to VARIABLE.

Table 5-79 EgTargetDetail

Parameter	Type	Description
target_project_id	String	Target project ID.
target_channel_id	String	Target channel ID.
target_region	String	Target region.
cross_region	Boolean	Indicates whether cross-region feature is enabled.
agency_name	String	Agency name.

Table 5-80 ApigwTargetDetail

Parameter	Type	Description
url	String	Target URL.
invocation_http_parameters	InvocationHttpParameters object	Parameters for invoking HTTP.

Table 5-81 InvocationHttpParameters

Parameter	Type	Description
header_parameters	Array of HeaderParameter objects	Object list.

Table 5-82 HeaderParameter

Parameter	Type	Description
is_value_secret	Boolean	Whether to encrypt the value.

Parameter	Type	Description
key	String	Header key.
value	String	Header value.

Table 5-83 DeadLetterQueue

Parameter	Type	Description
type	String	Queue type.
instance_id	String	Instance ID.
connection_id	String	Connection ID.
topic	String	Topic.

Table 5-84 RocketmqTargetDetail

Parameter	Type	Description
topic	String	Topic name.
key_transform	Transform object	Transform rule.

Table 5-85 Transform

Parameter	Type	Description
type	String	Type of the transform rule.

Parameter	Type	Description
value	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Example Requests

Update an event subscription.

PUT https://{endpoint}/v1/{project_id}/subscriptions/{subscription_id}

```
{
  "description": "For development",
  "sources": [ {
    "detail": { },
    "filter": {
      "source": [ {
        "op": "StringIn",
        "values": [ "ghm" ]
      } ]
    },
    "id": "4fca4f29-917b-44d3-bb30-4310f89d08cb",
    "name": "ghm",
    "provider_type": "CUSTOM"
  } ],
  "targets": [ {
    "id": "4261f07e-975c-457f-aa91-0bd33d64baba",
    "name": "HC.SMN",
    "provider_type": "OFFICIAL",
    "retry_times": 16,
    "smn_detail": {
      "agency_name": "EG_TARGET_AGENCY",
      "urn": "urn:smn:cn-north-7:bac852160cc743158936edaab6dda813:CES_notification_group_xMXxPQ1ry"
    },
    "transform": {
      "type": "ORIGINAL",
      "value": ""
    }
  } ]
}
```

```
    }  
  }  
}
```

Example Responses

Status code: 200

Information

```
{  
  "id" : "23709d68-54d5-423b-a6be-03302e893152",  
  "name" : "test-subscription",  
  "description" : "this is a test subscription",  
  "type" : "EVENT",  
  "status" : "CREATED",  
  "channel_id" : "05649f9a-b324-4920-9c49-156d4cd2e546",  
  "channel_name" : "channel006",  
  "used" : [ { } ],  
  "sources" : [ { } ],  
  "targets" : [ { } ],  
  "created_time" : "2021-12-09 09:00:00",  
  "updated_time" : "2021-12-09 09:00:00"  
}
```

Status Codes

Status Code	Description
200	Information

Error Codes

See [Error Codes](#).

5.1.4 Obtaining Event Subscription Details

Function

This API is used to obtain the details of an event subscription.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/subscriptions/{subscription_id}

Table 5-86 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
subscription_id	Yes	String	ID of the event subscription.

Table 5-87 Query Parameters

Parameter	Mandatory	Type	Description
enterprise_project_id	No	String	ID of an enterprise project used for creating a subscription.

Request Parameters

Table 5-88 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-89 Response body parameters

Parameter	Type	Description
id	String	Subscription ID.
name	String	Subscription name.
description	String	Description of the subscription.
type	String	Subscription type.
status	String	Status.
channel_id	String	ID of the event channel.

Parameter	Type	Description
channel_name	String	Name of the event channel.
used	Array of SubscriptionUsedInfo objects	Label information.
sources	Array of SubscriptionSourceInfo objects	List of subscription sources.
targets	Array of SubscriptionTargetInfo objects	List of subscription targets.
created_time	String	Time when the trigger is created.
updated_time	String	Time when the trigger is updated.

Table 5-90 SubscriptionUsedInfo

Parameter	Type	Description
resource_id	String	Associated resource ID.
owner	String	Management tenant account.
description	String	Description.

Table 5-91 SubscriptionSourceInfo

Parameter	Type	Description
id	String	ID of the event subscription source.
name	String	Name of the event subscription source.
provider_type	String	Provider type of the event subscription source.
detail	Object	List of event subscription source parameters.
filter	Object	Filtering rule of the event subscription source.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.

Table 5-92 SubscriptionTargetInfo

Parameter	Type	Description
id	String	ID of the event subscription target.
name	String	Name of the event subscription target.
provider_type	String	Provider type of the event subscription target.
connection_id	String	Connection ID used by the event subscription target.
detail	Object	List of event subscription target parameters.
kafka_detail	KafkaTargetDetail object	List of Kafka event subscription target parameters. The total length of this field after serialization cannot exceed 1024 bytes.
smn_detail	SmnTargetDetail object	List of SMN event target parameters for the subscription. The total length cannot exceed 1024 bytes after serialization.
eg_detail	EgTargetDetail object	List of EG event channel target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for EG channel event targets.
apigw_detail	ApigwTargetDetail object	List of APIGW URL target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for APIGW event targets.
retry_times	Integer	Number of retries.
transform	TransForm object	Transform rule of the event subscription target.
dead_letter_queue	DeadLetterQueue object	List of dead letter queue parameters for the subscription.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.
rocketmq_detail	RocketmqTargetDetail object	Parameters for RocketMQ in event subscription.

Table 5-93 KafkaTargetDetail

Parameter	Type	Description
topic	String	Topic.
keyTransform	keyTransform object	Key value rule.

Table 5-94 keyTransform

Parameter	Type	Description
type	String	Type of the key value rule.
value	String	Key value rule. This parameter is mandatory when type is VARIABLE or CONSTANT.
template	String	Key value rule template. This parameter is mandatory when type is VARIABLE.

Table 5-95 SmnTargetDetail

Parameter	Type	Description
urn	String	Specifies the topic URN.
agency_name	String	Agency name.
subject_transform	subject_transform object	Title rule.

Table 5-96 subject_transform

Parameter	Type	Description
type	String	Type of the title rule.
value	String	Title rule.
template	String	Title rule template. This parameter is mandatory when type is set to VARIABLE.

Table 5-97 EgTargetDetail

Parameter	Type	Description
target_project_id	String	Target project ID.
target_channel_id	String	Target channel ID.
target_region	String	Target region.
cross_region	Boolean	Indicates whether cross-region feature is enabled.
agency_name	String	Agency name.

Table 5-98 ApigwTargetDetail

Parameter	Type	Description
url	String	Target URL.
invocation_http_parameters	InvocationHttpParameters object	Parameters for invoking HTTP.

Table 5-99 InvocationHttpParameters

Parameter	Type	Description
header_parameters	Array of HeaderParameter objects	Object list.

Table 5-100 HeaderParameter

Parameter	Type	Description
is_value_secret	Boolean	Whether to encrypt the value.
key	String	Header key.
value	String	Header value.

Table 5-101 DeadLetterQueue

Parameter	Type	Description
type	String	Queue type.
instance_id	String	Instance ID.

Parameter	Type	Description
connection_id	String	Connection ID.
topic	String	Topic.

Table 5-102 RocketmqTargetDetail

Parameter	Type	Description
topic	String	Topic name.
key_transform	Transform object	Transform rule.

Table 5-103 Transform

Parameter	Type	Description
type	String	Type of the transform rule.
value	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Example Requests

Obtain event subscription details.

GET https://{endpoint}/v1/{project_id}/subscriptions/{subscription_id}

Example Responses

Status code: 200

Operation successful.

```
{
  "id" : "23709d68-54d5-423b-a6be-03302e893152",
  "name" : "test-subscription",
  "description" : "this is a test subscription",
  "type" : "EVENT",
  "status" : "CREATED",
  "channel_id" : "05649f9a-b324-4920-9c49-156d4cd2e546",
  "channel_name" : "channel006",
  "used" : [ { } ],
  "sources" : [ { } ],
  "targets" : [ { } ],
  "created_time" : "2021-12-09 09:00:00",
  "updated_time" : "2021-12-09 09:00:00"
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.1.5 Deleting an Event Subscription

Function

This API is used to delete an event subscription.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

DELETE /v1/{project_id}/subscriptions/{subscription_id}

Table 5-104 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Parameter	Mandatory	Type	Description
subscription_id	Yes	String	ID of the event subscription.

Table 5-105 Query Parameters

Parameter	Mandatory	Type	Description
enterprise_project_id	No	String	ID of an enterprise project used for creating a subscription.

Request Parameters

Table 5-106 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 204

Operation successful.

None

Example Requests

Delete an event subscription.

```
DELETE https://{endpoint}/v1/{project_id}/subscriptions/{subscription_id}
```

Example Responses

None

Status Codes

Status Code	Description
204	Operation successful.

Error Codes

See [Error Codes](#).

5.1.6 Updating an Event Subscription Source

Function

This API is used to update the source of an event subscription.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

PUT /v1/{project_id}/subscriptions/{subscription_id}/sources/{source_id}

Table 5-107 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
subscription_id	Yes	String	ID of the event subscription.
source_id	Yes	String	ID of the event source.

Table 5-108 Query Parameters

Parameter	Mandatory	Type	Description
enterprise_project_id	No	String	ID of an enterprise project used for creating a subscription.

Request Parameters

Table 5-109 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-110 Request body parameters

Parameter	Mandatory	Type	Description
id	No	String	ID of the subscription source, which must be globally unique. If the subscription source with the specified ID exists, the subscription source is updated. Otherwise, the subscription source is created. If no ID is specified, the system automatically generates an ID when creating the subscription source. Only lowercase letters, digits, and hyphens (-) are allowed. It must start with a letter or digit.
name	Yes	String	Name of the event subscription source.
provider_type	Yes	String	Provider type of the event subscription source.
detail	No	Object	List of event subscription source parameters. The total length of this field after serialization cannot exceed 1024 bytes.
filter	Yes	Object	Filtering rule of the event subscription source. The total length of this field after serialization cannot exceed 2048 bytes.

Response Parameters

Status code: 200

Table 5-111 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-112 Response body parameters

Parameter	Type	Description
id	String	ID of the event subscription source.
name	String	Name of the event subscription source.
provider_type	String	Provider type of the event subscription source.
detail	Object	List of event subscription source parameters.
filter	Object	Filtering rule of the event subscription source.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.

Example Requests

Update an event subscription source.

PUT https://{endpoint}/v1/{project_id}/subscriptions/{subscription_id}/sources/{source_id}

```
{
  "id" : "3a0eeff2-78a4-4122-dfge-7ty5e37f64er",
  "name" : "HC.OBS",
  "provider_type" : "OFFICIAL",
  "detail" : {
    "name" : "name"
  },
  "filter" : {
    "data" : {
      "count" : [ {
        "op" : "NumberIn",
        "values" : [ 1, 2 ]
      } ]
    }
  }
}
```

Example Responses

Status code: 200

Information

```
{
  "id" : "3a0eeff2-78a4-4122-dfge-7ty5e37f64er",
  "name" : "HC.OBS",
  "provider_type" : "OFFICIAL",
  "detail" : {
    "name" : "name"
  },
  "filter" : {
    "data" : {
      "count" : [ {
        "op" : "NumberIn",
        "values" : [ 1, 2 ]
      } ]
    }
  },
  "created_time" : "2021-12-09 09:00:00",
  "updated_time" : "2021-12-09 09:00:00"
}
```

Status Codes

Status Code	Description
200	Information

Error Codes

See [Error Codes](#).

5.1.7 Creating an Event Subscription Target

Function

This API is used to create a target for an event subscription.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/subscriptions/{subscription_id}/targets

Table 5-113 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
subscription_id	Yes	String	ID of the event subscription.

Table 5-114 Query Parameters

Parameter	Mandatory	Type	Description
enterprise_project_id	No	String	ID of an enterprise project used for creating a subscription.

Request Parameters

Table 5-115 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-116 Request body parameters

Parameter	Mandatory	Type	Description
id	No	String	Subscription target ID. The value must be globally unique. Only lowercase letters, digits, and hyphens (-) are allowed. It must start with a letter or digit. In the subscription update scenario, if the subscription target with the specified ID exists, the subscription target is updated. Otherwise, the subscription target is created. If no ID is specified, the system automatically generates an ID when creating the subscription target. If an ID is specified, the ID is used as the subscription target ID. This field is ignored when the subscription target is updated.
name	Yes	String	Name of the event subscription target.
provider_type	Yes	String	Provider type of the event subscription target.
connection_id	No	String	Connection ID used by the event subscription target.
detail	No	Object	List of event target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for function (urn, invoke_type, and agency_name), function flow (workflow_id and agency_name), and webhook (url) targets. An agency name must be specified for a function or function flow.
kafka_detail	No	KafkaTargetDetail object	List of Kafka event subscription target parameters. The total length of this field after serialization cannot exceed 1024 bytes.

Parameter	Mandatory	Type	Description
smn_detail	No	SmnTargetDetail object	List of SMN event target parameters for the subscription. The total length cannot exceed 1024 bytes after serialization.
eg_detail	No	EgTargetDetail object	List of EG event channel target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for EG channel event targets.
apigw_detail	No	ApigwTargetDetail object	List of APIGW URL target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for APIGW event targets.
retry_times	No	Integer	Number of retries.
transform	Yes	Transform object	Transform rule of the event subscription target.
dead_letter_queue	No	DeadLetterQueue object	List of dead letter queue parameters for the subscription.
rocketmq_detail	No	RocketmqTargetDetail object	Parameters for RocketMQ in event subscription.

Table 5-117 KafkaTargetDetail

Parameter	Mandatory	Type	Description
topic	Yes	String	Topic.
keyTransform	No	keyTransform object	Key value rule.

Table 5-118 keyTransform

Parameter	Mandatory	Type	Description
type	No	String	Type of the key value rule.

Parameter	Mandatory	Type	Description
value	No	String	Key value rule. This parameter is mandatory when type is VARIABLE or CONSTANT.
template	No	String	Key value rule template. This parameter is mandatory when type is VARIABLE.

Table 5-119 SmnTargetDetail

Parameter	Mandatory	Type	Description
urn	Yes	String	Specifies the topic URN.
agency_name	Yes	String	Agency name.
subject_transform	No	subject_transform object	Title rule.

Table 5-120 subject_transform

Parameter	Mandatory	Type	Description
type	Yes	String	Type of the title rule.
value	Yes	String	Title rule.
template	No	String	Title rule template. This parameter is mandatory when type is set to VARIABLE.

Table 5-121 EgTargetDetail

Parameter	Mandatory	Type	Description
target_project_id	Yes	String	Target project ID.
target_channel_id	Yes	String	Target channel ID.
target_region	Yes	String	Target region.
cross_region	No	Boolean	Indicates whether cross-region feature is enabled.
agency_name	Yes	String	Agency name.

Table 5-122 ApigwTargetDetail

Parameter	Mandatory	Type	Description
url	Yes	String	Target URL.
invocation_http_parameters	No	InvocationHttpParameters object	Parameters for invoking HTTP.

Table 5-123 InvocationHttpParameters

Parameter	Mandatory	Type	Description
header_parameters	No	Array of HeaderParameter objects	Object list.

Table 5-124 HeaderParameter

Parameter	Mandatory	Type	Description
is_value_secret	No	Boolean	Whether to encrypt the value.
key	No	String	Header key.
value	No	String	Header value.

Table 5-125 DeadLetterQueue

Parameter	Mandatory	Type	Description
type	Yes	String	Queue type.
instance_id	Yes	String	Instance ID.
connection_id	Yes	String	Connection ID.
topic	Yes	String	Topic.

Table 5-126 RocketmqTargetDetail

Parameter	Mandatory	Type	Description
topic	No	String	Topic name.
key_transform	No	Transform object	Transform rule.

Table 5-127 TransForm

Parameter	Mandatory	Type	Description
type	Yes	String	Type of the transform rule.
value	No	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	No	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Response Parameters

Status code: 200

Table 5-128 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-129 Response body parameters

Parameter	Type	Description
id	String	ID of the event subscription target.
name	String	Name of the event subscription target.
provider_type	String	Provider type of the event subscription target.
connection_id	String	Connection ID used by the event subscription target.
detail	Object	List of event subscription target parameters.
kafka_detail	KafkaTargetDetail object	List of Kafka event subscription target parameters. The total length of this field after serialization cannot exceed 1024 bytes.
smn_detail	SmnTargetDetail object	List of SMN event target parameters for the subscription. The total length cannot exceed 1024 bytes after serialization.
eg_detail	EgTargetDetail object	List of EG event channel target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for EG channel event targets.
apigw_detail	ApigwTargetDetail object	List of APIGW URL target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for APIGW event targets.
retry_times	Integer	Number of retries.
transform	TransForm object	Transform rule of the event subscription target.
dead_letter_queue	DeadLetterQueue object	List of dead letter queue parameters for the subscription.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.
rocketmq_detail	RocketmqTargetDetail object	Parameters for RocketMQ in event subscription.

Table 5-130 KafkaTargetDetail

Parameter	Type	Description
topic	String	Topic.
keyTransform	keyTransform object	Key value rule.

Table 5-131 keyTransform

Parameter	Type	Description
type	String	Type of the key value rule.
value	String	Key value rule. This parameter is mandatory when type is VARIABLE or CONSTANT.
template	String	Key value rule template. This parameter is mandatory when type is VARIABLE.

Table 5-132 SmnTargetDetail

Parameter	Type	Description
urn	String	Specifies the topic URN.
agency_name	String	Agency name.
subject_transform	subject_transform object	Title rule.

Table 5-133 subject_transform

Parameter	Type	Description
type	String	Type of the title rule.
value	String	Title rule.
template	String	Title rule template. This parameter is mandatory when type is set to VARIABLE.

Table 5-134 EgTargetDetail

Parameter	Type	Description
target_project_id	String	Target project ID.
target_channel_id	String	Target channel ID.
target_region	String	Target region.
cross_region	Boolean	Indicates whether cross-region feature is enabled.
agency_name	String	Agency name.

Table 5-135 ApigwTargetDetail

Parameter	Type	Description
url	String	Target URL.
invocation_http_parameters	InvocationHttpParameters object	Parameters for invoking HTTP.

Table 5-136 InvocationHttpParameters

Parameter	Type	Description
header_parameters	Array of HeaderParameter objects	Object list.

Table 5-137 HeaderParameter

Parameter	Type	Description
is_value_secret	Boolean	Whether to encrypt the value.
key	String	Header key.
value	String	Header value.

Table 5-138 DeadLetterQueue

Parameter	Type	Description
type	String	Queue type.
instance_id	String	Instance ID.

Parameter	Type	Description
connection_id	String	Connection ID.
topic	String	Topic.

Table 5-139 RocketmqTargetDetail

Parameter	Type	Description
topic	String	Topic name.
key_transform	TransForm object	Transform rule.

Table 5-140 TransForm

Parameter	Type	Description
type	String	Type of the transform rule.
value	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Example Requests

Create an event subscription target.

```
POST https://{endpoint}/v1/{project_id}/subscriptions/{subscription_id}/targets
```

```
{
  "connection_id" : "456eekj3-778u-4tyu-dfrt-er55e37f667t",
  "detail" : {
    "agency_name" : "EG_TARGET_AGENCY",
    "invoke_type" : "ASYNC",
    "url" : "http://10.213.96.90:8080/t/nodeapp/trigger-hello-nodejs",
    "urn" : "urn:fss:cn-north-7:bac852160cc743158936edaab6dda813:function:default:gxtestjava:latest",
    "workflow_id" : "86afc904-0019-46c8-baed-0225967c1b98"
  },
  "id" : "3a0eeff2-78a4-4122-dfge-7ty5e37f64er",
  "name" : "WEBHOOK",
  "provider_type" : "CUSTOM",
  "retry_times" : 16,
  "transform" : {
    "type" : "VARIABLE"
  }
}
```

Example Responses

Status code: 200

Information

```
{
  "id" : "3a0eeff2-78a4-4122-dfge-7ty5e37f64er",
  "name" : "WEBHOOK",
  "provider_type" : "CUSTOM",
  "connection_id" : "456eekj3-778u-4tyu-dfrt-er55e37f667t",
  "detail" : {
    "url" : "http://10.213.96.90:8080/t/nodeapp/trigger-hello-nodejs"
  },
  "kafka_detail" : { },
  "smn_detail" : { },
  "eg_detail" : { },
  "apigw_detail" : { },
  "retry_times" : 16,
  "transform" : { },
  "dead_letter_queue" : { },
  "created_time" : "2021-12-09 09:00:00",
  "updated_time" : "2021-12-09 09:00:00"
}
```

Status Codes

Status Code	Description
200	Information

Error Codes

See [Error Codes](#).

5.1.8 Updating an Event Subscription Target

Function

This API is used to update the target of an event subscription.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

PUT /v1/{project_id}/subscriptions/{subscription_id}/targets/{target_id}

Table 5-141 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
subscription_id	Yes	String	ID of the event subscription.
target_id	Yes	String	ID of the event subscription target.

Table 5-142 Query Parameters

Parameter	Mandatory	Type	Description
enterprise_project_id	No	String	ID of an enterprise project used for creating a subscription.

Request Parameters

Table 5-143 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-144 Request body parameters

Parameter	Mandatory	Type	Description
id	No	String	Subscription target ID. The value must be globally unique. Only lowercase letters, digits, and hyphens (-) are allowed. It must start with a letter or digit. In the subscription update scenario, if the subscription target with the specified ID exists, the subscription target is updated. Otherwise, the subscription target is created. If no ID is specified, the system automatically generates an ID when creating the subscription target. If an ID is specified, the ID is used as the subscription target ID. This field is ignored when the subscription target is updated.
name	Yes	String	Name of the event subscription target.
provider_type	Yes	String	Provider type of the event subscription target.
connection_id	No	String	Connection ID used by the event subscription target.
detail	No	Object	List of event target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for function (urn, invoke_type, and agency_name), function flow (workflow_id and agency_name), and webhook (url) targets. An agency name must be specified for a function or function flow.
kafka_detail	No	KafkaTargetDetail object	List of Kafka event subscription target parameters. The total length of this field after serialization cannot exceed 1024 bytes.

Parameter	Mandatory	Type	Description
smn_detail	No	SmnTargetDetail object	List of SMN event target parameters for the subscription. The total length cannot exceed 1024 bytes after serialization.
eg_detail	No	EgTargetDetail object	List of EG event channel target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for EG channel event targets.
apigw_detail	No	ApigwTargetDetail object	List of APIGW URL target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for APIGW event targets.
retry_times	No	Integer	Number of retries.
transform	Yes	Transform object	Transform rule of the event subscription target.
dead_letter_queue	No	DeadLetterQueue object	List of dead letter queue parameters for the subscription.
rocketmq_detail	No	RocketmqTargetDetail object	Parameters for RocketMQ in event subscription.

Table 5-145 KafkaTargetDetail

Parameter	Mandatory	Type	Description
topic	Yes	String	Topic.
keyTransform	No	keyTransform object	Key value rule.

Table 5-146 keyTransform

Parameter	Mandatory	Type	Description
type	No	String	Type of the key value rule.

Parameter	Mandatory	Type	Description
value	No	String	Key value rule. This parameter is mandatory when type is VARIABLE or CONSTANT.
template	No	String	Key value rule template. This parameter is mandatory when type is VARIABLE.

Table 5-147 SmnTargetDetail

Parameter	Mandatory	Type	Description
urn	Yes	String	Specifies the topic URN.
agency_name	Yes	String	Agency name.
subject_transform	No	subject_transform object	Title rule.

Table 5-148 subject_transform

Parameter	Mandatory	Type	Description
type	Yes	String	Type of the title rule.
value	Yes	String	Title rule.
template	No	String	Title rule template. This parameter is mandatory when type is set to VARIABLE.

Table 5-149 EgTargetDetail

Parameter	Mandatory	Type	Description
target_project_id	Yes	String	Target project ID.
target_channel_id	Yes	String	Target channel ID.
target_region	Yes	String	Target region.
cross_region	No	Boolean	Indicates whether cross-region feature is enabled.
agency_name	Yes	String	Agency name.

Table 5-150 ApigwTargetDetail

Parameter	Mandatory	Type	Description
url	Yes	String	Target URL.
invocation_http_parameters	No	InvocationHttpParameters object	Parameters for invoking HTTP.

Table 5-151 InvocationHttpParameters

Parameter	Mandatory	Type	Description
header_parameters	No	Array of HeaderParameter objects	Object list.

Table 5-152 HeaderParameter

Parameter	Mandatory	Type	Description
is_value_secret	No	Boolean	Whether to encrypt the value.
key	No	String	Header key.
value	No	String	Header value.

Table 5-153 DeadLetterQueue

Parameter	Mandatory	Type	Description
type	Yes	String	Queue type.
instance_id	Yes	String	Instance ID.
connection_id	Yes	String	Connection ID.
topic	Yes	String	Topic.

Table 5-154 RocketmqTargetDetail

Parameter	Mandatory	Type	Description
topic	No	String	Topic name.
key_transform	No	Transform object	Transform rule.

Table 5-155 TransForm

Parameter	Mandatory	Type	Description
type	Yes	String	Type of the transform rule.
value	No	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	No	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Response Parameters

Status code: 200

Table 5-156 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-157 Response body parameters

Parameter	Type	Description
id	String	ID of the event subscription target.
name	String	Name of the event subscription target.
provider_type	String	Provider type of the event subscription target.
connection_id	String	Connection ID used by the event subscription target.
detail	Object	List of event subscription target parameters.
kafka_detail	KafkaTargetDetail object	List of Kafka event subscription target parameters. The total length of this field after serialization cannot exceed 1024 bytes.
smn_detail	SmnTargetDetail object	List of SMN event target parameters for the subscription. The total length cannot exceed 1024 bytes after serialization.
eg_detail	EgTargetDetail object	List of EG event channel target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for EG channel event targets.
apigw_detail	ApigwTargetDetail object	List of APIGW URL target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for APIGW event targets.
retry_times	Integer	Number of retries.
transform	TransForm object	Transform rule of the event subscription target.
dead_letter_queue	DeadLetterQueue object	List of dead letter queue parameters for the subscription.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.
rocketmq_detail	RocketmqTargetDetail object	Parameters for RocketMQ in event subscription.

Table 5-158 KafkaTargetDetail

Parameter	Type	Description
topic	String	Topic.
keyTransform	keyTransform object	Key value rule.

Table 5-159 keyTransform

Parameter	Type	Description
type	String	Type of the key value rule.
value	String	Key value rule. This parameter is mandatory when type is VARIABLE or CONSTANT.
template	String	Key value rule template. This parameter is mandatory when type is VARIABLE.

Table 5-160 SmnTargetDetail

Parameter	Type	Description
urn	String	Specifies the topic URN.
agency_name	String	Agency name.
subject_transform	subject_transform object	Title rule.

Table 5-161 subject_transform

Parameter	Type	Description
type	String	Type of the title rule.
value	String	Title rule.
template	String	Title rule template. This parameter is mandatory when type is set to VARIABLE.

Table 5-162 EgTargetDetail

Parameter	Type	Description
target_project_id	String	Target project ID.
target_channel_id	String	Target channel ID.
target_region	String	Target region.
cross_region	Boolean	Indicates whether cross-region feature is enabled.
agency_name	String	Agency name.

Table 5-163 ApigwTargetDetail

Parameter	Type	Description
url	String	Target URL.
invocation_http_parameters	InvocationHttpParameters object	Parameters for invoking HTTP.

Table 5-164 InvocationHttpParameters

Parameter	Type	Description
header_parameters	Array of HeaderParameter objects	Object list.

Table 5-165 HeaderParameter

Parameter	Type	Description
is_value_secret	Boolean	Whether to encrypt the value.
key	String	Header key.
value	String	Header value.

Table 5-166 DeadLetterQueue

Parameter	Type	Description
type	String	Queue type.
instance_id	String	Instance ID.

Parameter	Type	Description
connection_id	String	Connection ID.
topic	String	Topic.

Table 5-167 RocketmqTargetDetail

Parameter	Type	Description
topic	String	Topic name.
key_transform	Transform object	Transform rule.

Table 5-168 Transform

Parameter	Type	Description
type	String	Type of the transform rule.
value	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Example Requests

Update an event subscription target.

```
PUT https://{endpoint}/v1/{project_id}/subscriptions/{subscription_id}/targets/{target_id}
```

```
{
  "connection_id" : "456eekj3-778u-4tyu-dfrt-er55e37f667t",
  "detail" : {
    "agency_name" : "EG_TARGET_AGENCY",
    "invoke_type" : "ASYNC",
    "url" : "http://10.213.96.90:8080/t/nodeapp/trigger-hello-nodejs",
    "urn" : "urn:fss:cn-north-7:bac852160cc743158936edaab6dda813:function:default:gxtestjava:latest",
    "workflow_id" : "86afc904-0019-46c8-baed-0225967c1b98"
  },
  "id" : "3a0eeff2-78a4-4122-dfge-7ty5e37f64er",
  "name" : "WEBHOOK",
  "provider_type" : "CUSTOM",
  "retry_times" : 16,
  "transform" : {
    "type" : "VARIABLE"
  }
}
```

Example Responses

Status code: 200

Information

```
{
  "id" : "3a0eeff2-78a4-4122-dfge-7ty5e37f64er",
  "name" : "WEBHOOK",
  "provider_type" : "CUSTOM",
  "connection_id" : "456eekj3-778u-4tyu-dfrt-er55e37f667t",
  "detail" : {
    "url" : "http://10.213.96.90:8080/t/nodeapp/trigger-hello-nodejs"
  },
  "retry_times" : 16,
  "created_time" : "2021-12-09 09:00:00",
  "updated_time" : "2021-12-09 09:00:00"
}
```

Status Codes

Status Code	Description
200	Information

Error Codes

See [Error Codes](#).

5.1.9 Obtaining Event Subscription Target Details

Function

This API is used to obtain the details of an event subscription's target.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/subscriptions/{subscription_id}/targets/{target_id}

Table 5-169 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
subscription_id	Yes	String	ID of the event subscription.
target_id	Yes	String	ID of the event subscription target.

Table 5-170 Query Parameters

Parameter	Mandatory	Type	Description
enterprise_project_id	No	String	ID of an enterprise project used for creating a subscription.

Request Parameters

Table 5-171 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-172 Response body parameters

Parameter	Type	Description
id	String	ID of the event subscription target.
name	String	Name of the event subscription target.

Parameter	Type	Description
provider_type	String	Provider type of the event subscription target.
connection_id	String	Connection ID used by the event subscription target.
detail	Object	List of event subscription target parameters.
kafka_detail	KafkaTargetDetail object	List of Kafka event subscription target parameters. The total length of this field after serialization cannot exceed 1024 bytes.
smn_detail	SmnTargetDetail object	List of SMN event target parameters for the subscription. The total length cannot exceed 1024 bytes after serialization.
eg_detail	EgTargetDetail object	List of EG event channel target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for EG channel event targets.
apigw_detail	ApigwTargetDetail object	List of APIGW URL target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for APIGW event targets.
retry_times	Integer	Number of retries.
transform	Transform object	Transform rule of the event subscription target.
dead_letter_queue	DeadLetterQueue object	List of dead letter queue parameters for the subscription.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.
rocketmq_detail	RocketmqTargetDetail object	Parameters for RocketMQ in event subscription.

Table 5-173 KafkaTargetDetail

Parameter	Type	Description
topic	String	Topic.
keyTransform	keyTransform object	Key value rule.

Table 5-174 keyTransform

Parameter	Type	Description
type	String	Type of the key value rule.
value	String	Key value rule. This parameter is mandatory when type is VARIABLE or CONSTANT.
template	String	Key value rule template. This parameter is mandatory when type is VARIABLE.

Table 5-175 SmnTargetDetail

Parameter	Type	Description
urn	String	Specifies the topic URN.
agency_name	String	Agency name.
subject_transform	subject_transform object	Title rule.

Table 5-176 subject_transform

Parameter	Type	Description
type	String	Type of the title rule.
value	String	Title rule.
template	String	Title rule template. This parameter is mandatory when type is set to VARIABLE.

Table 5-177 EgTargetDetail

Parameter	Type	Description
target_project_id	String	Target project ID.
target_channel_id	String	Target channel ID.
target_region	String	Target region.
cross_region	Boolean	Indicates whether cross-region feature is enabled.
agency_name	String	Agency name.

Table 5-178 ApigwTargetDetail

Parameter	Type	Description
url	String	Target URL.
invocation_http_parameters	InvocationHttpParameters object	Parameters for invoking HTTP.

Table 5-179 InvocationHttpParameters

Parameter	Type	Description
header_parameters	Array of HeaderParameter objects	Object list.

Table 5-180 HeaderParameter

Parameter	Type	Description
is_value_secret	Boolean	Whether to encrypt the value.
key	String	Header key.
value	String	Header value.

Table 5-181 DeadLetterQueue

Parameter	Type	Description
type	String	Queue type.
instance_id	String	Instance ID.

Parameter	Type	Description
connection_id	String	Connection ID.
topic	String	Topic.

Table 5-182 RocketmqTargetDetail

Parameter	Type	Description
topic	String	Topic name.
key_transform	Transform object	Transform rule.

Table 5-183 Transform

Parameter	Type	Description
type	String	Type of the transform rule.
value	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Example Requests

Obtain event subscription target details.

```
GET https://{endpoint}/v1/{project_id}/subscriptions/{subscription_id}/targets/{target_id}
```

Example Responses

Status code: 200

Operation successful.

```
{
  "id" : "3a0eeff2-78a4-4122-dfge-7ty5e37f64er",
  "name" : "WEBHOOK",
  "provider_type" : "CUSTOM",
  "connection_id" : "456eekj3-778u-4tyu-dfirt-er55e37f667t",
  "detail" : {
    "url" : "http://10.213.96.90:8080/t/nodeapp/trigger-hello-nodejs"
  },
  "kafka_detail" : { },
  "smn_detail" : { },
  "eg_detail" : { },
  "apigw_detail" : { },
  "retry_times" : 16,
  "transform" : { },
  "dead_letter_queue" : { },
  "created_time" : "2021-12-09 09:00:00",
  "updated_time" : "2021-12-09 09:00:00"
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.1.10 Deleting an Event Subscription Target

Function

This API is used to delete the target of an event subscription.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

DELETE /v1/{project_id}/subscriptions/{subscription_id}/targets/{target_id}

Table 5-184 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
subscription_id	Yes	String	ID of the event subscription.
target_id	Yes	String	ID of the event subscription target.

Table 5-185 Query Parameters

Parameter	Mandatory	Type	Description
enterprise_project_id	No	String	ID of an enterprise project used for creating a subscription.

Request Parameters

Table 5-186 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 204

Operation successful.

None

Example Requests

Delete an event subscription target.

```
DELETE https://{endpoint}/v1/{project_id}/subscriptions/{subscription_id}/targets/{target_id}
```

Example Responses

None

Status Codes

Status Code	Description
204	Operation successful.

Error Codes

See [Error Codes](#).

5.1.11 Enabling or Disabling Event Subscriptions

Function

This API is used to enable or disable event subscriptions.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/subscriptions/operation

Table 5-187 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-188 Query Parameters

Parameter	Mandatory	Type	Description
enterprise_project_id	No	String	ID of an enterprise project used for creating a subscription.

Request Parameters

Table 5-189 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-190 Request body parameters

Parameter	Mandatory	Type	Description
subscription_ids	No	Array of strings	List of subscription IDs. A maximum of 10 subscriptions are supported in batch.
operation	No	String	Operation type.

Response Parameters

Status code: 200

Table 5-191 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-192 Response body parameters

Parameter	Type	Description
failed_count	Integer	Number of subscriptions that fail to be operated.
events	Array of events objects	Event list.

Table 5-193 events

Parameter	Type	Description
error_code	String	Error code.
error_msg	String	Failure cause.
subscription_id	String	Subscription ID.

Example Requests

Enable or disable event subscriptions.

POST https://{endpoint}/v1/{project_id}/subscriptions/operation

```
{
  "subscription_ids" : [ "23709d68-54d5-423b-a6be-03302e893152" ],
  "operation" : "DISABLE"
}
```

Example Responses

Status code: 200

Demo Information

```
{
  "failed_count" : 0,
  "events" : [ {
    "subscription_id" : "23709d68-54d5-423b-a6be-03302e893152"
  } ]
}
```

Status Codes

Status Code	Description
200	Demo Information

Error Codes

See [Error Codes](#).

5.2 Event Channel Management

5.2.1 Creating a Custom Event Channel

Function

This API is used to create a custom event channel.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/channels

Table 5-194 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-195 Query Parameters

Parameter	Mandatory	Type	Description
enterprise_project_id	No	String	ID of an enterprise project used for creating a channel.

Request Parameters

Table 5-196 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-197 Request body parameters

Parameter	Mandatory	Type	Description
name	Yes	String	Name of the event channel. The value must be unique under a tenant. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot be default.

Parameter	Mandatory	Type	Description
description	No	String	Description of the event channel.
enterprise_project_id	No	String	Enterprise project ID.
provider_type	No	String	Event channel type. The options are CUSTOM (custom event channel) and INTERNAL (internal event channel).
policy	No	Object	Policy.

Response Parameters

Status code: 200

Table 5-198 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-199 Response body parameters

Parameter	Type	Description
id	String	ID of the event channel.
name	String	Name of the event channel.
description	String	Description of the event channel.
provider_type	String	Event channel provider type, which can be OFFICIAL (official event channel), CUSTOM (custom event channel), or PARTNER (partner event channel).
created_time	String	UTC time when the event channel is created.
updated_time	String	UTC time when the event channel is updated.
enterprise_project_id	String	Enterprise project ID.

Example Requests

Create a custom event channel.

POST https://{endpoint}/v1/{project_id}/channels

```
{
  "name" : "channel",
  "description" : "first channel",
  "enterprise_project_id" : "string",
  "provider_type" : "CUSTOM",
  "policy" : {
    "additionalProp1" : {
      "Sid" : "allow_account_to_put_events",
      "Effect" : "Allow",
      "Principal" : {
        "additionalProp1" : {
          "IAM" : [ "domainID" ]
        },
        "additionalProp2" : {
          "IAM" : [ "domainID" ]
        },
        "additionalProp3" : {
          "IAM" : [ "domainID" ]
        }
      },
      "Action" : "eg:channels:putEvents",
      "Resource" : "urn:eg:cn-east-2:07d52e5245000fef0f08c008b20dc5c0:channel:testChannel"
    },
    "additionalProp2" : {
      "Sid" : "allow_account_to_put_events",
      "Effect" : "Allow",
      "Principal" : {
        "additionalProp1" : {
          "IAM" : [ "domainID" ]
        },
        "additionalProp2" : {
          "IAM" : [ "domainID" ]
        },
        "additionalProp3" : {
          "IAM" : [ "domainID" ]
        }
      },
      "Action" : "eg:channels:putEvents",
      "Resource" : "urn:eg:cn-east-2:07d52e5245000fef0f08c008b20dc5c0:channel:testChannel"
    },
    "additionalProp3" : {
      "Sid" : "allow_account_to_put_events",
      "Effect" : "Allow",
      "Principal" : {
        "additionalProp1" : {
          "IAM" : [ "domainID" ]
        },
        "additionalProp2" : {
          "IAM" : [ "domainID" ]
        },
        "additionalProp3" : {
          "IAM" : [ "domainID" ]
        }
      },
      "Action" : "eg:channels:putEvents",
      "Resource" : "urn:eg:cn-east-2:07d52e5245000fef0f08c008b20dc5c0:channel:testChannel"
    }
  }
}
```

Example Responses

Status code: 200

Demo Information

```
{
  "id" : "bd14144e-8f3c-43d6-bdfd-bf09b52c2b96",
  "name" : "channel",
  "description" : "first channel",
  "provider_type" : "CUSTOM",
  "created_time" : "2021-12-09 09:00:00",
  "updated_time" : "2021-12-09 09:00:00",
  "enterprise_project_id" : "string"
}
```

Status Codes

Status Code	Description
200	Demo Information

Error Codes

See [Error Codes](#).

5.2.2 Obtaining the Event Channel List

Function

This API is used to obtain the list of event channels, including system and custom channels.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/channels

Table 5-200 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-201 Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Offset, which is the position where the query starts. The value must be greater than or equal to 0.
limit	No	Integer	Number of records displayed on each page. The value must be within the range [1, 1000].
sort	No	String	Sorting mode of the query results.
provider_type	No	String	Type of the provider.
name	No	String	Name of the event channel. It is used for exact match.
fuzzy_name	No	String	Name of the event channel. It is used for fuzzy match.
enterprise_project_id	No	String	Enterprise project ID for exact match.

Request Parameters

Table 5-202 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-203 Response body parameters

Parameter	Type	Description
total	Integer	Total number of records.

Parameter	Type	Description
size	Integer	Number of records displayed on the current page.
items	Array of ChannelInfo objects	Object list.

Table 5-204 ChannelInfo

Parameter	Type	Description
id	String	ID of the event channel.
name	String	Name of the event channel.
description	String	Description of the event channel.
provider_type	String	Event channel provider type, which can be OFFICIAL (official event channel), CUSTOM (custom event channel), or PARTNER (partner event channel).
created_time	String	UTC time when the event channel is created.
updated_time	String	UTC time when the event channel is updated.
enterprise_project_id	String	Enterprise project ID.

Example Requests

Obtain the event channel list.

```
GET https://{endpoint}/v1/{project_id}/channels
```

Example Responses

Status code: 200

Operation successful.

```
{
  "total" : 1,
  "size" : 1,
  "items" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.2.3 Updating a Custom Event Channel

Function

This API is used to update a custom event channel.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

PUT /v1/{project_id}/channels/{channel_id}

Table 5-205 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
channel_id	Yes	String	ID of the event channel.

Table 5-206 Query Parameters

Parameter	Mandatory	Type	Description
enterprise_project_id	No	String	Enterprise project ID.

Request Parameters

Table 5-207 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-208 Request body parameters

Parameter	Mandatory	Type	Description
description	No	String	Description of the event channel.
enterprise_project_id	No	String	Enterprise project ID.
policy	No	Object	Policy.

Response Parameters

Status code: 200

Table 5-209 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-210 Response body parameters

Parameter	Type	Description
id	String	ID of the event channel.
name	String	Name of the event channel.
description	String	Description of the event channel.

Parameter	Type	Description
provider_type	String	Event channel provider type, which can be OFFICIAL (official event channel), CUSTOM (custom event channel), or PARTNER (partner event channel).
created_time	String	UTC time when the event channel is created.
updated_time	String	UTC time when the event channel is updated.
enterprise_project_id	String	Enterprise project ID.

Example Requests

Update a custom event channel.

PUT https://{endpoint}/v1/{project_id}/channels/{channel_id}

```
{
  "description": "first channel",
  "enterprise_project_id": "string",
  "policy": {
    "additionalProp1": {
      "Sid": "allow_account_to_put_events",
      "Effect": "Allow",
      "Principal": {
        "additionalProp1": {
          "IAM": [ "domainID" ]
        },
        "additionalProp2": {
          "IAM": [ "domainID" ]
        },
        "additionalProp3": {
          "IAM": [ "domainID" ]
        }
      },
      "Action": "eg:channels:putEvents",
      "Resource": "urn:eg:cn-east-2:07d52e5245000fef0f08c008b20dc5c0:channel:testChannel"
    },
    "additionalProp2": {
      "Sid": "allow_account_to_put_events",
      "Effect": "Allow",
      "Principal": {
        "additionalProp1": {
          "IAM": [ "domainID" ]
        },
        "additionalProp2": {
          "IAM": [ "domainID" ]
        },
        "additionalProp3": {
          "IAM": [ "domainID" ]
        }
      },
      "Action": "eg:channels:putEvents",
      "Resource": "urn:eg:cn-east-2:07d52e5245000fef0f08c008b20dc5c0:channel:testChannel"
    },
    "additionalProp3": {
      "Sid": "allow_account_to_put_events",
      "Effect": "Allow",

```

```
{
  "Principal": {
    "additionalProp1": {
      "IAM": [ "domainID" ]
    },
    "additionalProp2": {
      "IAM": [ "domainID" ]
    },
    "additionalProp3": {
      "IAM": [ "domainID" ]
    }
  },
  "Action": "eg:channels:putEvents",
  "Resource": "urn:eg:cn-east-2:07d52e5245000fef0f08c008b20dc5c0:channel:testChannel"
}
```

Example Responses

Status code: 200

Information

```
{
  "id": "bd14144e-8f3c-43d6-bdfd-bf09b52c2b96",
  "name": "channel",
  "description": "first channel",
  "provider_type": "CUSTOM",
  "created_time": "2021-12-09 09:00:00",
  "updated_time": "2021-12-09 09:00:00",
  "enterprise_project_id": "string"
}
```

Status Codes

Status Code	Description
200	Information

Error Codes

See [Error Codes](#).

5.2.4 Obtaining Event Channel Details

Function

This API is used to obtain the details about an event channel.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/channels/{channel_id}

Table 5-211 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
channel_id	Yes	String	ID of the event channel.

Table 5-212 Query Parameters

Parameter	Mandatory	Type	Description
enterprise_project_id	No	String	Enterprise project ID.

Request Parameters

Table 5-213 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-214 Response body parameters

Parameter	Type	Description
id	String	ID of the event channel.
name	String	Name of the event channel.
description	String	Description of the event channel.

Parameter	Type	Description
provider_type	String	Event channel provider type, which can be OFFICIAL (official event channel), CUSTOM (custom event channel), or PARTNER (partner event channel).
created_time	String	UTC time when the event channel is created.
updated_time	String	UTC time when the event channel is updated.
enterprise_project_id	String	Enterprise project ID.

Example Requests

Obtain event channel details.

```
GET https://{endpoint}/v1/{project_id}/channels/{channel_id}
```

Example Responses

Status code: 200

Operation successful.

```
{
  "id" : "bd14144e-8f3c-43d6-bdfd-bf09b52c2b96",
  "name" : "channel",
  "description" : "first channel",
  "provider_type" : "CUSTOM",
  "created_time" : "2021-12-09 09:00:00",
  "updated_time" : "2021-12-09 09:00:00",
  "enterprise_project_id" : "string"
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.2.5 Deleting a Custom Event Channel

Function

This API is used to delete a custom event channel.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

DELETE /v1/{project_id}/channels/{channel_id}

Table 5-215 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
channel_id	Yes	String	ID of the event channel.

Table 5-216 Query Parameters

Parameter	Mandatory	Type	Description
enterprise_project_id	No	String	Enterprise project ID.

Request Parameters

Table 5-217 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 204

Operation successful.

None

Example Requests

Delete a custom event channel.

DELETE https://{endpoint}/v1/{project_id}/channels/{channel_id}

Example Responses

None

Status Codes

Status Code	Description
204	Operation successful.

Error Codes

See [Error Codes](#).

5.3 Event Management

5.3.1 Viewing Event Trace Details

Function

This API is used to view details about delivering an event from the source to the target.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/events/trace/detail/{trace_id}

Table 5-218 Path Parameters

Parameter	Mandatory	Type	Description
trace_id	Yes	String	Unique event ID.
project_id	Yes	String	Tenant resource space ID.

Table 5-219 Query Parameters

Parameter	Mandatory	Type	Description
channel_id	Yes	String	Channel ID.

Request Parameters

Table 5-220 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-221 Response body parameters

Parameter	Type	Description
eventId	String	Event ID.
eventSource	String	Event source.
eventType	String	Event type.
receiveTime	String	Receiving time.
channelId	String	Channel ID.
channelName	String	Channel name.
deliverList	Array of DeliverItem objects	List of delivered events.

Table 5-222 DeliverItem

Parameter	Type	Description
subscriptionId	String	Subscription ID, which is globally unique.

Parameter	Type	Description
subscriptionName	String	Subscription name.
successCounts	Integer	The number of successful deliveries.
failCounts	Integer	The number of failed deliveries.
allDeliverTimes	Integer	Total number of deliveries.
deliverTargetList	Array of DeliverTarget objects	Delivery details.

Table 5-223 DeliverTarget

Parameter	Type	Description
deliverTargetId	String	Delivery target ID, that is, the event target ID.
deliverTargetName	String	Delivery target name, that is, the event target name.
deliverStatus	String	Delivery status. Options: SUCCESS or FAILED.
deliverDetailList	Array of DeliverDetail objects	Number of records to be displayed. For example, only the latest three records are displayed.

Table 5-224 DeliverDetail

Parameter	Type	Description
deliverTime	String	Delivery time. Format: yyyy/mm/dd xx:yy:zz
deliverStatus	String	Delivery status. Options: SUCCESS or FAILED.
deliverConsuming	String	Time spent in the delivery. Unit: ms.
deliverRspCode	String	Delivery response code.

Example Requests

View event trace details.

```
GET https://{endpoint}/v1/{project_id}/events/trace/detail/{trace_id}
```

Example Responses

Status code: 200

Event trace response body.

```
{
  "eventId" : "21637dd2-c4af-46e9-a4ba-f21b71deaa82",
  "eventSource" : null,
  "eventType" : null,
  "receiveTime" : 0,
  "channelId" : "65688f41-81d4-479f-bd8f-9727e7595128",
  "channelName" : "default",
  "deliverList" : [ {
    "subscriptionId" : "83799a5c-4e3e-49e5-b2cf-a5aa38758ee0",
    "subscriptionName" : "subscription-03us",
    "successCounts" : 0,
    "failCounts" : 1,
    "allDeliverTimes" : 7,
    "deliverTargetList" : [ {
      "deliverTargetId" : "2ae78b38-46c5-4f64-a1d3-0fc6b0b9324e",
      "deliverTargetName" : "HC.FunctionGraph",
      "deliverStatus" : "fail",
      "deliverDetailList" : [ {
        "deliverTime" : "2023-03-17 18:37:38",
        "deliverStatus" : "FAILED",
        "deliverConsuming" : 1679049458706,
        "deliverRspCode" : ""
      }, {
        "deliverTime" : "2023-03-17 18:37:38",
        "deliverStatus" : "FAILED",
        "deliverConsuming" : 0,
        "deliverRspCode" : ""
      }, {
        "deliverTime" : "2023-03-17 18:37:38",
        "deliverStatus" : "FAILED",
        "deliverConsuming" : 0,
        "deliverRspCode" : ""
      }, {
        "deliverTime" : "2023-03-17 18:37:38",
        "deliverStatus" : "FAILED",
        "deliverConsuming" : 0,
        "deliverRspCode" : ""
      }, {
        "deliverTime" : "2023-03-17 18:37:38",
        "deliverStatus" : "FAILED",
        "deliverConsuming" : 0,
        "deliverRspCode" : ""
      }, {
        "deliverTime" : "2023-03-17 18:37:38",
        "deliverStatus" : "FAILED",
        "deliverConsuming" : 0,
        "deliverRspCode" : ""
      }
      ]
    }
  ]
}
```

Status Codes

Status Code	Description
200	Event trace response body.

Error Codes

See [Error Codes](#).

5.3.2 Obtaining Sent Message Content

Function

This API is used to obtain the details of an event based on the event ID.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/events/detail/{trace_id}

Table 5-225 Path Parameters

Parameter	Mandatory	Type	Description
trace_id	Yes	String	Unique ID of a trace.
project_id	Yes	String	Tenant resource space ID.

Request Parameters

Table 5-226 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-227 Response body parameters

Parameter	Type	Description
-	String	Operation successful.

Example Requests

Obtain sent message content.

```
GET https://{endpoint}/v1/{project_id}/events/detail/{trace_id}
```

Example Responses

None

Status Codes

Status Code	Description
200	Event content.

Error Codes

See [Error Codes](#).

5.3.3 Obtaining the Event Trace List

Function

This API is used to obtain the event trace list.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

```
GET /v1/{project_id}/traced-events
```

Table 5-228 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-229 Query Parameters

Parameter	Mandatory	Type	Description
start_time	Yes	Long	Start time for querying data.
end_time	Yes	Long	End time for querying data.
event_id	No	String	Event ID for query.
source_name	No	String	Event source name.
event_type	No	String	Event type for exact match.
subscription_name	No	String	Event subscription name.
limit	No	String	Number of items displayed on each page. The value cannot be less than 0.
offset	No	Integer	Offset, which is the position where the query starts. The value must be greater than or equal to 0.
channel_id	Yes	String	Channel ID.

Request Parameters

Table 5-230 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-231 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-232 Response body parameters

Parameter	Type	Description
total	Integer	Total number.
size	Integer	Number of records displayed on the current page.
result	Array of result objects	Event trace list.

Table 5-233 result

Parameter	Type	Description
subscription_name	String	Event subscription name.
source_name	String	Event source name.
source_provider	String	Event source provider.
event_type	String	Event type.
event_id	String	Event ID.
event_received_time	Integer	Event receiving time.

Example Requests

Obtain the event trace list.

```
GET https://{endpoint}/v1/{project_id}/traced-events
```

Example Responses

Status code: 200

Information

```
{  
  "total" : 1,  
  "size" : 1,
```

```
"result" : [ {  
  "subscription_name" : "subscription-xxxx",  
  "source_name" : "HC.SMN",  
  "source_provider" : "OFFICIAL",  
  "event_type" : "SMN:CloudTrace:ConsoleAction",  
  "event_id" : "ace774cb-d3f1-49c1-9d8b-9efd086ac9e00533366",  
  "event_received_time" : 1677651126823  
} ]  
}
```

Status Codes

Status Code	Description
200	Information

Error Codes

See [Error Codes](#).

5.3.4 Publishing an Event to an Event Channel

Function

This API is used to publish an event to an event channel. The API is only used for debugging purposes.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/channels/{channel_id}/events

Table 5-234 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
channel_id	Yes	String	ID of the event channel.

Request Parameters

Table 5-235 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-236 Request body parameters

Parameter	Mandatory	Type	Description
events	No	Array of CloudEvents objects	CloudEvents event format definition. For details, see https://github.com/cloudevents/spec/blob/v1.0.1/spec.md .

Table 5-237 CloudEvents

Parameter	Mandatory	Type	Description
id	Yes	String	Event ID. The ID must be unique for the same event source.
source	Yes	String	Event source name. The combination of source and id uniquely identifies an event. The URI-Reference format is used. For details, see https://tools.ietf.org/html/rfc3986#section-4.1 .
specversion	Yes	String	CloudEvents protocol version. The format is major.minor.
type	Yes	String	Event type.
datacontenttype	No	String	Event content format. Events use the MIME format and comply with RFC 2046. For details, see https://tools.ietf.org/html/rfc2046 .

Parameter	Mandatory	Type	Description
dataschema	No	String	URI defined by the event content schema, which complies with RFC 3986. For details, see https://tools.ietf.org/html/rfc3986#section-4.3 .
data	No	Object	Event payload content, which uses the format specified by the datacontenttype field. The content field complies with the description of the dataschema field.
time	No	String	UTC time when the event occurs. Events from the same source have the same format, which complies with RFC 3339. An example format is 2018-04-05T17:31:00Z. For details, see https://tools.ietf.org/html/rfc3339 .
subject	No	String	Subject or object where the event occurs.

Response Parameters

Status code: 200

Table 5-238 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-239 Response body parameters

Parameter	Type	Description
failed_count	Integer	Number of events that fail to be published.
events	Array of events objects	Event list.

Table 5-240 events

Parameter	Type	Description
error_code	String	Error code displayed for the publishing failure.
error_msg	String	Cause of the publishing failure.
event_id	String	Unique ID of the event.

Example Requests

Publish events to an event channel.

```
POST https://{endpoint}/v1/{project_id}/channels/{channel_id}/events
{
  "events": [ {
    "id": "id",
    "source": "source",
    "specversion": "specversion",
    "type": "blob_created"
  } ]
}
```

Example Responses

Status code: 200

Information

```
{
  "failed_count": 0,
  "events": [ {
    "event_id": "r652c3f4e52c4eab89265b7a09ae6196"
  } ]
}
```

Status Codes

Status Code	Description
200	Information

Error Codes

See [Error Codes](#).

5.3.5 Publishing an Official Event to an Event Channel

Function

This API is used to publish an official event to an event channel.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/official/sources/{source_name}/events

Table 5-241 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
source_name	Yes	String	Name of the event source.

Request Parameters

Table 5-242 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-243 Request body parameters

Parameter	Mandatory	Type	Description
events	No	Array of CloudEvents objects	CloudEvents event format definition. For details, see https://github.com/cloudevents/spec/blob/v1.0.1/spec.md .

Table 5-244 CloudEvents

Parameter	Mandatory	Type	Description
id	Yes	String	Event ID. The ID must be unique for the same event source.

Parameter	Mandatory	Type	Description
source	Yes	String	Event source name. The combination of source and id uniquely identifies an event. The URI-Reference format is used. For details, see https://tools.ietf.org/html/rfc3986#section-4.1 .
specversion	Yes	String	CloudEvents protocol version. The format is major.minor.
type	Yes	String	Event type.
datacontenttype	No	String	Event content format. Events use the MIME format and comply with RFC 2046. For details, see https://tools.ietf.org/html/rfc2046 .
dataschema	No	String	URI defined by the event content schema, which complies with RFC 3986. For details, see https://tools.ietf.org/html/rfc3986#section-4.3 .
data	No	Object	Event payload content, which uses the format specified by the datacontenttype field. The content field complies with the description of the dataschema field.
time	No	String	UTC time when the event occurs. Events from the same source have the same format, which complies with RFC 3339. An example format is 2018-04-05T17:31:00Z. For details, see https://tools.ietf.org/html/rfc3339 .
subject	No	String	Subject or object where the event occurs.

Response Parameters

Status code: 200

Table 5-245 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-246 Response body parameters

Parameter	Type	Description
failed_count	Integer	Number of events that fail to be published.
events	Array of events objects	Event list.

Table 5-247 events

Parameter	Type	Description
error_code	String	Error code displayed for the publishing failure.
error_msg	String	Cause of the publishing failure.
event_id	String	Unique ID of the event.

Example Requests

Publish an official event to an event channel.

```
POST https://{endpoint}/v1/{project_id}/official/sources/{source_name}/events
```

```
{
  "events": [ {
    "id": "id",
    "source": "source",
    "specversion": "specversion",
    "type": "blob_created"
  } ]
}
```

Example Responses

Status code: 200

Information

```
{
  "failed_count": 0,
  "events": [ {
    "event_id": "r652c3f4e52c4eab89265b7a09ae6196"
  } ]
}
```

```
}]  
}
```

Status Codes

Status Code	Description
200	Information

Error Codes

See [Error Codes](#).

5.3.6 Prechecking Event Publishing Status

Function

This API is used to precheck whether the events from an event source can be published successfully. For example, an event can be published successfully only if there is a subscription to the event source.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/events/check

Table 5-248 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Request Parameters

Table 5-249 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-250 Request body parameters

Parameter	Mandatory	Type	Description
sources	No	Array of sources objects	Event source parameters.

Table 5-251 sources

Parameter	Mandatory	Type	Description
channel_id	No	String	ID of the event channel.
source_name	No	String	Name of the event source.

Response Parameters

Status code: 200

Table 5-252 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-253 Response body parameters

Parameter	Type	Description
failed_count	Integer	Number of events that fail the precheck.
sources	Array of CheckPutEventsResult objects	Event source parameters.

Table 5-254 CheckPutEventsResult

Parameter	Type	Description
channel_id	String	ID of the event channel.
source_name	String	Name of the event source.
check_result	Boolean	Result indicating whether the event will be successfully published.
check_detail	String	Details about the precheck result.

Example Requests

Precheck event publishing status.

```
POST https://{endpoint}/v1/{project_id}/events/check
```

```
{
  "sources": [ {
    "channel_id": "092e1243e88146768798b0e8c9933192",
    "source_name": "source-demo"
  } ]
}
```

Example Responses

Status code: 200

Information

```
{
  "failed_count": 0,
  "sources": [ { } ]
}
```

Status Codes

Status Code	Description
200	Information

Error Codes

See [Error Codes](#).

5.4 Event Source Management

5.4.1 Creating a Custom Event Source

Function

This API is used to create a custom event source, which must use a custom event channel.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/sources

Table 5-255 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Request Parameters

Table 5-256 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-257 Request body parameters

Parameter	Mandatory	Type	Description
name	Yes	String	Name of the custom event source. The value must be unique under a tenant. Only lowercase letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with hc..
description	No	String	Description of the event source.
type	No	String	Type of the event source.
detail	No	EventSourceDetail object	Message instance connection information encapsulated in JSON format.

Table 5-258 EventSourceDetail

Parameter	Mandatory	Type	Description
instance_id	No	String	Message queue instance ID.
group	Yes	String	Consumer group.
topic	Yes	String	Topic
access_key	Yes	String	Username.
secret_key	Yes	String	Secret key.
vpc_id	No	String	VPC ID.
subnet_id	No	String	Subnet ID.
namesrv_address	No	String	Connection address.
ssl_enable	No	Boolean	SSL
enable_acl	No	Boolean	Whether to enable access control.
vhost_name	No	String	RabbitMQ exchange name.
queue_name	No	String	RabbitMQ queue name.
user_name	No	String	Username.
password	No	String	Password.

Response Parameters

Status code: 200

Table 5-259 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-260 Response body parameters

Parameter	Type	Description
id	String	ID of the event source.
name	String	Name of the event source.
label	String	Label of the event source.
description	String	Description of the event source.
provider_type	String	Type of the event source provider, which can be OFFICIAL (official cloud service event source), CUSTOM (custom event source), or PARTNER (partner event source).
event_types	Array of event_types objects	List of event types provided by the event source. Only the official cloud service event source provides event types.
created_time	String	UTC time when the event source is created.
updated_time	String	UTC time when the event source is updated.
channel_name	String	Name of the event channel to which the event source belongs.
type	String	Type of the event source.
detail	Object	Connection information encapsulated in JSON format in the message instance, such as the instance_id field of the RabbitMQ instance, vhost field of the virtual host, queue field, username, and password.
status	String	Status of the custom event source.

Parameter	Type	Description
error_info	ErrorInfo object	Error message.

Table 5-261 event_types

Parameter	Type	Description
name	String	Name of the event type.
description	String	Description of the event type.

Table 5-262 ErrorInfo

Parameter	Type	Description
error_code	String	Error code.
error_detail	String	Error details.
error_msg	String	Error message.

Example Requests

Create a custom event source.

```
POST https://{endpoint}/v1/{project_id}/sources
{
  "name": "first-source",
  "description": "first event source",
  "channel_id": "bd14144e-8f3c-43d6-bdfd-bf09b52c2b96",
  "type": "RABBITMQ"
}
```

Example Responses

Status code: 200

Operation successful.

```
{
  "id": "90e0b962-c6c1-438c-ba8a-3024fe592bda",
  "name": "first-source",
  "label": "first-source",
  "description": "first event source",
  "provider_type": "CUSTOM",
  "event_types": [ {
    "name": "OBS:CloudTrace:ApiCall",
    "description": "Service API call type event."
  } ],
  "created_time": "2021-12-09 09:00:00",
  "updated_time": "2021-12-09 09:00:00",
  "channel_name": "channel",
  "type": "RABBITMQ",
}
```

```
"detail" : "{ \"instance_id\": \"ac14144e-9v3c-43d6-acfd-bf09b52c98uy\", \"user_name\": \"rabbitmq_user\", \"password\": \"changeme\", \"vhost_name\": \"vhost_name\", \"queue_name\": \"queue_name\" }\", \"status\" : \"RUNNING\", \"error_info\" : { } }
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.4.2 Obtaining the Event Source List

Function

This API is used to obtain the list of event sources that meet certain conditions. For example, you can specify an event channel ID to obtain all event sources in this channel.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/sources

Table 5-263 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-264 Query Parameters

Parameter	Mandatory	Type	Description
channel_id	No	String	ID of the event channel.

Parameter	Mandatory	Type	Description
offset	No	Integer	Offset, which is the position where the query starts. The value must be greater than or equal to 0.
limit	No	Integer	Number of records displayed on each page. The value must be within the range [1, 1000].
sort	No	String	Sorting mode of the query results.
provider_type	No	String	Type of the provider.
name	No	String	Name of the event source. It is used for exact match.
fuzzy_name	No	String	Name of the event source. It is used for fuzzy match.
fuzzy_label	No	String	Label of the event source. It is used for fuzzy match.

Request Parameters

Table 5-265 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-266 Response body parameters

Parameter	Type	Description
total	Integer	Total number of records.
size	Integer	Number of records displayed on the current page.

Parameter	Type	Description
items	Array of CustomizeSourceInfo objects	Object list.

Table 5-267 CustomizeSourceInfo

Parameter	Type	Description
id	String	ID of the event source.
name	String	Name of the event source.
label	String	Label of the event source.
description	String	Description of the event source.
provider_type	String	Type of the event source provider, which can be OFFICIAL (official cloud service event source), CUSTOM (custom event source), or PARTNER (partner event source).
event_types	Array of event_types objects	List of event types provided by the event source. Only the official cloud service event source provides event types.
created_time	String	UTC time when the event source is created.
updated_time	String	UTC time when the event source is updated.
channel_name	String	Name of the event channel to which the event source belongs.
type	String	Type of the event source.
detail	Object	Connection information encapsulated in JSON format in the message instance, such as the instance_id field of the RabbitMQ instance, vhost field of the virtual host, queue field, username, and password.
status	String	Status of the custom event source.
error_info	ErrorInfo object	Error message.

Table 5-268 event_types

Parameter	Type	Description
name	String	Name of the event type.
description	String	Description of the event type.

Table 5-269 ErrorInfo

Parameter	Type	Description
error_code	String	Error code.
error_detail	String	Error details.
error_msg	String	Error message.

Example Requests

Obtain the event source list.

```
GET https://{endpoint}/v1/{project_id}/sources
```

Example Responses

Status code: 200

Operation successful.

```
{
  "total" : 1,
  "size" : 1,
  "items" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.4.3 Updating a Custom Event Source

Function

This API is used to update a custom event source.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

PUT /v1/{project_id}/sources/{source_id}

Table 5-270 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
source_id	Yes	String	ID of the event source.

Request Parameters

Table 5-271 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-272 Request body parameters

Parameter	Mandatory	Type	Description
description	No	String	Description of the event source.
detail	No	RocketMqDetail object	Message instance connection information encapsulated in JSON format.

Table 5-273 RocketMqDetail

Parameter	Mandatory	Type	Description
instance_id	No	String	RocketMQ instance ID.

Parameter	Mandatory	Type	Description
group	Yes	String	Consumer group.
topic	Yes	String	Topic
access_key	Yes	String	Username.
secret_key	Yes	String	Secret key.
vpc_id	No	String	VPC ID.
subnet_id	No	String	Subnet ID.
namesrv_address	No	String	Connection address.
ssl_enable	No	Boolean	SSL
enable_acl	No	Boolean	Indicates whether to enable ACL.

Response Parameters

Status code: 200

Table 5-274 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-275 Response body parameters

Parameter	Type	Description
id	String	ID of the event source.
name	String	Name of the event source.
label	String	Label of the event source.
description	String	Description of the event source.
provider_type	String	Type of the event source provider, which can be OFFICIAL (official cloud service event source), CUSTOM (custom event source), or PARTNER (partner event source).

Parameter	Type	Description
event_types	Array of event_types objects	List of event types provided by the event source. Only the official cloud service event source provides event types.
created_time	String	UTC time when the event source is created.
updated_time	String	UTC time when the event source is updated.
channel_name	String	Name of the event channel to which the event source belongs.
type	String	Type of the event source.
detail	Object	Connection information encapsulated in JSON format in the message instance, such as the instance_id field of the RabbitMQ instance, vhost field of the virtual host, queue field, username, and password.
status	String	Status of the custom event source.
error_info	ErrorInfo object	Error message.

Table 5-276 event_types

Parameter	Type	Description
name	String	Name of the event type.
description	String	Description of the event type.

Table 5-277 ErrorInfo

Parameter	Type	Description
error_code	String	Error code.
error_detail	String	Error details.
error_msg	String	Error message.

Example Requests

Update a custom event source.

```
PUT https://{endpoint}/v1/{project_id}/sources/{source_id}
```

```
{  
  "description" : "first event source"  
}
```

Example Responses

Status code: 200

Operation successful.

```
{  
  "id" : "90e0b962-c6c1-438c-ba8a-3024fe592bda",  
  "name" : "first-source",  
  "label" : "first-source",  
  "description" : "first event source",  
  "provider_type" : "CUSTOM",  
  "event_types" : [ {  
    "name" : "OBS:CloudTrace:ApiCall",  
    "description" : "Service API call type event."  
  } ],  
  "created_time" : "2021-12-09 09:00:00",  
  "updated_time" : "2021-12-09 09:00:00",  
  "channel_id" : "bd14144e-8f3c-43d6-bdfd-bf09b52c2b96",  
  "channel_name" : "channel",  
  "type" : "RABBITMQ",  
  "detail" : "{ \"instance_id\": \"ac14144e-9v3c-43d6-acfd-bf09b52c98uy\", \"user_name\": \"rabbitmq_user\", \"password\": \"changeme\", \"vhost_name\": \"vhost_name\", \"queue_name\": \"queue_name\" }",  
  "status" : "RUNNING",  
  "error_info" : { }  
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.4.4 Obtaining Event Source Details

Function

This API is used to obtain the details of an event source.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/sources/{source_id}

Table 5-278 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
source_id	Yes	String	ID of the event source.

Request Parameters

Table 5-279 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-280 Response body parameters

Parameter	Type	Description
id	String	ID of the event source.
name	String	Name of the event source.
label	String	Label of the event source.
description	String	Description of the event source.
provider_type	String	Type of the event source provider, which can be OFFICIAL (official cloud service event source), CUSTOM (custom event source), or PARTNER (partner event source).
event_types	Array of event_types objects	List of event types provided by the event source. Only the official cloud service event source provides event types.
created_time	String	UTC time when the event source is created.

Parameter	Type	Description
updated_time	String	UTC time when the event source is updated.
channel_name	String	Name of the event channel to which the event source belongs.
type	String	Type of the event source.
detail	Object	Connection information encapsulated in JSON format in the message instance, such as the instance_id field of the RabbitMQ instance, vhost field of the virtual host, queue field, username, and password.
status	String	Status of the custom event source.
error_info	ErrorInfo object	Error message.

Table 5-281 event_types

Parameter	Type	Description
name	String	Name of the event type.
description	String	Description of the event type.

Table 5-282 ErrorInfo

Parameter	Type	Description
error_code	String	Error code.
error_detail	String	Error details.
error_msg	String	Error message.

Example Requests

Obtain event source details.

```
GET https://{endpoint}/v1/{project_id}/sources/{source_id}
```

Example Responses

Status code: 200

Operation successful.

```
{  
  "id": "90e0b962-c6c1-438c-ba8a-3024fe592bda",  
}
```

```
"name" : "first-source",
"label" : "first-source",
"description" : "first event source",
"provider_type" : "CUSTOM",
"event_types" : [ {
  "name" : "OBS:CloudTrace:ApiCall",
  "description" : "Service API call type event."
} ],
"created_time" : "2021-12-09 09:00:00",
"updated_time" : "2021-12-09 09:00:00",
"channel_id" : "bd14144e-8f3c-43d6-bdfd-bf09b52c2b96",
"channel_name" : "channel",
"type" : "RABBITMQ",
"detail" : "{\"instance_id\":\"ac14144e-9v3c-43d6-acfd-bf09b52c98uy\",\"user_name\":\"rabbitmq_user\", \"password\":\"changeme\",\"vhost_name\":\"vhost_name\",\"queue_name\":\"queue_name\"}",
"status" : "RUNNING",
"error_info" : { }
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.4.5 Deleting a Custom Event Source

Function

This API is used to delete a custom event source.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

DELETE /v1/{project_id}/sources/{source_id}

Table 5-283 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
source_id	Yes	String	ID of the event source.

Request Parameters

Table 5-284 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 204

Operation successful.

None

Example Requests

Delete a custom event source.

```
DELETE https://{endpoint}/v1/{project_id}/sources/{source_id}
```

Example Responses

None

Status Codes

Status Code	Description
204	Operation successful.

Error Codes

See [Error Codes](#).

5.5 Event Target Catalog Management

5.5.1 Obtaining the Event Target Catalog

Function

This API is used to obtain the predefined target catalog of an event.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/target-catalogs

Table 5-285 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-286 Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Offset, which is the position where the query starts. The value must be greater than or equal to 0.
limit	No	Integer	Number of records displayed on each page. The value must be within the range [1, 1000].
sort	No	String	Sorting mode of the query results.
fuzzy_label	No	String	Label of the event target. It is used for fuzzy match.
support_types	No	Array of strings	Supported type of the event target, which can be SUBSCRIPTION (event subscription) or FLOW (event flow).

Request Parameters

Table 5-287 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200**Table 5-288** Response body parameters

Parameter	Type	Description
total	Integer	Total number of records.
size	Integer	Number of records displayed on the current page.
items	Array of CatalogTargetInfo objects	Object list.

Table 5-289 CatalogTargetInfo

Parameter	Type	Description
id	String	ID of the event target catalog.
name	String	Name of the event target catalog.
label	String	Label of the event target catalog.
description	String	Description of the event target catalog.
provider_type	String	Provider type, which can be OFFICIAL (official cloud service event target) and CUSTOM (third-party event target).
parameters	Array of CatalogTargetParameters objects	Event target category parameters.

Parameter	Type	Description
created_time	String	UTC time when the catalog is created.
updated_time	String	UTC time when the catalog is updated.

Table 5-290 CatalogTargetParameters

Parameter	Type	Description
name	String	Name of the target parameter.
label	String	Label of the target parameter.
metadata	Object	Metadata of the target parameter, for example, whether the parameter is mandatory and which text box type is used.

Example Requests

Obtain the event target catalog.

```
GET https://{endpoint}/v1/{project_id}/target-catalogs
```

Example Responses

Status code: 200

Operation successful.

```
{
  "total" : 1,
  "size" : 1,
  "items" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.6 Event Schema Management

5.6.1 Starting Automatic Event Schema Discovery

Function

This API is used to start automatic discovery of event schemas.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/schema-discover

Table 5-291 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Project ID.

Request Parameters

Table 5-292 Request body parameters

Parameter	Mandatory	Type	Description
body	No	Object	Request for discovering event schemas through event data.

Response Parameters

Status code: 200

Table 5-293 Response body parameters

Parameter	Type	Description
total	Integer	Total number of records.
size	Integer	Number of records displayed on the current page.
items	Array of CustomizeSchemaItemInfo objects	Object list.

Table 5-294 CustomizeSchemaItemInfo

Parameter	Type	Description
id	String	ID of the event schema.
name	String	Name of the event schema. The value must be unique under a tenant.
description	String	Description of the event schema.
compatibility	String	Compatibility of the event schema.
provider_type	String	Type of the event source provider, which can be OFFICIAL (official event source) or CUSTOM (custom event source).
format	String	Format of the event schema.
number_of_versions	Integer	Number of event schema versions.
event_type_id	String	Event type ID.
event_type_name	String	Name of the event type.
event_source_id	String	ID of the event source.
event_source_name	String	Event source name.
event_source_label	String	Event source label.
created_time	String	Time when the event schema is created.
updated_time	String	Time when the event schema is updated.

Example Requests

Start automatic schema discovery.

```
POST https://{endpoint}/v1/{project_id}/schema-discover
{ }
```

Example Responses

Status code: 200

Operation successful.

```
{
  "total" : 1,
  "size" : 1,
```

```
"items" : [ {} ]  
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.6.2 Creating a Custom Event Schema

Function

This API is used to create a custom event schema.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/schemas

Table 5-295 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Request Parameters

Table 5-296 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-297 Request body parameters

Parameter	Mandatory	Type	Description
name	Yes	String	Name of the event schema. The value must be unique under a tenant. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit.
description	No	String	Description of the event schema.
compatibility	Yes	String	Compatibility of the event schema.
format	No	String	Schema content format.
definition	Yes	String	Event schema content definition.

Response Parameters

Status code: 200

Table 5-298 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-299 Response body parameters

Parameter	Type	Description
id	String	ID of the event schema.
name	String	Name of the event schema. The value must be unique under a tenant.
description	String	Description of the event schema.
compatibility	String	Compatibility of the event schema.
provider_type	String	Type of the event source provider, which can be OFFICIAL (official event source) or CUSTOM (custom event source).

Parameter	Type	Description
format	String	Format of the event schema.
number_of_versions	Integer	Number of event schema versions.
created_time	String	Time when the event schema is created.
updated_time	String	Time when the event schema is updated.
version	Integer	Current version number of the event schema.
definition	String	Event schema content definition.

Example Requests

Create a schema.

POST https://{endpoint}/v1/{project_id}/schemas

```
{
  "name" : "file.upload",
  "description" : "Schema definition for a file upload event.",
  "compatibility" : "NONE",
  "format" : "OPENAPI_3_0",
  "definition" : "{ \"$schema\": \"http://json-schema.org/draft-06/schema#\", \"title\": \"fileUpload\", \"definitions\": { \"fileUpload\": { \"properties\": { \"fileName\": { \"type\": \"string\" }, \"fileSize\": { \"type\": \"integer\" }, \"required\": [ \"foo\", \"bar\" ], \"type\": \"object\" }, \"properties\": { \"specversion\": { \"type\": \"string\" }, \"id\": { \"type\": \"string\" }, \"type\": { \"type\": \"string\", \"source\": { \"type\": \"string\", \"subject\": { \"type\": \"string\", \"datacontenttype\": { \"type\": \"string\", \"dataschema\": { \"type\": \"string\", \"time\": { \"format\": \"date-time\", \"type\": \"string\", \"data\": { \"$ref\": \"#/definitions/fileUpload\" } }, \"required\": [ \"id\", \"source\", \"time\", \"type\", \"specversion\" ], \"type\": \"object\" } } } } } } }
```

Example Responses

Status code: 200

Demo Information

```
{
  "id" : "2a0ee4f2-78a4-4122-80af-7455e37f64ee",
  "name" : "file.upload",
  "description" : "Schema definition for a file upload event.",
  "compatibility" : "NONE",
  "provider_type" : "CUSTOM",
  "format" : "OPENAPI_3_0",
  "number_of_versions" : 1,
  "created_time" : "2021-12-09 09:00:00",
  "updated_time" : "2021-12-09 09:00:00",
  "version" : 1,
  "definition" : "{ \"$schema\": \"http://json-schema.org/draft-06/schema#\", \"title\": \"fileUpload\", \"definitions\": { \"fileUpload\": { \"properties\": { \"fileName\": { \"type\": \"string\" }, \"fileSize\": { \"type\": \"integer\" }, \"required\": [ \"foo\", \"bar\" ], \"type\": \"object\" }, \"properties\": { \"specversion\": { \"type\": \"string\" }, \"id\": { \"type\": \"string\" }, \"type\": { \"type\": \"string\", \"source\": { \"type\": \"string\", \"subject\": { \"type\": \"string\", \"datacontenttype\": { \"type\": \"string\", \"dataschema\": { \"type\": \"string\", \"time\": { \"format\": \"date-time\", \"type\": \"string\", \"data\": { \"$ref\": \"#/definitions/fileUpload\" } }, \"required\": [ \"id\", \"source\", \"time\", \"type\", \"specversion\" ], \"type\": \"object\" } } } } } } }
```

```
\"}},\n\"required\": [\n\"id\", \n\"source\", \n\"time\", \n\"type\", \n\"specversion\"], \n\"type\": \"object\"}\n}
```

Status Codes

Status Code	Description
200	Demo Information

Error Codes

See [Error Codes](#).

5.6.3 Obtaining the Event Schema List

Function

This API is used to obtain the list of event schemas, including system event schemas and custom event schemas.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/schemas

Table 5-300 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-301 Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Offset, which is the position where the query starts. The value must be greater than or equal to 0.
limit	No	Integer	Number of records displayed on each page. The value must be within the range [1, 1000].

Parameter	Mandatory	Type	Description
sort	No	String	Sorting mode of the query results.
provider_type	No	String	Type of the provider.
name	No	String	Name of the event schema. It is used for exact match.
fuzzy_name	No	String	Name of the event schema. It is used for fuzzy match.

Request Parameters

Table 5-302 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-303 Response body parameters

Parameter	Type	Description
total	Integer	Total number of records.
size	Integer	Number of records displayed on the current page.
items	Array of CustomizeSchemaItemInfo objects	Object list.

Table 5-304 CustomizeSchemaItemInfo

Parameter	Type	Description
id	String	ID of the event schema.

Parameter	Type	Description
name	String	Name of the event schema. The value must be unique under a tenant.
description	String	Description of the event schema.
compatibility	String	Compatibility of the event schema.
provider_type	String	Type of the event source provider, which can be OFFICIAL (official event source) or CUSTOM (custom event source).
format	String	Format of the event schema.
number_of_versions	Integer	Number of event schema versions.
event_type_id	String	Event type ID.
event_type_name	String	Name of the event type.
event_source_id	String	ID of the event source.
event_source_name	String	Event source name.
event_source_label	String	Event source label.
created_time	String	Time when the event schema is created.
updated_time	String	Time when the event schema is updated.

Example Requests

Obtain the event schema list.

```
GET https://{endpoint}/v1/{project_id}/schemas
```

Example Responses

Status code: 200

Operation successful.

```
{
  "total" : 1,
  "size" : 1,
  "items" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.6.4 Updating a Custom Event Schema

Function

This API is used to update a custom event schema.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

PUT /v1/{project_id}/schemas/{schema_id}

Table 5-305 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
schema_id	Yes	String	ID of the event schema.

Request Parameters

Table 5-306 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-307 Request body parameters

Parameter	Mandatory	Type	Description
description	No	String	Description of the event schema.
compatibility	No	String	Compatibility of the event schema.

Response Parameters

Status code: 200

Table 5-308 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-309 Response body parameters

Parameter	Type	Description
id	String	ID of the event schema.
name	String	Name of the event schema. The value must be unique under a tenant.
description	String	Description of the event schema.
compatibility	String	Compatibility of the event schema.
provider_type	String	Type of the event source provider, which can be OFFICIAL (official event source) or CUSTOM (custom event source).
format	String	Format of the event schema.
number_of_versions	Integer	Number of event schema versions.
created_time	String	Time when the event schema is created.
updated_time	String	Time when the event schema is updated.
version	Integer	Current version number of the event schema.

Parameter	Type	Description
definition	String	Event schema content definition.

Example Requests

Update a custom event schema.

```
PUT https://{endpoint}/v1/{project_id}/schemas/{schema_id}
{
  "description": "Schema definition for a file upload event.",
  "compatibility": "NONE"
}
```

Example Responses

Status code: 200

Information

```
{
  "id": "2a0ee4f2-78a4-4122-80af-7455e37f64ee",
  "name": "file.upload",
  "description": "Schema definition for a file upload event.",
  "compatibility": "NONE",
  "provider_type": "CUSTOM",
  "format": "OPENAPI_3_0",
  "number_of_versions": 1,
  "created_time": "2021-12-09 09:00:00",
  "updated_time": "2021-12-09 09:00:00",
  "version": 1,
  "definition": "{ \"$schema\": \"http://json-schema.org/draft-06/schema#\", \"title\": \"fileUpload\", \"definitions\": { \"fileUpload\": { \"properties\": { \"fileName\": { \"type\": \"string\" }, \"fileSize\": { \"type\": \"integer\" }, \"required\": [ \"foo\", \"bar\" ], \"type\": \"object\" }, \"properties\": { \"specversion\": { \"type\": \"string\" }, \"id\": { \"type\": \"string\" }, \"type\": { \"type\": \"string\" }, \"source\": { \"type\": \"string\" }, \"subject\": { \"type\": \"string\" }, \"datacontenttype\": { \"type\": \"string\" }, \"dataschema\": { \"type\": \"string\" }, \"time\": { \"format\": \"date-time\", \"type\": \"string\" }, \"data\": { \"$ref\": \"#/definitions/fileUpload\" } }, \"required\": [ \"id\", \"source\", \"time\", \"type\", \"specversion\" ], \"type\": \"object\" } } }
```

Status Codes

Status Code	Description
200	Information

Error Codes

See [Error Codes](#).

5.6.5 Obtaining Event Schema Details

Function

This API is used to obtain the details about an event schema.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/schemas/{schema_id}

Table 5-310 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
schema_id	Yes	String	ID of the event schema.

Request Parameters

Table 5-311 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-312 Response body parameters

Parameter	Type	Description
id	String	ID of the event schema.
name	String	Name of the event schema. The value must be unique under a tenant.

Parameter	Type	Description
description	String	Description of the event schema.
compatibility	String	Compatibility of the event schema.
provider_type	String	Type of the event source provider, which can be OFFICIAL (official event source) or CUSTOM (custom event source).
format	String	Format of the event schema.
number_of_versions	Integer	Number of event schema versions.
created_time	String	Time when the event schema is created.
updated_time	String	Time when the event schema is updated.
version	Integer	Current version number of the event schema.
definition	String	Event schema content definition.

Example Requests

Obtain the event schema details.

```
GET https://{endpoint}/v1/{project_id}/schemas/{schema_id}
```

Example Responses

Status code: 200

Operation successful.

```
{
  "id": "2a0ee4f2-78a4-4122-80af-7455e37f64ee",
  "name": "file.upload",
  "description": "Schema definition for a file upload event.",
  "compatibility": "NONE",
  "provider_type": "CUSTOM",
  "format": "OPENAPI_3_0",
  "number_of_versions": 1,
  "created_time": "2021-12-09 09:00:00",
  "updated_time": "2021-12-09 09:00:00",
  "version": 1,
  "definition": "{\n  \"$schema\": \"http://json-schema.org/draft-06/schema#\",\n  \"title\": \"fileUpload\",\n  \"definitions\": {\n    \"fileUpload\": {\n      \"properties\": {\n        \"fileName\": {\n          \"type\": \"string\"\n        },\n        \"fileSize\": {\n          \"type\": \"integer\"\n        },\n        \"required\": [\n          \"foo\",\n          \"bar\"\n        ],\n        \"type\": \"object\"\n      },\n      \"properties\": {\n        \"specversion\": {\n          \"type\": \"string\"\n        },\n        \"id\": {\n          \"type\": \"string\"\n        },\n        \"type\": {\n          \"type\": \"string\"\n        },\n        \"source\": {\n          \"type\": \"string\"\n        },\n        \"subject\": {\n          \"type\": \"string\"\n        },\n        \"datacontenttype\": {\n          \"type\": \"string\"\n        },\n        \"dataschema\": {\n          \"type\": \"string\"\n        },\n        \"format\": {\n          \"type\": \"date-time\"\n        },\n        \"time\": {\n          \"type\": \"string\"\n        },\n        \"data\": {\n          \"$ref\": \"#/definitions/fileUpload\"\n        }\n      },\n      \"required\": [\n        \"id\",\n        \"source\",\n        \"time\",\n        \"type\",\n        \"specversion\"\n      ],\n        \"type\": \"object\"\n    }\n  }\n}"
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.6.6 Deleting an Event Schema

Function

This API is used to delete an event schema.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

DELETE /v1/{project_id}/schemas/{schema_id}

Table 5-313 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
schema_id	Yes	String	ID of the event schema.

Request Parameters

Table 5-314 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 204

Operation successful.

None

Example Requests

Delete an event schema.

```
DELETE https://{endpoint}/v1/{project_id}/schemas/{schema_id}
```

Example Responses

None

Status Codes

Status Code	Description
204	Operation successful.

Error Codes

See [Error Codes](#).

5.6.7 Creating a Custom Event Schema Version

Function

This API is used to create a custom event schema version. The version number is automatically generated in the background.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/schemas/{schema_id}/versions

Table 5-315 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Parameter	Mandatory	Type	Description
schema_id	Yes	String	ID of the event schema.

Request Parameters

Table 5-316 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-317 Request body parameters

Parameter	Mandatory	Type	Description
definition	No	String	Event schema content definition.

Response Parameters

Status code: 200

Table 5-318 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-319 Response body parameters

Parameter	Type	Description
id	String	ID of the event schema version.
schema_id	String	ID of the event schema.
version	Integer	Version number of the event schema.

Parameter	Type	Description
format	String	Format of the event schema.
created_time	String	Time when the event schema is created.
updated_time	String	Time when the event schema is updated.
definition	String	Event schema content definition.

Example Requests

Create a schema version.

POST https://{endpoint}/v1/{project_id}/schemas/{schema_id}/versions

```
{
  "definition" : "{ \"$schema\": \"http://json-schema.org/draft-06/schema#\", \"title\": \"fileUpload\", \"definitions\": { \"fileUpload\": { \"properties\": { \"fileName\": { \"type\": \"string\" }, \"fileSize\": { \"type\": \"integer\" }, \"required\": [ \"foo\", \"bar\" ], \"type\": \"object\" }, \"properties\": { \"specversion\": { \"type\": \"string\" }, \"id\": { \"type\": \"string\" }, \"type\": { \"type\": \"string\" }, \"source\": { \"type\": \"string\" }, \"subject\": { \"type\": \"string\" }, \"datacontenttype\": { \"type\": \"string\" }, \"dataschema\": { \"type\": \"string\" }, \"time\": { \"format\": \"date-time\", \"type\": \"string\" }, \"data\": { \"$ref\": \"#/definitions/fileUpload\" }, \"required\": [ \"id\", \"source\", \"time\", \"type\", \"specversion\" ], \"type\": \"object\" } } } }
```

Example Responses

Status code: 200

Demo Information

```
{
  "id" : "6f70e150-f20c-4c22-85aa-78ceecd52b98",
  "schema_id" : "2a0ee4f2-78a4-4122-80af-7455e37f64ee",
  "version" : 1,
  "format" : "OPENAPI_3_0",
  "created_time" : "2021-12-09 09:00:00",
  "updated_time" : "2021-12-09 09:00:00",
  "definition" : "{ \"$schema\": \"http://json-schema.org/draft-06/schema#\", \"title\": \"fileUpload\", \"definitions\": { \"fileUpload\": { \"properties\": { \"fileName\": { \"type\": \"string\" }, \"fileSize\": { \"type\": \"integer\" }, \"required\": [ \"foo\", \"bar\" ], \"type\": \"object\" }, \"properties\": { \"specversion\": { \"type\": \"string\" }, \"id\": { \"type\": \"string\" }, \"type\": { \"type\": \"string\" }, \"source\": { \"type\": \"string\" }, \"subject\": { \"type\": \"string\" }, \"datacontenttype\": { \"type\": \"string\" }, \"dataschema\": { \"type\": \"string\" }, \"time\": { \"format\": \"date-time\", \"type\": \"string\" }, \"data\": { \"$ref\": \"#/definitions/fileUpload\" }, \"required\": [ \"id\", \"source\", \"time\", \"type\", \"specversion\" ], \"type\": \"object\" } } } }
```

Status Codes

Status Code	Description
200	Demo Information

Error Codes

See [Error Codes](#).

5.6.8 Obtaining the Event Schema Version List

Function

This API is used to obtain the list of event schema versions.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/schemas/{schema_id}/versions

Table 5-320 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
schema_id	Yes	String	ID of the event schema.

Table 5-321 Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Offset, which is the position where the query starts. The value must be greater than or equal to 0.
limit	No	Integer	Number of records displayed on each page. The value must be within the range [1, 1000].
sort	No	String	Sorting mode of the query results.
version	No	String	Version of the event schema.

Request Parameters

Table 5-322 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200**Table 5-323** Response body parameters

Parameter	Type	Description
total	Integer	Total number of records.
size	Integer	Number of records displayed on the current page.
items	Array of CustomizeSchemaVersionItemInfo objects	Object list.

Table 5-324 CustomizeSchemaVersionItemInfo

Parameter	Type	Description
id	String	ID of the event schema version.
version	Integer	Version number of the event schema.
created_time	String	Time when the event schema is created.
updated_time	String	Time when the event schema is updated.

Example Requests

Obtain the event schema version list.

GET https://{endpoint}/v1/{project_id}/schemas/{schema_id}/versions

Example Responses

Status code: 200

Operation successful.

```
{
  "total" : 1,
  "size" : 1,
  "items" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.6.9 Obtaining Event Schema Version Details

Function

This API is used to obtain the details about an event schema version.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/schemas/{schema_id}/versions/{version}

Table 5-325 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
schema_id	Yes	String	ID of the event schema.
version	Yes	Integer	Version of the event schema.

Request Parameters

Table 5-326 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200**Table 5-327** Response body parameters

Parameter	Type	Description
id	String	ID of the event schema version.
schema_id	String	ID of the event schema.
version	Integer	Version number of the event schema.
format	String	Format of the event schema.
created_time	String	Time when the event schema is created.
updated_time	String	Time when the event schema is updated.
definition	String	Event schema content definition.

Example Requests

Obtain the event schema version details.

```
GET https://{endpoint}/v1/{project_id}/schemas/{schema_id}/versions/{version}
```

Example Responses

Status code: 200

Operation successful.

```
{
  "id" : "6f70e150-f20c-4c22-85aa-78ceecd52b98",
  "schema_id" : "2a0ee4f2-78a4-4122-80af-7455e37f64ee",
  "version" : 1,
  "format" : "OPENAPI_3_0",
```

```
"created_time" : "2021-12-09 09:00:00",
"updated_time" : "2021-12-09 09:00:00",
"definition" : "{ \"$schema\": \"http://json-schema.org/draft-06/schema#\", \"title\": \"fileUpload\", \"definitions\": { \"fileUpload\": { \"properties\": { \"fileName\": { \"type\": \"string\" }, \"fileSize\": { \"type\": \"integer\" }, \"required\": [ \"foo\", \"bar\" ], \"type\": \"object\" }, \"properties\": { \"specversion\": { \"type\": \"string\" }, \"id\": { \"type\": \"string\" }, \"type\": { \"type\": \"string\" }, \"source\": { \"type\": \"string\" }, \"subject\": { \"type\": \"string\" }, \"datacontenttype\": { \"type\": \"string\" }, \"dataschema\": { \"type\": \"string\" }, \"time\": { \"format\": \"date-time\", \"type\": \"string\" }, \"data\": { \"$ref\": \"#/definitions/fileUpload\" } }, \"required\": [ \"id\", \"source\", \"time\", \"type\", \"specversion\" ], \"type\": \"object\" } }
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.6.10 Deleting an Event Schema Version

Function

This API is used to delete an event schema version.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

DELETE /v1/{project_id}/schemas/{schema_id}/versions/{version}

Table 5-328 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
schema_id	Yes	String	ID of the event schema.
version	Yes	Integer	Version of the event schema.

Request Parameters

Table 5-329 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 204

Operation successful.

None

Example Requests

Delete an event schema version.

```
DELETE https://{endpoint}/v1/{project_id}/schemas/{schema_id}/versions/{version}
```

Example Responses

None

Status Codes

Status Code	Description
204	Operation successful.

Error Codes

See [Error Codes](#).

5.7 Connection Management

5.7.1 Creating a Connection

Function

This API is used to create a connection.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/connections

Table 5-330 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Request Parameters

Table 5-331 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-332 Request body parameters

Parameter	Mandatory	Type	Description
name	Yes	String	Name of the connection. The value must be unique under a tenant. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot be default.
description	No	String	Description of the connection.
vpc_id	Yes	String	ID of the VPC to be connected.
subnet_id	Yes	String	ID of the subnet to be connected.

Parameter	Mandatory	Type	Description
type	No	String	Connection type. Options: WEBHOOK: custom HTTP/ HTTPS connection KAFKA: DMS for Kafka instance ROCKETMQ: DMS for RocketMQ instance
kafka_detail	No	KafkaConnectionDetail object	Kafka connection parameters.
rocketmq_detail	No	RocketmqConnectionDetail object	RocketMQ connection parameters.

Table 5-333 KafkaConnectionDetail

Parameter	Mandatory	Type	Description
instance_id	Yes	String	Kafka instance ID.
addr	Yes	String	Kafka connection address.
security_protocol	No	String	Security protocol.
enable_sasl_ssl	Yes	Boolean	Whether SASL_SSL is enabled for the Kafka instance.
user_name	No	String	Username of the Kafka instance. This parameter is mandatory when SASL_SSL is enabled for the instance.
password	No	String	Password of the Kafka instance. This parameter is mandatory when SASL_SSL is enabled for the instance.

Parameter	Mandatory	Type	Description
acks	No	String	Number of acknowledgments that the producer requires the server to return before considering a request complete. This controls the durability of records that are sent. Supported options: 0: The producer will not wait for any acknowledgment from the server at all. The record will be immediately added to the socket buffer and considered sent. No guarantee can be made that the server has received the record, and the retries configuration will not take effect (as the client generally does not know of any failures). The offset given back for each record will always be set to -1. 1: The leader will write the record to its local log but will respond without waiting until receiving full acknowledgement from all followers. If the leader fails immediately after acknowledging the record but before the followers have replicated it, the record will be lost. all: The leader will wait for the full set of replicas to acknowledge the record. This is the strongest available guarantee because the record will not be lost even if there is just one replica that works. <code>min.insync.replicas</code> specifies the minimum number of replicas that must acknowledge a write for the write to be considered successful.

Table 5-334 RocketmqConnectionDetail

Parameter	Mandatory	Type	Description
instance_id	Yes	String	Instance ID.
addr	Yes	String	Connection address.
use_tls	Yes	Boolean	Whether to enable SSL.
enable_acl	Yes	String	Whether to enable ACL.
user_name	No	String	Username. This parameter is required only when ACL is enabled.
password	No	String	Password. This parameter is required only when ACL is enabled.

Response Parameters

Status code: 200

Table 5-335 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-336 Response body parameters

Parameter	Type	Description
id	String	ID of the event source.
name	String	Name of the connection. The value must be unique under a tenant. Only lowercase letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot be default.
description	String	Description of the connection.
status	String	Status of the connection.
error_info	ErrorInfo object	Error message.
vpc_id	String	ID of the VPC to be connected.

Parameter	Type	Description
subnet_id	String	ID of the subnet to be connected.
agency	String	Name of the user agency used by the target private network connection.
flavor	flavor object	Flavor.
type	String	Connection type. Options: WEBHOOK: custom HTTP/HTTPS connection KAFKA: DMS for Kafka instance ROCKETMQ: DMS for RocketMQ instance
kafka_detail	KafkaConnectionDetail object	Kafka connection parameters.
created_time	String	UTC time when the connection is created.
updated_time	String	UTC time when the connection is updated.
rocketmq_detail	RocketmqConnectionDetail object	RocketMQ connection parameters.

Table 5-337 ErrorInfo

Parameter	Type	Description
error_code	String	Error code.
error_detail	String	Error details.
error_msg	String	Error message.

Table 5-338 flavor

Parameter	Type	Description
name	String	Flavor name.
concurrency_type	String	Concurrent flavor type.
concurrency	Integer	Number of concurrent requests.
bandwidth_type	String	Bandwidth type.

Table 5-339 KafkaConnectionDetail

Parameter	Type	Description
instance_id	String	Kafka instance ID.
addr	String	Kafka connection address.
security_protocol	String	Security protocol.
enable_sasl_ssl	Boolean	Whether SASL_SSL is enabled for the Kafka instance.
user_name	String	Username of the Kafka instance. This parameter is mandatory when SASL_SSL is enabled for the instance.
password	String	Password of the Kafka instance. This parameter is mandatory when SASL_SSL is enabled for the instance.

Parameter	Type	Description
acks	String	Number of acknowledgments that the producer requires the server to return before considering a request complete. This controls the durability of records that are sent. Supported options: 0: The producer will not wait for any acknowledgment from the server at all. The record will be immediately added to the socket buffer and considered sent. No guarantee can be made that the server has received the record, and the retries configuration will not take effect (as the client generally does not know of any failures). The offset given back for each record will always be set to -1. 1: The leader will write the record to its local log but will respond without waiting until receiving full acknowledgement from all followers. If the leader fails immediately after acknowledging the record but before the followers have replicated it, the record will be lost. all: The leader will wait for the full set of replicas to acknowledge the record. This is the strongest available guarantee because the record will not be lost even if there is just one replica that works. min.insync.replicas specifies the minimum number of replicas that must acknowledge a write for the write to be considered successful.

Table 5-340 RocketmqConnectionDetail

Parameter	Type	Description
instance_id	String	Instance ID.
addr	String	Connection address.
use_tls	Boolean	Whether to enable SSL.
enable_acl	String	Whether to enable ACL.
user_name	String	Username. This parameter is required only when ACL is enabled.

Parameter	Type	Description
password	String	Password. This parameter is required only when ACL is enabled.

Example Requests

Create a connection.

```
POST https://{endpoint}/v1/{project_id}/connections
```

```
{
  "name" : "private-link",
  "description" : "",
  "vpc_id" : "ac14144e-8fec-53d6-bdfd-8f09b52c09iu",
  "subnet_id" : "bf14153e-5fec-67d6-b89d-5409b52c0op8",
  "type" : { }
}
```

Example Responses

Status code: 200

Demo Information

```
{
  "id" : "90e0b962-c6c1-438c-ba8a-3024fe592bda",
  "name" : "private-link",
  "description" : "",
  "status" : "CREATING",
  "error_info" : { },
  "vpc_id" : "ac14144e-8fec-53d6-bdfd-8f09b52c09iu",
  "subnet_id" : "bf14153e-5fec-67d6-b89d-5409b52c0op8",
  "agency" : "EG_TRUST",
  "flavor" : {
    "name" : "default",
    "concurrency_type" : "exclusive",
    "concurrency" : 500,
    "bandwidth_type" : "exclusive"
  },
  "type" : { },
  "kafka_detail" : { },
  "created_time" : "2021-12-09 09:00:00",
  "updated_time" : "2021-12-09 09:00:00"
}
```

Status Codes

Status Code	Description
200	Demo Information

Error Codes

See [Error Codes](#).

5.7.2 Obtaining the Connection List

Function

This API is used to obtain the list of connections.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/connections

Table 5-341 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-342 Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Offset, which is the position where the query starts. The value must be greater than or equal to 0.
limit	No	Integer	Number of records displayed on each page. The value must be within the range [1, 1000].
sort	No	String	Sorting mode of the query results.
name	No	String	Name of the connection. It is used for exact match.
fuzzy_name	No	String	Name of the connection. It is used for fuzzy match.

Request Parameters

Table 5-343 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200**Table 5-344** Response body parameters

Parameter	Type	Description
total	Integer	Total number of records.
size	Integer	Number of records displayed on the current page.
items	Array of ConnectionInfo objects	Object list.

Table 5-345 ConnectionInfo

Parameter	Type	Description
id	String	ID of the event source.
name	String	Name of the connection. The value must be unique under a tenant. Only lowercase letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot be default.
description	String	Description of the connection.
status	String	Status of the connection.
error_info	ErrorInfo object	Error message.
vpc_id	String	ID of the VPC to be connected.
subnet_id	String	ID of the subnet to be connected.

Parameter	Type	Description
agency	String	Name of the user agency used by the target private network connection.
flavor	flavor object	Flavor.
type	String	Connection type. Options: WEBHOOK: custom HTTP/HTTPS connection KAFKA: DMS for Kafka instance ROCKETMQ: DMS for RocketMQ instance
kafka_detail	KafkaConnectionDetail object	Kafka connection parameters.
created_time	String	UTC time when the connection is created.
updated_time	String	UTC time when the connection is updated.
rocketmq_detail	RocketmqConnectionDetail object	RocketMQ connection parameters.

Table 5-346 ErrorInfo

Parameter	Type	Description
error_code	String	Error code.
error_detail	String	Error details.
error_msg	String	Error message.

Table 5-347 flavor

Parameter	Type	Description
name	String	Flavor name.
concurrency_type	String	Concurrent flavor type.
concurrency	Integer	Number of concurrent requests.
bandwidth_type	String	Bandwidth type.

Table 5-348 KafkaConnectionDetail

Parameter	Type	Description
instance_id	String	Kafka instance ID.
addr	String	Kafka connection address.
security_protocol	String	Security protocol.
enable_sasl_ssl	Boolean	Whether SASL_SSL is enabled for the Kafka instance.
user_name	String	Username of the Kafka instance. This parameter is mandatory when SASL_SSL is enabled for the instance.
password	String	Password of the Kafka instance. This parameter is mandatory when SASL_SSL is enabled for the instance.

Parameter	Type	Description
acks	String	Number of acknowledgments that the producer requires the server to return before considering a request complete. This controls the durability of records that are sent. Supported options: 0: The producer will not wait for any acknowledgment from the server at all. The record will be immediately added to the socket buffer and considered sent. No guarantee can be made that the server has received the record, and the retries configuration will not take effect (as the client generally does not know of any failures). The offset given back for each record will always be set to -1. 1: The leader will write the record to its local log but will respond without waiting until receiving full acknowledgement from all followers. If the leader fails immediately after acknowledging the record but before the followers have replicated it, the record will be lost. all: The leader will wait for the full set of replicas to acknowledge the record. This is the strongest available guarantee because the record will not be lost even if there is just one replica that works. min.insync.replicas specifies the minimum number of replicas that must acknowledge a write for the write to be considered successful.

Table 5-349 RocketmqConnectionDetail

Parameter	Type	Description
instance_id	String	Instance ID.
addr	String	Connection address.
use_tls	Boolean	Whether to enable SSL.
enable_acl	String	Whether to enable ACL.
user_name	String	Username. This parameter is required only when ACL is enabled.

Parameter	Type	Description
password	String	Password. This parameter is required only when ACL is enabled.

Example Requests

Obtain the connection list.

```
GET https://{endpoint}/v1/{project_id}/connections
```

Example Responses

Status code: 200

Operation successful.

```
{
  "total" : 1,
  "size" : 1,
  "items" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.7.3 Updating a Connection

Function

This API is used to update a connection.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

```
PUT /v1/{project_id}/connections/{connection_id}
```

Table 5-350 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
connection_id	Yes	String	ID of the connection.

Request Parameters

Table 5-351 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-352 Request body parameters

Parameter	Mandatory	Type	Description
description	No	String	Description of the connection.
kafka_detail	No	KafkaConnectionUpdateDetail object	Kafka connection parameters.
rocketmq_detail	No	RocketmqConnectionDetail object	RocketMQ connection parameters.

Table 5-353 KafkaConnectionUpdateDetail

Parameter	Mandatory	Type	Description
user_name	No	String	Username.
password	No	String	Password.

Table 5-354 RocketmqConnectionDetail

Parameter	Mandatory	Type	Description
instance_id	Yes	String	Instance ID.
addr	Yes	String	Connection address.
use_tls	Yes	Boolean	Whether to enable SSL.
enable_acl	Yes	String	Whether to enable ACL.
user_name	No	String	Username. This parameter is required only when ACL is enabled.
password	No	String	Password. This parameter is required only when ACL is enabled.

Response Parameters

Status code: 200

Table 5-355 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-356 Response body parameters

Parameter	Type	Description
id	String	ID of the event source.
name	String	Name of the connection. The value must be unique under a tenant. Only lowercase letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot be default.
description	String	Description of the connection.
status	String	Status of the connection.
error_info	ErrorInfo object	Error message.
vpc_id	String	ID of the VPC to be connected.

Parameter	Type	Description
subnet_id	String	ID of the subnet to be connected.
agency	String	Name of the user agency used by the target private network connection.
flavor	flavor object	Flavor.
type	String	Connection type. Options: WEBHOOK: custom HTTP/HTTPS connection KAFKA: DMS for Kafka instance ROCKETMQ: DMS for RocketMQ instance
kafka_detail	KafkaConnectionDetail object	Kafka connection parameters.
created_time	String	UTC time when the connection is created.
updated_time	String	UTC time when the connection is updated.
rocketmq_detail	RocketmqConnectionDetail object	RocketMQ connection parameters.

Table 5-357 ErrorInfo

Parameter	Type	Description
error_code	String	Error code.
error_detail	String	Error details.
error_msg	String	Error message.

Table 5-358 flavor

Parameter	Type	Description
name	String	Flavor name.
concurrency_type	String	Concurrent flavor type.
concurrency	Integer	Number of concurrent requests.
bandwidth_type	String	Bandwidth type.

Table 5-359 KafkaConnectionDetail

Parameter	Type	Description
instance_id	String	Kafka instance ID.
addr	String	Kafka connection address.
security_protocol	String	Security protocol.
enable_sasl_ssl	Boolean	Whether SASL_SSL is enabled for the Kafka instance.
user_name	String	Username of the Kafka instance. This parameter is mandatory when SASL_SSL is enabled for the instance.
password	String	Password of the Kafka instance. This parameter is mandatory when SASL_SSL is enabled for the instance.

Parameter	Type	Description
acks	String	Number of acknowledgments that the producer requires the server to return before considering a request complete. This controls the durability of records that are sent. Supported options: 0: The producer will not wait for any acknowledgment from the server at all. The record will be immediately added to the socket buffer and considered sent. No guarantee can be made that the server has received the record, and the retries configuration will not take effect (as the client generally does not know of any failures). The offset given back for each record will always be set to -1. 1: The leader will write the record to its local log but will respond without waiting until receiving full acknowledgement from all followers. If the leader fails immediately after acknowledging the record but before the followers have replicated it, the record will be lost. all: The leader will wait for the full set of replicas to acknowledge the record. This is the strongest available guarantee because the record will not be lost even if there is just one replica that works. <code>min.insync.replicas</code> specifies the minimum number of replicas that must acknowledge a write for the write to be considered successful.

Table 5-360 RocketmqConnectionDetail

Parameter	Type	Description
instance_id	String	Instance ID.
addr	String	Connection address.
use_tls	Boolean	Whether to enable SSL.
enable_acl	String	Whether to enable ACL.
user_name	String	Username. This parameter is required only when ACL is enabled.

Parameter	Type	Description
password	String	Password. This parameter is required only when ACL is enabled.

Example Requests

Update a connection.

```
PUT https://{endpoint}/v1/{project_id}/connections/{connection_id}
{
  "description" : ""
}
```

Example Responses

Status code: 200

Information

```
{
  "id" : "90e0b962-c6c1-438c-ba8a-3024fe592bda",
  "name" : "private-link",
  "description" : "",
  "status" : "CREATING",
  "error_info" : { },
  "vpc_id" : "ac14144e-8fec-53d6-bdfd-8f09b52c09iu",
  "subnet_id" : "bf14153e-5fec-67d6-b89d-5409b52c0op8",
  "agency" : "EG_TRUST",
  "flavor" : {
    "name" : "default",
    "concurrency_type" : "exclusive",
    "concurrency" : 500,
    "bandwidth_type" : "exclusive"
  },
  "type" : { },
  "kafka_detail" : { },
  "created_time" : "2021-12-09 09:00:00",
  "updated_time" : "2021-12-09 09:00:00"
}
```

Status Codes

Status Code	Description
200	Information

Error Codes

See [Error Codes](#).

5.7.4 Obtaining Connection Details

Function

This API is used to obtain the details about a connection.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/connections/{connection_id}

Table 5-361 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
connection_id	Yes	String	ID of the connection.

Request Parameters

Table 5-362 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-363 Response body parameters

Parameter	Type	Description
id	String	ID of the event source.

Parameter	Type	Description
name	String	Name of the connection. The value must be unique under a tenant. Only lowercase letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot be default.
description	String	Description of the connection.
status	String	Status of the connection.
error_info	ErrorInfo object	Error message.
vpc_id	String	ID of the VPC to be connected.
subnet_id	String	ID of the subnet to be connected.
agency	String	Name of the user agency used by the target private network connection.
flavor	flavor object	Flavor.
type	String	Connection type. Options: WEBHOOK: custom HTTP/HTTPS connection KAFKA: DMS for Kafka instance ROCKETMQ: DMS for RocketMQ instance
kafka_detail	KafkaConnectionDetail object	Kafka connection parameters.
created_time	String	UTC time when the connection is created.
updated_time	String	UTC time when the connection is updated.
rocketmq_detail	RocketmqConnectionDetail object	RocketMQ connection parameters.

Table 5-364 ErrorInfo

Parameter	Type	Description
error_code	String	Error code.
error_detail	String	Error details.
error_msg	String	Error message.

Table 5-365 flavor

Parameter	Type	Description
name	String	Flavor name.
concurrency_type	String	Concurrent flavor type.
concurrency	Integer	Number of concurrent requests.
bandwidth_type	String	Bandwidth type.

Table 5-366 KafkaConnectionDetail

Parameter	Type	Description
instance_id	String	Kafka instance ID.
addr	String	Kafka connection address.
security_protocol	String	Security protocol.
enable_sasl_ssl	Boolean	Whether SASL_SSL is enabled for the Kafka instance.
user_name	String	Username of the Kafka instance. This parameter is mandatory when SASL_SSL is enabled for the instance.
password	String	Password of the Kafka instance. This parameter is mandatory when SASL_SSL is enabled for the instance.

Parameter	Type	Description
acks	String	Number of acknowledgments that the producer requires the server to return before considering a request complete. This controls the durability of records that are sent. Supported options: 0: The producer will not wait for any acknowledgment from the server at all. The record will be immediately added to the socket buffer and considered sent. No guarantee can be made that the server has received the record, and the retries configuration will not take effect (as the client generally does not know of any failures). The offset given back for each record will always be set to -1. 1: The leader will write the record to its local log but will respond without waiting until receiving full acknowledgement from all followers. If the leader fails immediately after acknowledging the record but before the followers have replicated it, the record will be lost. all: The leader will wait for the full set of replicas to acknowledge the record. This is the strongest available guarantee because the record will not be lost even if there is just one replica that works. <code>min.insync.replicas</code> specifies the minimum number of replicas that must acknowledge a write for the write to be considered successful.

Table 5-367 RocketmqConnectionDetail

Parameter	Type	Description
instance_id	String	Instance ID.
addr	String	Connection address.
use_tls	Boolean	Whether to enable SSL.
enable_acl	String	Whether to enable ACL.
user_name	String	Username. This parameter is required only when ACL is enabled.

Parameter	Type	Description
password	String	Password. This parameter is required only when ACL is enabled.

Example Requests

Obtain the connection details.

```
GET https://{endpoint}/v1/{project_id}/connections/{connection_id}
```

Example Responses

Status code: 200

Operation successful.

```
{
  "id": "90e0b962-c6c1-438c-ba8a-3024fe592bda",
  "name": "private-link",
  "description": "",
  "status": "CREATING",
  "error_info": { },
  "vpc_id": "ac14144e-8fec-53d6-bdfd-8f09b52c09iu",
  "subnet_id": "bf14153e-5fec-67d6-b89d-5409b52c0op8",
  "agency": "EG_TRUST",
  "flavor": {
    "name": "default",
    "concurrency_type": "exclusive",
    "concurrency": 500,
    "bandwidth_type": "exclusive"
  },
  "type": { },
  "kafka_detail": { },
  "created_time": "2021-12-09 09:00:00",
  "updated_time": "2021-12-09 09:00:00"
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.7.5 Deleting a Connection

Function

This API is used to delete a connection.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

DELETE /v1/{project_id}/connections/{connection_id}

Table 5-368 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
connection_id	Yes	String	ID of the connection.

Request Parameters

Table 5-369 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 204

Operation successful.

None

Example Requests

Delete a connection.

```
DELETE https://{endpoint}/v1/{project_id}/connections/{connection_id}
```

Example Responses

None

Status Codes

Status Code	Description
204	Operation successful.

Error Codes

See [Error Codes](#).

5.8 Service Agency Management

5.8.1 Obtaining the Service Agency List

Function

This API is used to obtain the list of service agencies.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/service-agencies

Table 5-370 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-371 Query Parameters

Parameter	Mandatory	Type	Description
type	Yes	String	Type of the scenario of service agency authorization.

Request Parameters

Table 5-372 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-373 Response body parameters

Parameter	Type	Description
agencies	Array of strings	Service agency authorization record.

Example Requests

Obtain the service agency list.

```
GET https://{endpoint}/v1/{project_id}/service-agencies
```

Example Responses

Status code: 200

Operation successful.

```
{  
  "agencies" : [ "EG_DELEGATE_FG_AGENCY" ]  
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.8.2 Creating a Service Agency

Function

This API is used to create a service agency with just a few clicks.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/service-agencies

Table 5-374 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Request Parameters

Table 5-375 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-376 Request body parameters

Parameter	Mandatory	Type	Description
type	Yes	String	Type of the service agency scenario.

Response Parameters

Status code: 200

Table 5-377 Response body parameters

Parameter	Type	Description
agencies	Array of strings	Service agency authorization record.

Example Requests

Create a service agency.

```
POST https://{endpoint}/v1/{project_id}/service-agencies
```

```
{
  "type" : "TARGET_CONNECTION"
}
```

Example Responses

Status code: 200

Operation successful.

```
{
  "agencies" : [ "EG_DELEGATE_FG_AGENCY" ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.9 Quota Management

5.9.1 Obtaining the Quota

Function

This API is used to obtain the quota of the current tenant. If no quota is configured, the default one is returned.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/quotas

Table 5-378 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-379 Query Parameters

Parameter	Mandatory	Type	Description
type	No	String	Type of the resources for which the quota is to be queried.

Request Parameters

Table 5-380 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-381 Response body parameters

Parameter	Type	Description
quotas	QuotaResourceResp object	Description about the quota.

Table 5-382 QuotaResourceResp

Parameter	Type	Description
resources	Array of QuotaItemInfo objects	Error description.

Table 5-383 QuotaItemInfo

Parameter	Type	Description
name	String	Name.
type	String	Quota type.
max	Integer	Maximum quota.
min	Integer	Minimum quota.
quota	Integer	Current quota.
used	Integer	Used quota.

Example Requests

Query the resource quotas.

```
GET https://{endpoint}/v1/{project_id}/quotas
```

Example Responses

Status code: 200

Operation successful.

```
{  
  "quotas" : { }  
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.10 API Version Management

5.10.1 Obtaining the API Version List

Function

This API is used to obtain the list of API versions supported by the service.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /

Request Parameters

Table 5-384 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-385 Response body parameters

Parameter	Type	Description
versions	Array of versions objects	Versions.

Table 5-386 versions

Parameter	Type	Description
id	String	Version number, for example, v1
links	Array of links objects	URL.
version	String	If the APIs of the given version support micro-versions, set this parameter to the supported maximum micro-version. If not, leave this parameter blank.
min_version	String	If the APIs of the given version support micro-versions, set this parameter to the supported minimum micro-version. If not, leave this parameter blank.
status	String	Version status, which can be CURRENT (recommended), SUPPORTED (earlier version that is still supported), or DEPRECATED (deprecated version, which may be deleted later).
updated	String	UTC time when the version is released.

Table 5-387 links

Parameter	Type	Description
href	String	href property.
rel	String	rel property.

Example Requests

Obtain the API version list.

```
/
```

Example Responses

Status code: 200

Operation successful.

```
{
  "versions": [ {
    "id": "v1",
    "links": [ {
      "href": "https://eg.cn-north-4.myhuaweicloud.com/v1",
      "rel": "self"
    } ],
  } ],
}
```

```
"version" : "",  
"min_version" : "",  
"status" : "CURRENT",  
"updated" : "2022-04-19T12:20:10Z"  
}]  
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.11 Trigger Management

5.11.1 Obtaining the EG Trigger of a Function

Function

This API is used to obtain the trigger of a function specified by URN. A trigger is a subscription with a function URN as the target.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/subscription-triggers/{func_urn}

Table 5-388 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
func_urn	Yes	String	URN of the function.

Table 5-389 Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Offset, which is the position where the query starts. The value must be greater than or equal to 0.
limit	No	Integer	Number of records displayed on each page. The value must be within the range [1, 1000].
sort	No	String	Sorting mode of the query results.

Request Parameters

Table 5-390 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-391 Response body parameters

Parameter	Type	Description
total	Integer	Total number of records.
size	Integer	Number of records displayed on the current page.
items	Array of SubscriptionInfo objects	Object list.

Table 5-392 SubscriptionInfo

Parameter	Type	Description
id	String	Subscription ID.
name	String	Subscription name.
description	String	Description of the subscription.
type	String	Subscription type.
status	String	Status.
channel_id	String	ID of the event channel.
channel_name	String	Name of the event channel.
used	Array of SubscriptionUse- dInfo objects	Label information.
sources	Array of SubscriptionSour- ceInfo objects	List of subscription sources.
targets	Array of SubscriptionTar- getInfo objects	List of subscription targets.
created_time	String	Time when the trigger is created.
updated_time	String	Time when the trigger is updated.

Table 5-393 SubscriptionUsedInfo

Parameter	Type	Description
resource_id	String	Associated resource ID.
owner	String	Management tenant account.
description	String	Description.

Table 5-394 SubscriptionSourceInfo

Parameter	Type	Description
id	String	ID of the event subscription source.
name	String	Name of the event subscription source.
provider_type	String	Provider type of the event subscription source.

Parameter	Type	Description
detail	Object	List of event subscription source parameters.
filter	Object	Filtering rule of the event subscription source.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.

Table 5-395 SubscriptionTargetInfo

Parameter	Type	Description
id	String	ID of the event subscription target.
name	String	Name of the event subscription target.
provider_type	String	Provider type of the event subscription target.
connection_id	String	Connection ID used by the event subscription target.
detail	Object	List of event subscription target parameters.
kafka_detail	KafkaTargetDetail object	List of Kafka event subscription target parameters. The total length of this field after serialization cannot exceed 1024 bytes.
smn_detail	SmnTargetDetail object	List of SMN event target parameters for the subscription. The total length cannot exceed 1024 bytes after serialization.
eg_detail	EgTargetDetail object	List of EG event channel target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for EG channel event targets.
apigw_detail	ApigwTargetDetail object	List of APIGW URL target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for APIGW event targets.

Parameter	Type	Description
retry_times	Integer	Number of retries.
transform	Transform object	Transform rule of the event subscription target.
dead_letter_queue	DeadLetterQueue object	List of dead letter queue parameters for the subscription.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.
rocketmq_detail	RocketmqTargetDetail object	Parameters for RocketMQ in event subscription.

Table 5-396 KafkaTargetDetail

Parameter	Type	Description
topic	String	Topic.
keyTransform	keyTransform object	Key value rule.

Table 5-397 keyTransform

Parameter	Type	Description
type	String	Type of the key value rule.
value	String	Key value rule. This parameter is mandatory when type is VARIABLE or CONSTANT.
template	String	Key value rule template. This parameter is mandatory when type is VARIABLE.

Table 5-398 SmnTargetDetail

Parameter	Type	Description
urn	String	Specifies the topic URN.
agency_name	String	Agency name.

Parameter	Type	Description
subject_transform	subject_transform object	Title rule.

Table 5-399 subject_transform

Parameter	Type	Description
type	String	Type of the title rule.
value	String	Title rule.
template	String	Title rule template. This parameter is mandatory when type is set to VARIABLE.

Table 5-400 EgTargetDetail

Parameter	Type	Description
target_project_id	String	Target project ID.
target_channel_id	String	Target channel ID.
target_region	String	Target region.
cross_region	Boolean	Indicates whether cross-region feature is enabled.
agency_name	String	Agency name.

Table 5-401 ApigwTargetDetail

Parameter	Type	Description
url	String	Target URL.
invocation_http_parameters	InvocationHttpParameters object	Parameters for invoking HTTP.

Table 5-402 InvocationHttpParameters

Parameter	Type	Description
header_parameters	Array of HeaderParameter objects	Object list.

Table 5-403 HeaderParameter

Parameter	Type	Description
is_value_secret	Boolean	Whether to encrypt the value.
key	String	Header key.
value	String	Header value.

Table 5-404 DeadLetterQueue

Parameter	Type	Description
type	String	Queue type.
instance_id	String	Instance ID.
connection_id	String	Connection ID.
topic	String	Topic.

Table 5-405 RocketmqTargetDetail

Parameter	Type	Description
topic	String	Topic name.
key_transform	Transform object	Transform rule.

Table 5-406 Transform

Parameter	Type	Description
type	String	Type of the transform rule.

Parameter	Type	Description
value	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Example Requests

Obtain the EG trigger of a function.

```
GET https://{endpoint}/v1/{project_id}/subscription-triggers/{func_urn}
```

Example Responses

Status code: 200

Operation successful.

```
{
  "total" : 1,
  "size" : 1,
  "items" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.11.2 Obtaining the EG Trigger of a Function Flow

Function

This API is used to obtain the trigger of a function flow specified by ID. A trigger is a subscription with a function flow ID as the target.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/subscription-triggers/workflow/{workflow_id}

Table 5-407 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
workflow_id	Yes	String	ID of the function flow.

Table 5-408 Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Offset, which is the position where the query starts. The value must be greater than or equal to 0.
limit	No	Integer	Number of records displayed on each page. The value must be within the range [1, 1000].
sort	No	String	Sorting mode of the query results.

Request Parameters

Table 5-409 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200**Table 5-410** Response body parameters

Parameter	Type	Description
total	Integer	Total number of records.
size	Integer	Number of records displayed on the current page.
items	Array of SubscriptionInfo objects	Object list.

Table 5-411 SubscriptionInfo

Parameter	Type	Description
id	String	Subscription ID.
name	String	Subscription name.
description	String	Description of the subscription.
type	String	Subscription type.
status	String	Status.
channel_id	String	ID of the event channel.
channel_name	String	Name of the event channel.
used	Array of SubscriptionUse- dInfo objects	Label information.

Parameter	Type	Description
sources	Array of SubscriptionSourceInfo objects	List of subscription sources.
targets	Array of SubscriptionTargetInfo objects	List of subscription targets.
created_time	String	Time when the trigger is created.
updated_time	String	Time when the trigger is updated.

Table 5-412 SubscriptionUsedInfo

Parameter	Type	Description
resource_id	String	Associated resource ID.
owner	String	Management tenant account.
description	String	Description.

Table 5-413 SubscriptionSourceInfo

Parameter	Type	Description
id	String	ID of the event subscription source.
name	String	Name of the event subscription source.
provider_type	String	Provider type of the event subscription source.
detail	Object	List of event subscription source parameters.
filter	Object	Filtering rule of the event subscription source.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.

Table 5-414 SubscriptionTargetInfo

Parameter	Type	Description
id	String	ID of the event subscription target.
name	String	Name of the event subscription target.
provider_type	String	Provider type of the event subscription target.
connection_id	String	Connection ID used by the event subscription target.
detail	Object	List of event subscription target parameters.
kafka_detail	KafkaTargetDetail object	List of Kafka event subscription target parameters. The total length of this field after serialization cannot exceed 1024 bytes.
smn_detail	SmnTargetDetail object	List of SMN event target parameters for the subscription. The total length cannot exceed 1024 bytes after serialization.
eg_detail	EgTargetDetail object	List of EG event channel target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for EG channel event targets.
apigw_detail	ApigwTargetDetail object	List of APIGW URL target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for APIGW event targets.
retry_times	Integer	Number of retries.
transform	TransForm object	Transform rule of the event subscription target.
dead_letter_queue	DeadLetterQueue object	List of dead letter queue parameters for the subscription.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.
rocketmq_detail	RocketmqTargetDetail object	Parameters for RocketMQ in event subscription.

Table 5-415 KafkaTargetDetail

Parameter	Type	Description
topic	String	Topic.
keyTransform	keyTransform object	Key value rule.

Table 5-416 keyTransform

Parameter	Type	Description
type	String	Type of the key value rule.
value	String	Key value rule. This parameter is mandatory when type is VARIABLE or CONSTANT.
template	String	Key value rule template. This parameter is mandatory when type is VARIABLE.

Table 5-417 SmnTargetDetail

Parameter	Type	Description
urn	String	Specifies the topic URN.
agency_name	String	Agency name.
subject_transform	subject_transform object	Title rule.

Table 5-418 subject_transform

Parameter	Type	Description
type	String	Type of the title rule.
value	String	Title rule.
template	String	Title rule template. This parameter is mandatory when type is set to VARIABLE.

Table 5-419 EgTargetDetail

Parameter	Type	Description
target_project_id	String	Target project ID.
target_channel_id	String	Target channel ID.
target_region	String	Target region.
cross_region	Boolean	Indicates whether cross-region feature is enabled.
agency_name	String	Agency name.

Table 5-420 ApigwTargetDetail

Parameter	Type	Description
url	String	Target URL.
invocation_http_parameters	InvocationHttpParameters object	Parameters for invoking HTTP.

Table 5-421 InvocationHttpParameters

Parameter	Type	Description
header_parameters	Array of HeaderParameter objects	Object list.

Table 5-422 HeaderParameter

Parameter	Type	Description
is_value_secret	Boolean	Whether to encrypt the value.
key	String	Header key.
value	String	Header value.

Table 5-423 DeadLetterQueue

Parameter	Type	Description
type	String	Queue type.
instance_id	String	Instance ID.

Parameter	Type	Description
connection_id	String	Connection ID.
topic	String	Topic.

Table 5-424 RocketmqTargetDetail

Parameter	Type	Description
topic	String	Topic name.
key_transform	Transform object	Transform rule.

Table 5-425 Transform

Parameter	Type	Description
type	String	Type of the transform rule.
value	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Example Requests

Obtain the EG trigger of a function flow.

GET https://{endpoint}/v1/{project_id}/subscription-triggers/workflow/{workflow_id}

Example Responses

Status code: 200

Operation successful.

```
{
  "total" : 1,
  "size" : 1,
  "items" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.12 Endpoint Management

5.12.1 Updating an Endpoint

Function

This API is used to update an endpoint.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

PUT /v1/{project_id}/endpoints/{endpoint_id}

Table 5-426 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
endpoint_id	Yes	String	ID of the endpoint.

Request Parameters

Table 5-427 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-428 Request body parameters

Parameter	Mandatory	Type	Description
description	No	String	Description.

Response Parameters

Status code: 200

Table 5-429 Response body parameters

Parameter	Type	Description
id	String	ID of the endpoint.
name	String	Name of the endpoint.
vpc_id	String	ID of the VPC to which the endpoint belongs.
subnet_id	String	ID of the subnet to which the endpoint belongs.
domain	String	Access domain name.
description	String	Description.
status	String	Status of the endpoint.
error_info	ErrorInfo object	Error message.
type	String	Type of the endpoint.
scalable	Boolean	Whether the endpoint is accessible.
created_time	String	UTC time when the endpoint is created.

Parameter	Type	Description
updated_time	String	UTC time when the endpoint is updated.
endpoints	Array of EndpointConnection objects	List of endpoints.

Table 5-430 ErrorInfo

Parameter	Type	Description
error_code	String	Error code.
error_detail	String	Error details.
error_msg	String	Error message.

Table 5-431 EndpointConnection

Parameter	Type	Description
endpoint_service_id	String	Service ID of the endpoint.
endpoint_service_name	String	Service name of the endpoint.
marker_id	String	Packet ID of the endpoint.
id	String	Node ID of the endpoint.
ip	String	Node IP address of the endpoint.
created_time	String	Time when the endpoint is created.

Example Requests

Update an endpoint.

```
PUT https://{eg_endpoint}/v1/{project_id}/endpoints/{endpoint_id}
{
  "description" : "string"
}
```

Example Responses

Status code: 200

Operation successful.

```
{
  "id" : "23709d68-54d5-423b-a6be-03302e893152",
  "name" : "endpoint",
  "vpc_id" : "68bfbcc1-dff2-47e4-a9d4-332b9bc1b8de",
  "subnet_id" : "84758cf5-9c62-43ae-a778-3dbd8370c0a4",
  "domain" : "events.cn-north-4.myhuaweicloud.com",
  "description" : "Endpoint.",
  "status" : "CREATED",
  "error_info" : { },
  "type" : "PRIVATE",
  "scalable" : false,
  "created_time" : "2021-12-09 09:00:00",
  "updated_time" : "2021-12-09 09:00:00",
  "endpoints" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.12.2 Deleting an Endpoint

Function

This API is used to delete an endpoint.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

DELETE /v1/{project_id}/endpoints/{endpoint_id}

Table 5-432 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
endpoint_id	Yes	String	ID of the endpoint.

Request Parameters

Table 5-433 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 204

Operation successful.

None

Example Requests

Delete an endpoint.

```
DELETE https://{eg_endpoint}/v1/{project_id}/endpoints/{endpoint_id}
```

Example Responses

None

Status Codes

Status Code	Description
204	Operation successful.

Error Codes

See [Error Codes](#).

5.12.3 Creating an Endpoint

Function

This API is used to create an endpoint.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/endpoints

Table 5-434 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Request Parameters

Table 5-435 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-436 Request body parameters

Parameter	Mandatory	Type	Description
name	Yes	String	Name of the endpoint. The value must be unique under a tenant. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit.
vpc_id	Yes	String	ID of the VPC to which the endpoint belongs.
subnet_id	Yes	String	ID of the subnet to which the endpoint belongs.
description	No	String	Description.

Response Parameters

Status code: 200

Table 5-437 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-438 Response body parameters

Parameter	Type	Description
id	String	ID of the endpoint.
name	String	Name of the endpoint.
vpc_id	String	ID of the VPC to which the endpoint belongs.
subnet_id	String	ID of the subnet to which the endpoint belongs.
domain	String	Access domain name.
description	String	Description.
status	String	Status of the endpoint.
error_info	ErrorInfo object	Error message.
type	String	Type of the endpoint.
scalable	Boolean	Whether the endpoint is accessible.
created_time	String	UTC time when the endpoint is created.
updated_time	String	UTC time when the endpoint is updated.
endpoints	Array of EndpointConnection objects	List of endpoints.

Table 5-439 ErrorInfo

Parameter	Type	Description
error_code	String	Error code.

Parameter	Type	Description
error_detail	String	Error details.
error_msg	String	Error message.

Table 5-440 EndpointConnection

Parameter	Type	Description
endpoint_service_id	String	Service ID of the endpoint.
endpoint_service_name	String	Service name of the endpoint.
marker_id	String	Packet ID of the endpoint.
id	String	Node ID of the endpoint.
ip	String	Node IP address of the endpoint.
created_time	String	Time when the endpoint is created.

Example Requests

Create an endpoint.

```
GET https://{eg_endpoint}/v1/{project_id}/endpoints
```

```
{
  "name" : "endpoint",
  "vpc_id" : "68bfbcc1-dff2-47e4-a9d4-332b9bc1b8de",
  "subnet_id" : "84758cf5-9c62-43ae-a778-3dbd8370c0a4",
  "description" : "string"
}
```

Example Responses

Status code: 200

Operation successful.

```
{
  "id" : "23709d68-54d5-423b-a6be-03302e893152",
  "name" : "endpoint",
  "vpc_id" : "68bfbcc1-dff2-47e4-a9d4-332b9bc1b8de",
  "subnet_id" : "84758cf5-9c62-43ae-a778-3dbd8370c0a4",
  "domain" : "events.cn-north-4.myhuaweicloud.com",
  "description" : "Endpoint.",
  "status" : "CREATED",
  "error_info" : { },
  "type" : "PRIVATE",
  "scalable" : false,
  "created_time" : "2021-12-09 09:00:00",
  "updated_time" : "2021-12-09 09:00:00",
  "endpoints" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.12.4 Obtaining the Endpoint List

Function

This API is used to obtain the list of endpoints.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/endpoints

Table 5-441 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-442 Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Offset, which is the position where the query starts. The value must be greater than or equal to 0.
limit	No	Integer	Number of records displayed on each page. The value must be within the range [1, 1000].
sort	No	String	Sorting mode of the query results.
type	No	String	Type of the endpoint.

Parameter	Mandatory	Type	Description
name	No	String	Name of the endpoint.
vpc_id	No	String	VPC ID of the endpoint.
fuzzy_name	No	String	Name of the endpoint. It is used for fuzzy match.
subnet_id	No	String	Subnet ID for endpoint query.

Request Parameters

Table 5-443 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-444 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-445 Response body parameters

Parameter	Type	Description
total	Integer	Total number of records.
size	Integer	Number of records displayed on the current page.
items	Array of EndpointInfo objects	Object list.

Table 5-446 EndpointInfo

Parameter	Type	Description
id	String	ID of the endpoint.
name	String	Name of the endpoint.
vpc_id	String	ID of the VPC to which the endpoint belongs.
subnet_id	String	ID of the subnet to which the endpoint belongs.
domain	String	Access domain name.
description	String	Description.
status	String	Status of the endpoint.
error_info	ErrorInfo object	Error message.
type	String	Type of the endpoint.
scalable	Boolean	Whether the endpoint is accessible.
created_time	String	UTC time when the endpoint is created.
updated_time	String	UTC time when the endpoint is updated.
endpoints	Array of EndpointConnection objects	List of endpoints.

Table 5-447 ErrorInfo

Parameter	Type	Description
error_code	String	Error code.
error_detail	String	Error details.
error_msg	String	Error message.

Table 5-448 EndpointConnection

Parameter	Type	Description
endpoint_service_id	String	Service ID of the endpoint.

Parameter	Type	Description
endpoint_service_name	String	Service name of the endpoint.
marker_id	String	Packet ID of the endpoint.
id	String	Node ID of the endpoint.
ip	String	Node IP address of the endpoint.
created_time	String	Time when the endpoint is created.

Example Requests

Obtain the endpoint list.

```
GET https://{eg_endpoint}/v1/{project_id}/endpoints
```

Example Responses

Status code: 200

Operation successful.

```
{
  "total" : 1,
  "size" : 1,
  "items" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.13 OBS Bucket Management

5.13.1 Obtaining the OBS Bucket List

Function

This API is used to obtain the list of OBS buckets.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/subscriptions/obsbuckets

Table 5-449 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-450 Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Offset, which is the position where the query starts. The value must be greater than or equal to 0.
limit	No	Integer	Number of records displayed on each page. The value must be within the range [1, 1000].
sort	No	String	Sorting mode of the query results.

Request Parameters

Table 5-451 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-452 Response body parameters

Parameter	Type	Description
total	Integer	Total number of records.
size	Integer	Number of records displayed on the current page.
items	Array of ObsBucketInfo objects	Object list.

Table 5-453 ObsBucketInfo

Parameter	Type	Description
responseHeaders	Object	Response header.
originalHeaders	Object	Request header.
statusCode	Integer	Status.
bucketName	String	Bucket name.
owner	owner object	Owner of the bucket.
creationDate	String	Time when the bucket is created.
location	String	Location of the bucket.
storageClass	Object	Storage class of the object.
metadata	Object	Bucket metadata.
acl	Object	Bucket ACL.
bucketStorageClasses	Object	Storage class of the bucket.
bucketType	String	Bucket type.
requestId	String	Request ID.

Table 5-454 owner

Parameter	Type	Description
displayName	String	Label of the bucket.
id	String	Domain ID (account ID).

Example Requests

Obtain the OBS bucket list.

```
GET https://{eg_endpoint}/v1/{project_id}/subscriptions/obsbuckets
```

Example Responses

Status code: 200

Operation successful.

```
{
  "total" : 1,
  "size" : 1,
  "items" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.13.2 Refurbishing OBS

Function

This API is used to refurbish the FunctionGraph OBS trigger for EG subscription.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/subscriptions/obsbuckets/{bucket_name}/refurbishobs

Table 5-455 Path Parameters

Parameter	Mandatory	Type	Description
bucket_name	Yes	String	Bucket name.
project_id	Yes	String	Tenant resource space ID.

Request Parameters

Table 5-456 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-457 Request body parameters

Parameter	Mandatory	Type	Description
agency_name	Yes	String	Agency name.
id	Yes	String	ID of the trigger to be refurbished.
transform	Yes	Transform object	Transform rule of the event subscription target.

Table 5-458 Transform

Parameter	Mandatory	Type	Description
type	Yes	String	Type of the transform rule.

Parameter	Mandatory	Type	Description
value	No	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	No	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Response Parameters

Status code: 200

Table 5-459 Response body parameters

Parameter	Type	Description
id	String	Subscription ID.
name	String	Subscription name.
description	String	Description of the subscription.
type	String	Subscription type.
status	String	Status.
channel_id	String	ID of the event channel.
channel_name	String	Name of the event channel.

Parameter	Type	Description
used	Array of SubscriptionUsedInfo objects	Label information.
sources	Array of SubscriptionSourceInfo objects	List of subscription sources.
targets	Array of SubscriptionTargetInfo objects	List of subscription targets.
created_time	String	Time when the trigger is created.
updated_time	String	Time when the trigger is updated.

Table 5-460 SubscriptionUsedInfo

Parameter	Type	Description
resource_id	String	Associated resource ID.
owner	String	Management tenant account.
description	String	Description.

Table 5-461 SubscriptionSourceInfo

Parameter	Type	Description
id	String	ID of the event subscription source.
name	String	Name of the event subscription source.
provider_type	String	Provider type of the event subscription source.
detail	Object	List of event subscription source parameters.
filter	Object	Filtering rule of the event subscription source.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.

Table 5-462 SubscriptionTargetInfo

Parameter	Type	Description
id	String	ID of the event subscription target.
name	String	Name of the event subscription target.
provider_type	String	Provider type of the event subscription target.
connection_id	String	Connection ID used by the event subscription target.
detail	Object	List of event subscription target parameters.
kafka_detail	KafkaTargetDetail object	List of Kafka event subscription target parameters. The total length of this field after serialization cannot exceed 1024 bytes.
smn_detail	SmnTargetDetail object	List of SMN event target parameters for the subscription. The total length cannot exceed 1024 bytes after serialization.
eg_detail	EgTargetDetail object	List of EG event channel target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for EG channel event targets.
apigw_detail	ApigwTargetDetail object	List of APIGW URL target parameters for the subscription. The total length cannot exceed 1,024 bytes after serialization. This field is mandatory for APIGW event targets.
retry_times	Integer	Number of retries.
transform	TransForm object	Transform rule of the event subscription target.
dead_letter_queue	DeadLetterQueue object	List of dead letter queue parameters for the subscription.
created_time	String	Time when the event subscription is created.
updated_time	String	Time when the event subscription is updated.
rocketmq_detail	RocketmqTargetDetail object	Parameters for RocketMQ in event subscription.

Table 5-463 KafkaTargetDetail

Parameter	Type	Description
topic	String	Topic.
keyTransform	keyTransform object	Key value rule.

Table 5-464 keyTransform

Parameter	Type	Description
type	String	Type of the key value rule.
value	String	Key value rule. This parameter is mandatory when type is VARIABLE or CONSTANT.
template	String	Key value rule template. This parameter is mandatory when type is VARIABLE.

Table 5-465 SmnTargetDetail

Parameter	Type	Description
urn	String	Specifies the topic URN.
agency_name	String	Agency name.
subject_transform	subject_transform object	Title rule.

Table 5-466 subject_transform

Parameter	Type	Description
type	String	Type of the title rule.
value	String	Title rule.
template	String	Title rule template. This parameter is mandatory when type is set to VARIABLE.

Table 5-467 EgTargetDetail

Parameter	Type	Description
target_project_id	String	Target project ID.
target_channel_id	String	Target channel ID.
target_region	String	Target region.
cross_region	Boolean	Indicates whether cross-region feature is enabled.
agency_name	String	Agency name.

Table 5-468 ApigwTargetDetail

Parameter	Type	Description
url	String	Target URL.
invocation_http_parameters	InvocationHttpParameters object	Parameters for invoking HTTP.

Table 5-469 InvocationHttpParameters

Parameter	Type	Description
header_parameters	Array of HeaderParameter objects	Object list.

Table 5-470 HeaderParameter

Parameter	Type	Description
is_value_secret	Boolean	Whether to encrypt the value.
key	String	Header key.
value	String	Header value.

Table 5-471 DeadLetterQueue

Parameter	Type	Description
type	String	Queue type.
instance_id	String	Instance ID.

Parameter	Type	Description
connection_id	String	Connection ID.
topic	String	Topic.

Table 5-472 RocketmqTargetDetail

Parameter	Type	Description
topic	String	Topic name.
key_transform	Transform object	Transform rule.

Table 5-473 Transform

Parameter	Type	Description
type	String	Type of the transform rule.
value	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Example Requests

Refurbish the FunctionGraph trigger of OBS bucket obs1 for EG subscription.

```
POST https://{eg_endpoint}/v1/{project_id}/subscriptions/obsbuckets/obs1/refurbishobs
```

```
{
  "agency_name" : "string",
  "id" : "string",
  "transform" : {
    "type" : "VARIABLE",
    "value" : "{ \"contant_boolean\": true, \"contant_string\": \"constant\", \"variable_string\": \"${data.string}\", \"variable_json_object\": \"${data.object}\"",
    "template" : "{ \"contant_boolean\": ${contant_boolean}, \"contant_string\": \"${contant_string!\\\\\"default\\\\\"}\"",
    \"\"} \"variable_string\": \"${contant_boolean}\", \"variable_json_object\": \"${variable_json_object!\\\\\"null\\\\\"}\""
  }
}
```

Example Responses

Status code: 200

Operation successful.

```
{
  "id" : "23709d68-54d5-423b-a6be-03302e893152",
  "name" : "test-subscription",
  "description" : "this is a test subscription",
  "type" : "EVENT",
  "status" : "CREATED",
  "channel_id" : "05649f9a-b324-4920-9c49-156d4cd2e546",
  "channel_name" : "channel006",
  "used" : [ { } ],
  "sources" : [ { } ],
  "targets" : [ { } ],
  "created_time" : "2021-12-09 09:00:00",
  "updated_time" : "2021-12-09 09:00:00"
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.14 Event Stream Management

5.14.1 Creating an Event Stream

Function

This API is used to create an event stream.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/eventstreamings

Table 5-474 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Request Parameters

Table 5-475 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-476 Request body parameters

Parameter	Mandatory	Type	Description
name	Yes	String	Event stream name. The value must be unique under a tenant. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit.
description	No	String	Description of the event stream.
source	Yes	EventStreamingSource object	Event source. An event stream has only one source.

Parameter	Mandatory	Type	Description
sink	Yes	EventStreamingSink object	Event target. An event stream has only one event target. Either sink_fg or sink_kafka can be selected.
rule_config	No	rule_config object	Event rules, including filter and transform rules.
option	No	RunOption object	Running configuration.

Table 5-477 EventStreamingSource

Parameter	Mandatory	Type	Description
source_kafka	No	SourceKafkaMQParameters object	Event source parameters.
source_mobile_rocketmq	No	SourceMobileMQParameters object	ECloud RocketMQ event source parameters
source_community_rocketmq	No	SourceCommunityMQParameters object	Open-Source RocketMQ event source parameters.
source_dms_rocketmq	No	SourceDMSMQParameters object	DMS event source parameters.
name	No	String	Event source type name.

Table 5-478 SourceKafkaMQParameters

Parameter	Mandatory	Type	Description
addr	No	String	Kafka connection address.
group	Yes	String	Kafka consumer group.
instance_name	No	String	Kafka instance name.
security_protocol	No	String	Security protocol.
instance_id	No	String	Kafka instance ID.
topic	Yes	String	Kafka topic name.

Parameter	Mandatory	Type	Description
seek_to	No	String	Consumption offset.
enable_sasl_ssl	No	Boolean	Whether to enable SASL_SSL.
sasl_mechanism	No	String	SASL authentication mechanism.
ssl_certificate_url	No	String	SASL certificate URL, which is a URL in OBS.
ssl_certificate_pwd	No	String	SASL certificate password.
user_name	No	String	Username.
password	No	String	Password.

Table 5-479 SourceMobileMQParameters

Parameter	Mandatory	Type	Description
group_id	Yes	String	Consumer group ID.
instance_id	Yes	String	Instance ID.
topic	Yes	String	topic
tag	No	String	Tag.
authentication_required	No	Boolean	Indicates whether authentication is required.
msg_trace_switch	No	Boolean	Whether message tracing is required.
access_key	No	String	AccessKey
secret_key	No	String	SecretKey
message_model	Yes	String	Subscription mode.
addr_type	Yes	String	Access type.
addr	Yes	String	Address.
sdk_url	Yes	String	Client SDK.
consume_timeout	Yes	Integer	Consumption timeout.
message_type	Yes	String	Message type.
suspend_time	No	Integer	Retry waiting time.

Parameter	Mandatory	Type	Description
max_reconsumer_times	No	Integer	Maximum retries.
consumer_thread_nums	No	Integer	Consumption threads.
consumer_batch_max_size	No	Integer	Maximum number of messages that can be consumed in a batch.
consumer_max_wait	No	Integer	Maximum waiting duration for batch consumption, in seconds.
vpc_id	No	String	VPC ID.
subnet_id	No	String	Subnet ID.

Table 5-480 SourceCommunityMQParameters

Parameter	Mandatory	Type	Description
instance_name	No	String	Instance name. This parameter is required only for DMS for RocketMQ.
instance_id	No	String	Instance ID. This parameter is required only for DMS for RocketMQ.
addr	Yes	String	RocketMQ connection address.
group	Yes	String	Consumer group.
topic	Yes	String	Topic name.
tag	No	String	Tag.
vpc_id	Yes	String	VPC ID.
subnet_id	Yes	String	Subnet ID.
ssl_enable	No	Boolean	Whether to enable SSL.
enable_acl	No	Boolean	Indicates whether to enable ACL.
access_key	No	String	Username.
secret_key	No	String	Secret key.
message_type	No	String	Message type.

Parameter	Mandatory	Type	Description
consume_timeout	No	Integer	Consumption timeout.
consumer_thread_nums	No	Integer	Number of consumption threads.
consumer_batch_max_size	No	Integer	Maximum number of messages that can be consumed in a batch.
max_reconsume_times	No	Integer	Maximum number of retries. The value -1 indicates that the retry is performed continuously.
suspend_current_queue_time_millis	No	Integer	Retry interval, in milliseconds.

Table 5-481 SourceDMSMQParameters

Parameter	Mandatory	Type	Description
instance_name	No	String	Instance name. This parameter is required only for DMS for RocketMQ.
instance_id	Yes	String	Instance ID. This parameter is required only for DMS for RocketMQ.
group	Yes	String	Consumer group.
topic	Yes	String	Topic name.
tag	No	String	Tag.
ssl_enable	No	Boolean	Whether to enable SSL.
enable_acl	No	Boolean	Indicates whether to enable ACL.
access_key	No	String	Username.
secret_key	No	String	Secret key.

Parameter	Mandatory	Type	Description
message_type	No	String	Consumption mode. The consumption mode varies according to the message production sequence. 1. Orderly production with orderly consumption: Messages are sent in order and consumed in the same order within a group. 2. Orderly production with concurrent consumption: Messages are sent in order and consumed concurrently, as close to order as possible. 3. Disorderly production with orderly consumption: Messages are sent out of order and consumed in queue order, not necessarily matching the send order. 4. Disorderly production with concurrent consumption: Messages are sent out of order and consumed concurrently, as close to order as possible.
engine_version	No	String	RocketMQ instance version.
consume_timeout	No	Integer	Consumption timeout.
consumer_thread_nums	No	Integer	Number of consumption threads.
consumer_batch_max_size	No	Integer	Maximum number of messages that can be consumed in a batch.
max_reconsume_times	No	Integer	Maximum number of retries. The value -1 indicates that the retry is performed continuously.
suspend_current_queue_time_millis	No	Integer	Retry interval, in milliseconds.

Table 5-482 EventStreamingSink

Parameter	Mandatory	Type	Description
sink_fg	No	SinkFGParameters object	FunctionGraph event target parameters.
sink_kafka	No	SinkKafkaParameters object	Kafka event target parameters.
sink_obs	No	SinkObsParameters object	OBS event target parameters.
name	No	String	Event target name.

Table 5-483 SinkFGParameters

Parameter	Mandatory	Type	Description
invoke_type	No	String	Function invocation mode, which can be asynchronous or synchronous.
urn	No	String	Function URN.
agency	No	String	Tenant agency.

Table 5-484 SinkKafkaParameters

Parameter	Mandatory	Type	Description
topic	Yes	String	Topic name.
keyTransform	No	Array of TransForm objects	Key transform rule.
connectionId	Yes	String	Connection ID.

Table 5-485 TransForm

Parameter	Mandatory	Type	Description
type	Yes	String	Type of the transform rule.

Parameter	Mandatory	Type	Description
value	No	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	No	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Table 5-486 SinkObsParameters

Parameter	Mandatory	Type	Description
access_key	Yes	String	AK
secret_key	Yes	String	SK
obs_bucket	Yes	String	Bucket.
obs_path	No	String	Dump directory.
time_format	Yes	String	Time directory format.

Table 5-487 rule_config

Parameter	Mandatory	Type	Description
transform	No	TransForm object	Transform rule of the event subscription target.
filter	No	Object	Filter rule.

Table 5-488 RunOption

Parameter	Mandatory	Type	Description
thread_num	No	Integer	Concurrency.
batch_window	No	BatchWindow object	Batch push.

Table 5-489 BatchWindow

Parameter	Mandatory	Type	Description
count	No	Integer	Number of messages to push in a batch. Range: 1–10,000.
time	No	Integer	Number of retries.
interval	No	Integer	Batch push interval. Range: 0s to 15s.

Response Parameters

Status code: 200

Table 5-490 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-491 Response body parameters

Parameter	Type	Description
eventStreamingID	String	Event stream ID.

Example Requests

Create an event stream.

POST https://{eg_endpoint}/v1/{project_id}/eventstreamings

```
{
  "name" : "test-eventstreaming",
  "description" : "this is a test eventstreaming",
  "source" : {
    "source_kafka" : {
      "addr" : "10.10.10.10:8100",
      "group" : "group-test",
      "instance_name" : "instance-name-test",
      "security_protocol" : "PLAINTEXT",
      "instance_id" : "instance-id-test",
      "topic" : "topic-test",
      "seek_to" : "earliest",
      "enable_sasl_ssl" : true,
      "sasl_mechanism" : "PLAIN",
      "ssl_certificate_url" : "https://domain/kafka-certs.zip",
      "ssl_certificate_pwd" : null,
      "user_name" : "",
      "password" : ""
    },
    "source_mobile_rocketmq" : {
      "group_id" : "string",
      "instance_id" : "string",
      "topic" : "string",
      "tag" : "string",
      "authentication_required" : true,
      "msg_trace_switch" : true,
      "access_key" : "string",
      "secret_key" : "string",
      "message_model" : "CLUSTERING",
      "addr_type" : "PUBLIC",
      "addr" : "string",
      "sdk_url" : "string",
      "consume_timeout" : 30000,
      "message_type" : "string",
      "suspend_time" : 1800,
      "max_reconsumer_times" : 3,
      "consumer_thread_nums" : 20,
      "consumer_batch_max_size" : 20,
      "consumer_max_wait" : 5,
      "vpc_id" : "string",
      "subnet_id" : "string"
    },
    "source_community_rocketmq" : {
      "instance_name" : "instance-name-test",
      "instance_id" : "instance-id-test",
      "addr" : "10.10.10.10:8100",
      "group" : "group-test",
      "topic" : "topic-test",
      "tag" : "string",
      "vpc_id" : "string",
      "subnet_id" : "string",
      "ssl_enable" : true,
      "enable_acl" : true,
      "access_key" : "string",
      "secret_key" : "string",
      "message_type" : "string",
      "consume_timeout" : 30000,
      "consumer_thread_nums" : 20,
      "consumer_batch_max_size" : 1,
      "max_reconsume_times" : -1,
      "suspend_current_queue_time_millis" : 1000
    },
    "source_dms_rocketmq" : {
```

```
    "instance_name" : "instance-name-test",
    "instance_id" : "instance-id-test",
    "group" : "group-test",
    "topic" : "topic-test",
    "tag" : "string",
    "ssl_enable" : true,
    "enable_acl" : true,
    "access_key" : "string",
    "secret_key" : "string",
    "message_type" : "string",
    "engine_version" : "string",
    "consume_timeout" : 30000,
    "consumer_thread_nums" : 20,
    "consumer_batch_max_size" : 1,
    "max_reconsume_times" : -1,
    "suspend_current_queue_time_millis" : 1000
  },
  "name" : "string"
},
"sink" : {
  "sink_fg" : {
    "invoke_type" : "SYNC/ASYNC",
    "urn" : "String",
    "agency" : "string"
  },
  "sink_kafka" : {
    "topic" : "string",
    "keyTransform" : [ {
      "type" : "VARIABLE",
      "value" : "{\"contant_boolean\": true,\"contant_string\": \"constant\", \"variable_string\": \"$.data.string\", \"variable_json_object\": \"$.data.object\"}",
      "template" : "{\"contant_boolean\": ${contant_boolean}, \"contant_string\": \"${contant_string!}\\\"default\\\"}\"",
      "variable_string": \"${contant_boolean}\", \"variable_json_object\": \"${variable_json_object!}\\\"null\\\"}\""
    } ],
    "connectionId" : "string"
  },
  "sink_obs" : {
    "access_key" : "string",
    "secret_key" : "string",
    "obs_bucket" : "string",
    "obs_path" : "string",
    "time_format" : "string"
  },
  "name" : "string"
},
"rule_config" : {
  "transform" : {
    "type" : "VARIABLE",
    "value" : "{\"contant_boolean\": true,\"contant_string\": \"constant\", \"variable_string\": \"$.data.string\", \"variable_json_object\": \"$.data.object\"}",
    "template" : "{\"contant_boolean\": ${contant_boolean}, \"contant_string\": \"${contant_string!}\\\"default\\\"}\"",
    "variable_string": \"${contant_boolean}\", \"variable_json_object\": \"${variable_json_object!}\\\"null\\\"}\""
  },
  "filter" : { }
},
"option" : {
  "thread_num" : "3",
  "batch_window" : {
    "count" : 500,
    "time" : 10,
    "interval" : 0
  }
}
```

Example Responses

Status code: 200

Event stream created.

```
{  
  "eventStreamingID" : "23709d68-54d5-423b-a6be-03302e893152"  
}
```

Status Codes

Status Code	Description
200	Event stream created.

Error Codes

See [Error Codes](#).

5.14.2 Obtaining the Event Stream List

Function

This API is used to obtain the event stream list.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/eventstreamings

Table 5-492 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-493 Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Offset, which is the position where the query starts. The value must be greater than or equal to 0.

Parameter	Mandatory	Type	Description
limit	No	Integer	Number of records displayed on each page. The value must be within the range [1, 1000].

Request Parameters

Table 5-494 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-495 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-496 Response body parameters

Parameter	Type	Description
total	Integer	Total number.
size	Integer	Number of records displayed on the current page.
items	Array of EventStreamingDetail objects	Object list.

Table 5-497 EventStreamingDetail

Parameter	Type	Description
name	String	Event stream name. The value must be unique under a tenant. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit.
description	String	Description of the event stream.
source	EventStreamingSource object	Event source. An event stream has only one source.
sink	EventStreamingSink object	Event target. An event stream has only one event target. Either sink_fg or sink_kafka can be selected.
rule_config	rule_config object	Event rules, including filter and transform rules.
option	RunOption object	Running configuration.
status	String	Event stream status.
id	String	Event stream ID.
created_time	String	Creation time.
updated_time	String	Update time.

Table 5-498 EventStreamingSource

Parameter	Type	Description
source_kafka	SourceKafkaMQParameters object	Event source parameters.
source_mobile_rocketmq	SourceMobileMQParameters object	ECloud RocketMQ event source parameters
source_community_rocketmq	SourceCommunityMQParameters object	Open-Source RocketMQ event source parameters.
source_dms_rocketmq	SourceDMSMQParameters object	DMS event source parameters.
name	String	Event source type name.

Table 5-499 SourceKafkaMQParameters

Parameter	Type	Description
addr	String	Kafka connection address.
group	String	Kafka consumer group.
instance_name	String	Kafka instance name.
security_protocol	String	Security protocol.
instance_id	String	Kafka instance ID.
topic	String	Kafka topic name.
seek_to	String	Consumption offset.
enable_sasl_ssl	Boolean	Whether to enable SASL_SSL.
sasl_mechanism	String	SASL authentication mechanism.
ssl_certificate_url	String	SASL certificate URL, which is a URL in OBS.
ssl_certificate_password	String	SASL certificate password.
user_name	String	Username.
password	String	Password.

Table 5-500 SourceMobileMQParameters

Parameter	Type	Description
group_id	String	Consumer group ID.
instance_id	String	Instance ID.
topic	String	topic
tag	String	Tag.
authentication_required	Boolean	Indicates whether authentication is required.
msg_trace_switch	Boolean	Whether message tracing is required.
access_key	String	AccessKey
secret_key	String	SecretKey
message_model	String	Subscription mode.
addr_type	String	Access type.
addr	String	Address.

Parameter	Type	Description
sdk_url	String	Client SDK.
consume_timeout	Integer	Consumption timeout.
message_type	String	Message type.
suspend_time	Integer	Retry waiting time.
max_reconsumer_times	Integer	Maximum retries.
consumer_thread_nums	Integer	Consumption threads.
consumer_batch_max_size	Integer	Maximum number of messages that can be consumed in a batch.
consumer_max_wait	Integer	Maximum waiting duration for batch consumption, in seconds.
vpc_id	String	VPC ID.
subnet_id	String	Subnet ID.

Table 5-501 SourceCommunityMQParameters

Parameter	Type	Description
instance_name	String	Instance name. This parameter is required only for DMS for RocketMQ.
instance_id	String	Instance ID. This parameter is required only for DMS for RocketMQ.
addr	String	RocketMQ connection address.
group	String	Consumer group.
topic	String	Topic name.
tag	String	Tag.
vpc_id	String	VPC ID.
subnet_id	String	Subnet ID.
ssl_enable	Boolean	Whether to enable SSL.
enable_acl	Boolean	Indicates whether to enable ACL.
access_key	String	Username.
secret_key	String	Secret key.
message_type	String	Message type.

Parameter	Type	Description
consume_timeout	Integer	Consumption timeout.
consumer_thread_nums	Integer	Number of consumption threads.
consumer_batch_max_size	Integer	Maximum number of messages that can be consumed in a batch.
max_reconsume_times	Integer	Maximum number of retries. The value -1 indicates that the retry is performed continuously.
suspend_current_queue_time_millis	Integer	Retry interval, in milliseconds.

Table 5-502 SourceDMSMQParameters

Parameter	Type	Description
instance_name	String	Instance name. This parameter is required only for DMS for RocketMQ.
instance_id	String	Instance ID. This parameter is required only for DMS for RocketMQ.
group	String	Consumer group.
topic	String	Topic name.
tag	String	Tag.
ssl_enable	Boolean	Whether to enable SSL.
enable_acl	Boolean	Indicates whether to enable ACL.
access_key	String	Username.
secret_key	String	Secret key.

Parameter	Type	Description
message_type	String	Consumption mode. The consumption mode varies according to the message production sequence. 1. Orderly production with orderly consumption: Messages are sent in order and consumed in the same order within a group. 2. Orderly production with concurrent consumption: Messages are sent in order and consumed concurrently, as close to order as possible. 3. Disorderly production with orderly consumption: Messages are sent out of order and consumed in queue order, not necessarily matching the send order. 4. Disorderly production with concurrent consumption: Messages are sent out of order and consumed concurrently, as close to order as possible.
engine_version	String	RocketMQ instance version.
consume_timeout	Integer	Consumption timeout.
consumer_thread_nums	Integer	Number of consumption threads.
consumer_batch_max_size	Integer	Maximum number of messages that can be consumed in a batch.
max_reconsume_times	Integer	Maximum number of retries. The value -1 indicates that the retry is performed continuously.
suspend_current_queue_time_millis	Integer	Retry interval, in milliseconds.

Table 5-503 EventStreamingSink

Parameter	Type	Description
sink_fg	SinkFGParameters object	FunctionGraph event target parameters.
sink_kafka	SinkKafkaParameters object	Kafka event target parameters.
sink_obs	SinkObsParameters object	OBS event target parameters.
name	String	Event target name.

Table 5-504 SinkFGParameters

Parameter	Type	Description
invoke_type	String	Function invocation mode, which can be asynchronous or synchronous.
urn	String	Function URN.
agency	String	Tenant agency.

Table 5-505 SinkKafkaParameters

Parameter	Type	Description
topic	String	Topic name.
keyTransform	Array of TransForm objects	Key transform rule.
connectionId	String	Connection ID.

Table 5-506 TransForm

Parameter	Type	Description
type	String	Type of the transform rule.
value	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.

Parameter	Type	Description
template	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Table 5-507 SinkObsParameters

Parameter	Type	Description
access_key	String	AK
secret_key	String	SK
obs_bucket	String	Bucket.
obs_path	String	Dump directory.
time_format	String	Time directory format.

Table 5-508 rule_config

Parameter	Type	Description
transform	TransForm object	Transform rule of the event subscription target.
filter	Object	Filter rule.

Table 5-509 RunOption

Parameter	Type	Description
thread_num	Integer	Concurrency.
batch_window	BatchWindow object	Batch push.

Table 5-510 BatchWindow

Parameter	Type	Description
count	Integer	Number of messages to push in a batch. Range: 1–10,000.
time	Integer	Number of retries.
interval	Integer	Batch push interval. Range: 0s to 15s.

Example Requests

Obtain the event stream list.

```
GET https://{eg_endpoint}/v1/{project_id}/eventstreamings
```

Example Responses

Status code: 200

Operation successful.

```
{
  "total" : 1,
  "size" : 1,
  "items" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.14.3 Updating an Event Stream

Function

This API is used to update an event stream.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

```
PUT /v1/{project_id}/eventstreamings/{eventstreaming_id}
```

Table 5-511 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
eventstreaming_id	Yes	String	Event stream ID.

Request Parameters

Table 5-512 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-513 Request body parameters

Parameter	Mandatory	Type	Description
name	Yes	String	Event stream name. The value must be unique under a tenant. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit.
description	No	String	Description of the event stream.
source	Yes	EventStreamingSource object	Event source. An event stream has only one source.
sink	Yes	EventStreamingSink object	Event target. An event stream has only one event target. Either sink_fg or sink_kafka can be selected.
rule_config	No	rule_config object	Event rules, including filter and transform rules.
option	No	RunOption object	Running configuration.

Table 5-514 EventStreamingSource

Parameter	Mandatory	Type	Description
source_kafka	No	SourceKafkaMQParameters object	Event source parameters.

Parameter	Mandatory	Type	Description
source_mobile_rocketmq	No	SourceMobileMQParameters object	ECloud RocketMQ event source parameters
source_community_rocketmq	No	SourceCommunityMQParameters object	Open-Source RocketMQ event source parameters.
source_dms_rocketmq	No	SourceDMSMQParameters object	DMS event source parameters.
name	No	String	Event source type name.

Table 5-515 SourceKafkaMQParameters

Parameter	Mandatory	Type	Description
addr	No	String	Kafka connection address.
group	Yes	String	Kafka consumer group.
instance_name	No	String	Kafka instance name.
security_protocol	No	String	Security protocol.
instance_id	No	String	Kafka instance ID.
topic	Yes	String	Kafka topic name.
seek_to	No	String	Consumption offset.
enable_sasl_ssl	No	Boolean	Whether to enable SASL_SSL.
sasl_mechanism	No	String	SASL authentication mechanism.
ssl_certificate_url	No	String	SASL certificate URL, which is a URL in OBS.
ssl_certificate_pwd	No	String	SASL certificate password.
user_name	No	String	Username.
password	No	String	Password.

Table 5-516 SourceMobileMQParameters

Parameter	Mandatory	Type	Description
group_id	Yes	String	Consumer group ID.
instance_id	Yes	String	Instance ID.
topic	Yes	String	topic
tag	No	String	Tag.
authentication_required	No	Boolean	Indicates whether authentication is required.
msg_trace_switch	No	Boolean	Whether message tracing is required.
access_key	No	String	AccessKey
secret_key	No	String	SecretKey
message_model	Yes	String	Subscription mode.
addr_type	Yes	String	Access type.
addr	Yes	String	Address.
sdk_url	Yes	String	Client SDK.
consume_timeout	Yes	Integer	Consumption timeout.
message_type	Yes	String	Message type.
suspend_time	No	Integer	Retry waiting time.
max_reconsume_times	No	Integer	Maximum retries.
consumer_thread_nums	No	Integer	Consumption threads.
consumer_batch_max_size	No	Integer	Maximum number of messages that can be consumed in a batch.
consumer_max_wait	No	Integer	Maximum waiting duration for batch consumption, in seconds.
vpc_id	No	String	VPC ID.
subnet_id	No	String	Subnet ID.

Table 5-517 SourceCommunityMQParameters

Parameter	Mandatory	Type	Description
instance_name	No	String	Instance name. This parameter is required only for DMS for RocketMQ.
instance_id	No	String	Instance ID. This parameter is required only for DMS for RocketMQ.
addr	Yes	String	RocketMQ connection address.
group	Yes	String	Consumer group.
topic	Yes	String	Topic name.
tag	No	String	Tag.
vpc_id	Yes	String	VPC ID.
subnet_id	Yes	String	Subnet ID.
ssl_enable	No	Boolean	Whether to enable SSL.
enable_acl	No	Boolean	Indicates whether to enable ACL.
access_key	No	String	Username.
secret_key	No	String	Secret key.
message_type	No	String	Message type.
consume_timeout	No	Integer	Consumption timeout.
consumer_thread_nums	No	Integer	Number of consumption threads.
consumer_batch_max_size	No	Integer	Maximum number of messages that can be consumed in a batch.
max_reconsume_times	No	Integer	Maximum number of retries. The value -1 indicates that the retry is performed continuously.
suspend_current_queue_time_millis	No	Integer	Retry interval, in milliseconds.

Table 5-518 SourceDMSMQParameters

Parameter	Mandatory	Type	Description
instance_name	No	String	Instance name. This parameter is required only for DMS for RocketMQ.
instance_id	Yes	String	Instance ID. This parameter is required only for DMS for RocketMQ.
group	Yes	String	Consumer group.
topic	Yes	String	Topic name.
tag	No	String	Tag.
ssl_enable	No	Boolean	Whether to enable SSL.
enable_acl	No	Boolean	Indicates whether to enable ACL.
access_key	No	String	Username.
secret_key	No	String	Secret key.
message_type	No	String	Consumption mode. The consumption mode varies according to the message production sequence. 1. Orderly production with orderly consumption: Messages are sent in order and consumed in the same order within a group. 2. Orderly production with concurrent consumption: Messages are sent in order and consumed concurrently, as close to order as possible. 3. Disorderly production with orderly consumption: Messages are sent out of order and consumed in queue order, not necessarily matching the send order. 4. Disorderly production with concurrent consumption: Messages are sent out of order and consumed concurrently, as close to order as possible.
engine_version	No	String	RocketMQ instance version.

Parameter	Mandatory	Type	Description
consume_timeout	No	Integer	Consumption timeout.
consumer_thread_nums	No	Integer	Number of consumption threads.
consumer_batch_max_size	No	Integer	Maximum number of messages that can be consumed in a batch.
max_reconsume_times	No	Integer	Maximum number of retries. The value -1 indicates that the retry is performed continuously.
suspend_current_queue_time_millis	No	Integer	Retry interval, in milliseconds.

Table 5-519 EventStreamingSink

Parameter	Mandatory	Type	Description
sink_fg	No	SinkFGParameters object	FunctionGraph event target parameters.
sink_kafka	No	SinkKafkaParameters object	Kafka event target parameters.
sink_obs	No	SinkObsParameters object	OBS event target parameters.
name	No	String	Event target name.

Table 5-520 SinkFGParameters

Parameter	Mandatory	Type	Description
invoke_type	No	String	Function invocation mode, which can be asynchronous or synchronous.
urn	No	String	Function URN.
agency	No	String	Tenant agency.

Table 5-521 SinkKafkaParameters

Parameter	Mandatory	Type	Description
topic	Yes	String	Topic name.
keyTransform	No	Array of TransForm objects	Key transform rule.
connectionId	Yes	String	Connection ID.

Table 5-522 TransForm

Parameter	Mandatory	Type	Description
type	Yes	String	Type of the transform rule.
value	No	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	No	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Table 5-523 SinkObsParameters

Parameter	Mandatory	Type	Description
access_key	Yes	String	AK
secret_key	Yes	String	SK
obs_bucket	Yes	String	Bucket.
obs_path	No	String	Dump directory.
time_format	Yes	String	Time directory format.

Table 5-524 rule_config

Parameter	Mandatory	Type	Description
transform	No	TransForm object	Transform rule of the event subscription target.
filter	No	Object	Filter rule.

Table 5-525 RunOption

Parameter	Mandatory	Type	Description
thread_num	No	Integer	Concurrency.
batch_window	No	BatchWindow object	Batch push.

Table 5-526 BatchWindow

Parameter	Mandatory	Type	Description
count	No	Integer	Number of messages to push in a batch. Range: 1–10,000.
time	No	Integer	Number of retries.
interval	No	Integer	Batch push interval. Range: 0s to 15s.

Response Parameters

Status code: 200

Table 5-527 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-528 Response body parameters

Parameter	Type	Description
eventStreamingID	String	Event stream ID.

Example Requests

Update the eventstreaming_id event stream.

PUT https://{eg_endpoint}/v1/{project_id}/eventstreamings/{eventstreaming_id}

```
{
  "name" : "test-eventstreaming",
  "description" : "this is a test eventstreaming",
  "source" : {
    "source_kafka" : {
      "addr" : "10.10.10.10:8100",
      "group" : "group-test",
      "instance_name" : "instance-name-test",
      "security_protocol" : "PLAINTEXT",
      "instance_id" : "instance-id-test",
      "topic" : "topic-test",
      "seek_to" : "earliest",
      "enable_sasl_ssl" : true,
      "sasl_mechanism" : "PLAIN",
      "ssl_certificate_url" : "https://domain/kafka-certs.zip",
      "ssl_certificate_pwd" : null,
      "user_name" : "",
      "password" : ""
    },
    "source_mobile_rocketmq" : {
      "group_id" : "string",
      "instance_id" : "string",
      "topic" : "string",
      "tag" : "string",
      "authentication_required" : true,
      "msg_trace_switch" : true,
      "access_key" : "string",
      "secret_key" : "string",
      "message_model" : "CLUSTERING",
      "addr_type" : "PUBLIC",
      "addr" : "string",
      "sdk_url" : "string",
      "consume_timeout" : 30000,
      "message_type" : "string",
      "suspend_time" : 1800,
      "max_reconsumer_times" : 3,
      "consumer_thread_nums" : 20,
      "consumer_batch_max_size" : 20,
      "consumer_max_wait" : 5,
      "vpc_id" : "string",
      "subnet_id" : "string"
    }
  }
}
```

```
    },
    "source_community_rocketmq" : {
      "instance_name" : "instance-name-test",
      "instance_id" : "instance-id-test",
      "addr" : "10.10.10.10:8100",
      "group" : "group-test",
      "topic" : "topic-test",
      "tag" : "string",
      "vpc_id" : "string",
      "subnet_id" : "string",
      "ssl_enable" : true,
      "enable_acl" : true,
      "access_key" : "string",
      "secret_key" : "string",
      "message_type" : "string",
      "consume_timeout" : 30000,
      "consumer_thread_nums" : 20,
      "consumer_batch_max_size" : 1,
      "max_reconsume_times" : -1,
      "suspend_current_queue_time_millis" : 1000
    },
    "source_dms_rocketmq" : {
      "instance_name" : "instance-name-test",
      "instance_id" : "instance-id-test",
      "group" : "group-test",
      "topic" : "topic-test",
      "tag" : "string",
      "ssl_enable" : true,
      "enable_acl" : true,
      "access_key" : "string",
      "secret_key" : "string",
      "message_type" : "string",
      "engine_version" : "string",
      "consume_timeout" : 30000,
      "consumer_thread_nums" : 20,
      "consumer_batch_max_size" : 1,
      "max_reconsume_times" : -1,
      "suspend_current_queue_time_millis" : 1000
    },
    "name" : "string"
  },
  "sink" : {
    "sink_fg" : {
      "invoke_type" : "SYNC/ASYNC",
      "urn" : "String",
      "agency" : "string"
    },
    "sink_kafka" : {
      "topic" : "string",
      "keyTransform" : [ {
        "type" : "VARIABLE",
        "value" : "{ \"contant_boolean\": true, \"contant_string\": \"constant\", \"variable_string\": \"$.data.string\", \"variable_json_object\": \"$.data.object\" }",
        "template" : "{ \"contant_boolean\": ${contant_boolean}, \"contant_string\": \"${contant_string!}\\\"default\\\"\", \"variable_string\": \"${contant_boolean}\", \"variable_json_object\": ${variable_json_object!}\\\"null\\\"}\""
      } ],
      "connectionId" : "string"
    },
    "sink_obs" : {
      "access_key" : "string",
      "secret_key" : "string",
      "obs_bucket" : "string",
      "obs_path" : "string",
      "time_format" : "string"
    },
    "name" : "string"
  },
  "rule_config" : {
```

```
"transform" : {
  "type" : "VARIABLE",
  "value" : "{ \"contant_boolean\": true, \"contant_string\": \"constant\", \"variable_string\": \"$.data.string\", \"variable_json_object\": \"$.data.object\" }",
  "template" : "{ \"contant_boolean\": ${contant_boolean}, \"contant_string\": \"${contant_string!\\\\\"default\\\\\"}\"\", \"variable_string\": \"${contant_boolean}\", \"variable_json_object\": \"${variable_json_object!\"null\"}\"\" }",
  "filter" : { }
},
"option" : {
  "thread_num" : "3",
  "batch_window" : {
    "count" : 500,
    "time" : 10,
    "interval" : 0
  }
}
```

Example Responses

Status code: 200

Operation successful.

```
{
  "eventStreamingID" : "23709d68-54d5-423b-a6be-03302e893152"
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.14.4 Obtaining Event Stream Details

Function

This API is used to obtain the details of an event stream.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/eventstreamings/{eventstreaming_id}

Table 5-529 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
eventstreaming_id	Yes	String	Event stream ID.

Request Parameters

Table 5-530 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-531 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-532 Response body parameters

Parameter	Type	Description
name	String	Event stream name. The value must be unique under a tenant. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit.
description	String	Description of the event stream.
source	EventStreamingSource object	Event source. An event stream has only one source.

Parameter	Type	Description
sink	EventStreamingSink object	Event target. An event stream has only one event target. Either sink_fg or sink_kafka can be selected.
rule_config	rule_config object	Event rules, including filter and transform rules.
option	RunOption object	Running configuration.
status	String	Event stream status.
id	String	Event stream ID.
created_time	String	Creation time.
updated_time	String	Update time.

Table 5-533 EventStreamingSource

Parameter	Type	Description
source_kafka	SourceKafkaMQParameters object	Event source parameters.
source_mobile_rocketmq	SourceMobileMQParameters object	ECloud RocketMQ event source parameters
source_community_rocketmq	SourceCommunityMQParameters object	Open-Source RocketMQ event source parameters.
source_dms_rocketmq	SourceDMSMQParameters object	DMS event source parameters.
name	String	Event source type name.

Table 5-534 SourceKafkaMQParameters

Parameter	Type	Description
addr	String	Kafka connection address.
group	String	Kafka consumer group.
instance_name	String	Kafka instance name.
security_protocol	String	Security protocol.
instance_id	String	Kafka instance ID.
topic	String	Kafka topic name.

Parameter	Type	Description
seek_to	String	Consumption offset.
enable_sasl_ssl	Boolean	Whether to enable SASL_SSL.
sasl_mechanism	String	SASL authentication mechanism.
ssl_certificate_url	String	SASL certificate URL, which is a URL in OBS.
ssl_certificate_password	String	SASL certificate password.
user_name	String	Username.
password	String	Password.

Table 5-535 SourceMobileMQParameters

Parameter	Type	Description
group_id	String	Consumer group ID.
instance_id	String	Instance ID.
topic	String	topic
tag	String	Tag.
authentication_required	Boolean	Indicates whether authentication is required.
msg_trace_switch	Boolean	Whether message tracing is required.
access_key	String	AccessKey
secret_key	String	SecretKey
message_model	String	Subscription mode.
addr_type	String	Access type.
addr	String	Address.
sdk_url	String	Client SDK.
consume_timeout	Integer	Consumption timeout.
message_type	String	Message type.
suspend_time	Integer	Retry waiting time.
max_reconsumer_times	Integer	Maximum retries.
consumer_thread_nums	Integer	Consumption threads.

Parameter	Type	Description
consumer_batch_max_size	Integer	Maximum number of messages that can be consumed in a batch.
consumer_max_wait	Integer	Maximum waiting duration for batch consumption, in seconds.
vpc_id	String	VPC ID.
subnet_id	String	Subnet ID.

Table 5-536 SourceCommunityMQParameters

Parameter	Type	Description
instance_name	String	Instance name. This parameter is required only for DMS for RocketMQ.
instance_id	String	Instance ID. This parameter is required only for DMS for RocketMQ.
addr	String	RocketMQ connection address.
group	String	Consumer group.
topic	String	Topic name.
tag	String	Tag.
vpc_id	String	VPC ID.
subnet_id	String	Subnet ID.
ssl_enable	Boolean	Whether to enable SSL.
enable_acl	Boolean	Indicates whether to enable ACL.
access_key	String	Username.
secret_key	String	Secret key.
message_type	String	Message type.
consume_timeout	Integer	Consumption timeout.
consumer_thread_nums	Integer	Number of consumption threads.
consumer_batch_max_size	Integer	Maximum number of messages that can be consumed in a batch.
max_reconsume_times	Integer	Maximum number of retries. The value -1 indicates that the retry is performed continuously.

Parameter	Type	Description
suspend_current_queue_time_millis	Integer	Retry interval, in milliseconds.

Table 5-537 SourceDMSMQParameters

Parameter	Type	Description
instance_name	String	Instance name. This parameter is required only for DMS for RocketMQ.
instance_id	String	Instance ID. This parameter is required only for DMS for RocketMQ.
group	String	Consumer group.
topic	String	Topic name.
tag	String	Tag.
ssl_enable	Boolean	Whether to enable SSL.
enable_acl	Boolean	Indicates whether to enable ACL.
access_key	String	Username.
secret_key	String	Secret key.
message_type	String	Consumption mode. The consumption mode varies according to the message production sequence. 1. Orderly production with orderly consumption: Messages are sent in order and consumed in the same order within a group. 2. Orderly production with concurrent consumption: Messages are sent in order and consumed concurrently, as close to order as possible. 3. Disorderly production with orderly consumption: Messages are sent out of order and consumed in queue order, not necessarily matching the send order. 4. Disorderly production with concurrent consumption: Messages are sent out of order and consumed concurrently, as close to order as possible.
engine_version	String	RocketMQ instance version.
consume_timeout	Integer	Consumption timeout.

Parameter	Type	Description
consumer_thread_nums	Integer	Number of consumption threads.
consumer_batch_max_size	Integer	Maximum number of messages that can be consumed in a batch.
max_reconsume_times	Integer	Maximum number of retries. The value -1 indicates that the retry is performed continuously.
suspend_current_queue_time_millis	Integer	Retry interval, in milliseconds.

Table 5-538 EventStreamingSink

Parameter	Type	Description
sink_fg	SinkFGParameters object	FunctionGraph event target parameters.
sink_kafka	SinkKafkaParameters object	Kafka event target parameters.
sink_obs	SinkObsParameters object	OBS event target parameters.
name	String	Event target name.

Table 5-539 SinkFGParameters

Parameter	Type	Description
invoke_type	String	Function invocation mode, which can be asynchronous or synchronous.
urn	String	Function URN.
agency	String	Tenant agency.

Table 5-540 SinkKafkaParameters

Parameter	Type	Description
topic	String	Topic name.
keyTransform	Array of TransForm objects	Key transform rule.

Parameter	Type	Description
connectionId	String	Connection ID.

Table 5-541 TransForm

Parameter	Type	Description
type	String	Type of the transform rule.
value	String	For a constant type rule, the field is the constant content definition. For a variable type rule, the field is a variable definition and the content must be a JSON object string. A maximum of 100 variables are supported, and nested structures are not supported. The variable name can contain a maximum of 64 characters. Only letters, digits, periods (.), underscores (_), and hyphens (-) are allowed. It must start with a letter or digit and cannot start with HC.. The variable value expression can be a constant or JSONPath expression. The string length cannot exceed 1024 characters.
template	String	Template definition of the rule content when the rule is of the variable type. Defined variables can be referenced.

Table 5-542 SinkObsParameters

Parameter	Type	Description
access_key	String	AK
secret_key	String	SK
obs_bucket	String	Bucket.
obs_path	String	Dump directory.
time_format	String	Time directory format.

Table 5-543 rule_config

Parameter	Type	Description
transform	TransForm object	Transform rule of the event subscription target.
filter	Object	Filter rule.

Table 5-544 RunOption

Parameter	Type	Description
thread_num	Integer	Concurrency.
batch_window	BatchWindow object	Batch push.

Table 5-545 BatchWindow

Parameter	Type	Description
count	Integer	Number of messages to push in a batch. Range: 1–10,000.
time	Integer	Number of retries.
interval	Integer	Batch push interval. Range: 0s to 15s.

Example Requests

Obtain event stream details.

```
GET https://{eg_endpoint}/v1/{project_id}/eventstreamings/{eventstreaming_id}
```

Example Responses

Status code: 200

Details of an event stream.

```
{
  "name" : "test-eventstreaming",
  "description" : "this is a test eventstreaming",
  "source" : { },
  "sink" : { },
  "rule_config" : {
    "transform" : { },
    "filter" : { }
  },
  "option" : { },
  "status" : "running",
  "id" : "string",
  "created_time" : "string",
```

```
"updated_time" : "string"  
}
```

Status Codes

Status Code	Description
200	Details of an event stream.

Error Codes

See [Error Codes](#).

5.14.5 Deleting an Event Stream

Function

This API is used to delete an event stream.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

DELETE /v1/{project_id}/eventstreamings/{eventstreaming_id}

Table 5-546 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
eventstreaming_id	Yes	String	Event stream ID.

Request Parameters

Table 5-547 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 204

Successful.

None

Example Requests

Delete the event stream whose ID is 123.

```
DELETE https://{endpoint}/v1/{project_id}/eventstreamings/123
```

Example Responses

None

Status Codes

Status Code	Description
204	Successful.

Error Codes

See [Error Codes](#).

5.14.6 Starting/Stopping an Event Stream

Function

This API is used to start or stop an event stream.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/eventstreamings/operate/{eventstreaming_id}

Table 5-548 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
eventstreaming_id	Yes	String	Event stream ID.

Request Parameters

Table 5-549 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-550 Request body parameters

Parameter	Mandatory	Type	Description
operation	No	String	Operation type.

Response Parameters

Status code: 200

Table 5-551 Response header parameters

Parameter	Type	Description
X-Request-Id	String	This field is the request ID number for task tracking. Format is request_uuid-timestamp-hostname.

Table 5-552 Response body parameters

Parameter	Type	Description
eventStreamingID	String	Event stream ID.

Example Requests

Stop the event stream whose ID is 123.

```
POST https://{eg_endpoint}/v1/{project_id}/eventstreamings/operate/123
{
  "operation": "PAUSE"
}
```

Example Responses

Status code: 200

Operation successful.

```
{
  "eventStreamingID": "23709d68-54d5-423b-a6be-03302e893152"
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.15 Event Example Management

5.15.1 Obtaining the Event Example List

Function

This API is used to obtain the event example list.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/samples

Table 5-553 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-554 Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Offset, which is the position where the query starts. The value must be greater than or equal to 0.
limit	No	Integer	Number of records displayed on each page. The value must be within the range [1, 1000].
sort	No	String	Sorting mode of the query results.
name	No	String	Name of the event example. It is used for fuzzy match.
event_type_name	No	String	Event type name of the event example.
event_source_id	No	String	Event source of the event example.

Request Parameters

Table 5-555 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-556 Response body parameters

Parameter	Type	Description
total	Integer	Total number.
size	Integer	Number of records displayed on the current page.
items	Array of EventSampleItemInfo objects	Object list.

Table 5-557 EventSampleItemInfo

Parameter	Type	Description
id	String	Event example ID.
name	String	Event example name.
content	String	Event example content.
event_type_id	String	Event type ID corresponding to the event example.
event_type_name	String	Event type name corresponding to the event example.
event_source_id	String	Event source ID corresponding to the event example.
event_source_name	String	Name of the event source corresponding to the event example.

Parameter	Type	Description
created_time	String	Creation time.
updated_time	String	Update time.
deleted_time	String	Deletion time.

Example Requests

Obtain the event example list.

```
GET https://{eg_endpoint}/v1/{project_id}/samples
```

Example Responses

Status code: 200

Operation successful.

```
{
  "total" : 1,
  "size" : 1,
  "items" : [ { } ]
}
```

Status Codes

Status Code	Description
200	Operation successful.

Error Codes

See [Error Codes](#).

5.16 Professional Event Stream Job Management

5.16.1 Create a Professional Event Stream Job

Function

This API is used to create a professional event stream job.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/eventrouter/jobs

Table 5-558 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Request Parameters

Table 5-559 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-560 Request body parameters

Parameter	Mandatory	Type	Description
cluster_id	Yes	String	Professional event stream cluster ID.
name	Yes	String	Job name. Start with a letter or digit, and only include letters, digits, periods (.), underscores (_), and hyphens (-). (Max. 128 characters)
description	No	String	Job description. The description can contain a maximum of 256 characters.
scene_type	Yes	String	Scenario type. DISASTER_BACKUP: synchronization task.
source_config	No	EventRouterJobSource object	Source configuration of a professional event stream job.
sink_config	No	EventRouterJobSink object	Target configuration of a professional event stream job.

Parameter	Mandatory	Type	Description
advance_config	No	EventRouterAdvanceConfig object	Advanced configuration of professional event stream jobs.

Table 5-561 EventRouterJobSource

Parameter	Mandatory	Type	Description
source_kafka	No	KafkaParameters object	Kafka configuration.
source_rocketmq	No	RocketmqParameters object	RocketMQ configuration.
source_dcs	No	DcsParameters object	DCS configuration.

Table 5-562 EventRouterJobSink

Parameter	Mandatory	Type	Description
sink_kafka	No	KafkaParameters object	Kafka configuration.
sink_rocketmq	No	RocketmqParameters object	RocketMQ configuration.
sink_dcs	No	DcsParameters object	DCS configuration.

Table 5-563 KafkaParameters

Parameter	Mandatory	Type	Description
config_type	Yes	String	Instance type. CLOUD: DMS for Kafka instance.
region	Yes	String	Region ID.
project_id	Yes	String	Resource space ID.

Parameter	Mandatory	Type	Description
instance_id	No	String	Kafka instance ID. This parameter is mandatory when configuration type is set to CLOUD.
cluster_alias	Yes	String	Kafka cluster alias.
address	No	String	Kafka address.
authenticate_mode	No	String	Authentication mode for Kafka.
sasl_mechanism	No	String	SASL authentication mechanism.
user_name	No	String	Username. This parameter is mandatory when SASL_SSL is enabled.
password	No	String	Password. This parameter is mandatory when SASL_SSL is enabled.

Table 5-564 RocketmqParameters

Parameter	Mandatory	Type	Description
config_type	Yes	String	Instance type. CLOUD: DMS for RocketMQ instance
region	Yes	String	Region ID.
project_id	Yes	String	Resource space ID.
instance_id	No	String	RocketMQ instance ID. This parameter is mandatory when the configuration type is CLOUD.
cluster_alias	Yes	String	RocketMQ cluster alias.
address	No	String	RocketMQ address.
ssl_open	No	String	Whether to enable RocketMQ SSL. true: Enable false: Disable

Parameter	Mandatory	Type	Description
acl_open	No	Boolean	Whether to enable RocketMQ ACL. true: Enable false: Disable
user_name	No	String	Username. This parameter is mandatory when ACL is enabled.
password	No	String	Password. This parameter is mandatory when ACL is enabled.

Table 5-565 DcsParameters

Parameter	Mandatory	Type	Description
config_type	Yes	String	Instance type. CLOUD: DCS instance
region	Yes	String	Region ID.
project_id	Yes	String	Resource space ID.
instance_id	No	String	DCS instance ID. This parameter is mandatory when the configuration type is set to CLOUD.
address	No	String	DCS address.
password	No	String	Password.

Table 5-566 EventRouterAdvanceConfig

Parameter	Mandatory	Type	Description
kafka2kafka	No	Kafka2KafkaAdvanceConfig object	Kafka synchronization custom configuration.
rocketmq2rocketmq	No	Rocketmq2RocketmqAdvanceConfig object	RocketMQ synchronization custom configuration.
dcs2dcs	No	Dcs2DcsAdvanceConfig object	DCS synchronization custom configuration.

Table 5-567 Kafka2KafkaAdvanceConfig

Parameter	Mandatory	Type	Description
topics	No	String	Name of the topic to be synchronized. Use commas (,) to separate the topic names for exact match. Either this parameter or topic_regex must be specified.
topic_regex	No	String	Regular expression of the topic to be synchronized. Either this parameter or the topics parameter must be set.
replica_cnt	Yes	Integer	Number of replicas, which cannot be greater than the number of brokers.
seek_to	Yes	String	Data synchronization point.
compress_alg	Yes	String	Compression algorithm. none: The compression algorithm is not used. gzip: Gzip compression algorithm. snappy: Snappy compression algorithm. lz4: LZ4 compression algorithm. zstd: zstd compression algorithm.
is_sync_progress	Yes	Boolean	Indicates whether to synchronize the consumption progress. true: yes false: no
is_add_header	Yes	Boolean	Indicates whether to add the source header.
rename_topic	No	Boolean	Indicates whether to rename a topic.
topic_mappings	No	Array of KafkaTopicMapping objects	Topic mapping.

Table 5-568 KafkaTopicMapping

Parameter	Mandatory	Type	Description
source_topic	No	String	Source topic.
sink_topic	No	String	Target topic.

Table 5-569 Rocketmq2RocketmqAdvanceConfig

Parameter	Mandatory	Type	Description
topics	No	String	Specifies the name of the topic to be synchronized. Use commas (,) to separate the topic names for exact match. Either this parameter or topic_regex must be specified.
topic_regex	No	String	Regular expression of the topic to be synchronized. Either this parameter or the topics parameter must be set.
is_sync_progress	Yes	Boolean	Indicates whether to sync the consumption progress.
seek_to	Yes	String	Data synchronization point. Options: first, last, custom timestamp (long type).
compress_alg	Yes	String	Compression algorithm. none: The compression algorithm is not used. gzip: Gzip compression algorithm. lz4: LZ4 compression algorithm. zstd: zstd compression algorithm.

Table 5-570 Dcs2DcsAdvanceConfig

Parameter	Mandatory	Type	Description
synchronize_type	Yes	String	Synchronization type. Default: Full+Incremental.

Parameter	Mandatory	Type	Description
connect_retry_time	Yes	String	Retry interval upon connection failure. The default value is 60 seconds.
other_retry_time	Yes	String	Retry interval upon other failures. The default value is 60 seconds.
use_rate_limit	No	Boolean	Whether to limit the incremental synchronization rate. The default value is 5 MB/s. true: yes false: no
rate_limit	No	String	Limited incremental synchronization rate. The default value is 5 MB/s.
use_salve_node	No	Boolean	Whether to use the standby node. true: Use the standby node to synchronize data. false: Use the master node to synchronize data.
allow_keys	No	String	Keys that can be synchronized in Redis event stream jobs, separated by commas (,).
allow_key_prefix	No	String	Prefix of the key that can be synchronized in Redis event stream jobs, separated by commas (,).
allow_key_suffix	No	String	Suffix of the key that can be synchronized in Redis event stream jobs, separated by commas (,).
block_keys	No	String	Keys that cannot be synchronized in Redis event stream jobs, separated by commas (,).
block_key_prefix	No	String	Prefix of the key that cannot be synchronized in Redis event stream jobs, separated by commas (,).

Parameter	Mandatory	Type	Description
block_key_suffix	No	String	Suffix of the key that cannot be synchronized in Redis event stream jobs, separated by commas (,).
allow_db	No	Array of integers	List of databases that can be synchronized in Redis event stream jobs.
db_mapping	No	Map<String,String>	Mapping of Redis event stream jobs and databases.

Response Parameters

Status code: 200

Table 5-571 Response header parameters

Parameter	Type	Description
X-Request-Id	String	Request ID.

Table 5-572 Response body parameters

Parameter	Type	Description
cluster_id	String	Professional event stream cluster ID.
job_id	String	Professional event stream job ID.
name	String	Job name. Start with a letter or digit, and only include letters, digits, periods (.), underscores (_), and hyphens (-). (Max. 128 characters)
description	String	Job description. The description can contain a maximum of 256 characters.
scene_type	String	Scenario type.
source_type	String	Source type.
sink_type	String	Target type.
subnet_id	String	Subnet ID.
vpc_id	String	VPC ID.
source_config	EventRouterJobSource object	Source configuration of a professional event stream job.

Parameter	Type	Description
sink_config	EventRouterJobSink object	Target configuration of a professional event stream job.
advance_config	EventRouterAdvanceConfig object	Advanced configuration of professional event stream jobs.
status	String	Job status.
err_code	String	Error code.
err_message	String	Error cause.
created_time	String	UTC time when the event source is created.
updated_time	String	UTC time when the event source is updated.
sink_status	String	Target connectivity status.
sink_status_info	String	Target connectivity status information.
source_status	String	Source connectivity status.
source_status_info	String	Source connectivity status information.
log_group_id	String	ID of the user's log group for storing event stream job logs
log_stream_id	String	ID of the user's log stream for storing event stream job logs

Table 5-573 EventRouterJobSource

Parameter	Type	Description
source_kafka	KafkaParameters object	Kafka configuration.
source_rocketmq	RocketmqParameters object	RocketMQ configuration.
source_dcs	DcsParameters object	DCS configuration.

Table 5-574 EventRouterJobSink

Parameter	Type	Description
sink_kafka	KafkaParameters object	Kafka configuration.

Parameter	Type	Description
sink_rocketmq	RocketmqParameters object	RocketMQ configuration.
sink_dcs	DcsParameters object	DCS configuration.

Table 5-575 KafkaParameters

Parameter	Type	Description
config_type	String	Instance type. CLOUD: DMS for Kafka instance.
region	String	Region ID.
project_id	String	Resource space ID.
instance_id	String	Kafka instance ID. This parameter is mandatory when configuration type is set to CLOUD.
cluster_alias	String	Kafka cluster alias.
address	String	Kafka address.
authenticate_mode	String	Authentication mode for Kafka.
sasl_mechanism	String	SASL authentication mechanism.
user_name	String	Username. This parameter is mandatory when SASL_SSL is enabled.
password	String	Password. This parameter is mandatory when SASL_SSL is enabled.

Table 5-576 RocketmqParameters

Parameter	Type	Description
config_type	String	Instance type. CLOUD: DMS for RocketMQ instance
region	String	Region ID.
project_id	String	Resource space ID.
instance_id	String	RocketMQ instance ID. This parameter is mandatory when the configuration type is CLOUD.

Parameter	Type	Description
cluster_alias	String	RocketMQ cluster alias.
address	String	RocketMQ address.
ssl_open	String	Whether to enable RocketMQ SSL. true: Enable false: Disable
acl_open	Boolean	Whether to enable RocketMQ ACL. true: Enable false: Disable
user_name	String	Username. This parameter is mandatory when ACL is enabled.
password	String	Password. This parameter is mandatory when ACL is enabled.

Table 5-577 DcsParameters

Parameter	Type	Description
config_type	String	Instance type. CLOUD: DCS instance
region	String	Region ID.
project_id	String	Resource space ID.
instance_id	String	DCS instance ID. This parameter is mandatory when the configuration type is set to CLOUD.
address	String	DCS address.
password	String	Password.

Table 5-578 EventRouterAdvanceConfig

Parameter	Type	Description
kafka2kafka	Kafka2KafkaAdvanceConfig object	Kafka synchronization custom configuration.
rocketmq2rocketmq	Rocketmq2RocketmqAdvanceConfig object	RocketMQ synchronization custom configuration.

Parameter	Type	Description
dcs2dcs	Dcs2DcsAdvanceConfig object	DCS synchronization custom configuration.

Table 5-579 Kafka2KafkaAdvanceConfig

Parameter	Type	Description
topics	String	Name of the topic to be synchronized. Use commas (,) to separate the topic names for exact match. Either this parameter or topic_regex must be specified.
topic_regex	String	Regular expression of the topic to be synchronized. Either this parameter or the topics parameter must be set.
replica_cnt	Integer	Number of replicas, which cannot be greater than the number of brokers.
seek_to	String	Data synchronization point.
compress_alg	String	Compression algorithm. none: The compression algorithm is not used. gzip: Gzip compression algorithm. snappy: Snappy compression algorithm. lz4: LZ4 compression algorithm. zstd: zstd compression algorithm.
is_sync_progress	Boolean	Indicates whether to synchronize the consumption progress. true: yes false: no
is_add_header	Boolean	Indicates whether to add the source header.
rename_topic	Boolean	Indicates whether to rename a topic.
topic_mappings	Array of KafkaTopicMapping objects	Topic mapping.

Table 5-580 KafkaTopicMapping

Parameter	Type	Description
source_topic	String	Source topic.
sink_topic	String	Target topic.

Table 5-581 Rocketmq2RocketmqAdvanceConfig

Parameter	Type	Description
topics	String	Specifies the name of the topic to be synchronized. Use commas (,) to separate the topic names for exact match. Either this parameter or topic_regex must be specified.
topic_regex	String	Regular expression of the topic to be synchronized. Either this parameter or the topics parameter must be set.
is_sync_progress	Boolean	Indicates whether to sync the consumption progress.
seek_to	String	Data synchronization point. Options: first, last, custom timestamp (long type).
compress_alg	String	Compression algorithm. none: The compression algorithm is not used. gzip: Gzip compression algorithm. lz4: LZ4 compression algorithm. zstd: zstd compression algorithm.

Table 5-582 Dcs2DcsAdvanceConfig

Parameter	Type	Description
synchronize_type	String	Synchronization type. Default: Full +Incremental.
connect_retry_time	String	Retry interval upon connection failure. The default value is 60 seconds.
other_retry_time	String	Retry interval upon other failures. The default value is 60 seconds.

Parameter	Type	Description
use_rate_limit	Boolean	Whether to limit the incremental synchronization rate. The default value is 5 MB/s. true: yes false: no
rate_limit	String	Limited incremental synchronization rate. The default value is 5 MB/s.
use_salve_node	Boolean	Whether to use the standby node. true: Use the standby node to synchronize data. false: Use the master node to synchronize data.
allow_keys	String	Keys that can be synchronized in Redis event stream jobs, separated by commas (,).
allow_key_prefix	String	Prefix of the key that can be synchronized in Redis event stream jobs, separated by commas (,).
allow_key_suffix	String	Suffix of the key that can be synchronized in Redis event stream jobs, separated by commas (,).
block_keys	String	Keys that cannot be synchronized in Redis event stream jobs, separated by commas (,).
block_key_prefix	String	Prefix of the key that cannot be synchronized in Redis event stream jobs, separated by commas (,).
block_key_suffix	String	Suffix of the key that cannot be synchronized in Redis event stream jobs, separated by commas (,).
allow_db	Array of integers	List of databases that can be synchronized in Redis event stream jobs.
db_mapping	Map<String,String>	Mapping of Redis event stream jobs and databases.

Example Requests

Create a professional event stream job named xxx.

```
POST https://{eg_endpoint}/v1/{project_id}/eventrouter/jobs
```

```
{
  "cluster_id": "fac59513-6c18-4266-bc81-5d412dfc1925",
  "name": "eventRoute-qapbtr95",
  "scene_type": "DISASTER_BACKUP",
  "description": "",
  "source_config": [
    {
      "source_kafka": [
        {
          "config_type": "CLOUD",
          "region": "roma-dev-1",
          "project_id": "cb13a5c409fe40599271f44bbea5a2ad",
          "instance_id": "cdecf0b0-35b8-461b-a430-d7cd02d3d712",
          "cluster_alias": "aa",
          "address": "21.22.0.58:9092",
          "user_name": "",
          "password": null,
          "authenticate_mode": "PLAINTEXT",
          "sasl_mechanism": ""
        }
      ],
    },
  ],
  "sink_config": [
    {
      "sink_kafka": [
        {
          "config_type": "CLOUD",
          "region": "roma-dev-1",
          "project_id": "cb13a5c409fe40599271f44bbea5a2ad",
          "instance_id": "47896f0e-f90a-4528-b407-78ee00362cc9",
          "cluster_alias": "bb",
          "address": "21.22.0.175:9092",
          "user_name": null,
          "password": null,
          "authenticate_mode": "PLAINTEXT",
          "sasl_mechanism": ""
        }
      ],
    },
  ],
  "advance_config": [
    {
      "kafka2kafka": [
        {
          "topics": "t01",
          "topic_regex": "",
          "task_cnt": null,
          "topic_mappings": [],
          "rename_topic": false,
          "is_add_header": false,
          "is_sync_progress": false,
          "replica_cnt": 1,
          "seek_to": "earliest",
          "compress_alg": "none"
        }
      ],
    },
  ],
}
```

Example Responses

Status code: 200

Request succeeded.

```
{
  "cluster_id": "fac59513-6c18-4266-bc81-5d412dfc1925",
```

```
"job_id" : "fac59513-6c18-4266-bc81-5d412dfc1925",
"name" : "eventRoute-ifpcv5u4",
"description" : "",
"scene_type" : "DISASTER_BACKUP",
"source_type" : "KAFKA",
"source_config" : null,
"sink_type" : "KAFKA",
"sink_config" : null,
"advance_config" : null,
"status" : "CREATING",
"err_code" : null,
"err_message" : null,
"created_time" : "2024-05-16T11:46:07Z",
"updated_time" : "2024-05-16T11:46:07Z",
"vpc_id" : "199f632d-34e7-4915-b4d8-1bc4e2824867",
"subnet_id" : "0d1799e1-116e-4551-92dc-02dd8a860072"
}
```

Status Codes

Status Code	Description
200	Request succeeded.

Error Codes

See [Error Codes](#).

5.16.2 Querying Professional Event Stream Jobs

Function

This API is used to query professional event stream jobs.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/eventrouter/jobs

Table 5-583 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-584 Query Parameters

Parameter	Mandatory	Type	Description
fuzzy_name	No	String	Fuzzy query by name.
sink_region	No	String	Target region.
sink_instance_id	No	String	Target instance ID.
sink_address	No	String	Target address.
status	No	String	Job status.
cluster_id	No	String	Cluster ID of jobs.
offset	No	String	Offset.
limit	No	String	Number of records displayed on each page.

Request Parameters

Table 5-585 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-586 Response header parameters

Parameter	Type	Description
X-Request-Id	String	Request ID.

Table 5-587 Response body parameters

Parameter	Type	Description
total	Integer	Total number.

Parameter	Type	Description
size	Integer	Number of records displayed on the current page.
items	Array of EventRouterJobInfo objects	Object list.

Table 5-588 EventRouterJobInfo

Parameter	Type	Description
cluster_id	String	Professional event stream cluster ID.
job_id	String	Professional event stream job ID.
name	String	Job name. Start with a letter or digit, and only include letters, digits, periods (.), underscores (_), and hyphens (-). (Max. 128 characters)
description	String	Job description. The description can contain a maximum of 256 characters.
scene_type	String	Scenario type.
source_type	String	Source type.
sink_type	String	Target type.
subnet_id	String	Subnet ID.
vpc_id	String	VPC ID.
source_config	EventRouterJobSource object	Source configuration of a professional event stream job.
sink_config	EventRouterJobSink object	Target configuration of a professional event stream job.
advance_config	EventRouterAdvanceConfig object	Advanced configuration of professional event stream jobs.
status	String	Job status.
err_code	String	Error code.
err_message	String	Error cause.
created_time	String	UTC time when the event source is created.
updated_time	String	UTC time when the event source is updated.

Parameter	Type	Description
sink_status	String	Target connectivity status.
sink_status_info	String	Target connectivity status information.
source_status	String	Source connectivity status.
source_status_info	String	Source connectivity status information.
log_group_id	String	ID of the user's log group for storing event stream job logs
log_stream_id	String	ID of the user's log stream for storing event stream job logs

Table 5-589 EventRouterJobSource

Parameter	Type	Description
source_kafka	KafkaParameters object	Kafka configuration.
source_rocketmq	RocketmqParameters object	RocketMQ configuration.
source_dcs	DcsParameters object	DCS configuration.

Table 5-590 EventRouterJobSink

Parameter	Type	Description
sink_kafka	KafkaParameters object	Kafka configuration.
sink_rocketmq	RocketmqParameters object	RocketMQ configuration.
sink_dcs	DcsParameters object	DCS configuration.

Table 5-591 KafkaParameters

Parameter	Type	Description
config_type	String	Instance type. CLOUD: DMS for Kafka instance.
region	String	Region ID.

Parameter	Type	Description
project_id	String	Resource space ID.
instance_id	String	Kafka instance ID. This parameter is mandatory when configuration type is set to CLOUD.
cluster_alias	String	Kafka cluster alias.
address	String	Kafka address.
authenticate_mode	String	Authentication mode for Kafka.
sasl_mechanism	String	SASL authentication mechanism.
user_name	String	Username. This parameter is mandatory when SASL_SSL is enabled.
password	String	Password. This parameter is mandatory when SASL_SSL is enabled.

Table 5-592 RocketmqParameters

Parameter	Type	Description
config_type	String	Instance type. CLOUD: DMS for RocketMQ instance
region	String	Region ID.
project_id	String	Resource space ID.
instance_id	String	RocketMQ instance ID. This parameter is mandatory when the configuration type is CLOUD.
cluster_alias	String	RocketMQ cluster alias.
address	String	RocketMQ address.
ssl_open	String	Whether to enable RocketMQ SSL. true: Enable false: Disable
acl_open	Boolean	Whether to enable RocketMQ ACL. true: Enable false: Disable
user_name	String	Username. This parameter is mandatory when ACL is enabled.

Parameter	Type	Description
password	String	Password. This parameter is mandatory when ACL is enabled.

Table 5-593 DcsParameters

Parameter	Type	Description
config_type	String	Instance type. CLOUD: DCS instance
region	String	Region ID.
project_id	String	Resource space ID.
instance_id	String	DCS instance ID. This parameter is mandatory when the configuration type is set to CLOUD.
address	String	DCS address.
password	String	Password.

Table 5-594 EventRouterAdvanceConfig

Parameter	Type	Description
kafka2kafka	Kafka2KafkaAdvanceConfig object	Kafka synchronization custom configuration.
rocketmq2rocketmq	Rocketmq2RocketmqAdvanceConfig object	RocketMQ synchronization custom configuration.
dcs2dcs	Dcs2DcsAdvanceConfig object	DCS synchronization custom configuration.

Table 5-595 Kafka2KafkaAdvanceConfig

Parameter	Type	Description
topics	String	Name of the topic to be synchronized. Use commas (,) to separate the topic names for exact match. Either this parameter or topic_regex must be specified.

Parameter	Type	Description
topic_regex	String	Regular expression of the topic to be synchronized. Either this parameter or the topics parameter must be set.
replica_cnt	Integer	Number of replicas, which cannot be greater than the number of brokers.
seek_to	String	Data synchronization point.
compress_alg	String	Compression algorithm. none: The compression algorithm is not used. gzip: Gzip compression algorithm. snappy: Snappy compression algorithm. lz4: LZ4 compression algorithm. zstd: zstd compression algorithm.
is_sync_progress	Boolean	Indicates whether to synchronize the consumption progress. true: yes false: no
is_add_header	Boolean	Indicates whether to add the source header.
rename_topic	Boolean	Indicates whether to rename a topic.
topic_mappings	Array of KafkaTopicMapping objects	Topic mapping.

Table 5-596 KafkaTopicMapping

Parameter	Type	Description
source_topic	String	Source topic.
sink_topic	String	Target topic.

Table 5-597 Rocketmq2RocketmqAdvanceConfig

Parameter	Type	Description
topics	String	Specifies the name of the topic to be synchronized. Use commas (,) to separate the topic names for exact match. Either this parameter or topic_regex must be specified.
topic_regex	String	Regular expression of the topic to be synchronized. Either this parameter or the topics parameter must be set.
is_sync_progress	Boolean	Indicates whether to sync the consumption progress.
seek_to	String	Data synchronization point. Options: first, last, custom timestamp (long type).
compress_alg	String	Compression algorithm. none: The compression algorithm is not used. gzip: Gzip compression algorithm. lz4: LZ4 compression algorithm. zstd: zstd compression algorithm.

Table 5-598 Dcs2DcsAdvanceConfig

Parameter	Type	Description
synchronize_type	String	Synchronization type. Default: Full +Incremental.
connect_retry_time	String	Retry interval upon connection failure. The default value is 60 seconds.
other_retry_time	String	Retry interval upon other failures. The default value is 60 seconds.
use_rate_limit	Boolean	Whether to limit the incremental synchronization rate. The default value is 5 MB/s. true: yes false: no
rate_limit	String	Limited incremental synchronization rate. The default value is 5 MB/s.

Parameter	Type	Description
use_salve_node	Boolean	Whether to use the standby node. true: Use the standby node to synchronize data. false: Use the master node to synchronize data.
allow_keys	String	Keys that can be synchronized in Redis event stream jobs, separated by commas (,).
allow_key_prefix	String	Prefix of the key that can be synchronized in Redis event stream jobs, separated by commas (,).
allow_key_suffix	String	Suffix of the key that can be synchronized in Redis event stream jobs, separated by commas (,).
block_keys	String	Keys that cannot be synchronized in Redis event stream jobs, separated by commas (,).
block_key_prefix	String	Prefix of the key that cannot be synchronized in Redis event stream jobs, separated by commas (,).
block_key_suffix	String	Suffix of the key that cannot be synchronized in Redis event stream jobs, separated by commas (,).
allow_db	Array of integers	List of databases that can be synchronized in Redis event stream jobs.
db_mapping	Map<String,String>	Mapping of Redis event stream jobs and databases.

Example Requests

Query jobs of cluster abc.

```
GET https://{eg_endpoint}/v1/{project_id}/eventrouter/jobs?cluster_id=abc&limit=1000&offset=0
```

Example Responses

Status code: 200

Request succeeded.

```
{  
  "size" : 1,  
  "total" : 1,  
  "items" : [ {
```

```
"cluster_id" : "fac59513-6c18-4266-bc81-5d412dfc1925",
"job_id" : "fac59513-6c18-4266-bc81-5d412dfc1925",
"name" : "eventRoute-ifpcv5u4",
"description" : null,
"scene_type" : "DISASTER_BACKUP",
"source_type" : "KAFKA",
"source_config" : null,
"sink_type" : "KAFKA",
"sink_config" : null,
"advance_config" : null,
"status" : "NO_CONFIGURATION",
"err_code" : null,
"err_message" : null,
"created_time" : "2024-05-16T11:46:07Z",
"updated_time" : "2024-05-16T11:46:07Z",
"vpc_id" : "199f632d-34e7-4915-b4d8-1bc4e2824867",
"subnet_id" : "0d1799e1-116e-4551-92dc-02dd8a860072"
} ]
}
```

Status Codes

Status Code	Description
200	Request succeeded.

Error Codes

See [Error Codes](#).

5.16.3 Deleting a Professional Event Stream Job

Function

This API is used to delete a professional event stream job.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

DELETE /v1/{project_id}/eventrouter/jobs/{job_id}

Table 5-599 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
job_id	Yes	String	Job ID.

Request Parameters

Table 5-600 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-601 Response header parameters

Parameter	Type	Description
X-Request-Id	String	Request ID.

Table 5-602 Response body parameters

Parameter	Type	Description
job_id	String	Job ID.

Example Requests

Delete the professional event stream job whose ID is 123.

```
DELETE https://{eg_endpoint}/v1/123/eventrouter/jobs/123
```

Example Responses

Status code: 200

Request succeeded.

```
{
  "job_id" : "fac59513-6c18-4266-bc81-5d412dfc1925"
}
```

Status Codes

Status Code	Description
200	Request succeeded.

Error Codes

See [Error Codes](#).

5.16.4 Querying Details About a Professional Event Stream Job

Function

This API is used to query details about a professional event stream job.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/eventrouter/jobs/{job_id}

Table 5-603 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
job_id	Yes	String	Job ID.

Request Parameters

Table 5-604 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-605 Response header parameters

Parameter	Type	Description
X-Request-Id	String	Request ID.

Table 5-606 Response body parameters

Parameter	Type	Description
cluster_id	String	Professional event stream cluster ID.
job_id	String	Professional event stream job ID.
name	String	Job name. Start with a letter or digit, and only include letters, digits, periods (.), underscores (_), and hyphens (-). (Max. 128 characters)
description	String	Job description. The description can contain a maximum of 256 characters.
scene_type	String	Scenario type.
source_type	String	Source type.
sink_type	String	Target type.
subnet_id	String	Subnet ID.
vpc_id	String	VPC ID.
source_config	EventRouterJobSource object	Source configuration of a professional event stream job.
sink_config	EventRouterJobSink object	Target configuration of a professional event stream job.
advance_config	EventRouterAdvanceConfig object	Advanced configuration of professional event stream jobs.
status	String	Job status.
err_code	String	Error code.
err_message	String	Error cause.
created_time	String	UTC time when the event source is created.
updated_time	String	UTC time when the event source is updated.

Parameter	Type	Description
sink_status	String	Target connectivity status.
sink_status_info	String	Target connectivity status information.
source_status	String	Source connectivity status.
source_status_info	String	Source connectivity status information.
log_group_id	String	ID of the user's log group for storing event stream job logs
log_stream_id	String	ID of the user's log stream for storing event stream job logs

Table 5-607 EventRouterJobSource

Parameter	Type	Description
source_kafka	KafkaParameters object	Kafka configuration.
source_rocketmq	RocketmqParameters object	RocketMQ configuration.
source_dcs	DcsParameters object	DCS configuration.

Table 5-608 EventRouterJobSink

Parameter	Type	Description
sink_kafka	KafkaParameters object	Kafka configuration.
sink_rocketmq	RocketmqParameters object	RocketMQ configuration.
sink_dcs	DcsParameters object	DCS configuration.

Table 5-609 KafkaParameters

Parameter	Type	Description
config_type	String	Instance type. CLOUD: DMS for Kafka instance.
region	String	Region ID.

Parameter	Type	Description
project_id	String	Resource space ID.
instance_id	String	Kafka instance ID. This parameter is mandatory when configuration type is set to CLOUD.
cluster_alias	String	Kafka cluster alias.
address	String	Kafka address.
authenticate_mode	String	Authentication mode for Kafka.
sasl_mechanism	String	SASL authentication mechanism.
user_name	String	Username. This parameter is mandatory when SASL_SSL is enabled.
password	String	Password. This parameter is mandatory when SASL_SSL is enabled.

Table 5-610 RocketmqParameters

Parameter	Type	Description
config_type	String	Instance type. CLOUD: DMS for RocketMQ instance
region	String	Region ID.
project_id	String	Resource space ID.
instance_id	String	RocketMQ instance ID. This parameter is mandatory when the configuration type is CLOUD.
cluster_alias	String	RocketMQ cluster alias.
address	String	RocketMQ address.
ssl_open	String	Whether to enable RocketMQ SSL. true: Enable false: Disable
acl_open	Boolean	Whether to enable RocketMQ ACL. true: Enable false: Disable
user_name	String	Username. This parameter is mandatory when ACL is enabled.

Parameter	Type	Description
password	String	Password. This parameter is mandatory when ACL is enabled.

Table 5-611 DcsParameters

Parameter	Type	Description
config_type	String	Instance type. CLOUD: DCS instance
region	String	Region ID.
project_id	String	Resource space ID.
instance_id	String	DCS instance ID. This parameter is mandatory when the configuration type is set to CLOUD.
address	String	DCS address.
password	String	Password.

Table 5-612 EventRouterAdvanceConfig

Parameter	Type	Description
kafka2kafka	Kafka2KafkaAdvanceConfig object	Kafka synchronization custom configuration.
rocketmq2rocketmq	Rocketmq2RocketmqAdvanceConfig object	RocketMQ synchronization custom configuration.
dcs2dcs	Dcs2DcsAdvanceConfig object	DCS synchronization custom configuration.

Table 5-613 Kafka2KafkaAdvanceConfig

Parameter	Type	Description
topics	String	Name of the topic to be synchronized. Use commas (,) to separate the topic names for exact match. Either this parameter or topic_regex must be specified.

Parameter	Type	Description
topic_regex	String	Regular expression of the topic to be synchronized. Either this parameter or the topics parameter must be set.
replica_cnt	Integer	Number of replicas, which cannot be greater than the number of brokers.
seek_to	String	Data synchronization point.
compress_alg	String	Compression algorithm. none: The compression algorithm is not used. gzip: Gzip compression algorithm. snappy: Snappy compression algorithm. lz4: LZ4 compression algorithm. zstd: zstd compression algorithm.
is_sync_progress	Boolean	Indicates whether to synchronize the consumption progress. true: yes false: no
is_add_header	Boolean	Indicates whether to add the source header.
rename_topic	Boolean	Indicates whether to rename a topic.
topic_mappings	Array of KafkaTopicMapping objects	Topic mapping.

Table 5-614 KafkaTopicMapping

Parameter	Type	Description
source_topic	String	Source topic.
sink_topic	String	Target topic.

Table 5-615 Rocketmq2RocketmqAdvanceConfig

Parameter	Type	Description
topics	String	Specifies the name of the topic to be synchronized. Use commas (,) to separate the topic names for exact match. Either this parameter or topic_regex must be specified.
topic_regex	String	Regular expression of the topic to be synchronized. Either this parameter or the topics parameter must be set.
is_sync_progress	Boolean	Indicates whether to sync the consumption progress.
seek_to	String	Data synchronization point. Options: first, last, custom timestamp (long type).
compress_alg	String	Compression algorithm. none: The compression algorithm is not used. gzip: Gzip compression algorithm. lz4: LZ4 compression algorithm. zstd: zstd compression algorithm.

Table 5-616 Dcs2DcsAdvanceConfig

Parameter	Type	Description
synchronize_type	String	Synchronization type. Default: Full +Incremental.
connect_retry_time	String	Retry interval upon connection failure. The default value is 60 seconds.
other_retry_time	String	Retry interval upon other failures. The default value is 60 seconds.
use_rate_limit	Boolean	Whether to limit the incremental synchronization rate. The default value is 5 MB/s. true: yes false: no
rate_limit	String	Limited incremental synchronization rate. The default value is 5 MB/s.

Parameter	Type	Description
use_salve_node	Boolean	Whether to use the standby node. true: Use the standby node to synchronize data. false: Use the master node to synchronize data.
allow_keys	String	Keys that can be synchronized in Redis event stream jobs, separated by commas (,).
allow_key_prefix	String	Prefix of the key that can be synchronized in Redis event stream jobs, separated by commas (,).
allow_key_suffix	String	Suffix of the key that can be synchronized in Redis event stream jobs, separated by commas (,).
block_keys	String	Keys that cannot be synchronized in Redis event stream jobs, separated by commas (,).
block_key_prefix	String	Prefix of the key that cannot be synchronized in Redis event stream jobs, separated by commas (,).
block_key_suffix	String	Suffix of the key that cannot be synchronized in Redis event stream jobs, separated by commas (,).
allow_db	Array of integers	List of databases that can be synchronized in Redis event stream jobs.
db_mapping	Map<String,String>	Mapping of Redis event stream jobs and databases.

Example Requests

Query details about the professional event stream job whose ID is 123.

```
GET https://{eg_endpoint}/v1/{project_id}/eventrouter/jobs/123
```

Example Responses

Status code: 200

Request succeeded.

```
{
  "cluster_id" : "fac59513-6c18-4266-bc81-5d412dfc1925",
  "job_id" : "fac59513-6c18-4266-bc81-5d412dfc1925",
  "name" : "eventRoute-ifpcv5u4",
```

```
"description" : "",
"scene_type" : "DISASTER_BACKUP",
"source_type" : "KAFKA",
"source_config" : null,
"sink_type" : "KAFKA",
"sink_config" : null,
"advance_config" : null,
"status" : "CREATING",
"err_code" : null,
"err_message" : null,
"created_time" : "2024-05-16T11:46:07Z",
"updated_time" : "2024-05-16T11:46:07Z",
"vpc_id" : "199f632d-34e7-4915-b4d8-1bc4e2824867",
"subnet_id" : "0d1799e1-116e-4551-92dc-02dd8a860072",
"log_group_id" : "3cfe3347-43b9-4aa4-b62e-xxxxxxxxxxxx",
"log_stream_id" : "1a5b9d49-3003-49d3-93af-xxxxxxxxxxxx"
}
```

Status Codes

Status Code	Description
200	Request succeeded.

Error Codes

See [Error Codes](#).

5.16.5 Updating a Professional Event Stream Job

Function

This API is used to update a professional event stream job.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

PUT /v1/{project_id}/eventrouter/jobs/{job_id}

Table 5-617 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
job_id	Yes	String	Job ID.

Request Parameters

Table 5-618 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-619 Request body parameters

Parameter	Mandatory	Type	Description
cluster_id	Yes	String	Professional event stream cluster ID.
name	Yes	String	Job name. Start with a letter or digit, and only include letters, digits, periods (.), underscores (_), and hyphens (-). (Max. 128 characters)
description	No	String	Job description. The description can contain a maximum of 256 characters.
scene_type	Yes	String	Scenario type. DISASTER_BACKUP: synchronization task.
source_config	No	EventRouterJobSource object	Source configuration of a professional event stream job.
sink_config	No	EventRouterJobSink object	Target configuration of a professional event stream job.
advance_config	No	EventRouterAdvanceConfig object	Advanced configuration of professional event stream jobs.

Table 5-620 EventRouterJobSource

Parameter	Mandatory	Type	Description
source_kafka	No	KafkaParameters object	Kafka configuration.

Parameter	Mandatory	Type	Description
source_rocketmq	No	RocketmqParameters object	RocketMQ configuration.
source_dcs	No	DcsParameters object	DCS configuration.

Table 5-621 EventRouterJobSink

Parameter	Mandatory	Type	Description
sink_kafka	No	KafkaParameters object	Kafka configuration.
sink_rocketmq	No	RocketmqParameters object	RocketMQ configuration.
sink_dcs	No	DcsParameters object	DCS configuration.

Table 5-622 KafkaParameters

Parameter	Mandatory	Type	Description
config_type	Yes	String	Instance type. CLOUD: DMS for Kafka instance.
region	Yes	String	Region ID.
project_id	Yes	String	Resource space ID.
instance_id	No	String	Kafka instance ID. This parameter is mandatory when configuration type is set to CLOUD.
cluster_alias	Yes	String	Kafka cluster alias.
address	No	String	Kafka address.
authenticate_mode	No	String	Authentication mode for Kafka.
sasl_mechanism	No	String	SASL authentication mechanism.

Parameter	Mandatory	Type	Description
user_name	No	String	Username. This parameter is mandatory when SASL_SSL is enabled.
password	No	String	Password. This parameter is mandatory when SASL_SSL is enabled.

Table 5-623 RocketmqParameters

Parameter	Mandatory	Type	Description
config_type	Yes	String	Instance type. CLOUD: DMS for RocketMQ instance
region	Yes	String	Region ID.
project_id	Yes	String	Resource space ID.
instance_id	No	String	RocketMQ instance ID. This parameter is mandatory when the configuration type is CLOUD.
cluster_alias	Yes	String	RocketMQ cluster alias.
address	No	String	RocketMQ address.
ssl_open	No	String	Whether to enable RocketMQ SSL. true: Enable false: Disable
acl_open	No	Boolean	Whether to enable RocketMQ ACL. true: Enable false: Disable
user_name	No	String	Username. This parameter is mandatory when ACL is enabled.
password	No	String	Password. This parameter is mandatory when ACL is enabled.

Table 5-624 DcsParameters

Parameter	Mandatory	Type	Description
config_type	Yes	String	Instance type. CLOUD: DCS instance
region	Yes	String	Region ID.
project_id	Yes	String	Resource space ID.
instance_id	No	String	DCS instance ID. This parameter is mandatory when the configuration type is set to CLOUD.
address	No	String	DCS address.
password	No	String	Password.

Table 5-625 EventRouterAdvanceConfig

Parameter	Mandatory	Type	Description
kafka2kafka	No	Kafka2KafkaAdvanceConfig object	Kafka synchronization custom configuration.
rocketmq2rocketmq	No	Rocketmq2RocketmqAdvanceConfig object	RocketMQ synchronization custom configuration.
dcs2dcs	No	Dcs2DcsAdvanceConfig object	DCS synchronization custom configuration.

Table 5-626 Kafka2KafkaAdvanceConfig

Parameter	Mandatory	Type	Description
topics	No	String	Name of the topic to be synchronized. Use commas (,) to separate the topic names for exact match. Either this parameter or topic_regex must be specified.
topic_regex	No	String	Regular expression of the topic to be synchronized. Either this parameter or the topics parameter must be set.

Parameter	Mandatory	Type	Description
replica_cnt	Yes	Integer	Number of replicas, which cannot be greater than the number of brokers.
seek_to	Yes	String	Data synchronization point.
compress_alg	Yes	String	Compression algorithm. none: The compression algorithm is not used. gzip: Gzip compression algorithm. snappy: Snappy compression algorithm. lz4: LZ4 compression algorithm. zstd: zstd compression algorithm.
is_sync_progress	Yes	Boolean	Indicates whether to synchronize the consumption progress. true: yes false: no
is_add_header	Yes	Boolean	Indicates whether to add the source header.
rename_topic	No	Boolean	Indicates whether to rename a topic.
topic_mappings	No	Array of KafkaTopicMapping objects	Topic mapping.

Table 5-627 KafkaTopicMapping

Parameter	Mandatory	Type	Description
source_topic	No	String	Source topic.
sink_topic	No	String	Target topic.

Table 5-628 Rocketmq2RocketmqAdvanceConfig

Parameter	Mandatory	Type	Description
topics	No	String	Specifies the name of the topic to be synchronized. Use commas (,) to separate the topic names for exact match. Either this parameter or topic_regex must be specified.
topic_regex	No	String	Regular expression of the topic to be synchronized. Either this parameter or the topics parameter must be set.
is_sync_progress	Yes	Boolean	Indicates whether to sync the consumption progress.
seek_to	Yes	String	Data synchronization point. Options: first, last, custom timestamp (long type).
compress_alg	Yes	String	Compression algorithm. none: The compression algorithm is not used. gzip: Gzip compression algorithm. lz4: LZ4 compression algorithm. zstd: zstd compression algorithm.

Table 5-629 Dcs2DcsAdvanceConfig

Parameter	Mandatory	Type	Description
synchronize_type	Yes	String	Synchronization type. Default: Full+Incremental.
connect_retry_time	Yes	String	Retry interval upon connection failure. The default value is 60 seconds.
other_retry_time	Yes	String	Retry interval upon other failures. The default value is 60 seconds.

Parameter	Mandatory	Type	Description
use_rate_limit	No	Boolean	Whether to limit the incremental synchronization rate. The default value is 5 MB/s. true: yes false: no
rate_limit	No	String	Limited incremental synchronization rate. The default value is 5 MB/s.
use_standby_node	No	Boolean	Whether to use the standby node. true: Use the standby node to synchronize data. false: Use the master node to synchronize data.
allow_keys	No	String	Keys that can be synchronized in Redis event stream jobs, separated by commas (,).
allow_key_prefix	No	String	Prefix of the key that can be synchronized in Redis event stream jobs, separated by commas (,).
allow_key_suffix	No	String	Suffix of the key that can be synchronized in Redis event stream jobs, separated by commas (,).
block_keys	No	String	Keys that cannot be synchronized in Redis event stream jobs, separated by commas (,).
block_key_prefix	No	String	Prefix of the key that cannot be synchronized in Redis event stream jobs, separated by commas (,).
block_key_suffix	No	String	Suffix of the key that cannot be synchronized in Redis event stream jobs, separated by commas (,).
allow_db	No	Array of integers	List of databases that can be synchronized in Redis event stream jobs.

Parameter	Mandatory	Type	Description
db_mapping	No	Map<String,String>	Mapping of Redis event stream jobs and databases.

Response Parameters

Status code: 200

Table 5-630 Response header parameters

Parameter	Type	Description
X-Request-Id	String	Request ID.

Table 5-631 Response body parameters

Parameter	Type	Description
cluster_id	String	Professional event stream cluster ID.
job_id	String	Professional event stream job ID.
name	String	Job name. Start with a letter or digit, and only include letters, digits, periods (.), underscores (_), and hyphens (-). (Max. 128 characters)
description	String	Job description. The description can contain a maximum of 256 characters.
scene_type	String	Scenario type.
source_type	String	Source type.
sink_type	String	Target type.
subnet_id	String	Subnet ID.
vpc_id	String	VPC ID.
source_config	EventRouterJobSource object	Source configuration of a professional event stream job.
sink_config	EventRouterJobSink object	Target configuration of a professional event stream job.
advance_config	EventRouterAdvanceConfig object	Advanced configuration of professional event stream jobs.
status	String	Job status.
err_code	String	Error code.

Parameter	Type	Description
err_message	String	Error cause.
created_time	String	UTC time when the event source is created.
updated_time	String	UTC time when the event source is updated.
sink_status	String	Target connectivity status.
sink_status_info	String	Target connectivity status information.
source_status	String	Source connectivity status.
source_status_info	String	Source connectivity status information.
log_group_id	String	ID of the user's log group for storing event stream job logs
log_stream_id	String	ID of the user's log stream for storing event stream job logs

Table 5-632 EventRouterJobSource

Parameter	Type	Description
source_kafka	KafkaParameters object	Kafka configuration.
source_rocketmq	RocketmqParameters object	RocketMQ configuration.
source_dcs	DcsParameters object	DCS configuration.

Table 5-633 EventRouterJobSink

Parameter	Type	Description
sink_kafka	KafkaParameters object	Kafka configuration.
sink_rocketmq	RocketmqParameters object	RocketMQ configuration.
sink_dcs	DcsParameters object	DCS configuration.

Table 5-634 KafkaParameters

Parameter	Type	Description
config_type	String	Instance type. CLOUD: DMS for Kafka instance.
region	String	Region ID.
project_id	String	Resource space ID.
instance_id	String	Kafka instance ID. This parameter is mandatory when configuration type is set to CLOUD.
cluster_alias	String	Kafka cluster alias.
address	String	Kafka address.
authenticate_mode	String	Authentication mode for Kafka.
sasl_mechanism	String	SASL authentication mechanism.
user_name	String	Username. This parameter is mandatory when SASL_SSL is enabled.
password	String	Password. This parameter is mandatory when SASL_SSL is enabled.

Table 5-635 RocketmqParameters

Parameter	Type	Description
config_type	String	Instance type. CLOUD: DMS for RocketMQ instance
region	String	Region ID.
project_id	String	Resource space ID.
instance_id	String	RocketMQ instance ID. This parameter is mandatory when the configuration type is CLOUD.
cluster_alias	String	RocketMQ cluster alias.
address	String	RocketMQ address.
ssl_open	String	Whether to enable RocketMQ SSL. true: Enable false: Disable

Parameter	Type	Description
acl_open	Boolean	Whether to enable RocketMQ ACL. true: Enable false: Disable
user_name	String	Username. This parameter is mandatory when ACL is enabled.
password	String	Password. This parameter is mandatory when ACL is enabled.

Table 5-636 DcsParameters

Parameter	Type	Description
config_type	String	Instance type. CLOUD: DCS instance
region	String	Region ID.
project_id	String	Resource space ID.
instance_id	String	DCS instance ID. This parameter is mandatory when the configuration type is set to CLOUD.
address	String	DCS address.
password	String	Password.

Table 5-637 EventRouterAdvanceConfig

Parameter	Type	Description
kafka2kafka	Kafka2KafkaAdvanceConfig object	Kafka synchronization custom configuration.
rocketmq2rocketmq	Rocketmq2RocketmqAdvanceConfig object	RocketMQ synchronization custom configuration.
dcs2dcs	Dcs2DcsAdvanceConfig object	DCS synchronization custom configuration.

Table 5-638 Kafka2KafkaAdvanceConfig

Parameter	Type	Description
topics	String	Name of the topic to be synchronized. Use commas (,) to separate the topic names for exact match. Either this parameter or topic_regex must be specified.
topic_regex	String	Regular expression of the topic to be synchronized. Either this parameter or the topics parameter must be set.
replica_cnt	Integer	Number of replicas, which cannot be greater than the number of brokers.
seek_to	String	Data synchronization point.
compress_alg	String	Compression algorithm. none: The compression algorithm is not used. gzip: Gzip compression algorithm. snappy: Snappy compression algorithm. lz4: LZ4 compression algorithm. zstd: zstd compression algorithm.
is_sync_progress	Boolean	Indicates whether to synchronize the consumption progress. true: yes false: no
is_add_header	Boolean	Indicates whether to add the source header.
rename_topic	Boolean	Indicates whether to rename a topic.
topic_mappings	Array of KafkaTopicMapping objects	Topic mapping.

Table 5-639 KafkaTopicMapping

Parameter	Type	Description
source_topic	String	Source topic.
sink_topic	String	Target topic.

Table 5-640 Rocketmq2RocketmqAdvanceConfig

Parameter	Type	Description
topics	String	Specifies the name of the topic to be synchronized. Use commas (,) to separate the topic names for exact match. Either this parameter or topic_regex must be specified.
topic_regex	String	Regular expression of the topic to be synchronized. Either this parameter or the topics parameter must be set.
is_sync_progress	Boolean	Indicates whether to sync the consumption progress.
seek_to	String	Data synchronization point. Options: first, last, custom timestamp (long type).
compress_alg	String	Compression algorithm. none: The compression algorithm is not used. gzip: Gzip compression algorithm. lz4: LZ4 compression algorithm. zstd: zstd compression algorithm.

Table 5-641 Dcs2DcsAdvanceConfig

Parameter	Type	Description
synchronize_type	String	Synchronization type. Default: Full +Incremental.
connect_retry_time	String	Retry interval upon connection failure. The default value is 60 seconds.
other_retry_time	String	Retry interval upon other failures. The default value is 60 seconds.
use_rate_limit	Boolean	Whether to limit the incremental synchronization rate. The default value is 5 MB/s. true: yes false: no
rate_limit	String	Limited incremental synchronization rate. The default value is 5 MB/s.

Parameter	Type	Description
use_salve_node	Boolean	Whether to use the standby node. true: Use the standby node to synchronize data. false: Use the master node to synchronize data.
allow_keys	String	Keys that can be synchronized in Redis event stream jobs, separated by commas (,).
allow_key_prefix	String	Prefix of the key that can be synchronized in Redis event stream jobs, separated by commas (,).
allow_key_suffix	String	Suffix of the key that can be synchronized in Redis event stream jobs, separated by commas (,).
block_keys	String	Keys that cannot be synchronized in Redis event stream jobs, separated by commas (,).
block_key_prefix	String	Prefix of the key that cannot be synchronized in Redis event stream jobs, separated by commas (,).
block_key_suffix	String	Suffix of the key that cannot be synchronized in Redis event stream jobs, separated by commas (,).
allow_db	Array of integers	List of databases that can be synchronized in Redis event stream jobs.
db_mapping	Map<String,String>	Mapping of Redis event stream jobs and databases.

Example Requests

Update the professional event stream job whose ID is 123.

```
PUT https://{eg_endpoint}/v1/{project_id}/eventrouter/jobs/123
```

```
{
  "advance_config" : {
    "kafka2kafka" : {
      "compress_alg" : "none",
      "is_add_header" : false,
      "is_sync_progress" : true,
      "rename_topic" : false,
      "replica_cnt" : 1,
      "seek_to" : "earliest",
      "topic_mappings" : [ ],
      "topic_regex" : ".*",
      "topics" : ""
    }
  }
}
```

```
}
},
"cluster_id": "1a8b384f-b788-3000-0010-924ef6f516b2",
"description": "",
"name": "eventRoute-0ztrqj7o",
"scene_type": "DISASTER_BACKUP",
"sink_config": {
  "sink_kafka": {
    "address": "192.168.0.49:9092,192.168.0.91:9092,192.168.0.210:9092",
    "authenticate_mode": "PLAINTEXT",
    "cluster_alias": "b",
    "config_type": "CLOUD",
    "instance_id": "d7d5bcec-2b73-4331-a568-1288f23dbbb0",
    "password": null,
    "project_id": "bac852160cc743158936edaab6dda813",
    "region": "cn-north-7",
    "sasl_mechanism": "",
    "user_name": ""
  }
},
"source_config": {
  "source_kafka": {
    "address": "192.168.0.107:9092,192.168.0.216:9092,192.168.0.220:9092",
    "authenticate_mode": "PLAINTEXT",
    "cluster_alias": "a",
    "config_type": "CLOUD",
    "instance_id": "9280ed54-bd21-4721-bd99-7773b6b724ab",
    "password": null,
    "project_id": "bac852160cc743158936edaab6dda813",
    "region": "cn-north-7",
    "sasl_mechanism": "",
    "user_name": ""
  }
}
}
```

Example Responses

Status code: 200

Request succeeded.

```
{
  "advance_config": {
    "dcs2dcs": null,
    "kafka2kafka": {
      "compress_alg": "none",
      "is_add_header": false,
      "is_sync_progress": true,
      "rename_topic": false,
      "replica_cnt": 1,
      "seek_to": "earliest",
      "topic_mappings": [ ],
      "topic_regex": ".*",
      "topics": ""
    }
  },
  "cluster_id": "1a8b384f-b788-3000-0010-924ef6f516b2",
  "created_time": "2025-04-25T03:16:32Z",
  "description": "",
  "err_code": null,
  "err_message": null,
  "job_id": "1a959958-06f9-0000-0013-0bcb5b2cb356",
  "name": "eventRoute-0ztrqj7o",
  "scene_type": "DISASTER_BACKUP",
  "sink_config": {
    "sink_kafka": {
      "address": "192.168.0.49:9092,192.168.0.91:9092,192.168.0.210:9092",
      "authenticate_mode": "PLAINTEXT",
```

```
{
  "cluster_alias": "b",
  "config_type": "CLOUD",
  "instance_id": "d7d5bcec-2b73-4331-a568-1288f23dbbb0",
  "password": null,
  "project_id": "bac852160cc743158936edaab6dda813",
  "region": "cn-north-7",
  "sas_l_mechanism": "",
  "user_name": ""
},
"sink_status": "UNDEFINED",
"sink_status_info": "",
"sink_type": "KAFKA",
"source_config": {
  "source_kafka": {
    "address": "192.168.0.107:9092,192.168.0.216:9092,192.168.0.220:9092",
    "authenticate_mode": "PLAINTEXT",
    "cluster_alias": "a",
    "config_type": "CLOUD",
    "instance_id": "9280ed54-bd21-4721-bd99-7773b6b724ab",
    "password": null,
    "project_id": "bac852160cc743158936edaab6dda813",
    "region": "cn-north-7",
    "sas_l_mechanism": "",
    "user_name": ""
  }
},
"source_status": "UNDEFINED",
"source_type": "KAFKA",
"status": "WAIT_START",
"subnet_id": "33bd70bd-1d62-4438-96c8-da19fdd65230",
"updated_time": "2025-04-25T03:16:32Z",
"vpc_id": "0c4975eb-5575-4be0-b788-539ee002f45c"
}
```

Status Codes

Status Code	Description
200	Request succeeded.

Error Codes

See [Error Codes](#).

5.16.6 Performing Operations on a Professional Event Stream Job

Function

This API is used to perform operations on a professional event stream job.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/eventrouter/jobs/{job_id}/action

Table 5-642 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
job_id	Yes	String	Job ID.

Request Parameters

Table 5-643 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-644 Request body parameters

Parameter	Mandatory	Type	Description
operation	Yes	String	Operation type.
config	No	OperateConfig object	Additional parameters of the operation.

Table 5-645 OperateConfig

Parameter	Mandatory	Type	Description
switch_now	No	Boolean	Whether to perform switch source and target immediately. The default value is false.

Parameter	Mandatory	Type	Description
sink_address	No	String	Target IP address after the switchover. Multiple IP addresses are separated by commas (.). If the source IP address of the current job is matched, a switchover is performed. If the target IP address of the current job is matched, no switchover is performed. Otherwise, an error is reported.

Response Parameters

Status code: 200

Table 5-646 Response header parameters

Parameter	Type	Description
X-Request-Id	String	Request ID.

Table 5-647 Response body parameters

Parameter	Type	Description
job_id	String	Job ID.

Example Requests

Start the professional event stream job whose ID is 123.

```
POST https://{eg_endpoint}/v1/{project_id}/eventrouter/jobs/123/action
```

```
{
  "operation" : "START"
}
```

Example Responses

Status code: 200

Request succeeded.

```
{
  "job_id" : "fac59513-6c18-4266-bc81-5d412dfc1925"
}
```

Status Codes

Status Code	Description
200	Request succeeded.

Error Codes

See [Error Codes](#).

5.16.7 Verifying Professional Event Stream Jobs

Function

This API is used to verify professional event stream jobs.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/eventrouter/jobs/validation

Table 5-648 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-649 Query Parameters

Parameter	Mandatory	Type	Description
validate_type	No	String	Verification type.

Request Parameters

Table 5-650 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-651 Request body parameters

Parameter	Mandatory	Type	Description
cluster_id	Yes	String	Cluster ID.
source_config	No	EventRouterJobSource object	Source configuration of a professional event stream job.
sink_config	No	EventRouterJobSink object	Target configuration of a professional event stream job.

Table 5-652 EventRouterJobSource

Parameter	Mandatory	Type	Description
source_kafka	No	KafkaParameters object	Kafka configuration.
source_rocketmq	No	RocketmqParameters object	RocketMQ configuration.
source_dcs	No	DcsParameters object	DCS configuration.

Table 5-653 EventRouterJobSink

Parameter	Mandatory	Type	Description
sink_kafka	No	KafkaParameters object	Kafka configuration.

Parameter	Mandatory	Type	Description
sink_rocketmq	No	RocketmqParameters object	RocketMQ configuration.
sink_dcs	No	DcsParameters object	DCS configuration.

Table 5-654 KafkaParameters

Parameter	Mandatory	Type	Description
config_type	Yes	String	Instance type. CLOUD: DMS for Kafka instance.
region	Yes	String	Region ID.
project_id	Yes	String	Resource space ID.
instance_id	No	String	Kafka instance ID. This parameter is mandatory when configuration type is set to CLOUD.
cluster_alias	Yes	String	Kafka cluster alias.
address	No	String	Kafka address.
authenticate_mode	No	String	Authentication mode for Kafka.
sasl_mechanism	No	String	SASL authentication mechanism.
user_name	No	String	Username. This parameter is mandatory when SASL_SSL is enabled.
password	No	String	Password. This parameter is mandatory when SASL_SSL is enabled.

Table 5-655 RocketmqParameters

Parameter	Mandatory	Type	Description
config_type	Yes	String	Instance type. CLOUD: DMS for RocketMQ instance

Parameter	Mandatory	Type	Description
region	Yes	String	Region ID.
project_id	Yes	String	Resource space ID.
instance_id	No	String	RocketMQ instance ID. This parameter is mandatory when the configuration type is CLOUD.
cluster_alias	Yes	String	RocketMQ cluster alias.
address	No	String	RocketMQ address.
ssl_open	No	String	Whether to enable RocketMQ SSL. true: Enable false: Disable
acl_open	No	Boolean	Whether to enable RocketMQ ACL. true: Enable false: Disable
user_name	No	String	Username. This parameter is mandatory when ACL is enabled.
password	No	String	Password. This parameter is mandatory when ACL is enabled.

Table 5-656 DcsParameters

Parameter	Mandatory	Type	Description
config_type	Yes	String	Instance type. CLOUD: DCS instance
region	Yes	String	Region ID.
project_id	Yes	String	Resource space ID.
instance_id	No	String	DCS instance ID. This parameter is mandatory when the configuration type is set to CLOUD.
address	No	String	DCS address.
password	No	String	Password.

Response Parameters

Status code: 200

Table 5-657 Response header parameters

Parameter	Type	Description
X-Request-Id	String	Request ID.

Table 5-658 Response body parameters

Parameter	Type	Description
results	Array of ValidateResult objects	Job verification result list.

Table 5-659 ValidateResult

Parameter	Type	Description
check_item_name	String	Check item ID.
name	String	Check item name.
content	String	Check item content.
status	String	Check items status.
error_code	String	Error code corresponding to the check failure.
reason	String	Check failure cause.
solution	String	Solution to the check failure.

Example Requests

Verify the professional event stream job whose jobid is 123.

```
POST https://{eg_endpoint}/v1/{project_id}/eventrouter/jobs/validation?
validate_type=SOURCE_NETWORK&job_id=123
```

```
{
  "cluster_id" : "fac59513-6c18-4266-bc81-5d412dfc1926",
  "source_config" : {
    "source_dcs" : {
      "config_type" : "CLOUD",
      "region" : "roma-dev-1",
      "project_id" : "cb13a5c409fe40599271f44bbea5a2ad",
      "instance_id" : "228cdb80-fabb-4490-83bd-0a91e8bef9b4",
      "password" : null
    }
  }
}
```

```
}  
}
```

Example Responses

Status code: 200

Request succeeded.

```
{  
  "results": [ {  
    "check_item_name": "SOURCE_NETWORK",  
    "name": "Source connectivity",  
    "content": "Check whether the data transfer server can connect to the source service.",  
    "status": "SUCCESS",  
    "error_code": null,  
    "reason": null,  
    "solution": null  
  } ]  
}
```

Status Codes

Status Code	Description
200	Request succeeded.

Error Codes

See [Error Codes](#).

5.16.8 Querying the Synchronization Status of a Professional Event Job

Function

This API is used to query the synchronization status of a professional event job.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/eventrouter/jobs/{job_id}/syncDetail

Table 5-660 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Parameter	Mandatory	Type	Description
job_id	Yes	String	Job ID.

Request Parameters

Table 5-661 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-662 Request body parameters

Parameter	Mandatory	Type	Description
offset	Yes	Integer	Offset. The value ranges from 0 to 10000.
limit	Yes	Integer	The number of records displayed on a page. The value ranges from 10 to 1000.
conditions	No	Array of Condition objects	Condition.

Table 5-663 Condition

Parameter	Mandatory	Type	Description
key	Yes	String	Query condition key. Its value can only be topic.
operate	Yes	String	Query operation. Only EQUAL LIKE is supported.
value	Yes	Object	Value of the query condition, which can be a topic name.

Response Parameters

Status code: 200

Table 5-664 Response header parameters

Parameter	Type	Description
X-Request-Id	String	Request ID.

Table 5-665 Response body parameters

Parameter	Type	Description
metadata	MQSyncDetailMetadata object	Metadata.
total	Integer	Total number.
size	Integer	Quantity.
type	String	Type.
items_kafka	Array of KafkaSyncDetailData objects	Return value of the Kafka type. The value is items instead of _kafka.
items_rocketmq	Array of RocketMQSyncDetailData objects	Return value of the RocketMQ type. The value is items instead of _rocketmq.
items_redis	Array of RedisSyncDetailData objects	Return value of the Redis type. The value is items instead of _redis.

Table 5-666 MQSyncDetailMetadata

Parameter	Type	Description
sync_remain_total	Integer	The total number of remaining events to be synchronized.
source_key_num	Integer	Number of DCS source keys.
sink_key_num	Integer	Number of DCS target keys.

Table 5-667 KafkaSyncDetailData

Parameter	Type	Description
topic	String	Topic.
number	Integer	Quantity.

Parameter	Type	Description
sync_remain_num	Integer	The number of remaining events to be synchronized.
offset_details	Array of OffsetDetail objects	Offset details.

Table 5-668 OffsetDetail

Parameter	Type	Description
partition	KafkaPartition object	Partition.
offset	KafkaOffset object	Offset.

Table 5-669 KafkaPartition

Parameter	Type	Description
cluter	String	Cluster.
topic	String	Topic.
partition	Integer	Partition.

Table 5-670 KafkaOffset

Parameter	Type	Description
offset	Integer	Offset.
max_offset	Integer	Maximum offset.

Table 5-671 RocketMQSyncDetaiData

Parameter	Type	Description
topic	String	Topic.
number	Integer	Quantity.
sync_remain_num	Integer	The number of remaining events to be synchronized.

Parameter	Type	Description
offset_details	Array of RocketMQOffsetDetail objects	Offset details.

Table 5-672 RocketMQOffsetDetail

Parameter	Type	Description
queue	RocketMQQueueInfo object	Queue.
offset	RocketMQOffsetInfo object	Offset.

Table 5-673 RocketMQQueueInfo

Parameter	Type	Description
rocketmq_topic	String	RocketMQ topic.
rocketmq_broker	String	RocketMQ broker.
rocketmq_queue	Integer	RocketMQ queue.

Table 5-674 RocketMQOffsetInfo

Parameter	Type	Description
rocketmq_offset	Integer	RocketMQ offset.
max_offset	Integer	Maximum offset of RocketMQ.

Table 5-675 RedisSyncDetailData

Parameter	Type	Description
sourceAddr	String	Source IP address + port, which describes the source address information.
sinkAddr	String	Target IP address + port: which describes the target address information.

Parameter	Type	Description
taskProgress	String	Job progress. The value is within the range [0,1]. 1 indicates that the progress is 100%.
syncPhase	String	Synchronization phase. Options: full, full+incremental. Currently, only the full+incremental mode is supported.
sourceOffset	Integer	Source offset, which indicates the number of synchronized events in source.
sinkOffset	Integer	Target offset, which indicates the number of synchronized events in target.
taskStatus	String	Job status. Options: created, syncing, failed, stopped, finish.

Example Requests

Check the synchronization status of the professional event stream job whose ID is 123.

```
POST https://{eg_endpoint}/v1/{project_id}/eventrouter/jobs/123/syncDetail
{
  "offset" : 0,
  "limit" : 1000
}
```

Example Responses

Status code: 200

Request succeeded.

```
{
  "metadata" : {
    "sync_remain_total" : 0,
    "source_key_num" : 4,
    "sink_key_num" : 1
  },
  "total" : 1,
  "size" : 1,
  "type" : "DCS"
}
```

Status Codes

Status Code	Description
200	Request succeeded.

Error Codes

See [Error Codes](#).

5.17 Professional Event Stream Cluster Management

5.17.1 Querying AZs of a Professional Event Stream Cluster

Function

This API is used to query AZs of a professional event stream cluster.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/eventrouter/clusters/availability-zone

Table 5-676 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Request Parameters

Table 5-677 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-678 Response header parameters

Parameter	Type	Description
X-Request-Id	String	Request ID.

Table 5-679 Response body parameters

Parameter	Type	Description
zone_names	Array of strings	AZ name.

Example Requests

Query AZs of the professional event stream cluster of \${project_id}.

GET https://{eg_endpoint}/v1/{project_id}/eventrouter/clusters/availability-zone

Example Responses

Status code: 200

Request succeeded.

```
{  
  "zone_names" : [ "az1", "az2" ]  
}
```

Status Codes

Status Code	Description
200	Request succeeded.

Error Codes

See [Error Codes](#).

5.17.2 Creating a Professional Event Stream Cluster

Function

This API is used to create a professional event stream cluster.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

POST /v1/{project_id}/eventrouter/clusters

Table 5-680 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Request Parameters

Table 5-681 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-682 Request body parameters

Parameter	Mandatory	Type	Description
name	Yes	String	Cluster name. Start with a letter or digit, and only include letters, digits, periods (.), underscores (_), and hyphens (-). (Max. 128 characters)
description	No	String	Cluster description. The description can contain a maximum of 256 characters.
source_type	Yes	String	Source type, which can be Kafka, RocketMQ, or DCS. The value must be the same as the target type.
sink_type	Yes	String	Target type.
vpc_id	Yes	String	VPC ID.
subnet_id	Yes	String	Subnet ID.
zone_names	No	String	AZ name.

Parameter	Mandatory	Type	Description
bss_param	No	bssParam object	Parameter related to the billing mode. If this parameter is left blank, the billing mode is pay-per-use by default. If this parameter is not left blank, the billing mode is yearly/monthly.
flavor	No	String	Cluster flavor.
public_access_enabled	Yes	Boolean	Whether public access is enabled for the event stream cluster.
nat_id	No	String	ID of the NAT instance bound to the cluster when public access is enabled.
eip_id	No	String	ID of the EIP instance bound to the cluster when public access is enabled.

Table 5-683 bssParam

Parameter	Mandatory	Type	Description
charging_mode	Yes	String	Billing mode.

Response Parameters

Status code: 200

Table 5-684 Response header parameters

Parameter	Type	Description
X-Request-Id	String	Request ID.

Table 5-685 Response body parameters

Parameter	Type	Description
cluster_id	String	Professional event stream cluster ID.

Parameter	Type	Description
name	String	Cluster name. Start with a letter or digit, and only include letters, digits, periods (.), underscores (_), and hyphens (-). (Max. 128 characters)
description	String	Cluster description. The description can contain a maximum of 256 characters.
source_type	String	Source type.
sink_type	String	Target type.
subnet_id	String	Subnet ID.
vpc_id	String	VPC ID.
zone_names	String	AZ name.
status	String	Job status.
job_count	Number	Number of jobs in the current cluster.
flavor	String	Flavor.
charging_mode	String	Billing mode.
err_code	String	Error code.
err_message	String	Error cause.
created_time	String	UTC time when the event source is created.
updated_time	String	UTC time when the event source is updated.

Example Requests

Create a Kafka professional event stream cluster named cluster-qapbtr95.

POST https://{eg_endpoint}/v1/{project_id}/eventrouter/clusters

```
{
  "name" : "cluster-qapbtr95",
  "description" : "",
  "vpc_id" : "199f632d-34e7-4915-b4d8-1bc4e2824867",
  "subnet_id" : "0d1799e1-116e-4551-92dc-02dd8a860072",
  "source_type" : "KAFKA",
  "sink_type" : "KAFKA",
  "public_access_enabled" : false
}
```

Example Responses

Status code: 200

Request succeeded.

```
{
  "cluster_id": "fac59513-6c18-4266-bc81-5d412dfc1925",
  "name": "cluster-ifpcv5u4",
  "description": "",
  "source_type": "KAFKA",
  "sink_type": "KAFKA",
  "status": "CREATING",
  "job_count": 0,
  "err_code": null,
  "err_message": null,
  "created_time": "2024-05-16T11:46:07Z",
  "updated_time": "2024-05-16T11:46:07Z",
  "vpc_id": "199f632d-34e7-4915-b4d8-1bc4e2824867",
  "subnet_id": "0d1799e1-116e-4551-92dc-02dd8a860072",
  "zone_names": "az0",
  "public_access_enabled": false
  "nat_id": null,
  "eip_id": null
}
```

Status Codes

Status Code	Description
200	Request succeeded.

Error Codes

See [Error Codes](#).

5.17.3 Querying the Professional Event Stream Clusters

Function

This API is used to query the professional event stream clusters.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/eventrouter/clusters

Table 5-686 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.

Table 5-687 Query Parameters

Parameter	Mandatory	Type	Description
fuzzy_name	No	String	Fuzzy query by name.
offset	No	String	Offset.
limit	No	String	Number of records displayed on each page.

Request Parameters

Table 5-688 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-689 Response header parameters

Parameter	Type	Description
X-Request-Id	String	Request ID.

Table 5-690 Response body parameters

Parameter	Type	Description
total	Integer	Total number.
size	Integer	Number of records displayed on the current page.
items	Array of EventRouterClusterInfo objects	Object list.

Table 5-691 EventRouterClusterInfo

Parameter	Type	Description
cluster_id	String	Professional event stream cluster ID.
name	String	Cluster name. Start with a letter or digit, and only include letters, digits, periods (.), underscores (_), and hyphens (-). (Max. 128 characters)
description	String	Cluster description. The description can contain a maximum of 256 characters.
source_type	String	Source type.
sink_type	String	Target type.
subnet_id	String	Subnet ID.
vpc_id	String	VPC ID.
zone_names	String	AZ name.
status	String	Job status.
job_count	Number	Number of jobs in the current cluster.
flavor	String	Flavor.
charging_mode	String	Billing mode.
err_code	String	Error code.
err_message	String	Error cause.
created_time	String	UTC time when the event source is created.
updated_time	String	UTC time when the event source is updated.

Example Requests

Query the professional event stream clusters.

```
GET https://{eg_endpoint}/v1/{project_id}/eventrouter/clusters?limit=1000&offset=0
```

Example Responses

Status code: 200

Request succeeded.

```
{
  "size" : 1,
  "total" : 1,
  "items" : [ {
    "cluster_id" : "fac59513-6c18-4266-bc81-5d412dfc1925",
```

```
"name" : "cluster-ifpcv5u4",
"description" : null,
"source_type" : "KAFKA",
"sink_type" : "KAFKA",
"status" : "RUNNING",
"job_count" : 1,
"err_code" : null,
"err_message" : null,
"created_time" : "2024-05-16T11:46:07Z",
"updated_time" : "2024-05-16T11:46:07Z",
"vpc_id" : "199f632d-34e7-4915-b4d8-1bc4e2824867",
"subnet_id" : "0d1799e1-116e-4551-92dc-02dd8a860072",
"zone_names" : "az0",
"public_access_enabled" : true,
"nat_id" : "c43e1888-6589-4b43-xxxxxxxxxxxx",
"eip_id" : "e7d72bae-653e-4fb5-xxxxxxxxxxxx"
}]
}
```

Status Codes

Status Code	Description
200	Request succeeded.

Error Codes

See [Error Codes](#).

5.17.4 Deleting a Professional Event Stream Cluster

Function

This API is used to delete a professional event stream cluster.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

DELETE /v1/{project_id}/eventrouter/clusters/{cluster_id}

Table 5-692 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
cluster_id	Yes	String	Cluster ID.

Request Parameters

Table 5-693 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-694 Response header parameters

Parameter	Type	Description
X-Request-Id	String	Request ID.

Table 5-695 Response body parameters

Parameter	Type	Description
-	String	Operation successful.

Example Requests

Delete a professional event stream cluster.

```
DELETE https://{eg_endpoint}/v1/{project_id}/eventrouter/clusters/{cluster_id}
```

Example Responses

Status code: 200

Request succeeded.

```
{
  "cluster_id" : "fac59513-6c18-4266-bc81-5d412dfc1925"
}
```

Status Codes

Status Code	Description
200	Request succeeded.

Error Codes

See [Error Codes](#).

5.17.5 Querying Details about a Professional Event Stream Cluster

Function

This API is used to query details about a professional event stream cluster.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

GET /v1/{project_id}/eventrouter/clusters/{cluster_id}

Table 5-696 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
cluster_id	Yes	String	Cluster ID.

Request Parameters

Table 5-697 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Response Parameters

Status code: 200

Table 5-698 Response header parameters

Parameter	Type	Description
X-Request-Id	String	Request ID.

Table 5-699 Response body parameters

Parameter	Type	Description
cluster_id	String	Professional event stream cluster ID.
name	String	Cluster name. Start with a letter or digit, and only include letters, digits, periods (.), underscores (_), and hyphens (-). (Max. 128 characters)
description	String	Cluster description. The description can contain a maximum of 256 characters.
source_type	String	Source type.
sink_type	String	Target type.
subnet_id	String	Subnet ID.
vpc_id	String	VPC ID.
zone_names	String	AZ name.
status	String	Job status.
job_count	Number	Number of jobs in the current cluster.
flavor	String	Flavor.
charging_mode	String	Billing mode.
err_code	String	Error code.
err_message	String	Error cause.
created_time	String	UTC time when the event source is created.
updated_time	String	UTC time when the event source is updated.

Example Requests

Query details about a professional event stream cluster.

GET https://{eg_endpoint}/v1/{project_id}/eventrouter/clusters/{cluster_id}

Example Responses

Status code: 200

Request succeeded.

```
{
  "cluster_id" : "fac59513-6c18-4266-bc81-5d412dfc1925",
  "name" : "cluster-ifpcv5u4",
  "description" : null,
  "source_type" : "KAFKA",
  "sink_type" : "KAFKA",
  "status" : "RUNNING",
  "job_count" : 1,
  "err_code" : null,
  "err_message" : null,
  "created_time" : "2024-05-16T11:46:07Z",
  "updated_time" : "2024-05-16T11:46:07Z",
  "vpc_id" : "199f632d-34e7-4915-b4d8-1bc4e2824867",
  "subnet_id" : "0d1799e1-116e-4551-92dc-02dd8a860072",
  "public_access_enabled" : true,
  "nat_id" : "c43e1888-6589-4b43-xxxxxxxxxxxx",
  "eip_id" : "e7d72bae-653e-4fb5-xxxxxxxxxxxx"
}
```

Status Codes

Status Code	Description
200	Request succeeded.

Error Codes

See [Error Codes](#).

5.17.6 Updating a Professional Event Stream Cluster

Function

This API is used to update a professional event stream cluster.

Authorization Information

Each account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. For details about the required permissions, see [Permissions Policies and Supported Actions](#).

URI

PUT /v1/{project_id}/eventrouter/clusters/{cluster_id}

Table 5-700 Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Tenant resource space ID.
cluster_id	Yes	String	Cluster ID.

Request Parameters

Table 5-701 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	User token. The token can be obtained by calling the IAM API used to obtain a user token. The value of X-Subject-Token in the response header is the user token.

Table 5-702 Request body parameters

Parameter	Mandatory	Type	Description
name	No	String	Cluster name. Start with a letter or digit, and only include letters, digits, periods (.), underscores (_), and hyphens (-). (Max. 128 characters)
description	No	String	Cluster description. The description can contain a maximum of 256 characters.
public_access_enabled	No	Boolean	Whether public access is enabled for the event stream cluster.
nat_id	No	String	ID of the NAT instance bound to the cluster when public access is enabled.
eip_id	No	String	ID of the EIP instance bound to the cluster when public access is enabled.

Response Parameters

Status code: 200

Table 5-703 Response header parameters

Parameter	Type	Description
X-Request-Id	String	Request ID.

Table 5-704 Response body parameters

Parameter	Type	Description
cluster_id	String	Professional event stream cluster ID.
name	String	Cluster name. Start with a letter or digit, and only include letters, digits, periods (.), underscores (_), and hyphens (-). (Max. 128 characters)
description	String	Cluster description. The description can contain a maximum of 256 characters.
source_type	String	Source type.
sink_type	String	Target type.
subnet_id	String	Subnet ID.
vpc_id	String	VPC ID.
zone_names	String	AZ name.
status	String	Job status.
job_count	Number	Number of jobs in the current cluster.
flavor	String	Flavor.
charging_mode	String	Billing mode.
err_code	String	Error code.
err_message	String	Error cause.
created_time	String	UTC time when the event source is created.
updated_time	String	UTC time when the event source is updated.

Example Requests

Update the description of the professional event stream cluster cluster-xspx0v5v.

```
PUT https://{eg_endpoint}/v1/{project_id}/eventrouter/clusters/{cluster_id}

{
  "name" : "cluster-xsp0v5v",
  "description" : "xxx",
  "public_access_enabled" : true,
  "nat_id" : "c43e1888-6589-4b43-xxxxxxxxxxxx",
  "eip_id" : "e7d72bae-653e-4fb5-xxxxxxxxxxxx"
}
```

Example Responses

Status code: 200

Request succeeded.

```
{
  "cluster_id" : "fac59513-6c18-4266-bc81-5d412dfc1925",
  "name" : "cluster-ifpcv5u4",
  "description" : null,
  "source_type" : "KAFKA",
  "sink_type" : "KAFKA",
  "status" : "RUNNING",
  "job_count" : 1,
  "err_code" : null,
  "err_message" : null,
  "created_time" : "2024-05-16T11:46:07Z",
  "updated_time" : "2024-05-16T11:46:07Z",
  "vpc_id" : "199f632d-34e7-4915-b4d8-1bc4e2824867",
  "subnet_id" : "0d1799e1-116e-4551-92dc-02dd8a860072",
  "public_access_enabled" : true,
  "nat_id" : "c43e1888-6589-4b43-xxxxxxxxxxxx",
  "eip_id" : "e7d72bae-653e-4fb5-xxxxxxxxxxxx"
}
```

Status Codes

Status Code	Description
200	Request succeeded.

Error Codes

See [Error Codes](#).

6 Permissions Policies and Supported Actions

This chapter describes fine-grained permissions management for your EG. If your Huawei Cloud account does not require individual IAM users, you can skip this chapter.

New IAM users do not have any permissions assigned by default. You need to first add them to one or more groups and attach policies or roles to these groups. After authorization, the user can perform specified operations on cloud services based on the permissions.

You can grant users permissions by using [roles](#) and [policies](#). Roles are a type of coarse-grained authorization mechanism that defines permissions related to user responsibilities. Policies define API-based permissions for operations on specific resources under certain conditions, allowing for more fine-grained, secure access control of cloud resources.

NOTE

Policy-based authorization is useful if you want to allow or deny the access to an API.

An account has all the permissions required to call all APIs, but IAM users must be assigned the required permissions. The permissions required for calling an API are determined by the actions supported by the API. Only users who have been granted permissions can call the API successfully. For example, if an IAM user creates event sources using an API, the user must have been granted permissions that allow the **eg:sources:create** action.

Supported Actions

EG provides system-defined policies that can be directly used in IAM. You can also create custom policies to supplement system-defined policies for more refined access control. Operations supported by policies are specific to APIs. The following are common concepts related to policies:

- Permissions: statements in a policy that allow or deny certain operations
- APIs: APIs that will be called for performing certain operations
- Actions: specific operations that are allowed or denied

- IAM projects or enterprise projects: A custom policy can be applied to IAM projects or enterprise projects or both. Policies that contain actions supporting both IAM and enterprise projects can be assigned to user groups and take effect in both IAM and Enterprise Management. Policies that only contain actions supporting IAM projects can be assigned to user groups and only take effect for IAM. Such policies will not take effect if they are assigned to user groups in Enterprise Management. For details about the differences between IAM and enterprise projects, see [What Are the Differences Between IAM and Enterprise Management?](#)

EG supports the following actions that can be defined in custom policies. Permissions must be obtained before calling APIs. For details on how to obtain permissions, visit the [Identity and Access Management help center](#).

Table 6-1 EG permissions

Permission	API	Action	IAM Project	Enterprise Project
Create event channels	POST /v1/{project_id}/channels	eg:channels:create	√	x
View the event channel list	GET /v1/{project_id}/channels	eg:channels:list	√	x
Update event channels	PUT /v1/{project_id}/channels/{channel_id}	eg:channels:update	√	x
Delete event channels	DELETE /v1/{project_id}/channels/{channel_id}	eg:channels:delete	√	x
View event channel details	GET /v1/{project_id}/channels/{channel_id}	eg:channels:get	√	x
Publish events to event channels	POST /v1/{project_id}/channels/{channel_id}/events	eg:channels:putEvents	√	x
Create event sources	POST /v1/{project_id}/sources	eg:sources:create	√	x
View the event source list	GET /v1/{project_id}/sources	eg:sources:list	√	x
Update event sources	PUT /v1/{project_id}/sources/{source_id}	eg:sources:update	√	x

Permission	API	Action	IAM Project	Enterprise Project
Delete event sources	DELETE /v1/{project_id}/sources/{source_id}	eg:sources:delete	√	x
View event source details	GET /v1/{project_id}/sources/{source_id}	eg:sources:get	√	x
View the event target catalog list	GET /v1/{project_id}/target-catalogs	eg:targetCatalogs:list	√	x
Create event subscriptions	POST /v1/{project_id}/subscriptions	eg:subscriptions:create	√	x
View the event subscription list	GET /v1/{project_id}/subscriptions	eg:subscriptions:list	√	x
Update event subscriptions	PUT /v1/{project_id}/subscriptions/{subscription_id}	eg:subscriptions:update	√	x
Delete event subscriptions	DELETE /v1/{project_id}/subscriptions/{subscription_id}	eg:subscriptions:delete	√	x
View event subscription details	GET /v1/{project_id}/subscriptions/{subscription_id}	eg:subscriptions:get	√	x
Enable or disable event subscriptions	POST /v1/{project_id}/subscriptions/operation	eg:subscriptions:update	√	x
Create schemas	POST /v1/{project_id}/schemas	eg:schemas:create	√	x
View the schema list	GET /v1/{project_id}/schemas	eg:schemas:list	√	x
Update schemas	PUT /v1/{project_id}/schemas/{schema_id}	eg:schemas:update	√	x

Permission	API	Action	IAM Project	Enterprise Project
Delete schemas	DELETE /v1/{project_id}/schemas/{schema_id}	eg:schemas:delete	√	x
View schema details	GET /v1/{project_id}/schemas/{schema_id}	eg:schemas:get	√	x
View the schema version list	GET /v1/{project_id}/schemas/{schema_id}/versions	eg:schemas:listVersions	√	x
View schema version details	GET /v1/{project_id}/schemas/{schema_id}/versions/{version}	eg:schemas:getVersion	√	x
Delete schema versions	DELETE /v1/{project_id}/schemas/{schema_id}/versions/{version}	eg:schemas:deleteVersion	√	x
Discover schemas	POST /v1/{project_id}/schema-discover	eg:schemas:getDiscovered	√	x
Query quotas	GET /v1/{project_id}/quotas	eg:quotas:list	√	x

7 Appendix

7.1 Status Codes

Table 7-1 lists status codes.

Table 7-1 Status codes

Status Code	Name	Description
100	Continue	The client should continue with its request. This interim response is used to inform the client that some requests have been received and have not been rejected by the server.
101	Switching Protocols	The protocol should be switched. The protocol can only be switched to a more advanced protocol. For example, the current HTTP protocol is switched to a later version of HTTP.
200	OK	Request sent successfully.
201	Created	The request for creating resources has been fulfilled.
202	Accepted	The request has been accepted, but the processing has not been completed.
203	Non-Authoritative Information	The request has been fulfilled.
204	NoContent	The server has successfully processed the request, but is not returning any response body. The status code is returned in response to an HTTP OPTIONS request.

Status Code	Name	Description
205	Reset Content	The server has fulfilled the request, but the requester is required to reset the content.
206	Partial Content	The server has successfully processed a part of the request.
300	Multiple Choices	There are multiple options for the requested resource. For example, this code could be used to present a list of resource characteristics and addresses from which the client such as a browser may choose.
301	Moved Permanently	This and all future requests have been permanently moved to the given URI indicated in this response.
302	Found	The requested resource was temporarily moved.
303	See Other	Retrieve another URL using a GET or POST method.
304	Not Modified	The requested resource has not been modified. When the server returns this status code, it does not return any resources.
305	Use Proxy	The requested resource is available only through a proxy.
306	Unused	This HTTP status code is no longer used.
400	BadRequest	Invalid request. The client should modify the request instead of re-initiating it.
401	Unauthorized	The authorization information provided by the client is incorrect or invalid.
402	Payment Required	Reserved for future use.
403	Forbidden	The request is rejected. The server has received the request and understood it, but the server is refusing to respond to it. The client should not repeat the request without modifications.
404	NotFound	The requested resource cannot be found. The client should modify the request instead of re-initiating it.

Status Code	Name	Description
405	MethodNotAllowed	A request method is not supported for the requested resource. The client should modify the request instead of re-initiating it.
406	Not Acceptable	The server cannot fulfill the request based on the content characteristics of the request.
407	Proxy Authentication Required	This code is similar to 401, but indicates that the client must first authenticate itself with the proxy.
408	Request Time-out	The server timed out when waiting for the request. The client may re-initiate the request without any modification at any time.
409	Conflict	The request could not be processed due to a conflict. The resource that the client attempts to create already exists, or the update request fails to be processed because of a conflict.
410	Gone	The requested resource cannot be found. The requested resource has been deleted permanently.
411	Length Required	The server refused to process the request because the request does not specify the length of its content.
412	Precondition Failed	The server does not meet one of the preconditions that the requester puts on the request.
413	Request Entity Too Large	The server refuses to process a request because the request is too large. The server may close the connection to prevent the client from continuing the request. If the server cannot process the request temporarily, the response will contain a Retry-After field.
414	Request-URI Too Large	The URI provided was too long for the server to process.
415	Unsupported Media Type	The server does not support the media type in the request.
416	Requested range not satisfiable	The requested range is invalid.

Status Code	Name	Description
417	Expectation Failed	The server fails to meet the requirements of the Expect request-header field.
422	UnprocessableEntity	The request is well-formed but unable to be processed due to semantic errors.
429	TooManyRequests	The client has sent more requests than its rate limit is allowed within a given amount of time, or the server has received more requests than it is able to process within a given amount of time. In this case, the client should re-initiate requests after the time specified in the Retry-After header of the response expires.
500	InternalServerError	The server is able to receive the request but it could not understand the request.
501	Not Implemented	The server does not support the requested function.
502	Bad Gateway	The server acting as a gateway or proxy receives an invalid response from a remote server.
503	ServiceUnavailable	The requested service is invalid. The client should modify the request instead of re-initiating it.
504	ServerTimeout	The request cannot be fulfilled within a given time. This status code is returned to the client only when the duration specified by Timeout in the request timed out.
505	HTTP Version not supported	The server does not support the HTTP protocol version used in the request.

7.2 Error Codes

If an error code starting with **APIGW** is returned after you call an API, rectify the fault according to [API Gateway Error Codes](#).

Status Code	Error code.	Error Message	Description	Solution
400	EG.00513000	Invalid parameter.	Invalid parameter.	Check the parameter.
400	EG.00513001	Name duplicated.	The name already exists.	Enter a new name.

Status Code	Error code.	Error Message	Description	Solution
400	EG.00513002	Invalid subscription status.	Enabled subscriptions cannot be edited.	Try again later.
400	EG.00513003	Invalid target address.	The custom event target URL is invalid.	Check the event target URL.
400	EG.00513004	Invalid filter parameters.	The event source filter rule is invalid.	Check the event source filter rule.
400	EG.00513005	Invalid channel.	The event channel is unavailable.	Select another event channel.
400	EG.00513006	VPC conflict.	This VPC already has a private endpoint.	You do not need to create a new one.
400	EGS.00516010	Must be in ZIP format.	Must be in ZIP format.	Check whether the format of the compressed package is correct.
400	EGS.00516011	Invalid download URL.	Invalid download URL.	Check the certificate download URL.
400	EGS.00516012	Download OBS files failed.	Download OBS files failed.	Contact your administrator.
400	EGS.00516013	Upload file to OBS failed.	Upload file to OBS failed.	Contact your administrator.
400	EGS.00516015	Create OBS bucket failed.	Create OBS bucket failed.	Contact your administrator.
400	EGS.00516016	The certificate does not exist in the compressed package.	The certificate does not exist in the compressed package.	Check the content of the package and ensure that the certificate exists.
400	EGS.00516017	Too many files.	Too many files.	Check the number of files in the package.

Status Code	Error code.	Error Message	Description	Solution
400	EGS.00516018	File too large.	File too large.	Check the size of the file in the compressed package.
403	EG.00512000	No permission.	No permission.	Contact your administrator.
403	EG.00512001	The account is frozen, operation is not permitted.	Your account is frozen.	Top up your account or contact your administrator to unfreeze the account.
403	EG.00512002	Your account does not have the permission to create agencies.	Your account does not have the permission to create agencies.	Contact your administrator to grant you the required permissions.
403	EG.00512003	Agency required.	The agency does not exist.	Create an agency.
403	EG.00514003	The resource quota is insufficient.	The resource quota is insufficient.	Increase the resource quota.
403	EG.00514004	The resource cannot be modified.	The resource cannot be modified.	Resources created by other services cannot be modified.
404	EG.00514001	The resource does not exist.	The resource does not exist.	Contact your administrator.
409	EG.00514002	The resource is bound to other resources.	The resource is bound to other resources.	Delete the bound resources first.
409	EG.00514005	Resource can not be deleted.	The connection is being created and cannot be deleted.	Try again later.
500	EG.00511000	Internal server error.	Internal service error.	Contact your administrator.

Status Code	Error code.	Error Message	Description	Solution
500	EG.00515001	The resource does not exist.	The resource does not exist when the event is published.	Contact your administrator.
503	EG.00511001	The service is unavailable.	The service is unavailable.	Contact your administrator.

7.3 Obtaining a Project ID

Scenario

A project ID is required for some URLs when an API is called. Obtain a project ID using either of the following methods:

- [Obtaining a Project ID by Calling an API](#)
- [Obtaining a Project ID on the Console](#)

Obtaining a Project ID by Calling an API

You can obtain a project ID by calling the API used to [query projects based on specified criteria](#).

The API used to obtain a project ID is **GET https://{Endpoint}/v3/projects**, where *{Endpoint}* indicates the IAM endpoint. You can obtain the IAM endpoint from [Regions and Endpoints](#). For details on API calling authentication, see [Performing Authentication](#).

In the following example, **id** indicates the project ID.

```
{
  "projects": [
    {
      "domain_id": "65382450e8f64ac0870cd180d14e684b",
      "is_domain": false,
      "parent_id": "65382450e8f64ac0870cd180d14e684b",
      "name": "xxx-xxx-xxx",
      "description": "",
      "links": {
        "next": null,
        "previous": null,
        "self": "https://www.example.com/v3/projects/a4a5d4098fb4474fa22cd05f897d6b99"
      },
      "id": "a4a5d4098fb4474fa22cd05f897d6b99",
      "enabled": true
    }
  ],
  "links": {
    "next": null,
    "previous": null,
    "self": "https://www.example.com/v3/projects"
  }
}
```

Obtaining a Project ID on the Console


A project ID is required for some URLs when an API is called. You can obtain a project ID on the console.

The following procedure describes how to obtain a project ID:

- Step 1** Log in to the management console.
- Step 2** Hover the pointer over the username in the upper right corner and choose **My Credentials** from the drop-down list.

On the **API Credentials** page, view the project ID in the project list.

Figure 7-1 Viewing a project ID



----End


7.4 Obtaining the Account Name and Account ID

When calling APIs, you need to specify your domain name and domain ID in certain URLs. To do so, you need to obtain domain name and domain ID on the console first. The following procedure describes how to obtain the domain and domain ID:

- Log in to the management console.
- Hover the pointer over the username in the upper right corner and choose **My Credentials** from the drop-down list.

View the account name and account ID.

Figure 7-2 Viewing the account name and account ID



8 Description

Released On	Description
2023-03-31	This issue is the first official release.