

KooDrive

# API Reference

Issue 01  
Date 2025-03-06



HUAWEI CLOUD COMPUTING TECHNOLOGIES CO., LTD.



**Copyright © Huawei Cloud Computing Technologies Co., Ltd. 2025. All rights reserved.**

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Cloud Computing Technologies Co., Ltd.

## **Trademarks and Permissions**



HUAWEI and other Huawei trademarks are the property of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

## **Notice**

The purchased products, services and features are stipulated by the contract made between Huawei Cloud and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

# Contents

---

|  |           |
|--|-----------|
| <b>1 Before You Start.....</b>                               | <b>1</b>  |
| <b>2 API Overview.....</b>                                   | <b>3</b>  |
| <b>3 Calling APIs.....</b>                                   | <b>5</b>  |
| 3.1 Making an API Request.....                               | 5         |
| 3.2 Authentication.....                                      | 7         |
| 3.3 Response.....  | 8         |
| <b>4 API.....</b>  | <b>10</b> |
| 4.1 Department Management.....                               | 10        |
| 4.1.1 Listing Departments.....                               | 10        |
| 4.1.2 Querying a Department.....                             | 13        |
| 4.1.3 Creating a Department.....                             | 15        |
| 4.1.4 Modifying a Department.....                            | 18        |
| 4.1.5 Deleting a Department.....                             | 20        |
| 4.2 User Management.....                                     | 22        |
| 4.2.1 Querying Information About a User.....                 | 22        |
| 4.2.2 Listing Users.....                                     | 24        |
| 4.2.3 Counting Members in an Organization or Department..... | 27        |
| 4.2.4 Creating a User.....                                   | 29        |
| 4.2.5 Modifying a User.....                                  | 32        |
| 4.2.6 Deleting a User.....                                   | 34        |
| 4.2.7 Querying the Mobile Number of a User.....              | 36        |
| 4.2.8 Pre-verification API.....                              | 38        |
| 4.2.9 Change the maximum number of OrgID users.....          | 41        |
| 4.3 Space Management.....                                    | 43        |
| 4.3.1 Listing Departments Spaces.....                        | 43        |
| 4.3.2 Querying Space Information.....                        | 46        |
| 4.3.3 Creating a Space for a Department or Individual.....   | 50        |
| 4.3.4 Modifying Space Information.....                       | 54        |
| 4.3.5 Deleting a Space.....                                  | 57        |
| 4.3.6 Querying Space Details by Space ID.....                | 59        |
| 4.3.7 Querying Information About a Team Space.....           | 62        |
| 4.3.8 Creating a Group Space.....                            | 65        |

|   |     |
|---|-----|
| 4.3.9 Dismissing a Team Space.....  | 69  |
| 4.3.10 Listing Group Spaces in an Enterprise.....   | 71  |
| 4.3.11 Listing User Spaces.....   | 74  |
| 4.3.12 Obtains space information.....   | 78  |
| 4.4 Group Management.....   | 81  |
| 4.4.1 Creating a User Group.....  | 81  |
| 4.4.2 Listing User Groups.....  | 83  |
| 4.4.3 Modifying Group Information.....  | 86  |
| 4.4.4 Deleting a Group.....   | 88  |
| 4.4.5 Listing Members in a User Group.....  | 90  |
| 4.4.6 Adding Members to a User Group.....   | 93  |
| 4.4.7 Deleting Members from a User Group.....   | 97  |
| 4.5 Session Management.....   | 100 |
| 4.5.1 Checking Whether a User Session Is Invalid Based on Token Information.....              | 100 |
| 4.5.2 Obtaining the URL of an OrgID Authorization Code for KooDrive.....                      | 102 |
| 4.5.3 Initializing and Creating a Session.....  | 104 |
| 4.5.4 Refreshing a Session.....   | 106 |
| 4.5.5 Signing In and Signing Out.....   | 108 |
| 4.6 Service Subscription.....   | 110 |
| 4.6.1 Obtaining the Subscription Status.....  | 110 |
| 4.6.2 Querying Service Usage.....   | 112 |
| 4.7 Enterprise Settings.....  | 115 |
| 4.7.1 Setting the Expiration Time of a Compressed Package.....                                | 115 |
| 4.8 Other APIs.....   | 117 |
| 4.8.1 Obtain the JavaScript SDK.....  | 117 |
| 4.9 Permissions Templates.....  | 119 |
| 4.9.1 Creating a Permissions Template.....  | 119 |
| 4.9.2 Editing a Permissions Template.....   | 125 |
| 4.9.3 Modifying the Status of Permissions Templates.....                                      | 129 |
| 4.9.4 Deleting Permissions Templates in Batches.....  | 130 |
| 4.9.5 Querying Permissions Template Details Based on the Permissions Template ID Array.....   | 132 |
| 4.9.6 Listing Permissions Templates by Condition.....   | 136 |
| 4.9.7 Adding or Modifying the Association Relationship of the Initial Member Permissions..... | 140 |
| 4.9.8 Querying Whether a Permissions Template Is Used.....                                    | 143 |
| 4.10 File Moderation.....   | 145 |
| 4.10.1 Querying the Review List.....  | 145 |
| 4.10.2 Adding Content Moderation Records in Batches.....                                      | 148 |
| 4.10.3 Querying Content Moderation Records in Batches.....                                    | 150 |
| 4.11 Cloud Decompression.....   | 153 |
| 4.11.1 Listing Directories in a Compressed Package.....                                       | 153 |
| 4.12 Batch Task Operations.....   | 156 |
| 4.12.1 Listing Batch Tasks.....   | 156 |

|  |     |
|--|-----|
| 4.12.2 Creating a Batch Task.....                                | 161 |
| 4.12.3 Querying Details About a Batch Task.....                  | 166 |
| 4.12.4 Cancelling a Batch Task.....                              | 171 |
| 4.13 Basic Task Operations.....                                  | 174 |
| 4.13.1 Creating a Task.....                                      | 174 |
| 4.13.2 Listing Tasks.....  | 177 |
| 4.13.3 Obtaining Task Details.....                               | 180 |
| 4.13.4 Obtains the information about the handover recipient..... | 182 |
| 4.13.5 Queries the task result.....                              | 184 |
| 4.14 File List Query.....  | 187 |
| 4.14.1 Listing Files in the Individual Space.....                | 187 |
| 4.14.2 Listing Files in a Group or Department Space.....         | 196 |
| 4.15 File Management.....  | 206 |
| 4.15.1 Obtaining File Details.....                               | 206 |
| 4.15.2 Adding a File Directory.....                              | 213 |
| 4.15.3 Creating File Metadata.....                               | 217 |
| 4.15.4 Obtains the upload link.....                              | 223 |
| 4.15.5 Checking Whether File Upload Is Completed.....            | 229 |
| 4.15.6 Obtaining Download Links.....                             | 231 |
| 4.15.7 Renaming a File.....                                      | 234 |
| 4.15.8 Clearing the Recycle Bin.....                             | 237 |
| 4.15.9 Retrieving Files Using Search Engine Capabilities.....    | 239 |
| 4.15.10 Collecting Folder Statistics.....                        | 255 |
| 4.15.11 Obtaining the Full Name and ID Paths of a File.....      | 257 |
| 4.16 File Favorites.....   | 259 |
| 4.16.1 Adding Files to Favorites.....                            | 259 |
| 4.16.2 Listing Files in Favorites.....                           | 262 |
| 4.17 Sharing Management - Shared by You.....                     | 273 |
| 4.17.1 Sharing a File.....                                       | 273 |
| 4.17.2 Listing Files Shared by You.....                          | 276 |
| 4.17.3 Obtaining Sharing Details.....                            | 281 |
| 4.17.4 Modifying Sharing Settings.....                           | 284 |
| 4.17.5 Stopping Sharing Files.....                               | 288 |
| 4.18 Sharing Management - Shared with You.....                   | 290 |
| 4.18.1 Listing Files Shared with You.....                        | 290 |
| 4.18.2 Obtain Sharing Details.....                               | 294 |
| 4.18.3 Removing Yourself from Shared Files.....                  | 297 |
| 4.19 Sharing Management - Access Links.....                      | 299 |
| 4.19.1 Accessing a Sharing Link.....                             | 299 |
| 4.19.2 Obtaining Sharing Information.....                        | 301 |
| 4.19.3 Verifying a Sharing Access Code.....                      | 303 |
| 4.19.4 Listing Files Shared with You.....                        | 305 |

|   |            |
|---|------------|
| 4.19.5 Downloading a File.....  | 310        |
| 4.19.6 Creating an Asynchronous Sharing Task.....   | 312        |
| 4.19.7 Querying an Asynchronous Task.....   | 314        |
| 4.20 Collaboration Portal.....  | 317        |
| 4.20.1 Listing Related Files.....   | 317        |
| 4.20.2 Listing Recently Visited Files.....  | 322        |
| 4.21 Message Notifications.....   | 326        |
| 4.21.1 Obtaining the Number of Unread Messages.....   | 326        |
| 4.21.2 Listing Messages.....  | 328        |
| 4.21.3 Marking Messages as Read in Batches.....   | 330        |
| 4.21.4 Batch Message Deletion.....  | 332        |
| 4.21.5 Modify message status (marks all unread messages as read or deletes all messages)..... | 334        |
| 4.22 Refined Authorization.....   | 336        |
| 4.22.1 Obtaining the User Permissions List.....   | 336        |
| 4.22.2 Updating Permissions in Batches.....   | 341        |
| 4.22.3 Querying Initial Permissions of a Member.....  | 345        |
| <b>5 Appendixes.....</b>  | <b>349</b> |
| 5.1 Status Codes.....   | 349        |
| 5.2 Error Codes.....  | 349        |

# 1

## Before You Start

---

### Overview

KooDrive is an online service provided by Huawei Cloud for government and enterprise customers. It provides functions such as data storage, access, synchronization, management, and collaboration. It is a one-stop digital content center for enterprises and enables efficient knowledge collaboration.

This document describes how to use application programming interfaces (APIs) to perform operations on KooDrive, such as adding file directories, obtaining file details, and renaming files. For details about all supported operations, see [API Overview](#).

If you plan to access KooDrive through an API, ensure that you are familiar with KooDrive concepts. For details, see [Service Overview](#).

### API Calling

KooDrive supports Representational State Transfer (REST) APIs, allowing you to call APIs using HTTPS. For details about API calling, see [Calling APIs](#).

### Endpoints

An endpoint is the request address for calling an API. Endpoints vary depending on services and regions. Currently, KooDrive is deployed only in the **AP-Singapore** region, and the endpoint is [intl.myhuaweicloud-koodrive.com](http://intl.myhuaweicloud-koodrive.com).

### Constraints

None

### Concepts

- Account

An account is created upon successful registration with the cloud system. The account has full access permissions for all of its cloud services and resources. It can be used to reset user passwords and grant user permissions. The account is a payment entity and should not be directly used to perform routine management. For security purposes, create Identity and Access

Management (IAM) users and grant them permissions for routine management.

- User

A KooDrive user is created by the tenant administrator (also called system administrator) in the **KooDrive service plane**. After a KooDrive user signs in to the service system, an Access-Token (AT) is generated. The AT is used for verification and authentication of subsequent API calling.

- Region

Regions are divided based on geographical location and network latency. Public services, such as Elastic Cloud Server (ECS), Elastic Volume Service (EVS), Object Storage Service (OBS), Virtual Private Cloud (VPC), Elastic IP (EIP), and Image Management Service (IMS), are shared within the same region. Regions are classified into universal regions and dedicated regions. A universal region provides universal cloud services for common tenants. A dedicated region provides specific services for specific tenants.

For details, see [Region and AZ](#).

- AZ

An AZ contains one or more physical data centers. Each AZ has independent cooling, fire extinguishing, moisture-proof, and electricity facilities. Within an AZ, computing, network, storage, and other resources are logically divided into multiple clusters. AZs within a region are interconnected using high-speed optical fibers to support cross-AZ high-availability systems.

# 2 API Overview

**Table 2-1** describes the KooDrive APIs.

**Table 2-1** API overview

| Type   | Description  |
|--|--|
| <a href="#"><b>Department Management</b></a> | Manage departments, including creating, modifying, deleting, and querying a department.  |
| <a href="#"><b>User Management</b></a>       | Manage users, including creating, modifying, deleting, and querying a user.              |
| <a href="#"><b>Space Management</b></a>      | Manage spaces, including creating, modifying, deleting, and querying a space.            |
| <a href="#"><b>Group Management</b></a>      | Manage groups, including creating and deleting a user group.                             |
| <a href="#"><b>Session Management</b></a>    | Manage sessions, including session creation and update, sign-in, and sign-out.           |
| <a href="#"><b>Service Subscription</b></a>  | Obtain the subscription status of the management and control service.                    |
| <a href="#"><b>Enterprise Settings</b></a>   | Set the time for deleting expired compressed packages generated during package download. |
| <a href="#"><b>Other APIs</b></a>            | Obtain the JS-SDK.   |
| <a href="#"><b>Refined Authorization</b></a> | Obtain the user permissions list and update permissions in batches.                      |
| <a href="#"><b>Permissions Templates</b></a> | Create and edit permissions templates.   |
| <a href="#"><b>File Moderation</b></a>       | Provide APIs for querying the review list and adding content review records in batches.  |
| <a href="#"><b>Cloud Decompression</b></a>   | List compressed package directories.   |

| Type   | Description   |
|--|---|
| <a href="#">Batch Task Operations</a>                | Manage batch tasks, including creating a batch task, canceling a batch task, and listing batch tasks.                   |
| <a href="#">Basic Task Operations</a>                | Create tasks and obtain the task list.  |
| <a href="#">File List Query</a>                      | List files in the individual space and department space.  |
| <a href="#">File Management</a>                      | Manage files, including obtaining details about a file, adding a file directory, uploading a file, and renaming a file. |
| <a href="#">File Favorites</a>                       | Manage files in favorites, including adding files to favorites and listing files in favorites.                          |
| <a href="#">Sharing Management - Shared by You</a>   | Manage files shared by you, including sharing a file, obtaining sharing details, and modifying sharing.                 |
| <a href="#">Sharing Management - Shared with You</a> | Manage files shared with you, including obtaining sharing details and removing yourself from shared files.              |
| <a href="#">Sharing Management - Access Links</a>    | Manage access links, including obtaining sharing details and verifying a sharing code.                                  |
| <a href="#">Collaboration Portal</a>                 | Query files related to you and files that you recently visited.   |
| <a href="#">Message Notifications</a>                | Query and obtain unread messages, message lists, and delete messages in batches.  |

# 3 Calling APIs

## 3.1 Making an API Request

This section describes the structure of a REST API request, and uses the KooDrive API for processing files as an example to demonstrate how to call an API.

### Request URI

A request URI is in the following format:

**{URI-scheme}://{Endpoint}/{resource-path}?{query-string}**

Although a request URI is included in the request header, most programming languages or frameworks require the request URI to be transmitted separately.

**Table 3-1** URI parameters

| Parameter     | Description   |
|---------------|---|
| URI-scheme    | Protocol used to transmit requests. All KooDrive APIs use HTTPS.  |
| Endpoint      | Domain name or IP address of the server bearing the REST service. The endpoint varies between services in different regions. Currently, KooDrive is deployed only in the <b>AP-Singapore</b> region, and the endpoint is <b>intl.myhuaweicloud-koodrive.com</b> .                                       |
| resource-path | Access path of an API. Obtain the path from the URI of an API. For example, the <b>resource-path</b> of the API used to create a batch task is <b>/koodrive/ose/v1/jobs</b> .   |
| query-string  | This optional parameter is used to query the data of a parameter. Ensure that a question mark (?) is included before each query parameter that is in the format of <i>Parameter name=Parameter value</i> . For example, <b>?limit=10</b> indicates that a maximum of 10 data records will be displayed. |

For example, to create a batch task in the **AP-Singapore** region, obtain the endpoint of KooDrive ([intl.myhuaweicloud-koodrive.com](https://intl.myhuaweicloud-koodrive.com)) for this region and the **resource-path** (`/koodrive/ose/v1/jobs`) in the URI of the API used to create a batch task. Then, construct the URI as follows:

```
https://intl.myhuaweicloud-koodrive.com/koodrive/ose/v1/jobs
```

## Request Methods

The HTTP protocol defines the following request methods that can be used to send a request to the server:

**Table 3-2** HTTP methods

| Method | Description   |
|--------|---|
| GET    | Request the server to return specified resources.                         |
| POST   | Request the server to add resources or perform special operations.        |
| DELETE | Request the server to delete specified resources, for example, an object. |
| PUT    | Request the server to update specified resources.                         |

For example, in the case of the API used to create a batch task, the request method is POST. The request is as follows:

```
POST https://intl.myhuaweicloud-koodrive.com/koodrive/ose/v1/jobs
```

## Request Header

- **Content-Type**: (optional) request body type or format. The default value is **application/json**. Other values of this field will be provided for specific APIs if any.
- **Authorization**: authentication.

Request header example:

```
POST https://intl.myhuaweicloud-koodrive.com/koodrive/ose/v1/jobs
Content-Type: application/json
Authorization: xxx
```

## Request Body

The body of a request is often sent in a structured format as specified in the **Content-Type** header field. The request body transfers content except the request header.

The request body varies between APIs. Some APIs do not require the request body, such as the APIs requested using the GET and DELETE methods.

For the API used to process files, an example of the request body is as follows:

```
{  
    "taskType":1  
    "actionType":101  
    "dstContainerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"  
    "taskInfo": {  
        "srcContainerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"  
        "newFilePath": "Fm9UdqBNTAQDos6l1xPlFnIqXJg2-UdqA"  
        "fileInfo": [  
            {  
                "fileId": "FuZmQ66CF0DdpKRG1Y29lwajbq04Nhwu3"  
            }  
        ]  
    }  
}
```

If all data required for the API request is available, you can send the request to call the API through [curl](#), [Postman](#), or coding.

## 3.2 Authentication

Currently, KooDrive uses token-based authentication. App-based authentication is also provided to directly call KooDrive APIs.

Requests are authenticated using a token.

### Constraints

A token is valid for 20 minutes. If an API is called within the validity period of the token, the validity period is reset. If no operation is performed within the validity period, the token becomes invalid.

Ensure that the token is valid when you use it. Using a token that will soon expire may cause API calling failures.

The authorization validity period is 15 minutes. Currently, [Session Management](#) and [Other APIs](#) do not support app-based authentication.

### Token-based Authentication

A token specifies temporary permissions in a computer system. During API authentication using a token, the token is added to requests to get permissions for calling the API.

A token is obtained from the cookies after you log in to the service frontend. As shown in [Figure 3-1](#), the value of **Authorization** is the AT to be obtained.

**Figure 3-1** Obtaining a token

The screenshot shows the Chrome DevTools Application tab. On the left, there's a tree view with 'Application' expanded, showing 'Manifest', 'Service workers', and 'Storage'. Under 'Storage', 'Local storage', 'Session storage', 'IndexedDB', and 'Cookies' are listed; 'Cookies' is expanded, and 'https:' is selected. On the right, a table has 'Name' and 'Value' columns. One row shows 'Authorization' with a blurred 'Value' field.

After a token is obtained, the **Authorization** header field must be added to requests to specify the token when calling other APIs. For example, if the token is **ABCDEFJ....**, **Authorization: ABCDEFJ....** can be added to a request as follows:

```
POST https://intl.myhuaweicloud-koodrive.com/koodrive/ose/v1/files/batch
Content-Type: application/json
Authorization: xxx
```

## App-based Authentication

You can use the app-based authentication generation rule provided by KooDrive to obtain the authentication and add the authentication to the request header.

Example:

```
Authorization: HMAC-SHA256
AppId=a378331eca141163119eb602adb67b7802cc79cd33ba44c7d2fe61d1586c96a1,SignedHeaders=host;x-
date;x-user-id,Signature=bd355f202be40f95bf9510fd7bd48ad711a7d144c01df07d515ee0fbf3a47416
X-User-Id: 1505084218764547200
Host: 10.32.45.165
X-Date: 20240909T033325Z
```

## 3.3 Response

### Status Code

After sending a request, you will receive a response, including a status code, response header, and response body.

A status code is a group of digits, ranging from 1xx to 5xx. It indicates the status of a request. For more information, see [Status Codes](#).

For example, if status code **0** is returned for calling the API used to process files, the request is successful.

### Response Header

Similar to a request, a response also has a header, for example, **Content-Type**.

[Figure 3-2](#) shows the response header of the API used to process files.

**Figure 3-2 Response header**

| Body | Cookies | Headers (2)      | Test Results                    |
|------|---------|------------------|---------------------------------|
| Key  |         |                  | Value                           |
|      |         | Content-Type ⓘ   | application/json; charset=utf-8 |
|      |         | content-length ⓘ | 127                             |

## Response Body

The body of a response is often returned in structured format as specified in the **Content-Type** header field. The response body transfers content except the response header.

The following is part of the response body for the API used to process files.

```
{  
    "data": "1309243162258308352"  
    "code": 0,  
    "msg": "success"  
}
```

If an error occurs during API calling, an error code and a message will be displayed. The following shows an error response body.

```
{  
    "code": 13000201,  
    "msg": "inner server invoke failure"  
}
```

In the response body, **code** is an error code, and **msg** provides information about the error.

# 4 API

## 4.1 Department Management

### 4.1.1 Listing Departments

#### Function

List sub-departments under an organization or department. Only the top-level sub-departments are returned. To query sub-department of the lowest level, use the caller to perform recursive query.

#### URI

GET /koodrive/ose/v1/departmentList

**Table 4-1** Query Parameters

| Parameter    | Mandatory | Type   | Description   |
|--------------|-----------|--------|---|
| departmentId | No        | String | Department ID. If no value is passed, the root department ID is used. |
| keyWord      | No        | String | Search keyword. You can use <b>name</b> as the search criterion.      |

## Request Parameters

**Table 4-2** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

Status code: 200

**Table 4-3** Response body parameters

| Parameter | Type    | Description           |
|-----------|---------|-----------------------|
| code      | Integer | Response code.        |
| msg       | String  | Response information. |

| Parameter | Type   | Description      |
|-----------|--|------------------|
| list      | Array of<br><b>departmentInfo</b><br>objects | Department list. |

**Table 4-4** departmentInfo

| Parameter | Type    | Description                              |
|-----------|---------|--|
| code      | Integer | Response code.                           |
| msg       | String  | Response information.                    |
| id        | String  | Department ID.                           |
| orgId     | String  | ID of the organization created in OrgID. |
| deptId    | String  | ID of the department created in OrgID.   |
| parentId  | String  | ID of the parent department in KooDrive. |
| name      | String  | Department name.                         |
| tenantId  | String  | Tenant ID.                               |

## Example Requests

Lists sub-departments under department **1245640257345455489**.

```
GET /koodrive/ose/v1/departmentList?departmentId=1245640257345455489
```

```
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

Returns the list of sub-departments under an organization or department.

```
{
  "list": [
    {
      "id": "1248723349513736065",
      "orgId": "9190086000001210958",
      "deptId": "b06f091567064db9a1f6a7dc8d08e8a7",
      "parentId": "1245640257345455489",
      "name": "sub11rt",
      "tenantId": "40086000004871666"
    },
    {
      "id": "1252924812435692416",
      "orgId": "9190086000001210958",
      "deptId": "f63c3008420c4c55b3963b6191096e2e",
      "parentId": "1245640257345455489",
      "name": "1234666",
      "tenantId": "40086000004871666"
    }
  ]
}
```

```
    },
    "code" : 0,
    "msg" : "success"
}
```

## Status Codes

| Status Code | Description  |
|-------------|--|
| 200         | Returns the list of sub-departments under an organization or department. |

## 4.1.2 Querying a Department

### Function

Query the information about a department.

### URI

GET /koodrive/ose/v1/departments/{department\_id}

**Table 4-5** Path Parameters

| Parameter     | Mandatory | Type   | Description    |
|---------------|-----------|--------|----------------|
| department_id | Yes       | String | Department ID. |

### Request Parameters

**Table 4-6** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| X-Traceid | No        | String | Message log trace ID. The value contains 58 bits.  |
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |
| X-User-Id | Yes       | String | User ID, which is used for app authentication.   |
| X-Date    | Yes       | String | Date, which is used for app authentication.  |
| Host      | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

Status code: 200

**Table 4-7** Response body parameters

| Parameter | Type    | Description                              |
|-----------|---------|--|
| code      | Integer | Response code.                           |
| msg       | String  | Response information.                    |
| id        | String  | Department ID.                           |
| orgId     | String  | ID of the organization created in OrgID. |
| deptId    | String  | ID of the department created in OrgID.   |
| parentId  | String  | ID of the parent department in KooDrive. |
| name      | String  | Department name.                         |
| tenantId  | String  | Tenant ID.                               |

## Example Requests

Queries information about department **1319678187126486144**.

GET /koodrive/ose/v1/departments/1319678187126486144

Authorization:Bearer+10f88\*\*\*\*\*4791e9ff

## Example Responses

**Status code: 200**

Department information.

```
{  
    "id" : "1319678187126486144",  
    "orgId" : "9190086000001210958",  
    "deptId" : "a4fd0d798f5344ccac2c695646ef66d3",  
    "parentId" : "1245640257345455489",  
    "name" : "test16",  
    "tenantId" : "40086000004871666",  
    "code" : 0,  
    "msg" : "success"  
}
```

## Status Codes

| Status Code | Description             |
|-------------|-------------------------|
| 200         | Department information. |

## 4.1.3 Creating a Department

### Function

Create a department and allocate a space to the department.

### URI

POST /koodrive/ose/v1/departments

## Request Parameters

**Table 4-8** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-9** Request body parameters

| Parameter | Mandatory | Type   | Description           |
|-----------|-----------|--------|-----------------------|
| name      | Yes       | String | Department name.      |
| parentId  | Yes       | String | Parent department ID. |

## Response Parameters

Status code: 200

**Table 4-10** Response body parameters

| Parameter | Type            | Description       |
|-----------|-----------------|-------------------|
| data      | DeptData object | Message body.     |
| code      | Integer         | Information code. |
| msg       | String          | Information.      |

**Table 4-11** DeptData

| Parameter | Type   | Description    |
|-----------|--------|----------------|
| id        | String | Department ID. |

## Example Requests

Creates a department named **test16** under department whose ID is **1245640257345455489**.

```
POST /koodrive/ose/v1/departments
Authorization: Bearer+10f88*****4791e9ff
{
  "name": "test16",
  "parentId": "1245640257345455489"
}
```

## Example Responses

### Status code: 200

Department creation result.

```
{
  "data": {
    "id": "String"
  }
  "code": 0,
  "msg": "success"
}
```

## Status Codes

| Status Code | Description                 |
|-------------|-----------------------------|
| 200         | Department creation result. |

## 4.1.4 Modifying a Department

### Function

Modify the information about a department (including the team space).

### URI

PUT /koodrive/ose/v1/departments/{department\_id}

**Table 4-12** Path Parameters

| Parameter     | Mandatory | Type   | Description    |
|---------------|-----------|--------|----------------|
| department_id | Yes       | String | Department ID. |

### Request Parameters

**Table 4-13** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| X-Date    | Yes       | String | Date, which is used for app authentication.    |
| Host      | Yes       | String | Address, which is used for app authentication. |

**Table 4-14** Request body parameters

| Parameter | Mandatory | Type   | Description           |
|-----------|-----------|--------|-----------------------|
| name      | Yes       | String | Department name.      |
| parentId  | Yes       | String | Parent department ID. |

## Response Parameters

**Status code: 200**

**Table 4-15** Response body parameters

| Parameter | Type    | Description    |
|-----------|---------|----------------|
| code      | Integer | Error code.    |
| msg       | String  | Error message. |

## Example Requests

Modifies the information about the department **1319678187126486144**.

```
PUT /koodrive/ose/v1/departments/1319678187126486144
```

```
Authorization:Bearer+10f88*****4791e9ff
```

```
{  
    "name" : "test16",  
    "parentId" : "1243696974704704000"  
}
```

## Example Responses

**Status code: 200**

Basic response. Only the error code and error information are returned.

```
{  
    "code" : 0,  
    "msg" : "success"  
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Basic response. Only the error code and error information are returned. |

## 4.1.5 Deleting a Department

### Function

Delete a department and its team space.

### URI

DELETE /koodrive/ose/v1/departments/{department\_id}

**Table 4-16** Path Parameters

| Parameter     | Mandatory | Type   | Description    |
|---------------|-----------|--------|----------------|
| department_id | Yes       | String | Department ID. |

### Request Parameters

**Table 4-17** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |
| X-User-Id | Yes       | String | User ID, which is used for app authentication.   |
| X-Date    | Yes       | String | Date, which is used for app authentication.  |
| Host      | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-18** Response body parameters

| Parameter | Type    | Description    |
|-----------|---------|----------------|
| code      | Integer | Error code.    |
| msg       | String  | Error message. |

## Example Requests

Deletes department **1319678187126486144**.

```
DELETE /koodrive/ose/v1/departments/1319678187126486144
```

```
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

Basic response. Only the error code and error information are returned.

```
{  
  "code" : 0,  
  "msg" : "success"  
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Basic response. Only the error code and error information are returned. |

## 4.2 User Management

### 4.2.1 Querying Information About a User

#### Function

Query the information about a user.

#### URI

GET /koodrive/ose/v1/users/{user\_id}

**Table 4-19** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| user_id   | Yes       | String | User ID.    |

#### Request Parameters

**Table 4-20** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |
| X-User-Id | Yes       | String | User ID, which is used for app authentication.   |
| X-Date    | Yes       | String | Date, which is used for app authentication.  |
| Host      | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

Status code: 200

**Table 4-21** Response body parameters

| Parameter | Type                            | Description       |
|-----------|---------------------------------|-------------------|
| code      | Integer                         | Response code.    |
| msg       | String                          | Response message. |
| data      | <a href="#">userInfo</a> object | User information. |

**Table 4-22** userInfo

| Parameter | Type    | Description          |
|-----------|---------|----------------------|
| name      | String  | Name.                |
| userId    | String  | User ID.             |
| deptId    | String  | Department ID.       |
| deptName  | String  | Department name.     |
| mobile    | String  | Mobile number.       |
| role      | Integer | Role.                |
| status    | Integer | Status.              |
| id        | String  | Third-party user ID. |

## Example Requests

Queries the information about user **1316083732377070977**.

```
GET /koodrive/ose/v1/users/1316083732377070977
```

```
Authorization: Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

User information.

```
{  
    "data": {  
        "id": "1316083732377070977",  
        "orgId": "9190086000001210958",  
        "userId": "1008600000293202821",  
        "deptId": "1243693141656107521",  
        "deptName": "newDept",  
        "mobile": "0086181****8439",  
        "name": "Sam",  
        "role": 1,  
        "status": 0,  
    },  
    "code": 0,  
    "msg": "success"  
}
```

## Status Codes

| Status Code | Description       |
|-------------|-------------------|
| 200         | User information. |

## 4.2.2 Listing Users

### Function

List users in a department. If **department\_id** is not specified, the user list of the organization to which the current sign-in user belongs is queried.

### URI

```
GET /koodrive/ose/v1/userList
```

**Table 4-23** Query Parameters

| Parameter | Mandatory | Type   | Description    |
|-----------|-----------|--------|----------------|
| deptId    | No        | String | Department ID. |

| Parameter | Mandatory | Type    | Description  |
|-----------|-----------|---------|--|
| isDirect  | No        | Boolean | Whether the user belongs to the root department. Default value: false. |
| offset    | Yes       | String  | Offset. Minimum value: 0.  |
| limit     | Yes       | String  | Maximum number of records to be returned. Value range: 1 to 100.       |
| keyWord   | No        | String  | Search keyword. You can use <b>name</b> as the search criterion.       |

## Request Parameters

**Table 4-24** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| Host      | Yes       | String | Address, which is used for app authentication. |

## Response Parameters

Status code: 200

**Table 4-25** Response body parameters

| Parameter | Type                                      | Description       |
|-----------|---|-------------------|
| code      | Integer                                   | Response code.    |
| msg       | String                                    | Response message. |
| list      | Array of <a href="#">userInfo</a> objects | User information. |
| total     | Integer                                   | Total number.     |

**Table 4-26** userInfo

| Parameter | Type    | Description          |
|-----------|---------|----------------------|
| name      | String  | Name.                |
| userId    | String  | User ID.             |
| deptId    | String  | Department ID.       |
| deptName  | String  | Department name.     |
| mobile    | String  | Mobile number.       |
| role      | Integer | Role.                |
| status    | Integer | Status.              |
| id        | String  | Third-party user ID. |

## Example Requests

Lists 10 users in department **1243693141656107521**, starting from the first user.

```
GET /koodrive/ose/v1/userList?deptId=1243693141656107521&offset=0&limit=10
```

```
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

User list information.

```
{  
  "list": [  
    {  
      "id": "1316083732377071000VW5TYWZlSW50ZWdlcg==",  
      "userId": "1008600000293202821",  
      "deptId": "1243693141656107500VW5TYWZlSW50ZWdlcg==",  
      "deptName": "newDept",  
      "mobile": "0086181****8439",  
      "name": "Sam",  
      "role": 1,  
      "status": 0,  
    },  
    {  
      "id": "1315783852559526700VW5TYWZlSW50ZWdlcg==",  
      "userId": "1008600000292227464",  
      "deptId": "1243693141656107500VW5TYWZlSW50ZWdlcg==",  
      "deptName": "newDept",  
      "mobile": "0086151****8338",  
      "name": "test123",  
      "role": 1,  
      "status": 2  
    }  
  "total": 2,  
  "code": 0,  
  "msg": "success"  
}
```

## Status Codes

| Status Code | Description            |
|-------------|------------------------|
| 200         | User list information. |

## 4.2.3 Counting Members in an Organization or Department

### Function

Count members in a department or organization. If **dept\_id** is not specified, the number of all members in the current organization is queried.

### URI

GET /koodrive/ose/v1/users/count

**Table 4-27** Query Parameters

| Parameter | Mandatory | Type   | Description    |
|-----------|-----------|--------|----------------|
| deptId    | No        | String | Department ID. |

## Request Parameters

**Table 4-28** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-29** Response body parameters

| Parameter | Type    | Description              |
|-----------|---------|--------------------------|
| code      | Integer | Response code.           |
| msg       | String  | Response information.    |
| total     | Integer | Total number of records. |

## Example Requests

Counts members in the current organization.

```
GET /koodrive/ose/v1/users/count?deptId=  
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

Total number of members.

```
{  
    "total" : 218,  
    "code" : 0,  
    "msg" : "success"  
}
```

## Status Codes

| Status Code | Description              |
|-------------|--------------------------|
| 200         | Total number of members. |

## 4.2.4 Creating a User

### Function

Create a user.

### URI

POST /koodrive/ose/v1/users

## Request Parameters

**Table 4-30** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |

**Table 4-31** Request body parameters

| Parameter         | Mandatory | Type                            | Description                             |
|-------------------|-----------|---------------------------------|---|
| userId            | Yes       | String                          | User ID.                                |
| modifyUserInfoReq | Yes       | <b>modifyUserInfoReq</b> object | Request for modifying user information. |

**Table 4-32** modifyUserInfoReq

| Parameter | Mandatory | Type   | Description    |
|-----------|-----------|--------|----------------|
| deptId    | No        | String | Department ID. |
| role      | No        | String | Role.          |

## Response Parameters

**Status code: 200**

**Table 4-33** Response body parameters

| Parameter | Type            | Description       |
|-----------|-----------------|-------------------|
| data      | DeptData object | Message body.     |
| code      | Integer         | Information code. |
| msg       | String          | Information.      |

**Table 4-34** DeptData

| Parameter | Type   | Description    |
|-----------|--------|----------------|
| id        | String | Department ID. |

## Example Requests

Creates a user whose **userId** in OrgID is **1008600000029937613**.

```
POST /koodrive/ose/v1/users
Authorization: Bearer+10f88*****4791e9ff
{
  "userId": "1008600000029937613"
}
```

## Example Responses

**Status code: 200**

Basic response. Only the error code and error information are returned.

```
{
  "code": 0,
  "msg": "success"
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Basic response. Only the error code and error information are returned. |

## 4.2.5 Modifying a User

### Function

Modify the information about a user.

### URI

PUT /koodrive/ose/v1/users/{user\_id}

**Table 4-35** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| user_id   | Yes       | String | User ID.    |

### Request Parameters

**Table 4-36** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| Host      | Yes       | String | Address, which is used for app authentication.   |
| X-Traceid | No        | String | Message log trace ID. The value contains 58 bits.  |
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |

**Table 4-37** Request body parameters

| Parameter | Mandatory | Type    | Description  |
|-----------|-----------|---------|--|
| deptId    | No        | Long    | KooDrive department ID.  |
| role      | No        | Integer | Role. <ul style="list-style-type: none"><li>• <b>0:</b> department administrator.</li><li>• <b>1:</b> common user.</li><li>• <b>2:</b> system administrator.</li><li>• <b>5:</b> member with the management permissions.</li></ul> |
| status    | No        | Integer | User account status. <ul style="list-style-type: none"><li>• <b>0:</b> enabled (can be used for sign-in).</li><li>• <b>1:</b> disabled (cannot be used for sign-in).</li></ul>   |

## Response Parameters

**Status code: 200**

**Table 4-38** Response body parameters

| Parameter | Type    | Description    |
|-----------|---------|----------------|
| code      | Integer | Error code.    |
| msg       | String  | Error message. |

## Example Requests

Modifies the information about user **1289290865663084545**.

```
PUT /koodrive/ose/v1/users/1289290865663084545
```

```
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

Basic response. Only the error code and error information are returned.

```
{  
  "code" : 0,  
  "msg" : "success"  
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Basic response. Only the error code and error information are returned. |

## 4.2.6 Deleting a User

### Function

Delete a user and the corresponding resources.

### URI

```
DELETE /koodrive/ose/v1/users/{user_id}
```

**Table 4-39** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| user_id   | Yes       | String | User ID.    |

## Request Parameters

**Table 4-40** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-41** Response body parameters

| Parameter | Type    | Description    |
|-----------|---------|----------------|
| code      | Integer | Error code.    |
| msg       | String  | Error message. |

## Example Requests

Deletes user **1244780780316557312** and the corresponding resources.

```
DELETE /koodrive/ose/v1/users/1244780780316557312
```

```
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

Basic response. Only the error code and error information are returned.

```
{  
  "code" : 0,  
  "msg" : "success"  
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Basic response. Only the error code and error information are returned. |

## 4.2.7 Querying the Mobile Number of a User

### Function

Query the mobile number of a user.

### URI

```
GET /koodrive/ose/v1/users/mobile/{user_id}
```

**Table 4-42** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| user_id   | Yes       | String | User ID.    |

## Request Parameters

**Table 4-43** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-44** Response body parameters

| Parameter | Type    | Description       |
|-----------|---------|-------------------|
| code      | Integer | Response code.    |
| msg       | String  | Response message. |
| mobile    | String  | Mobile number.    |

## Example Requests

Obtain the mobile number of user 1244780780316557312.

```
GET /koodrive/ose/v1/users/mobile/1244780780316557312
```

```
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

Mobile number of a user.

```
{  
    "mobile": "178*****",  
    "code": 0,  
    "msg": "success"  
}
```

## Status Codes

| Status Code | Description              |
|-------------|--------------------------|
| 200         | Mobile number of a user. |

## 4.2.8 Pre-verification API

### Function

Pre-verification API.

### URI

```
POST /koodrive/ose/v1/users/batchimport/preverify
```

## Request Parameters

**Table 4-45** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |

**Table 4-46** Request body parameters

| Parameter | Mandatory | Type                                   | Description                    |
|-----------|-----------|--|--------------------------------|
| curDeptId | Yes       | Integer                                | ID of the selected department. |
| users     | Yes       | Array of <b>ImportUserInfo</b> objects | Imported user information.     |

**Table 4-47** ImportUserInfo

| Parameter      | Mandatory | Type   | Description                    |
|----------------|-----------|--------|--------------------------------|
| targetDeptName | No        | String | Name of the target department. |

| Parameter          | Mandatory | Type    | Description   |
|--------------------|-----------|---------|---|
| personalCapacity   | Yes       | Integer | Capacity of the allocated individual space. If <b>isAllocateCapacity</b> is set to <b>false</b> , the value is <b>0</b> . |
| isAllocateCapacity | Yes       | Boolean | Whether the individual space is allocated.  |

## Response Parameters

Status code: 200

**Table 4-48** Response body parameters

| Parameter | Type  | Description       |
|-----------|---|-------------------|
| code      | Integer   | Response code.    |
| msg       | String  | Response message. |
| data      | Array of <a href="#">ImportUserVerifyResult</a> objects | Result.           |

**Table 4-49** ImportUserVerifyResult

| Parameter | Type    | Description                           |
|-----------|---------|---------------------------------------|
| isSuccess | Integer | Import result (successful or failed). |
| reason    | String  | Failure reason.                       |

## Example Requests

Performing Pre-verification

```
/koodrive/ose/v1/users/batchimport/preverify

{
  "curDeptId": 1575416580416769793
  "users": [
    {
      "targetDeptName": "Dept",
      "personalCapacity": 10,
      "isAllocateCapacity": true
    }
  ]
}
```

## Example Responses

### Status code: 200

Response body of the pre-verification API.

```
{  
    "code": 0,  
    "msg": "Successful",  
    "data": [  
        {"isSuccess": 0}  
    ]  
}
```

## Status Codes

| Status Code | Description                                |
|-------------|--|
| 200         | Response body of the pre-verification API. |

## 4.2.9 Change the maximum number of OrgID users.

### Function

Change the maximum number of OrgID users.

### URI

POST /koodrive/ose/v1/user/expand/{orgId}

**Table 4-50** Path Parameters

| Parameter | Mandatory | Type   | Description       |
|-----------|-----------|--------|-------------------|
| orgId     | Yes       | String | User ID in OrgID. |

## Request Parameters

**Table 4-51** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permissions. When an API is called, the token is added to the request header to obtain the operation permissions. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |

## Response Parameters

**Status code: 200**

**Table 4-52** Response body parameters

| Parameter | Type    | Description    |
|-----------|---------|----------------|
| code      | Integer | Error code.    |
| msg       | String  | Error message. |

## Example Requests

Change the maximum number of OrgID users.

```
POST /koodrive/ose/v1/user/expand/{orgId}
```

```
Authorization: Bearer+10f88*****4791e9ff
```

## Example Responses

### Status code: 200

Response to the request for changing the maximum number of OrgID users.

```
{  
  "code" : 0,  
  "msg" : "OK"  
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Response to the request for changing the maximum number of OrgID users. |

## 4.3 Space Management

### 4.3.1 Listing Departments Spaces

#### Function

List department spaces.

#### URI

GET /koodrive/ose/v1/space/departmentList

**Table 4-53** Query Parameters

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| offset    | Yes       | String | Offset. Minimum value: 0.  |
| limit     | Yes       | String | Maximum number of records to be returned. Value range: 1 to 100.                         |
| keyWord   | No        | String | Search keyword. You can use <b>name</b> and <b>administrator</b> as the search criteria. |

## Request Parameters

**Table 4-54** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-55** Response body parameters

| Parameter | Type    | Description              |
|-----------|---------|--------------------------|
| code      | Integer | Error code.              |
| msg       | String  | Error message.           |
| total     | String  | Total number of records. |

| Parameter   | Type  | Description                   |
|-------------|---|-------------------------------|
| departments | Array of<br><a href="#">departmentSpaceInfo</a> objects | Department space information. |

**Table 4-56** departmentSpaceInfo

| Parameter | Type   | Description                              |
|-----------|--------|--|
| id        | String | Department ID.                           |
| parentId  | String | ID of the parent department in KooDrive. |
| name      | String | Department name.                         |
| tenantId  | String | Tenant ID.                               |

## Example Requests

Lists the spaces of up to 10 departments.

```
GET /koodrive/cloudfile/v1/space/departmentList?offset=0&limit=10
```

```
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

Department space list.

```
{  
    "total" : 364,  
    "departments" : [ {  
        "tenantId" : "40086000004871666",  
        "creator" : "369528171409614001",  
        "createTime" : "2023-11-14T20:39:06.000Z",  
        "modifier" : "369528171409614001",  
        "updateTime" : "2023-12-26T11:40:08.000Z",  
        "ownerId" : "1289173668999530369",  
        "status" : 0,  
        "capacity" : 1,  
        "spaceUsed" : 654777,  
        "containerId" : "IAADfsBFC06WtAtuAb7e92cde625843cfb7f4ceba802e0b",  
        "bizRootFileId" : "DEUI7pa0C24ArootIAADfsBFC06WtAtuAb7e92cde625843cfb7f4ceba802e0b",  
        "bizSboxFileId" : "DEUI7pa0C24AsboxIAADfsBFC06WtAtuAb7e92cde625843cfb7f4ceba802e0b",  
        "id" : "1289173668999530369",  
        "parentId" : "1289171275545118721",  
        "name" : "Department 1699953477584",  
        "userNum" : 1  
    }, {  
        "tenantId" : "40086000004871666",  
        "id" : "1289173650183882753",  
        "parentId" : "1289171275545118721",  
        "name" : "Department 1699953475619"  
    }, {  
        "tenantId" : "40086000004871666",  
        "id" : "1289173650183882753",  
        "parentId" : "1289171275545118721",  
        "name" : "Department 1699953475619"  
    } ]  
}
```

```
"tenantId" : "40086000004871666",
"id" : "1289173631275960193",
"parentId" : "1289171275545118721",
"name" : "Department 1699953473454"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173612200265729",
"parentId" : "1289171275545118721",
"name" : "Department 1699953470101"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173593258788737",
"parentId" : "1289171275545118721",
"name" : "Department 169995346896"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173574392809473",
"parentId" : "1289171275545118721",
"name" : "Department 1699953466973"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173555140953985",
"parentId" : "1289171275545118721",
"name" : "Department 1699953463567"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173535931041664",
"parentId" : "1289171275545118721",
"name" : "Department 1699953461741"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173517174114305",
"parentId" : "1289171275545118721",
"name" : "Department 1699953459399"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173498115196929",
"parentId" : "1289171275545118721",
"name" : "Department 1699953457405"
} ],
"code" : 0,
"msg" : "OK"
}
```

## Status Codes

| Status Code | Description            |
|-------------|------------------------|
| 200         | Department space list. |

## 4.3.2 Querying Space Information

### Function

Query the space information of an individual, department, or group.

### URI

GET /koodrive/ose/v1/space/{owner\_id}

**Table 4-57** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| owner_id  | Yes       | String | Owner ID.   |

**Table 4-58** Query Parameters

| Parameter   | Mandatory | Type   | Description   |
|-------------|-----------|--------|---|
| type        | Yes       | String | Space type. <ul style="list-style-type: none"><li>• 0: department.</li><li>• 1: individual.</li><li>• 2: group.</li></ul> |
| containerId | No        | String | When <b>type</b> is set to 1 and there are multiple individual spaces, <b>containerId</b> must be specified.              |

## Request Parameters

**Table 4-59** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |
| X-User-Id | Yes       | String | User ID, which is used for app authentication.   |
| X-Date    | Yes       | String | Date, which is used for app authentication.  |
| Host      | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

Status code: 200

**Table 4-60** Response body parameters

| Parameter | Type                             | Description        |
|-----------|----------------------------------|--------------------|
| code      | Integer                          | Response code.     |
| msg       | String                           | Response message.  |
| data      | <a href="#">SpaceInfo object</a> | Space information. |

**Table 4-61** SpaceInfo

| Parameter | Type   | Description  |
|-----------|--------|--|
| type      | String | Owner type. <b>0</b> : department space; <b>1</b> : individual space; <b>2</b> : group space.  |
| status    | String | Status.  |
| ownerId   | String | Space owner.<br>1. For a department space, the department ID is returned.<br>2. For an individual space, the user ID is returned.<br>3. For a group space, the group ID is returned. |

| Parameter     | Type   | Description  |
|---------------|--------|--|
| containerId   | String | Space ID.  |
| bizRootFileId | String | ID of the service root directory, which stores unencrypted common files. |
| bizSboxFileId | String | ID of the service safe directory, which stores encrypted files.          |
| capacity      | String | Space size.  |
| spaceUsed     | String | Size of the used space.  |
| tenantId      | String | Tenant ID.   |
| creator       | String | Creator.   |
| createTime    | String | Creation time.   |
| modifier      | String | Modifier ID.   |
| updateTime    | String | Update time.   |
| rootFileId    | String | ID of the space root directory.  |

## Example Requests

Queries the space information of user **369528171409614001**.

```
GET /koodrive/ose/v1/space/369528171409614001?type=1
```

```
Authorization: Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

Space information.

```
{  
    "data" : {  
        "tenantId" : "40086000004871666",  
        "creator" : "369528171409614001",  
        "createTime" : "2023-11-07T20:36:35.000Z",  
        "modifier" : "369528171409614001",  
        "updateTime" : "2023-12-26T11:40:07.000Z",  
        "ownerId" : "369528171409614001",  
        "type" : 1,  
        "status" : 0,  
        "capacity" : 800,  
        "spaceUsed" : 91966408,  
        "containerId" : "IAADfsBFC06WtAtuA315074383680425b8aa9a130cba2d4",  
        "rootFileId" : "HFFdlb642fU51JWKAULP6mwUVc8oDNKbO",  
        "bizRootFileId" : "DEUI7pa0C24ArootIAADfsBFC06WtAtuA315074383680425b8aa9a130cba2d4",  
        "bizSboxFileId" : "DEUI7pa0C24AsboxIAADfsBFC06WtAtuA315074383680425b8aa9a130cba2d4"  
    },  
    "code" : 0,  
    "msg" : "OK"  
}
```

## Status Codes

| Status Code | Description        |
|-------------|--------------------|
| 200         | Space information. |

### 4.3.3 Creating a Space for a Department or Individual

#### Function

Create a space for a department or individual.

#### URI

POST /koodrive/ose/v1/space/{owner\_id}

**Table 4-62** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| owner_id  | Yes       | String | Owner ID.   |

#### Request Parameters

**Table 4-63** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| Host      | Yes       | String | Address, which is used for app authentication.   |
| X-Traceid | No        | String | Message log trace ID. The value contains 58 bits.  |
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |

**Table 4-64** Request body parameters

| Parameter    | Mandatory | Type                          | Description   |
|--------------|-----------|-------------------------------|---|
| capacity     | Yes       | String                        | Requested space size.   |
| type         | Yes       | Integer                       | Space type. <ul style="list-style-type: none"><li>• <b>0</b>: department.</li><li>• <b>1</b>: individual.</li></ul> |
| capabilities | No        | <b>Capabilities</b><br>object | User permissions.   |

**Table 4-65** Capabilities

| Parameter              | Mandatory | Type    | Description   |
|------------------------|-----------|---------|---|
| addChildNodePermission | Yes       | Boolean | Permission to create a file or folder. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| copyPermission         | Yes       | Boolean | Copy permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                       |

| Parameter                 | Mandatory | Type    | Description   |
|---------------------------|-----------|---------|---|
| deletePermission          | Yes       | Boolean | Delete permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| downloadPermission        | Yes       | Boolean | Download permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.         |
| editPermission            | Yes       | Boolean | Edit permissions. <b>true</b> : granted; <b>false</b> : not granted (editing is not supported.)   |
| listChildNodePermission   | Yes       | Boolean | Permission to view the list. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| removeChildNodePermission | Yes       | Boolean | Move permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.             |
| renameFilePermission      | Yes       | Boolean | Rename permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| shareFilePermission       | Yes       | Boolean | Share permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.            |
| uploadPermission          | Yes       | Boolean | Upload permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| viewPermission            | Yes       | Boolean | Preview permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.          |

## Response Parameters

Status code: 200

**Table 4-66** Response body parameters

| Parameter | Type                                       | Description        |
|-----------|--|--------------------|
| data      | <a href="#">createSpaceRspln fo object</a> | Space information. |
| code      | Integer                                    | Information code.  |
| msg       | String                                     | Information.       |

**Table 4-67** createSpaceRsplnfo

| Parameter     | Type    | Description  |
|---------------|---------|--|
| type          | Integer | Owner type. <b>0</b> : department space; <b>1</b> : individual space; <b>2</b> : group space.  |
| status        | Integer | Status.  |
| ownerId       | String  | Space owner.<br>1. For a department space, the department ID is returned.<br>2. For an individual space, the user ID is returned.<br>3. For a group space, the group ID is returned. |
| containerId   | String  | Space ID.  |
| bizRootFileId | String  | ID of the service root directory, which stores unencrypted common files.   |
| bizSboxFileId | String  | ID of the service safe directory, which stores encrypted files.  |
| capacity      | Integer | Space size.  |
| spaceUsed     | Integer | Size of the used space.  |
| tenantId      | String  | Tenant ID.   |
| creator       | String  | Creator.   |
| modifier      | String  | Modifier ID.   |
| rootFileId    | String  | ID of the space root directory.  |
| operatorId    | Integer | Operator ID.   |

## Example Requests

Creates a space of 1 GB for department **1289173650183882753**.

```
POST /koodrive/ose/v1/space/1289173650183882753
Authorization: Bearer+10f88*****4791e9ff
{
  "capacity": 1,
  "type": 0
}
```

## Example Responses

**Status code: 200**

Basic response. Only the error code and error information are returned.

```
{
  "code": 0,
  "msg": "OK"
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Basic response. Only the error code and error information are returned. |

## 4.3.4 Modifying Space Information

### Function

Modify the space information of a department or individual.

### URI

PUT /koodrive/ose/v1/space/{owner\_id}

**Table 4-68** Path Parameters

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| owner_id  | Yes       | String | Space owner. The value can be a department or a user ID. |

## Request Parameters

**Table 4-69** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-70** Request body parameters

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| status    | No        | String | Space status. <ul style="list-style-type: none"><li>● <b>0:</b> normal (A space has been allocated and can be used.)</li><li>● <b>1:</b> disabled (A space has been allocated, but the used space cannot be accessed.)</li></ul> |

| Parameter | Mandatory | Type    | Description   |
|-----------|-----------|---------|---|
| capacity  | No        | String  | Capacity.   |
| type      | Yes       | Integer | Space type. <ul style="list-style-type: none"><li>• 0: department.</li><li>• 1: individual.</li></ul> |

## Response Parameters

**Status code: 200**

**Table 4-71** Response body parameters

| Parameter | Type    | Description    |
|-----------|---------|----------------|
| code      | Integer | Error code.    |
| msg       | String  | Error message. |

## Example Requests

Updates the space size of department **1289173650183882753** to 1 GB.

```
PUT /koodrive/ose/v1/space/1289173650183882753
Authorization: Bearer+10f88*****4791e9ff
{
  "status": 1,
  "type": 0
}
```

## Example Responses

**Status code: 200**

Basic response. Only the error code and error information are returned.

```
{
  "code": 0,
  "msg": "OK"
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Basic response. Only the error code and error information are returned. |

## 4.3.5 Deleting a Space

### Function

Delete a space.

### URI

DELETE /koodrive/ose/v1/space/{owner\_id}

**Table 4-72** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| owner_id  | Yes       | String | Owner ID.   |

**Table 4-73** Query Parameters

| Parameter   | Mandatory | Type    | Description  |
|-------------|-----------|---------|--|
| type        | Yes       | Integer | Space type. <ul style="list-style-type: none"><li>• 0: department.</li><li>• 1: individual.</li></ul>                              |
| containerId | No        | String  | Space ID. Multiple individual spaces exist during third-party integration. This parameter must be specified during space deletion. |

### Request Parameters

**Table 4-74** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| X-Traceid | No        | String | Message log trace ID. The value contains 58 bits.  |
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |
| X-User-Id | Yes       | String | User ID, which is used for app authentication.   |
| X-Date    | Yes       | String | Date, which is used for app authentication.  |
| Host      | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

Status code: 200

**Table 4-75** Response body parameters

| Parameter | Type    | Description    |
|-----------|---------|----------------|
| code      | Integer | Error code.    |
| msg       | String  | Error message. |

## Example Requests

Deletes the space of department **1289173650183882753**.

```
DELETE /koodrive/ose/v1/space/1289173650183882753?type=0
```

```
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

Status code: 200

Basic response. Only the error code and error information are returned.

```
{  
    "code" : 0,  
    "msg" : "OK"  
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Basic response. Only the error code and error information are returned. |

## 4.3.6 Querying Space Details by Space ID

### Function

Query space details by space ID. This API applies only to machine-to-machine calling.

### URI

GET /koodrive/ose/v1/space/container/{container\_id}

**Table 4-76** Path Parameters

| Parameter    | Mandatory | Type   | Description |
|--------------|-----------|--------|-------------|
| container_id | Yes       | String | Space ID.   |

### Request Parameters

**Table 4-77** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |
| X-User-Id | Yes       | String | User ID, which is used for app authentication.   |
| X-Date    | Yes       | String | Date, which is used for app authentication.  |
| Host      | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-78** Response body parameters

| Parameter | Type                             | Description        |
|-----------|----------------------------------|--------------------|
| code      | Integer                          | Response code.     |
| msg       | String                           | Response message.  |
| data      | <a href="#">SpaceInfo object</a> | Space information. |

**Table 4-79** SpaceInfo

| Parameter | Type   | Description  |
|-----------|--------|--|
| type      | String | Owner type. <b>0</b> : department space; <b>1</b> : individual space; <b>2</b> : group space.  |
| status    | String | Status.  |
| ownerId   | String | Space owner.<br>1. For a department space, the department ID is returned.<br>2. For an individual space, the user ID is returned.<br>3. For a group space, the group ID is returned. |

| Parameter     | Type   | Description  |
|---------------|--------|--|
| containerId   | String | Space ID.  |
| bizRootFileId | String | ID of the service root directory, which stores unencrypted common files. |
| bizSboxFileId | String | ID of the service safe directory, which stores encrypted files.          |
| capacity      | String | Space size.  |
| spaceUsed     | String | Size of the used space.  |
| tenantId      | String | Tenant ID.   |
| creator       | String | Creator.   |
| createTime    | String | Creation time.   |
| modifier      | String | Modifier ID.   |
| updateTime    | String | Update time.   |
| rootFileId    | String | ID of the space root directory.  |

## Example Requests

Queries details about a space whose ID is  
IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b.

```
GET /koodrive/ose/v1/space/container/IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b
```

```
Authorization: Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

Space details.

```
{  
    "data" : {  
        "tenantId" : "40086000004871666",  
        "creator" : "369528171409614001",  
        "createTime" : "2023-11-14T20:39:06.000Z",  
        "modifier" : "369528171409614001",  
        "updateTime" : "2023-12-27T03:41:49.000Z",  
        "ownerId" : "1289173668999530369",  
        "type" : 0,  
        "status" : 0,  
        "capacity" : 1,  
        "spaceUsed" : 654777,  
        "containerId" : "IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b",  
        "rootFileId" : "HFaETMi24qYqOM5KQmpNY2ATjKJeAunIK",  
        "bizRootFileId" : "DEU17pa0C24ArootIAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b",  
        "bizSboxFileId" : "DEU17pa0C24AsboxIAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b"  
    },  
    "code" : 0,  
    "msg" : "OK"  
}
```

## Status Codes

| Status Code | Description    |
|-------------|----------------|
| 200         | Space details. |

## 4.3.7 Querying Information About a Team Space

### Function

Query information about a team space.

### URI

GET /koodrive/ose/v1/space/teamList

**Table 4-80** Query Parameters

| Parameter | Mandatory | Type    | Description  |
|-----------|-----------|---------|--|
| offset    | Yes       | Integer | Offset. Minimum value: 0.  |
| limit     | Yes       | Integer | Maximum number of records to be returned. Value range: 1 to 100.                     |
| keyWord   | No        | String  | Search keyword. You can use <b>name</b> and <b>ownerName</b> as the search criteria. |
| teamType  | No        | Integer | Team type.   |

## Request Parameters

**Table 4-81** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-82** Response body parameters

| Parameter | Type    | Description              |
|-----------|---------|--------------------------|
| code      | Integer | Error code.              |
| msg       | String  | Error message.           |
| total     | String  | Total number of records. |

| Parameter | Type   | Description      |
|-----------|--|------------------|
| teams     | Array of<br><a href="#">TeamSpaceInfo</a><br>objects | Team space list. |

**Table 4-83** TeamSpaceInfo

| Parameter     | Type    | Description  |
|---------------|---------|--|
| id            | String  | ID of the department, user group, or group to which the space belongs. |
| status        | Integer | Space status.  |
| capacity      | Integer | Space size.  |
| spaceUsed     | String  | Size of the used space.  |
| containerId   | String  | Space ID.  |
| userNum       | Integer | Number of users.   |
| ownerId       | String  | Owner ID.  |
| ownerName     | String  | Owner name.  |
| tenantId      | String  | Tenant ID.   |
| creator       | String  | Creator.   |
| createTime    | String  | Creation time.   |
| modifier      | String  | Modifier ID.   |
| updateTime    | String  | Update time.   |
| bizRootFileId | String  | ID of the space root directory.  |
| bizSboxFileId | String  | ID of the space safe directory.  |
| iconUrl       | String  | Icon link.   |
| top           | Integer | Whether this record is pinned to top.                                  |
| role          | Integer | Role.  |
| type          | Integer | Space type. 0: department space; 1: personal space; 2: group space     |
| teamType      | Integer | Team type.   |

## Example Requests

Queries the space information of team **369528171409614001**.

```
GET /koodrive/ose/v1/space/teamList  
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

### Status code: 200

Space information.

```
{  
  "data" : {  
    "tenantId" : "40086000004871666",  
    "creator" : "369528171409614001",  
    "createTime" : "2023-11-07T20:36:35.000Z",  
    "modifier" : "369528171409614001",  
    "updateTime" : "2023-12-26T11:40:07.000Z",  
    "ownerId" : "369528171409614001",  
    "type" : 1,  
    "status" : 0,  
    "capacity" : 800,  
    "spaceUsed" : 91966408,  
    "containerId" : "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",  
    "rootFileId" : "HFFdlb642fU51JWKAULP6mwUVc8oDNKbO",  
    "bizRootFileId" : "DEUI7pa0C24ArootIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",  
    "bizSboxFileId" : "DEUI7pa0C24AsboxIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"  
  },  
  "code" : 0,  
  "msg" : "OK"  
}
```

## Status Codes

| Status Code | Description        |
|-------------|--------------------|
| 200         | Space information. |

## 4.3.8 Creating a Group Space

### Function

Create a group space.

### URI

```
POST /koodrive/ose/v1/space/group
```

## Request Parameters

**Table 4-84** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-85** Request body parameters

| Parameter     | Mandatory | Type                                  | Description                             |
|---------------|-----------|---------------------------------------|---|
| name          | Yes       | String                                | Space name.                             |
| iconUrl       | No        | String                                | Space profile picture.                  |
| capacity      | No        | Integer                               | Space size.                             |
| addGroupUsers | Yes       | Array of <b>AddGroupUsers</b> objects | List of users to be added to the group. |

**Table 4-86** AddGroupUsers

| Parameter    | Mandatory | Type                | Description  |
|--------------|-----------|---------------------|--|
| userId       | Yes       | String              | User ID.   |
| template     | Yes       | Long                | Permissions template ID. For a custom template, the value is -1. |
| capabilities | No        | Capabilities object | Permissions value (transferred when a template is customized).   |

**Table 4-87** Capabilities

| Parameter               | Mandatory | Type    | Description   |
|-------------------------|-----------|---------|---|
| addChildNodePermission  | Yes       | Boolean | Permission to create a file or folder. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| copyPermission          | Yes       | Boolean | Copy permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                       |
| deletePermission        | Yes       | Boolean | Delete permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                     |
| downloadPermission      | Yes       | Boolean | Download permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                   |
| editPermission          | Yes       | Boolean | Edit permissions. <b>true</b> : granted; <b>false</b> : not granted (editing is not supported.)   |
| listChildNodePermission | Yes       | Boolean | Permission to view the list. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |

| Parameter                 | Mandatory | Type    | Description  |
|---------------------------|-----------|---------|--|
| removeChildNodePermission | Yes       | Boolean | Move permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.    |
| renameFilePermission      | Yes       | Boolean | Rename permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.  |
| shareFilePermission       | Yes       | Boolean | Share permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.   |
| uploadPermission          | Yes       | Boolean | Upload permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.  |
| viewPermission            | Yes       | Boolean | Preview permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |

## Response Parameters

Status code: 200

**Table 4-88** Response body parameters

| Parameter  | Type             | Description        |
|------------|------------------|--------------------|
| code       | Integer          | Error code.        |
| msg        | String           | Error description. |
| failedList | Array of strings | Failure list.      |
| id         | String           | Space ID.          |

## Example Requests

Creates a space of 20 GB for a group.

```
POST /koodrive/ose/v1/space/  
Authorization:Bearer+10f88*****4791e9ff  
{  
    "name": "API Demo",  
    "capacity": 20,  
    "iconUrl": "1",  
    "userIds": []  
}
```

## Example Responses

### Status code: 200

Basic response. Only the error code and error information are returned.

```
{  
    "id" : "xxx",  
    "failedList" : [ ],  
    "code" : 0,  
    "msg" : "OK"  
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Basic response. Only the error code and error information are returned. |

## 4.3.9 Dismissing a Team Space

### Function

Dismiss a team space.

### URI

DELETE /koodrive/ose/v1/space/group/{group\_id}

**Table 4-89** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| group_id  | Yes       | String | Group ID.   |

## Request Parameters

**Table 4-90** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-91** Response body parameters

| Parameter | Type    | Description    |
|-----------|---------|----------------|
| code      | Integer | Error code.    |
| msg       | String  | Error message. |

## Example Requests

Deletes the space of department **1289173650183882753**.

```
DELETE /koodrive/ose/v1/space/1289173650183882753?type=2
```

```
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

Basic response. Only the error code and error information are returned.

```
{  
  "code" : 0,  
  "msg" : "OK"  
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Basic response. Only the error code and error information are returned. |

## 4.3.10 Listing Group Spaces in an Enterprise

### Function

List group spaces in an enterprise. (Only tenant administrators have the permission to call this API.)

### URI

```
GET /koodrive/ose/v1/space/groupList
```

**Table 4-92** Query Parameters

| Parameter | Mandatory | Type    | Description  |
|-----------|-----------|---------|--|
| offset    | Yes       | Integer | Offset. Minimum value: 0.  |
| limit     | Yes       | Integer | Maximum number of records to be returned. Value range: 1 to 100.                     |
| keyWord   | No        | String  | Search keyword. You can use <b>name</b> and <b>ownerName</b> as the search criteria. |

## Request Parameters

**Table 4-93** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-94** Response body parameters

| Parameter | Type    | Description              |
|-----------|---------|--------------------------|
| code      | Integer | Error code.              |
| msg       | String  | Error message.           |
| total     | Integer | Total number of records. |

| Parameter        | Type  | Description               |
|------------------|---|---------------------------|
| groupsTotal      | Integer   | Total number of groups.   |
| groupsMax        | Integer   | Maximum number of groups. |
| assignedCapacity | String  | Assigned capacity.        |
| maxCapacity      | String  | Maximum capacity.         |
| groups           | Array of<br><a href="#">GroupSpaceInfo</a><br>objects | Group space information.  |

**Table 4-95** GroupSpaceInfo

| Parameter     | Type    | Description  |
|---------------|---------|--|
| id            | String  | ID of the department, user group, or group to which the space belongs. |
| status        | Integer | Space status.  |
| capacity      | Integer | Space size.  |
| spaceUsed     | String  | Size of the used space.  |
| containerId   | String  | Space ID.  |
| userNum       | Integer | Number of users.   |
| ownerId       | String  | Owner ID.  |
| ownerName     | String  | Owner name.  |
| tenantId      | String  | Tenant ID.   |
| creator       | String  | Creator.   |
| createTime    | String  | Creation time.   |
| modifier      | String  | Modifier ID.   |
| updateTime    | String  | Update time.   |
| bizRootFileId | String  | ID of the space root directory.  |
| bizSboxFileId | String  | ID of the space safe directory.  |
| iconUrl       | String  | Icon link.   |
| name          | String  | Space name.  |

## Example Requests

Lists group spaces in an enterprise.

```
GET /koodrive/ose/v1/space/groupList?offset=0&limit=10
```

```
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

### Status code: 200

Information about the group space list.

```
{
  "total": 1,
  "groupsTotal": 1,
  "groupsMax": 500,
  "assignedCapacity": 100,
  "maxCapacity": 2048,
  "groups": [
    {
      "tenantId": "cad444830661464d9da88784a96d960c",
      "creator": "1410172329509745795",
      "createTime": "2024-05-10T01:46:22.000Z",
      "modifier": "1410172329509745795",
      "updateTime": "2024-05-10T02:27:23.000Z",
      "ownerId": "1410172329509745795",
      "status": 0,
      "capacity": 20,
      "spaceUsed": 0,
      "containerId": "IAAE49hOR8LulgAAA1417956457328121729",
      "bizRootFileId": "DE5Hwu6WAAArootIAAE49hOR8LulgAAA1417956457328121729",
      "bizSboxFileId": "DE5Hwu6WAAAAsboxIAAE49hOR8LulgAAA1417956457328121729",
      "id": "1417956457311344513",
      "groupName": "api01",
      "iconUrl": "1",
      "ownerName": "hid99522477",
      "userNum": 1
    },
    "code" : 0,
    "msg": "Successful"
}
```

## Status Codes

| Status Code | Description                             |
|-------------|---|
| 200         | Information about the group space list. |

## 4.3.11 Listing User Spaces

### Function

List user spaces in a department. If **department\_id** is not specified, the user space list of the organization to which the current sign-in user belongs is queried.

### URI

```
GET /koodrive/ose/v1/space/userList
```

**Table 4-96** Query Parameters

| Parameter   | Mandatory | Type    | Description  |
|-------------|-----------|---------|--|
| deptId      | No        | String  | Department ID. If this parameter is not specified, the user space list of the organization is queried if the current user is a system administrator, and the user space list of the department is queried if the current user is a department administrator. |
| isDirect    | No        | Boolean | Whether the user belongs to the root department. Default value: false.   |
| offset      | Yes       | String  | Offset. Minimum value: 0.  |
| limit       | Yes       | String  | Maximum number of records to be returned. Value range: 1 to 100.   |
| keyWord     | No        | String  | Search keyword. You can use <b>name</b> and <b>mobile</b> as the search criteria.  |
| spaceStatus | No        | String  | Space status.  |

## Request Parameters

**Table 4-97** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | 1. The format is <b>Bearer {app_access_token}</b> . The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using <b>clientid</b> and <b>clientSecret</b> obtained during application creation.<br>2. The application is the KooDrive server. |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en_us</b> indicates English (United States). |
| X-User-Id | Yes       | String | User ID, which is used for app authentication.   |
| X-Date    | Yes       | String | Date, which is used for app authentication.  |
| Host      | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

Status code: 200

**Table 4-98** Response body parameters

| Parameter | Type   | Description              |
|-----------|--|--------------------------|
| code      | Integer  | Response code.           |
| msg       | String   | Response message.        |
| users     | Array of <a href="#">userSpaceInfo</a> objects | User space information.  |
| total     | String   | Total number of records. |

**Table 4-99** userSpaceInfo

| Parameter   | Type    | Description          |
|-------------|---------|----------------------|
| name        | String  | Username.            |
| deptId      | String  | Department ID.       |
| deptName    | String  | Department name.     |
| mobile      | String  | Mobile number.       |
| role        | Integer | User role.           |
| status      | Integer | User account status. |
| containerId | String  | Space ID.            |

| Parameter   | Type   | Description             |
|-------------|--------|-------------------------|
| capacity    | Long   | Individual space size.  |
| spaceUsed   | Long   | Size of the used space. |
| tenantId    | String | Tenant ID.              |
| id          | String | User space ID.          |
| userId      | String | User ID.                |
| spaceStatus | String | Space status.           |

## Example Requests

Lists user spaces in a department.

```
GET /koodrive/ose/v1/space/userList?deptId=&isDirect=&offset=0&limit=100&keyWord
```

```
Authorization: Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

Information about the user space list.

```
{
  "total": 1,
  "users": [ {
    "tenantId": "cad444830661464d9da88784a96d960c",
    "status": 0,
    "capacity": 10,
    "spaceUsed": 189,
    "containerId": "IAAE49hOR8LulgAAA1410765425310141185",
    "id": "1410765364786334592",
    "role": 1,
    "name": "xx",
    "deptName": "xxx",
    "userId": "1008600000445114904",
    "deptId": 141018381147566000,
    "mobile": "0086147****6900",
    "spaceStatus": "0"
  }],
  "code": 0,
  "msg": "OK"
}
```

## Status Codes

| Status Code | Description                            |
|-------------|--|
| 200         | Information about the user space list. |

## 4.3.12 Obtains space information.

### Function

Obtains space information. (A user may have multiple spaces. This API is used to obtain the space information list.)

### URI

GET /koodrive/ose/v2/space/{owner\_id}

**Table 4-100** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| owner_id  | Yes       | String | User ID.    |

**Table 4-101** Query Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| type      | No        | String | Space type. |

### Request Parameters

**Table 4-102** Request header parameters

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| X-User-Id | Yes       | String | User ID, which is used for app authentication. |
| X-Date    | Yes       | String | Date, which is used for app authentication.    |
| Host      | Yes       | String | Address, which is used for app authentication. |

| Parameter     | Mandatory | Type   | Description   |
|---------------|-----------|--------|---|
| Authorization | Yes       | String | <ol style="list-style-type: none"><li>1. The format is Bearer {app_access_token}. The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using clientId and clientSecret obtained during application creation.</li><li>2. The application is the KooDrive server.</li></ol> |

## Response Parameters

Status code: 200

**Table 4-103** Response body parameters

| Parameter | Type   | Description       |
|-----------|--|-------------------|
| code      | Integer  | Information code. |
| msg       | String   | Information.      |
| data      | Array of<br><a href="#">SpaceInfoV2</a><br>objects | Space list.       |

**Table 4-104** SpaceInfoV2

| Parameter   | Type   | Description   |
|-------------|--------|---|
| type        | String | Owner type. <b>0</b> : department space; <b>1</b> : individual space; <b>2</b> : group space.   |
| status      | String | Status.   |
| ownerId     | String | Space owner. <ol style="list-style-type: none"><li>1. For a department space, the department ID is returned.</li><li>2. For an individual space, the user ID is returned.</li><li>3. For a group space, the group ID is returned.</li></ol> |
| containerId | String | Space ID.   |

| Parameter     | Type   | Description  |
|---------------|--------|--|
| bizRootFileId | String | ID of the service root directory, which stores unencrypted common files. |
| bizSboxFileId | String | ID of the service safe directory, which stores encrypted files.          |
| capacity      | String | Space size.  |
| spaceUsed     | String | Size of the used space.  |
| tenantId      | String | Tenant ID.   |
| creator       | String | Creator.   |
| modifier      | String | Modifier ID.   |
| rootFileId    | String | ID of the space root directory.  |

## Example Requests

Obtains space information. (A user may have multiple spaces. This API is used to obtain the space information list.)

```
GET /koodrive/ose/v2/space/12156464
```

```
Authorization: HMAC-SHA256
AppId=a378331eca141163119eb602adb67b7802cc79cd33ba44c7d2fe61d1586c96a1,SignedHeaders=host;x-
date;x-user-id,Signature=bd35f202be40f95bf9510fd7bd48ad711a7d144c01df07d515ee0fbf3a47416
X-User-Id: 1505084218764547200
Host: 10.32.45.165
X-Date: 20240909T033325Z
```

## Example Responses

**Status code: 200**

Response to the request for obtaining space information.

```
{
  "data": {
    "tenantId": "0929b397a3424384b32cf8f96d9f35e4",
    "creator": "1465814559892958208",
    "modifier": "1465814559892958208",
    "ownerId": 1517293342025685000,
    "type": 1,
    "status": 0,
    "capacity": 1,
    "spaceUsed": 0,
    "containerId": "IAACk0hRXpq9DAWkA1537830432752646913",
    "rootFileId": "HFNKeRWAXJU4itbTKM7OQCFOojoMDWV",
    "bizRootFileId": "DFFemr0MBaQAr0otIAACk0hRXpq9DAWkA1537830432752646913",
    "bizSboxFileId": "DFFemr0MBaQAsboxIAACk0hRXpq9DAWkA1537830432752646913",
    "operatorId": 1465814559892958200,
    "name": "121-2"
  },
  "code": 0,
  "msg": "Operation successful."
}
```

## Status Codes

| Status Code | Description  |
|-------------|--|
| 200         | Response to the request for obtaining space information. |

# 4.4 Group Management

## 4.4.1 Creating a User Group

### Function

Create a user group.

### URI

POST /koodrive/ose/v1/usergroups

### Request Parameters

**Table 4-105** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| X-User-Id | Yes       | String | User ID, which is used for app authentication. |
| X-Date    | Yes       | String | Date, which is used for app authentication.    |
| Host      | Yes       | String | Address, which is used for app authentication. |

**Table 4-106** Request body parameters

| Parameter  | Mandatory | Type    | Description  |
|------------|-----------|---------|--|
| groupName  | Yes       | String  | User group name, which cannot contain <> :"*?/\ or emojis. The value cannot be two periods (..), a period (.), or a space. |
| sourceType | Yes       | Integer | User group type.   |

## Response Parameters

Status code: 200

**Table 4-107** Response body parameters

| Parameter | Type    | Description       |
|-----------|---------|-------------------|
| id        | String  | Group ID.         |
| code      | Integer | Information code. |
| msg       | String  | Information.      |

## Example Requests

Creates a group.

```
POST /koodrive/ose/v1/usergroups
Authorization:Bearer+c69b0f40334782d560bb154032cf22ef43d671843c4ffbad
{
  "capacity": 1,
  "type": 0
}
```

## Example Responses

### Status code: 200

Basic response. For a successful response, the ID of the created user group is returned. For an error response, only the error code and error information are returned.

```
{  
  "code" : 0,  
  "msg" : "OK",  
  "id" : "xxx"  
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Basic response. For a successful response, the ID of the created user group is returned. For an error response, only the error code and error information are returned. |

## 4.4.2 Listing User Groups

### Function

List groups that a user joins.

### URI

GET /koodrive/ose/v1/usergroups

**Table 4-108** Query Parameters

| Parameter  | Mandatory | Type    | Description   |
|------------|-----------|---------|---|
| pageSize   | Yes       | Integer | Number of records to be returned on each page. Default and maximum value: 100. It is possible that partial or empty result pages are returned before the end of the result list has been reached. |
| pageCursor | Yes       | String  | Current page cursor, which is obtained from <b>nextCursor</b> of the previous response.   |
| groupName  | No        | String  | User group name.  |
| sourceType | Yes       | Integer | User group type.  |

## Request Parameters

**Table 4-109** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

Status code: 200

**Table 4-110** Response body parameters

| Parameter | Type    | Description           |
|-----------|---------|-----------------------|
| code      | Integer | Response code.        |
| msg       | String  | Response information. |

| Parameter     | Type   | Description   |
|---------------|--|---|
| nextCursor    | String   | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| userGroupList | Array of<br><a href="#">UserGroupInfo</a><br>objects | User group information.   |
| total         | Integer  | Total number of records.  |

**Table 4-111 UserGroupInfo**

| Parameter   | Type   | Description      |
|-------------|--------|------------------|
| id          | String | User group ID.   |
| groupName   | String | User group name. |
| ownerId     | String | Creator ID.      |
| createdTime | String | Creation time.   |
| updatedTime | String | Update time.     |

## Example Requests

Lists the groups that a user joins.

```
GET /koodrive/ose/v1/usergroups
```

```
Authorization:Bearer+c69b0f40334782d560bb154032cf22ef43d671843c4ffbad
```

## Example Responses

**Status code: 200**

Group list information.

```
{
  "total" : 2,
  "userGroupList" : [ {
    "id" : "1407237551361847809",
    "groupName" : "7",
    "ownerId" : "1395476983395324033",
    "createdTime" : "2024-04-25T06:49:49.000Z",
    "updatedTime" : "2024-04-25T06:49:49.000Z"
  }, {
    "id" : "1404926806536180481",
    "groupName" : "111",
    "ownerId" : "1395476983395324033",
    "createdTime" : "2024-04-22T02:18:46.000Z",
    "updatedTime" : "2024-04-22T02:18:46.000Z"
  }],
  "code" : 0,
  "msg" : "OK"
}
```

## Status Codes

| Status Code | Description             |
|-------------|-------------------------|
| 200         | Group list information. |

## 4.4.3 Modifying Group Information

### Function

Modify group information.

### URI

PUT /koodrive/ose/v1/usergroups/{group\_id}

**Table 4-112** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| group_id  | Yes       | String | Group ID.   |

### Request Parameters

**Table 4-113** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |
| X-User-Id | Yes       | String | User ID, which is used for app authentication.   |
| X-Date    | Yes       | String | Date, which is used for app authentication.  |
| Host      | Yes       | String | Address, which is used for app authentication.   |

**Table 4-114** Request body parameters

| Parameter  | Mandatory | Type    | Description   |
|------------|-----------|---------|---|
| groupName  | Yes       | String  | User group name.  |
| userId     | No        | String  | User ID.  |
| role       | No        | String  | User group role.  |
| iconUrl    | No        | String  | Link of the group profile picture.  |
| top        | No        | String  | Whether this record is pinned to top. <b>1</b> : pinned to top. <b>0</b> : displayed in sequence. |
| sourceType | Yes       | Integer | User group type.  |

## Response Parameters

**Status code: 200**

**Table 4-115** Response body parameters

| Parameter | Type    | Description           |
|-----------|---------|-----------------------|
| code      | Integer | Response code.        |
| msg       | String  | Response information. |

## Example Requests

Updates the group information of department **1289173650183882753**.

```
PUT /koodrive/ose/v1/usergroup/1289173650183882753
Authorization:Bearer+c69b0f40334782d560bb154032cf22ef43d671843c4ffbad
{
  "groupName": "123",
  "sourceType": 0
}
```

## Example Responses

**Status code: 200**

Response after the modification is successful.

```
{
  "code": 0,
  "msg": "OK"
}
```

## Status Codes

| Status Code | Description                                    |
|-------------|--|
| 200         | Response after the modification is successful. |

## 4.4.4 Deleting a Group

### Function

Delete a group.

### URI

DELETE /koodrive/ose/v1/usergroups/{group\_id}

**Table 4-116** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| group_id  | Yes       | String | Group ID.   |

## Request Parameters

**Table 4-117** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-118** Response body parameters

| Parameter | Type    | Description    |
|-----------|---------|----------------|
| code      | Integer | Error code.    |
| msg       | String  | Error message. |

## Example Requests

Deletes group **1289173650183882753**.

```
DELETE /koodrive/ose/v1/usergroup/1289173650183882753
```

```
Authorization:Bearer+c69b0f40334782d560bb154032cf22ef43d671843c4ffbad
```

## Example Responses

**Status code: 200**

Basic response.

```
{  
  "code" : 0,  
  "msg" : "OK"  
}
```

## Status Codes

| Status Code | Description     |
|-------------|-----------------|
| 200         | Basic response. |

## 4.4.5 Listing Members in a User Group

### Function

List members in a group.

### URI

```
GET /koodrive/ose/v1/usergroups/{group_id}/members
```

**Table 4-119** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| group_id  | Yes       | String | Group ID.   |

**Table 4-120** Query Parameters

| Parameter | Mandatory | Type    | Description  |
|-----------|-----------|---------|--|
| offset    | Yes       | Integer | Offset. Minimum value: 0.  |
| limit     | Yes       | Integer | Maximum number of records to be returned. Value range: 1 to 100. |

| Parameter | Mandatory | Type   | Description   |
|-----------|-----------|--------|---|
| keyWord   | No        | String | Search keyword. You can use <b>name</b> and <b>ownerNamer</b> as the search criteria. |

## Request Parameters

**Table 4-121** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-122** Response body parameters

| Parameter            | Type                                     | Description                              |
|----------------------|--|--|
| code                 | Integer                                  | Response code.                           |
| msg                  | String                                   | Response information.                    |
| total                | Integer                                  | Total number of members in a user group. |
| userGroupMemberInfos | Array of<br><b>MemberInfo</b><br>objects | Member list.                             |

**Table 4-123** MemberInfo

| Parameter   | Type    | Description  |
|-------------|---------|--|
| userId      | String  | Member user ID.  |
| userName    | String  | Username.  |
| deptId      | String  | Department ID.   |
| deptName    | String  | Department name.   |
| mobile      | String  | Mobile number.   |
| createdTime | String  | Time when the member is added.                               |
| updatedTime | String  | Update time.   |
| role        | Integer | Role.  |
| top         | Integer | Top ID. 1: top. 0: display in sequence.<br>Default value: 0. |

## Example Requests

Lists members in group **369528171409614001**.

```
GET /koodrive/ose/v1/usergroups/369528171409614001/members
```

```
Authorization:Bearer+c69b0f40334782d560bb154032cf22ef43d671843c4ffbad
```

## Example Responses

**Status code: 200**

Group member list.

```
{
  "data": {
    "tenantId": "40086000004871666",
    "creator": "369528171409614001",
    "createTime": "2023-11-07T20:36:35.000Z",
```

```
"modifier" : "369528171409614001",
"updateTime" : "2023-12-26T11:40:07.000Z",
"ownerId" : "369528171409614001",
"type" : 1,
"status" : 0,
"capacity" : 800,
"spaceUsed" : 91966408,
"containerId" : "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
"rootFileId" : "HFFd1b642fU51JWKAUIP6mwUVc8oDNKbO",
"bizRootFileId" : "DEUI7pa0C24ArootIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
"bizSboxFileId" : "DEUI7pa0C24AsboxIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"
},
"code" : 0,
"msg" : "OK"
}
```

## Status Codes

| Status Code | Description        |
|-------------|--------------------|
| 200         | Group member list. |

## 4.4.6 Adding Members to a User Group

### Function

Add members to a user group.

### URI

POST /koodrive/ose/v1/usergroups/{group\_id}/members/batchAdd

**Table 4-124** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| group_id  | Yes       | String | Group ID.   |

## Request Parameters

**Table 4-125** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-126** Request body parameters

| Parameter     | Mandatory | Type                                 | Description                                |
|---------------|-----------|--------------------------------------|--|
| amendModRoles | Yes       | Array of <b>AmendModRole</b> objects | User permission information to be updated. |

**Table 4-127** AmendModRole

| Parameter    | Mandatory | Type                | Description  |
|--------------|-----------|---------------------|--|
| userId       | Yes       | Long                | User ID.   |
| template     | Yes       | Long                | Permission template ID. For an anonymous template, set this parameter to -1. (This parameter is optional when members are added to or deleted from a user group in batches.) |
| capabilities | No        | Capabilities object | Permission value (transferred when a template is customized).  |

**Table 4-128** Capabilities

| Parameter              | Mandatory | Type    | Description   |
|------------------------|-----------|---------|---|
| addChildNodePermission | Yes       | Boolean | Permission to create a file or folder. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| copyPermission         | Yes       | Boolean | Copy permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                       |
| deletePermission       | Yes       | Boolean | Delete permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                     |
| downloadPermission     | Yes       | Boolean | Download permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                   |
| editPermission         | Yes       | Boolean | Edit permissions. <b>true</b> : granted; <b>false</b> : not granted (editing is not supported.)   |

| Parameter                 | Mandatory | Type    | Description   |
|---------------------------|-----------|---------|---|
| listChildNodePermission   | Yes       | Boolean | Permission to view the list. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| removeChildNodePermission | Yes       | Boolean | Move permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.             |
| renameFilePermission      | Yes       | Boolean | Rename permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| shareFilePermission       | Yes       | Boolean | Share permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.            |
| uploadPermission          | Yes       | Boolean | Upload permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| viewPermission            | Yes       | Boolean | Preview permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.          |

## Response Parameters

Status code: 200

**Table 4-129** Response body parameters

| Parameter | Type    | Description   |
|-----------|---------|---|
| code      | Integer | Response code.  |
| msg       | String  | Response information.   |
| status    | Integer | Response status. <b>0</b> : all successful; <b>1</b> : partially successful; <b>2</b> : all failed. |

| Parameter  | Type             | Description           |
|------------|------------------|-----------------------|
| failedList | Array of strings | Failed response list. |

## Example Requests

Adds users to group **369528171409614001**.

```
POST /koodrive/ose/v1/usergroups/369528171409614001/members/batchAdd
Authorization:Bearer+c69b0f40334782d560bb154032cf22ef43d671843c4ffbad
{
  "userIds": ["3432423464657862424","132543141414141414"]
}
```

## Example Responses

**Status code: 200**

Response for adding users.

```
{
  "code" : 0,
  "msg" : "OK",
  "id" : "xxx"
}
```

## Status Codes

| Status Code | Description                |
|-------------|----------------------------|
| 200         | Response for adding users. |

## 4.4.7 Deleting Members from a User Group

### Function

Delete members from a user group.

### URI

```
POST /koodrive/ose/v1/usergroups/{group_id}/members/batchDelete
```

**Table 4-130** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| group_id  | Yes       | String | Group ID.   |

## Request Parameters

**Table 4-131** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-132** Request body parameters

| Parameter     | Mandatory | Type                                       | Description                  |
|---------------|-----------|--|------------------------------|
| amendModRoles | Yes       | Array of <b>AmendModRoleDelete</b> objects | List of users to be deleted. |

**Table 4-133** AmendModRoleDelete

| Parameter | Mandatory | Type | Description |
|-----------|-----------|------|-------------|
| userId    | Yes       | Long | User ID.    |

## Response Parameters

**Status code: 200**

**Table 4-134** Response body parameters

| Parameter  | Type             | Description   |
|------------|------------------|---|
| code       | Integer          | Response code.  |
| msg        | String           | Response information.   |
| status     | Integer          | Response status. <b>0</b> : all successful; <b>1</b> : partially successful; <b>2</b> : all failed. |
| failedList | Array of strings | List of IDs of failed files.  |

## Example Requests

Deletes users from group **369528171409614001**.

```
POST /koodrive/ose/v1/usergroups/369528171409614001/members/batchDelete
Authorization: Bearer+c69b0f40334782d560bb154032cf22ef43d671843c4ffbad
{
  "userIds": ["3432423464657862424", "132543141414141414"]
}
```

## Example Responses

**Status code: 200**

Response for deleting users.

```
{
  "code": 0,
  "msg": "OK",
  "id": "xxx"
}
```

## Status Codes

| Status Code | Description                  |
|-------------|------------------------------|
| 200         | Response for deleting users. |

## 4.5 Session Management

### 4.5.1 Checking Whether a User Session Is Invalid Based on Token Information

#### Function

Check whether a user session is invalid based on token information.

#### URI

GET /koodrive/ose/v1/session/auth

#### Request Parameters

**Table 4-135** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |

#### Response Parameters

**Status code: 200**

**Table 4-136** Response body parameters

| Parameter | Type               | Description       |
|-----------|--------------------|-------------------|
| code      | Integer            | Error code.       |
| msg       | String             | Error message.    |
| data      | OrgUserInfo object | User information. |

**Table 4-137** OrgUserInfo

| Parameter   | Type    | Description  |
|-------------|---------|--|
| role        | String  | Role. <ul style="list-style-type: none"><li>● 0: common administrator.</li><li>● 1: common user.</li><li>● 2: super administrator.</li></ul> |
| innerUserId | String  | Internal user ID.  |
| userName    | String  | Username.  |
| orgId       | String  | orgId  |
| orgName     | String  | Name in OrgID.   |
| tenantId    | String  | Tenant code, that is, enterprise code.   |
| userCount   | Integer | Number of users.   |
| deptId      | String  | Department ID.   |
| userId      | String  | User ID.   |

## Example Requests

Request for verifying a token.

```
GET /koodrive/ose/v1/session/auth
```

```
Authorization: Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

User information.

```
{  
  "data": {  
    "role": "2",  
    "userName": "Tenant Administrator",  
    "innerUserId": "369528171409614001",  
    "userId": "1008600000016806899",  
  }  
}
```

```
        "tenantId": "40086000004871666",
        "orgId": "9190086000001210958",
        "orgName": "KooDrive",
        "deptId": "1395496464656556464"
        "userCount": 7000
    },
    "code": 0,
    "msg": "success"
}
```

## Status Codes

| Status Code | Description       |
|-------------|-------------------|
| 200         | User information. |

## 4.5.2 Obtaining the URL of an OrgID Authorization Code for KooDrive

### Function

Obtain the URL of an OrgID authorization code for KooDrive.

### URI

GET /koodrive/ose/v1/session/authCodeURL

**Table 4-138** Query Parameters

| Parameter | Mandatory | Type   | Description           |
|-----------|-----------|--------|-----------------------|
| domain    | Yes       | String | Frontend domain name. |

### Request Parameters

**Table 4-139** Request header parameters

| Parameter | Mandatory | Type   | Description                                       |
|-----------|-----------|--------|---|
| X-Traceid | No        | String | Message log trace ID. The value contains 58 bits. |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |

## Response Parameters

**Status code: 200**

**Table 4-140** Response body parameters

| Parameter | Type    | Description             |
|-----------|---------|-------------------------|
| uri       | String  | Login address of OrgID. |
| orgIdHost | String  | Domain host of OrgID.   |
| code      | Integer | Response code.          |
| msg       | String  | Response message.       |

## Example Requests

Obtain the OrgID authorization code.

```
GET /koodrive/ose/v1/session/authCodeURL?domain=cn.myhuaweicloud-koodrive.com
```

## Example Responses

**Status code: 200**

URL of an OrgID authorization code for KooDrive.

```
{
  "uri" : "https://orgid-beta.ulangqab.huawei.com/oauth2/authorize?
response_type=code&client_id=be93d606a69a214642bf324e147af3366aef98f2cb1eb0b51bf8a27647d135b0&
scope=phone+profile+email&redirect_uri=https://kdconsole-sec.hwcloudtest.cn/cloudfile/index.html",
  "orgIdHost" : "https://orgid-beta.ulangqab.huawei.com",
  "code" : 0,
  "msg" : "success"
}
```

## Status Codes

| Status Code | Description                                      |
|-------------|--|
| 200         | URL of an OrgID authorization code for KooDrive. |

## 4.5.3 Initializing and Creating a Session

### Function

Initialize and create a session.

### URI

POST /koodrive/ose/v1/session/

### Request Parameters

**Table 4-141** Request header parameters

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| X-Traceid | No        | String | Message log trace ID. The value contains 58 bits.  |
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |

**Table 4-142** Request body parameters

| Parameter | Mandatory | Type   | Description         |
|-----------|-----------|--------|---------------------|
| code      | Yes       | String | Authorization code. |

### Response Parameters

**Status code: 200**

**Table 4-143** Response body parameters

| Parameter | Type                                     | Description                                     |
|-----------|--|---|
| code      | Integer                                  | Response code.                                  |
| msg       | String                                   | Response information.                           |
| data      | <a href="#">SessionUserDto</a><br>object | Authorization code required by the service API. |

**Table 4-144** SessionUserDto

| Parameter   | Type                                      | Description                                     |
|-------------|---|---|
| accessToken | String                                    | Authorization code required by the service API. |
| sessionId   | String                                    | Session ID.                                     |
| userId      | String                                    | User ID.  |
| userInfo    | <a href="#">SessionUserInfo</a><br>object | Enterprise-level user information.              |

**Table 4-145** SessionUserInfo

| Parameter   | Type    | Description   |
|-------------|---------|---|
| role        | String  | Role. <ul style="list-style-type: none"><li>● <b>0:</b> common administrator.</li><li>● <b>1:</b> common user.</li><li>● <b>2:</b> super administrator.</li></ul> |
| userName    | String  | Username.   |
| innerUserId | String  | Internal user ID.   |
| userId      | String  | External user ID.   |
| tenantId    | String  | Tenant code, that is, enterprise code.  |
| orgId       | String  | orgId   |
| orgName     | String  | Name in OrgID.  |
| xHwSchema   | String  | Database object set allocated to the tenant.  |
| userCount   | Integer | Number of users.  |
| deptId      | String  | Department ID.  |

## Example Requests

Request for initializing a session.

```
POST /koodrive/ose/v1/session

{
  "code" :
  "FrBMohdqj86v6sMZlFSSuG3E0_9RsDpL08BlYfNQPhvibLET266cQhDI_WczEXJOAoloKGCdqN2shKX1yfqrVci8n
  SFdMlxljNFhoffVvH93uSzloyFxK4P7yhY6fDXa",
  "domain" : "kdconsole-***_***.*****.cn:8080"
}
```

## Example Responses

**Status code: 200**

Session response information.

```
{
  "data": {
    "accessToken": "Bearer 6ebb6266dd5cdefa1d7126af2eb6173ce0a054d8ba4295be",
    "sessionId": "c17c8903e9382a0aa1b82e9d42cb82ba12760a18d6cf018d",
    "userId": "1008600000701011122",
    "userInfo": {
      "role": "2",
      "userName": "199*****04",
      "innerUserId": "1574641576007768198",
      "userId": "1008600000701011122",
      "tenantId": "28389189a7744593a59940c0d0fc451",
      "orgId": "9190086000001721760",
      "orgName": "lym09",
      "deptId": "1574641574824974465",
      "userCount": 40,
      "xhwSchema": "tenants1_liantiao"
    }
  },
  "code": 0,
  "msg": "Successful"
}
```

## Status Codes

| Status Code | Description                   |
|-------------|-------------------------------|
| 200         | Session response information. |

## 4.5.4 Refreshing a Session

### Function

Refresh a session.

### URI

POST /koodrive/ose/v1/session/refresh

## Request Parameters

**Table 4-146** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| x-session-id  | Yes       | String | Session ID.  |

## Response Parameters

**Status code: 200**

**Table 4-147** Response body parameters

| Parameter   | Type    | Description           |
|-------------|---------|-----------------------|
| code        | Integer | Response code.        |
| msg         | String  | Response information. |
| accessToken | String  | Authentication.       |

## Example Requests

Request for refreshing a session.

```
POST /koodrive/ose/v1/session/refresh
```

```
Authorization:Bearer+10f88d*****a544791e9ff  
x-session-id:b49*****ee67d90c07be
```

## Example Responses

**Status code: 200**

Session refresh result.

```
{  
    "accessToken": "Bearer+013b4daf12f4099a6eb74e2708000cb7a418409192f3e149,  
    "code": 0,  
    "msg": "success"  
}
```

## Status Codes

| Status Code | Description             |
|-------------|-------------------------|
| 200         | Session refresh result. |

## 4.5.5 Signing In and Signing Out

### Function

Clear session information when a member signs out.

### URI

GET /koodrive/ose/v1/session/logoff

### Request Parameters

**Table 4-148** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | No        | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| X-Traceid | No        | String | Message log trace ID. The value contains 58 bits.  |
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |

## Response Parameters

**Status code: 200**

**Table 4-149** Response body parameters

| Parameter | Type    | Description    |
|-----------|---------|----------------|
| code      | Integer | Error code.    |
| msg       | String  | Error message. |

## Example Requests

Sign-out request.

```
GET /koodrive/ose/v1/session/logoff
```

```
Authorization:Bearer+10f88d0*****a544791e9ff
```

## Example Responses

**Status code: 200**

Basic response. Only the error code and error information are returned.

```
{  
  "code" : 0,  
  "msg" : "success"  
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Basic response. Only the error code and error information are returned. |

## 4.6 Service Subscription

### 4.6.1 Obtaining the Subscription Status

#### Function

Obtain the subscription status of the management console service.

#### URI

GET /koodrive/ose/v1/service

#### Request Parameters

**Table 4-150** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

Status code: 200

**Table 4-151** Response body parameters

| Parameter | Type                           | Description                        |
|-----------|--------------------------------|------------------------------------|
| code      | Integer                        | Response code.                     |
| msg       | String                         | Response message.                  |
| data      | <b>ServiceStatus</b><br>object | Cloud service subscription status. |

**Table 4-152** ServiceStatus

| Parameter            | Type    | Description  |
|----------------------|---------|--|
| status               | Integer | Service status. <ul style="list-style-type: none"><li>● <b>0</b>: normal (The cloud service restores, for example, after being unfrozen.)</li><li>● <b>1</b>: frozen (Resources and data are reserved but the cloud service cannot be used.)</li></ul> |
| spaceCapacity        | Integer | Space quota.   |
| userCount            | Integer | OrgID user quota.  |
| groupSpaceSize       | Integer | Default size of the team space. <b>0</b> indicates that no space is enabled.   |
| personalSpaceSize    | Integer | Default size of the individual space. <b>0</b> indicates that no space is enabled.   |
| organizationName     | String  | Organization name.   |
| organizationId       | String  | Organization ID.   |
| rootDeptCode         | String  | Root department code generated after the organization is created in OrgID.   |
| tenantId             | String  | Tenant ID.   |
| departmentSpace-Size | Integer | Default size of the department space. <b>0</b> indicates that no space is enabled.   |
| aiAvailable          | Boolean | Whether AI is enabled.   |
| wpsAvailable         | Boolean | Whether WPS is enabled.  |
| productType          | String  | Product type.  |

| Parameter       | Type   | Description             |
|-----------------|--------|-------------------------|
| manualAuditOpen | String | Manual review switch.   |
| publicShareFlag | String | Sharing switch.         |
| aiFlag          | String | AI switch.              |
| telcomFlag      | String | South Africa AIS switch |

## Example Requests

Request for obtaining the subscription status of the management console service.

```
GET /koodrive/ose/v1/service  
Authorization:Bearer+10f88d*****4791e9ff
```

## Example Responses

**Status code: 200**

Service status.

```
{  
  "data": {  
    "tenantId": "40086000004871666",  
    "status": 0,  
    "spaceCapacity": 10000,  
    "userCount": 7000,  
    "personalSpaceSize": 0,  
    "groupSpaceSize": 10,  
    "organizationName": "KooDrive",  
    "organizationId": "9190086000001210958",  
    "rootDeptCode": "aed8a3763f9b4177beb2dd8bce1a3885",  
    "departmentSpaceSize": 0  
    "productType": "2"  
    "wpsAvailable": true  
    "aiAvailable": true  
  },  
  "code": 0,  
  "msg": "Successful"  
}
```

## Status Codes

| Status Code | Description     |
|-------------|-----------------|
| 200         | Service status. |

## 4.6.2 Querying Service Usage

### Function

Query service usage (space and OrgID user quotas).

## URI

GET /koodrive/ose/v1/service/quotaUsed

## Request Parameters

**Table 4-153** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | No        | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permissions. When an API is called, the token is added to the request header to obtain the operation permissions. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-154** Response body parameters

| Parameter | Type                        | Description            |
|-----------|-----------------------------|------------------------|
| code      | Integer                     | Response code.         |
| msg       | String                      | Response message.      |
| data      | <a href="#">data object</a> | Current service usage. |

**Table 4-155** data

| Parameter              | Type    | Description   |
|------------------------|---------|---|
| spaceQuotaUsed         | Integer | Used space quota.                                     |
| userCount              | Integer | Number of created OrgID users.                        |
| spaceCapacity          | Integer | Total space capacity subscribed by the tenant, in GB. |
| userMaxCount           | Integer | User quantity subscribed by the tenant.               |
| spaceUsed              | Integer | Used space.   |
| deptSpaceQuota         | Integer | Department space quota.                               |
| personalSpaceQuota     | Integer | Individual space quota.                               |
| groupSpaceQuota        | Integer | Group space quota.                                    |
| reservedSpaceQuota     | Integer | Reserved space quota.                                 |
| deptSpaceUsed          | Integer | Used department space.                                |
| deptSpaceQuotaUsed     | Integer | Used department space quota.                          |
| personalSpaceUsed      | Integer | Used individual space.                                |
| personalSpaceQuotaUsed | Integer | Used individual space quota.                          |
| groupSpaceUsed         | Integer | Used group space.                                     |
| groupSpaceQuotaUsed    | Integer | Used group space quota.                               |
| packageDownloadExpires | Integer | Expiration time of package download.                  |
| productType            | String  | Product type.   |

## Example Requests

Query the current service usage.

```
GET /koodrive/ose/v1/service/quotaUsed
```

```
Authorization:Bearer+10f88d*****4791e9f
```

## Example Responses

**Status code: 200**

Response for querying service usage.

```
{  
    "data" : {  
        "spaceUsed" : 7753298,  
        "spaceCapacity" : 10240,  
        "deptSpaceQuota" : 6144,  
        "personalSpaceQuota" : 2048,  
        "groupSpaceQuota" : 2048,  
        "reservedSpaceQuota" : 0,  
        "spaceQuotaUsed" : 327,  
        "deptSpaceUsed" : 1975057,  
        "deptSpaceQuotaUsed" : 42,  
        "personalSpaceUsed" : 3933426,  
        "personalSpaceQuotaUsed" : 35,  
        "groupSpaceUsed" : 1844815,  
        "groupSpaceQuotaUsed" : 250,  
        "userCount" : 20,  
        "userMaxCount" : 100,  
        "packageDownloadExpires" : 7,  
        "productType" : "1"  
    },  
    "code" : 0,  
    "msg" : "success"  
}
```

## Status Codes

| Status Code | Description                          |
|-------------|--------------------------------------|
| 200         | Response for querying service usage. |

## 4.7 Enterprise Settings

### 4.7.1 Setting the Expiration Time of a Compressed Package

#### Function

Set the expiration time of a compressed package generated during package download.

#### URI

POST /koodrive/ose/v1/org/package

#### Request Parameters

**Table 4-156** Request header parameters

| Parameter | Mandatory | Type   | Description                                       |
|-----------|-----------|--------|---|
| X-Traceid | No        | String | Message log trace ID. The value contains 58 bits. |

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en_us</b> indicates English (United States).   |
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-157** Request body parameters

| Parameter              | Mandatory | Type    | Description   |
|------------------------|-----------|---------|---|
| tenantId               | No        | String  | Tenant ID.  |
| packageDownloadExpires | Yes       | Integer | Time for invalidating and deleting the temporary package generated during package download. Default value: 7. Value range: [1, 30]. |

## Response Parameters

**Status code: 200**

**Table 4-158** Response body parameters

| Parameter | Type    | Description    |
|-----------|---------|----------------|
| code      | Integer | Error code.    |
| msg       | String  | Error message. |

## Example Requests

Set the expiration time of a compressed package generated during package download.

```
POST /koodrive/ose/v1/org/package
{
  "packageDownloadExpires": 6
}
```

## Example Responses

**Status code: 200**

Result of setting the expiration time of a compressed package generated during package download.

```
{
  "code": 0,
  "msg": "Success."
}
```

## Status Codes

| Status Code | Description  |
|-------------|--|
| 200         | Result of setting the expiration time of a compressed package generated during package download. |

## 4.8 Other APIs

### 4.8.1 Obtain the JavaScript SDK.

#### Function

Obtain the JavaScript SDK.

#### URI

```
GET /koodrive/ose/v1/sdk/get-js-sdk-info
```

## Request Parameters

**Table 4-159** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |

## Response Parameters

**Status code: 200**

**Table 4-160** Response body parameters

| Parameter | Type                    | Description                 |
|-----------|-------------------------|-----------------------------|
| code      | Integer                 | Response code.              |
| msg       | String                  | Response information.       |
| data      | <b>JsSdkData</b> object | JavaScript SDK information. |

**Table 4-161** JsSdkData

| Parameter        | Type   | Description                            |
|------------------|--------|--|
| page_token_key   | String | Parameter returned by the backend API. |
| page_token       | String | Parameter returned by the backend API. |
| js_sdk_url       | String | JavaScript SDK address.                |
| retry_js_sdk_url | String | JavaScript SDK address.                |
| transaction_id   | String | Transaction ID.                        |

| Parameter    | Type   | Description   |
|--------------|--------|---|
| orgid_config | String | Parameter returned by the backend API. The value must be a JSON string. <b>sdk_auth_code</b> can be used only once. The backend must obtain it again for each initialization. |

## Example Requests

Obtain the JavaScript SDK.

```
GET /koodrive/ose/sdk/get-js-sdk-info
```

```
Authorization:Bearer+10f88*****4791e9f
```

## Example Responses

**Status code: 200**

Obtain the JavaScript SDK response.

```
{  
    "data": {  
        "page_token_key": "1724663471194",  
        "page_token": "752*****2aa",  
        "js_sdk_url": "https://orgid-beta.ulangab.huawei.com/orgid/console-web/jssdk/jssdk.umd.js",  
        "retry_js_sdk_url": "https://orgid-beta.ulangab.huawei.com/orgid/console-web/jssdk/jssdk.umd.js",  
        "transaction_id": "1724663471194",  
        "orgid_config": "{\"sdk_auth_code\":\"043*****5e1\"},\"organization_source\":\"HUAWEI_ID\""}  
    "code": 0,  
    "msg": "Successful."  
}
```

## Status Codes

| Status Code | Description                         |
|-------------|-------------------------------------|
| 200         | Obtain the JavaScript SDK response. |

## 4.9 Permissions Templates

### 4.9.1 Creating a Permissions Template

#### Function

Create a permissions template.

## URI

POST /koodrive/ose/v1/permission/template/create

## Request Parameters

**Table 4-162** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | The format is <b>Bearer</b> <i>{app_access_token}</i> . The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using <b>clientid</b> and <b>clientSecret</b> obtained during application creation. |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | No        | String | Address, which is used for app authentication.   |

**Table 4-163** Request body parameters

| Parameter   | Mandatory | Type    | Description   |
|-------------|-----------|---------|---|
| name        | Yes       | String  | Permissions template name. The value contains up to 24 characters. Letters and digits are allowed.              |
| description | No        | String  | Permissions template description. The value contains up to 50 characters.                                       |
| type        | Yes       | Integer | Permissions template type. <b>0</b> : preset; <b>1</b> : custom.  |
| company     | Yes       | String  | Enterprise to which the permissions template belongs. The value can be an organization ID or an application ID. |

| Parameter    | Mandatory | Type                | Description   |
|--------------|-----------|---------------------|---|
| capabilities | Yes       | Capabilities object | Permissions values. The value of <b>ControlService</b> needs to be converted into the decimal value of the final permissions and saved to the database. |

**Table 4-164 Capabilities**

| Parameter                 | Mandatory | Type    | Description   |
|---------------------------|-----------|---------|---|
| addChildNodePermission    | Yes       | Boolean | Permission to create a file or folder. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| copyPermission            | Yes       | Boolean | Copy permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                       |
| deletePermission          | Yes       | Boolean | Delete permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                     |
| downloadPermission        | Yes       | Boolean | Download permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                   |
| editPermission            | Yes       | Boolean | Edit permissions. <b>true</b> : granted; <b>false</b> : not granted (editing is not supported.)   |
| listChildNodePermission   | Yes       | Boolean | Permission to view the list. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| removeChildNodePermission | Yes       | Boolean | Move permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                       |

| Parameter            | Mandatory | Type    | Description  |
|----------------------|-----------|---------|--|
| renameFilePermission | Yes       | Boolean | Rename permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.  |
| shareFilePermission  | Yes       | Boolean | Share permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.   |
| uploadPermission     | Yes       | Boolean | Upload permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.  |
| viewPermission       | Yes       | Boolean | Preview permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |

## Response Parameters

Status code: 200

**Table 4-165** Response body parameters

| Parameter | Type                                      | Description                       |
|-----------|---|-----------------------------------|
| code      | Integer                                   | Response code.                    |
| msg       | String                                    | Response message.                 |
| data      | <a href="#">PermissionTemplate object</a> | Permissions template information. |

**Table 4-166** PermissionTemplate

| Parameter   | Type   | Description                          |
|-------------|--------|--------------------------------------|
| id          | String | Unique ID of a permissions template. |
| name        | String | Permissions template name.           |
| description | String | Permissions template description.    |

| Parameter    | Type                | Description   |
|--------------|---------------------|---|
| templateType | Integer             | Permissions template type. <b>0</b> : preset; <b>1</b> : custom.  |
| status       | Integer             | Permissions template status. <b>0</b> : disabled; <b>1</b> : enabled.   |
| company      | String              | Enterprise to which the permissions template belongs. The value can be an organization ID or an application ID. |
| createTime   | String              | Time when the permissions template is created.  |
| updateTime   | String              | Time when the permissions template is updated.  |
| capabilities | Capabilities object | Permissions value.  |

**Table 4-167** Capabilities

| Parameter               | Type    | Description   |
|-------------------------|---------|---|
| addChildNodePermission  | Boolean | Permission to create a file or folder. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| copyPermission          | Boolean | Copy permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                       |
| deletePermission        | Boolean | Delete permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                     |
| downloadPermission      | Boolean | Download permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                   |
| editPermission          | Boolean | Edit permissions. <b>true</b> : granted; <b>false</b> : not granted (editing is not supported.)   |
| listChildNodePermission | Boolean | Permission to view the list. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |

| Parameter                 | Type    | Description  |
|---------------------------|---------|--|
| removeChildNodePermission | Boolean | Move permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.    |
| renameFilePermission      | Boolean | Rename permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.  |
| shareFilePermission       | Boolean | Share permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.   |
| uploadPermission          | Boolean | Upload permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.  |
| viewPermission            | Boolean | Preview permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |

## Example Requests

```
/koodrive/ose/v1/permission/template/create

{
  "company" : "*****",
  "name" : "*****",
  "templateType" : 1,
  "description" : "",
  "capabilities" : {
    "listChildNodePermission" : true,
    "viewPermission" : false,
    "editPermission" : false,
    "uploadPermission" : false,
    "downloadPermission" : false,
    "shareFilePermission" : false,
    "removeChildNodePermission" : false,
    "copyPermission" : false,
    "renameFilePermission" : false,
    "deletePermission" : false,
    "addChildNodePermission" : false
  }
}
```

## Example Responses

Status code: 200

Response body for creating a template.

```
{
  "data" : {
```

```
"id" : "1590*****52215169",
"name" : "*****",
"description" : "",
"templateType" : 1,
"status" : 0,
"company" : "*****",
"createTime" : "2025-01-03T07:56:29.450Z",
"updateTime" : "2025-01-03T07:56:29.450Z",
"capabilities" : {
    "addChildNodePermission" : false,
    "copyPermission" : false,
    "deletePermission" : false,
    "downloadPermission" : false,
    "editPermission" : false,
    "listChildNodePermission" : true,
    "removeChildNodePermission" : false,
    "renameFilePermission" : false,
    "shareFilePermission" : false,
    "uploadPermission" : false,
    "viewPermission" : false
},
"code" : 0,
"msg" : "Successful."
}
```

## Status Codes

| Status Code | Description                            |
|-------------|--|
| 200         | Response body for creating a template. |

## 4.9.2 Editing a Permissions Template

### Function

Edit a permissions template.

### URI

POST /koodrive/ose/v1/permission/template/edit

## Request Parameters

**Table 4-168** Request header parameters

| Parameter     | Mandatory | Type   | Description   |
|---------------|-----------|--------|---|
| Authorization | Yes       | String | The format is <b>Bearer {app_access_token}</b> . The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using <b>clientid</b> and <b>clientSecret</b> obtained during application creation. |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.  |
| X-Date        | Yes       | String | Date, which is used for app authentication.   |
| Host          | No        | String | Address, which is used for app authentication.  |

**Table 4-169** Request body parameters

| Parameter    | Mandatory | Type                | Description    |
|--------------|-----------|---------------------|----------------|
| id           | Yes       | Long                | Template ID.   |
| name         | Yes       | String              | Template name. |
| description  | No        | String              | Description.   |
| capabilities | No        | Capabilities object | Permissions.   |

**Table 4-170** Capabilities

| Parameter               | Mandatory | Type    | Description   |
|-------------------------|-----------|---------|---|
| addChildNode Permission | Yes       | Boolean | Permission to create a file or folder. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |

| Parameter                 | Mandatory | Type    | Description   |
|---------------------------|-----------|---------|---|
| copyPermission            | Yes       | Boolean | Copy permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.             |
| deletePermission          | Yes       | Boolean | Delete permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| downloadPermission        | Yes       | Boolean | Download permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.         |
| editPermission            | Yes       | Boolean | Edit permissions. <b>true</b> : granted; <b>false</b> : not granted (editing is not supported.)   |
| listChildNodePermission   | Yes       | Boolean | Permission to view the list. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| removeChildNodePermission | Yes       | Boolean | Move permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.             |
| renameFilePermission      | Yes       | Boolean | Rename permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| shareFilePermission       | Yes       | Boolean | Share permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.            |
| uploadPermission          | Yes       | Boolean | Upload permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |

| Parameter      | Mandatory | Type    | Description  |
|----------------|-----------|---------|--|
| viewPermission | Yes       | Boolean | Preview permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |

## Response Parameters

Status code: 200

**Table 4-171** Response body parameters

| Parameter | Type    | Description           |
|-----------|---------|-----------------------|
| code      | Integer | Response code.        |
| msg       | String  | Response information. |

## Example Requests

```
/koodrive/ose/v1/permission/template/edit

{
  "id" : "1590*****215169",
  "name" : "****",
  "description" : "s",
  "capabilities" : {
    "listChildNodePermission" : true,
    "viewPermission" : false,
    "editPermission" : false,
    "uploadPermission" : false,
    "downloadPermission" : false,
    "shareFilePermission" : false,
    "removeChildNodePermission" : false,
    "copyPermission" : false,
    "renameFilePermission" : false,
    "deletePermission" : false,
    "addChildNodePermission" : false
  }
}
```

## Example Responses

Status code: 200

Response body for editing a permissions template.

```
{
  "code" : 0,
  "msg" : "Successful."
```

## Status Codes

| Status Code | Description                                       |
|-------------|---|
| 200         | Response body for editing a permissions template. |

## 4.9.3 Modifying the Status of Permissions Templates

### Function

Modify the status of permissions templates in batches.

### URI

POST /koodrive/ose/v1/permission/template/status/modify

### Request Parameters

**Table 4-172** Request header parameters

| Parameter     | Mandatory | Type   | Description   |
|---------------|-----------|--------|---|
| Authorization | Yes       | String | The format is <b>Bearer {app_access_token}</b> . The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using <b>clientid</b> and <b>clientSecret</b> obtained during application creation. |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.  |
| X-Date        | Yes       | String | Date, which is used for app authentication.   |
| Host          | No        | String | Address, which is used for app authentication.  |

**Table 4-173** Request body parameters

| Parameter | Mandatory | Type | Description                          |
|-----------|-----------|------|--------------------------------------|
| id        | Yes       | Long | Unique ID of a permissions template. |

| Parameter | Mandatory | Type    | Description   |
|-----------|-----------|---------|---|
| status    | Yes       | Integer | Permissions template status. 0: disabled; 1: enabled. |

## Response Parameters

**Status code: 200**

**Table 4-174** Response body parameters

| Parameter | Type   | Description    |
|-----------|--------|----------------|
| code      | String | Error code.    |
| msg       | String | Error message. |

## Example Requests

```
/koodrive/ose/v1/permission/template/status/modify
{
  "id" : "15906*****52928",
  "status" : 1
}
```

## Example Responses

**Status code: 200**

Response body for modifying the status of permissions templates.

```
{
  "code" : 0,
  "msg" : "Successful."
}
```

## Status Codes

| Status Code | Description  |
|-------------|--|
| 200         | Response body for modifying the status of permissions templates. |

## 4.9.4 Deleting Permissions Templates in Batches

### Function

Delete permissions templates in batches.

## URI

POST /koodrive/ose/v1/permission/template/delete

## Request Parameters

**Table 4-175** Request header parameters

| Parameter     | Mandatory | Type   | Description   |
|---------------|-----------|--------|---|
| Authorization | Yes       | String | The format is <b>Bearer {app_access_token}</b> . The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using <b>clientid</b> and <b>clientSecret</b> obtained during application creation. |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.  |
| X-Date        | Yes       | String | Date, which is used for app authentication.   |
| Host          | No        | String | Address, which is used for app authentication.  |

**Table 4-176** Request body parameters

| Parameter | Mandatory | Type           | Description   |
|-----------|-----------|----------------|---|
| ids       | Yes       | Array of longs | Permissions template ID list. $1 \leq \text{size} \leq 100$ |

## Response Parameters

Status code: 200

**Table 4-177** Response body parameters

| Parameter | Type   | Description    |
|-----------|--------|----------------|
| code      | String | Error code.    |
| msg       | String | Error message. |

## Example Requests

```
/koodrive/ose/v1/permission/template/delete  
{  
    "ids" : [ "1590626552448551681" ]  
}
```

## Example Responses

**Status code: 200**

Response body.

```
{  
    "code" : 0,  
    "msg" : "Successful."  
}
```

## Status Codes

| Status Code | Description    |
|-------------|----------------|
| 200         | Response body. |

## 4.9.5 Querying Permissions Template Details Based on the Permissions Template ID Array

### Function

Query permissions template details based on the permissions template ID array.

### URI

POST /koodrive/ose/v1/permission/template/batchGet

### Request Parameters

**Table 4-178** Request header parameters

| Parameter     | Mandatory | Type   | Description   |
|---------------|-----------|--------|---|
| Authorization | Yes       | String | The format is <b>Bearer {app_access_token}</b> . The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using <b>clientId</b> and <b>clientSecret</b> obtained during application creation. |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| X-User-Id | Yes       | String | User ID, which is used for app authentication. |
| X-Date    | Yes       | String | Date, which is used for app authentication.    |
| Host      | No        | String | Address, which is used for app authentication. |

**Table 4-179** Request body parameters

| Parameter | Mandatory | Type           | Description   |
|-----------|-----------|----------------|---|
| ids       | Yes       | Array of longs | Permissions template ID array. $1 \leq \text{size} \leq 200$ . The validity of each ID is verified, for example, whether the ID exists. |

## Response Parameters

Status code: 200

**Table 4-180** Response body parameters

| Parameter | Type   | Description                            |
|-----------|--|--|
| code      | Integer  | Response code.                         |
| msg       | String   | Response information.                  |
| data      | Array of<br><a href="#">PermissionTemplate</a> objects | Permissions template information list. |

**Table 4-181** PermissionTemplate

| Parameter    | Type    | Description  |
|--------------|---------|--|
| id           | String  | Unique ID of a permissions template.                             |
| name         | String  | Permissions template name.                                       |
| description  | String  | Permissions template description.                                |
| templateType | Integer | Permissions template type. <b>0</b> : preset; <b>1</b> : custom. |

| Parameter    | Type                          | Description   |
|--------------|-------------------------------|---|
| status       | Integer                       | Permissions template status. <b>0</b> : disabled; <b>1</b> : enabled.   |
| company      | String                        | Enterprise to which the permissions template belongs. The value can be an organization ID or an application ID. |
| createTime   | String                        | Time when the permissions template is created.  |
| updateTime   | String                        | Time when the permissions template is updated.  |
| capabilities | <b>Capabilities</b><br>object | Permissions value.  |

**Table 4-182** Capabilities

| Parameter               | Type    | Description   |
|-------------------------|---------|---|
| addChildNodePermission  | Boolean | Permission to create a file or folder. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| copyPermission          | Boolean | Copy permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                       |
| deletePermission        | Boolean | Delete permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                     |
| downloadPermission      | Boolean | Download permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                   |
| editPermission          | Boolean | Edit permissions. <b>true</b> : granted; <b>false</b> : not granted (editing is not supported.)   |
| listChildNodePermission | Boolean | Permission to view the list. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |

| Parameter                 | Type    | Description  |
|---------------------------|---------|--|
| removeChildNodePermission | Boolean | Move permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.    |
| renameFilePermission      | Boolean | Rename permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.  |
| shareFilePermission       | Boolean | Share permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.   |
| uploadPermission          | Boolean | Upload permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.  |
| viewPermission            | Boolean | Preview permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |

## Example Requests

```
/koodrive/ose/v1/permission/template/batchGet
{
  "ids" : [ "1590626552448551681" ]
```

## Example Responses

**Status code: 200**

Response body.

```
{
  "data" : [ {
    "id" : "*****",
    "name" : "File List, Preview, Download, and Share",
    "description" : "File list, preview, download, and share.",
    "templateType" : 1,
    "status" : 1,
    "company" : "*****",
    "createTime" : "2024-12-19T07:59:34.032Z",
    "updateTime" : "2024-12-19T07:59:57.786Z",
    "capabilities" : {
      "addChildNodePermission" : false,
      "copyPermission" : false,
      "deletePermission" : false,
      "downloadPermission" : true,
      "editPermission" : false,
      "listChildNodePermission" : true,
      "removeChildNodePermission" : false,
```

```
        "renameFilePermission" : false,
        "shareFilePermission" : true,
        "uploadPermission" : false,
        "viewPermission" : true
    }
},
"code" : 0,
"msg" : "success"
}
```

## Status Codes

| Status Code | Description    |
|-------------|----------------|
| 200         | Response body. |

## 4.9.6 Listing Permissions Templates by Condition

### Function

List permissions templates by condition.

### URI

GET /koodrive/ose/v1/permission/template/list

**Table 4-183** Query Parameters

| Parameter    | Mandatory | Type    | Description  |
|--------------|-----------|---------|--|
| limit        | Yes       | Integer | Maximum number of records to be returned. Value range: 1 to 100.   |
| offset       | Yes       | Integer | Offset. Minimum value: 0.  |
| id           | No        | Long    | Unique ID of a permissions template.   |
| templateType | No        | Integer | Permissions template type. <b>0</b> : preset; <b>1</b> : custom.   |
| status       | No        | Integer | Permissions template status. <b>0</b> : disabled; <b>1</b> : enabled.  |
| orderByTime  | No        | Integer | Sorted by <b>createTime</b> . The value can only be <b>0</b> (descending order) or <b>1</b> (ascending order). |
| preBefore    | No        | Boolean | Whether preset templates are placed on the top or at the bottom.   |

## Request Parameters

**Table 4-184** Request header parameters

| Parameter     | Mandatory | Type   | Description   |
|---------------|-----------|--------|---|
| Authorization | Yes       | String | The format is <b>Bearer {app_access_token}</b> . The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using <b>clientid</b> and <b>clientSecret</b> obtained during application creation. |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.  |
| X-Date        | Yes       | String | Date, which is used for app authentication.   |
| Host          | No        | String | Address, which is used for app authentication.  |

## Response Parameters

**Status code: 200**

**Table 4-185** Response body parameters

| Parameter | Type  | Description   |
|-----------|---|---|
| code      | Integer                                       | Response code.  |
| msg       | String  | Response information.   |
| data      | Array of<br><b>PermissionTemplate</b> objects | Permissions template information.   |
| total     | Integer                                       | Total number of permissions templates (including preset templates) in the current enterprise. |

**Table 4-186** PermissionTemplate

| Parameter | Type   | Description                          |
|-----------|--------|--------------------------------------|
| id        | String | Unique ID of a permissions template. |

| Parameter    | Type                | Description   |
|--------------|---------------------|---|
| name         | String              | Permissions template name.  |
| description  | String              | Permissions template description.   |
| templateType | Integer             | Permissions template type. <b>0</b> : preset; <b>1</b> : custom.  |
| status       | Integer             | Permissions template status. <b>0</b> : disabled; <b>1</b> : enabled.   |
| company      | String              | Enterprise to which the permissions template belongs. The value can be an organization ID or an application ID. |
| createTime   | String              | Time when the permissions template is created.  |
| updateTime   | String              | Time when the permissions template is updated.  |
| capabilities | Capabilities object | Permissions value.  |

**Table 4-187** Capabilities

| Parameter              | Type    | Description   |
|------------------------|---------|---|
| addChildNodePermission | Boolean | Permission to create a file or folder. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| copyPermission         | Boolean | Copy permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                       |
| deletePermission       | Boolean | Delete permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                     |
| downloadPermission     | Boolean | Download permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                   |
| editPermission         | Boolean | Edit permissions. <b>true</b> : granted; <b>false</b> : not granted (editing is not supported.)   |

| Parameter                 | Type    | Description   |
|---------------------------|---------|---|
| listChildNodePermission   | Boolean | Permission to view the list. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| removeChildNodePermission | Boolean | Move permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.             |
| renameFilePermission      | Boolean | Rename permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| shareFilePermission       | Boolean | Share permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.            |
| uploadPermission          | Boolean | Upload permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| viewPermission            | Boolean | Preview permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.          |

## Example Requests

```
/koodrive/cloudfile/v1/permission/template/list?offset=0&limit=20&orderByTime=0&templateType=1
```

```
Authorization: Bearer+10f88*****4791e9f
```

## Example Responses

**Status code: 200**

Response body.

```
{
  "total": 1,
  "data": [
    {
      "id": "****",
      "name": "*****",
      "description": "",
      "templateType": 1,
      "status": 1,
      "company": "*****",
      "createTime": "2025-01-03T08:15:14.339Z",
      "updateTime": "2025-01-03T08:54:47.814Z",
      "capabilities": {
        "addChildNodePermission": false,
        "copyPermission": false,
        "movePermission": false,
        "renamePermission": false,
        "sharePermission": false,
        "uploadPermission": false
      }
    }
  ]
}
```

```
        "deletePermission" : false,
        "downloadPermission" : false,
        "editPermission" : false,
        "listChildNodePermission" : true,
        "removeChildNodePermission" : false,
        "renameFilePermission" : false,
        "shareFilePermission" : false,
        "uploadPermission" : false,
        "viewPermission" : false
    }
},
"code" : 0,
"msg" : "Successful."
}
```

## Status Codes

| Status Code | Description    |
|-------------|----------------|
| 200         | Response body. |

## 4.9.7 Adding or Modifying the Association Relationship of the Initial Member Permissions

### Function

Add or modify the association relationship with the initial member permissions. If an association relationship does not exist in the table, it will be added. If it exists in the table, it will be modified.

### URI

POST /koodrive/ose/v1/permission/member/initial

### Request Parameters

**Table 4-188** Request header parameters

| Parameter     | Mandatory | Type   | Description   |
|---------------|-----------|--------|---|
| Authorization | Yes       | String | The format is <b>Bearer {app_access_token}</b> . The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using <b>clientid</b> and <b>clientSecret</b> obtained during application creation. |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.  |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| X-Date    | Yes       | String | Date, which is used for app authentication.    |
| Host      | No        | String | Address, which is used for app authentication. |

**Table 4-189** Request body parameters

| Parameter    | Mandatory | Type                | Description  |
|--------------|-----------|---------------------|--|
| spaceId      | Yes       | Long                | Group or department ID.  |
| templateId   | Yes       | String              | Permissions template ID. For an anonymous template, the value is -1.                       |
| capabilities | No        | Capabilities object | This field is required for an anonymous template, but it is optional for a named template. |

**Table 4-190** Capabilities

| Parameter              | Mandatory | Type    | Description   |
|------------------------|-----------|---------|---|
| addChildNodePermission | Yes       | Boolean | Permission to create a file or folder. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| copyPermission         | Yes       | Boolean | Copy permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                       |
| deletePermission       | Yes       | Boolean | Delete permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                     |
| downloadPermission     | Yes       | Boolean | Download permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                   |

| Parameter                 | Mandatory | Type    | Description   |
|---------------------------|-----------|---------|---|
| editPermission            | Yes       | Boolean | Edit permissions. <b>true</b> : granted; <b>false</b> : not granted (editing is not supported.)   |
| listChildNodePermission   | Yes       | Boolean | Permission to view the list. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| removeChildNodePermission | Yes       | Boolean | Move permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.             |
| renameFilePermission      | Yes       | Boolean | Rename permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| shareFilePermission       | Yes       | Boolean | Share permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.            |
| uploadPermission          | Yes       | Boolean | Upload permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| viewPermission            | Yes       | Boolean | Preview permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.          |

## Response Parameters

Status code: 200

**Table 4-191** Response body parameters

| Parameter | Type   | Description    |
|-----------|--------|----------------|
| code      | String | Error code.    |
| msg       | String | Error message. |

## Example Requests

```
/koodrive/ose/v1/permission/member/initial

{
  "spaceId": "*****",
  "templateId": "*****",
  "capabilities": {
    "addChildNodePermission": false,
    "copyPermission": false,
    "deletePermission": false,
    "downloadPermission": true,
    "editPermission": false,
    "listChildNodePermission": true,
    "removeChildNodePermission": false,
    "renameFilePermission": false,
    "shareFilePermission": false,
    "uploadPermission": false,
    "viewPermission": true
  }
}
```

## Example Responses

**Status code: 200**

Response body.

```
{
  "code": 0,
  "msg": "success"
}
```

## Status Codes

| Status Code | Description    |
|-------------|----------------|
| 200         | Response body. |

## 4.9.8 Querying Whether a Permissions Template Is Used

### Function

Query whether a permissions template is used.

### URI

GET /koodrive/ose/v1/permission/template/ref/{id}

**Table 4-192** Path Parameters

| Parameter | Mandatory | Type | Description              |
|-----------|-----------|------|--------------------------|
| id        | Yes       | Long | Permissions template ID. |

## Request Parameters

**Table 4-193** Request header parameters

| Parameter     | Mandatory | Type   | Description   |
|---------------|-----------|--------|---|
| Authorization | Yes       | String | The format is <b>Bearer {app_access_token}</b> . The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using <b>clientid</b> and <b>clientSecret</b> obtained during application creation. |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.  |
| X-Date        | Yes       | String | Date, which is used for app authentication.   |
| Host          | No        | String | Address, which is used for app authentication.  |

## Response Parameters

Status code: 200

**Table 4-194** Response body parameters

| Parameter   | Type    | Description                               |
|-------------|---------|---|
| templateRef | Boolean | Whether the permissions template is used. |
| code        | Integer | Response code.                            |
| msg         | String  | Response information.                     |

## Example Requests

```
/koodrive/ose/v1/permission/template/ref/{1*****681}
```

```
Authorization:Bearer+10f88*****4791e9f
```

## Example Responses

### Status code: 200

Response body for querying whether a permissions template is used.

```
{  
    "templateRef": false,  
    "code": 0,  
    "msg": "Successful."  
}
```

## Status Codes

| Status Code | Description  |
|-------------|--|
| 200         | Response body for querying whether a permissions template is used. |

## 4.10 File Moderation

### 4.10.1 Querying the Review List

#### Function

Query the content moderation information about all low-sensitive and high-sensitive files of the current tenant. (This function is available only to whitelisted users.)

#### URI

GET /koodrive/ose/v1/audit

**Table 4-195** Query Parameters

| Parameter | Mandatory | Type    | Description   |
|-----------|-----------|---------|---|
| pageSize  | No        | String  | Number of records to be returned on each page. Default and maximum value: 100.          |
| cursor    | No        | String  | Current page cursor, which is obtained from <b>nextCursor</b> of the previous response. |
| hasUrl    | No        | Boolean | Whether to return the download link. The default value is false.                        |

## Request Parameters

**Table 4-196** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | 1. The format is Bearer {app_access_token}. The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using clientId and clientSecret obtained during application creation.<br>2. The application is the KooDrive server. |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en_us</b> indicates English (United States).   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-197** Response body parameters

| Parameter | Type                              | Description           |
|-----------|-----------------------------------|-----------------------|
| code      | String                            | Response code.        |
| msg       | String                            | Response information. |
| auditList | Array of <b>AuditData</b> objects | Moderation result.    |

| Parameter  | Type   | Description   |
|------------|--------|---|
| nextCursor | String | Pagination cursor. If the cursor does not exist, the last record has been returned. |

**Table 4-198 AuditData**

| Parameter   | Type    | Description   |
|-------------|---------|---|
| sha256      | String  | SHA-256 fingerprint of a file.  |
| size        | Long    | File size.  |
| auditResult | Integer | File moderation result.<br>2: low-sensitivity file; 3: high-sensitivity file.   |
| auditDetail | String  | Moderation result details. The value is a JSON string and can only be accessed. |
| auditLevel  | Integer | Moderation level.<br>10: machine moderation.<br>20: manual moderation.          |
| downloadUrl | String  | Original file download link.  |

## Example Requests

```
/koodrive/ose/v1/audit?pageSize=1&cursor=1&hasUrl=false
```

```
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

### Status code: 200

Response to the request for querying the moderation list

```
{
  "auditList": [
    {
      "sha256": "d5757c6fe0882122d45456d1ecd2fbce59abfb00f86508be7f62304e7b0ec6d9",
      "size": 11239,
      "auditLevel": 10,
      "auditResult": 3,
      "auditDetail": "REJECT",
      "downloadUrl": "string",
    }
  ],
  "nextCursor": "MTcwODIzODc5MjAwMF9kNTc1N2M2ZmUwODgyMTIyZDQ1NDU2ZDFIY2QyZmJjZTU5YWJmYjAwZjg2NTA4YmU3ZjYyMzA0ZTdiMGVjNmQ5XzExMjM5",
  "code": 0,
}
```

```
        "msg": "success"  
    }
```

## Status Codes

| Status Code | Description  |
|-------------|--|
| 200         | Response to the request for querying the moderation list |

## 4.10.2 Adding Content Moderation Records in Batches

### Function

Add or modify content moderation records in batches. (This function is available only to whitelisted users.)

### URI

POST /koodrive/ose/v1/audit/batch

### Request Parameters

**Table 4-199** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | 1. The format is Bearer {app_access_token}. The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using clientId and clientSecret obtained during application creation.<br>2. The application is the KooDrive server. |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en_us</b> indicates English (United States).   |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| X-User-Id | Yes       | String | User ID, which is used for app authentication. |
| X-Date    | Yes       | String | Date, which is used for app authentication.    |
| Host      | Yes       | String | Address, which is used for app authentication. |

**Table 4-200** Request body parameters

| Parameter | Mandatory | Type                                   | Description                     |
|-----------|-----------|--|---------------------------------|
| list      | Yes       | Array of <a href="#">Audit</a> objects | Content moderation record list. |

**Table 4-201** Audit

| Parameter   | Mandatory | Type    | Description   |
|-------------|-----------|---------|---|
| sha256      | Yes       | String  | SHA-256 fingerprint of a file.  |
| size        | Yes       | Long    | File size.  |
| auditResult | Yes       | Integer | File moderation result.<br>1: normal file.<br>2: low-sensitivity file.<br>3: high-sensitivity file. |
| auditDetail | No        | String  | Moderation result details.<br>The value is a JSON string and can only be accessed.                  |
| fileId      | No        | String  | Only logs are recorded. Only contained in the request.  |

## Response Parameters

Status code: 200

**Table 4-202** Response body parameters

| Parameter | Type   | Description    |
|-----------|--------|----------------|
| code      | String | Response code. |

| Parameter | Type   | Description       |
|-----------|--------|-------------------|
| msg       | String | Response message. |

## Example Requests

```
/koodrive/ose/v1/audit/batch

{
  "list" : [ {
    "sha256" : "6247ade6b2ef00bcd7ca618af137f8c0154395f4edc2b2f64566f7b676b33a10",
    "size" : 528263,
    "auditResult" : "3",
    "auditDetail" : "json",
    "fileId" : "string"
  } ]
}
```

## Example Responses

### Status code: 200

Response to the request for adding a content moderation record.

```
{
  "code" : 0,
  "msg" : "success"
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Response to the request for adding a content moderation record. |

## 4.10.3 Querying Content Moderation Records in Batches

### Function

Query the moderation results of a specified file in batches. If the file is not moderated, no result is returned. (This function is available only to whitelisted users.)

### URI

POST /koodrive/ose/v1/audit/batchGet

## Request Parameters

**Table 4-203** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | 1. The format is Bearer {app_access_token}. The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using clientId and clientSecret obtained during application creation.<br>2. The application is the KooDrive server. |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en_us</b> indicates English (United States).   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-204** Request body parameters

| Parameter   | Mandatory | Type                            | Description        |
|-------------|-----------|---------------------------------|--------------------|
| featureList | Yes       | Array of <b>Feature</b> objects | File feature list. |

**Table 4-205** Feature

| Parameter | Mandatory | Type   | Description       |
|-----------|-----------|--------|-------------------|
| sha256    | Yes       | String | File fingerprint. |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| size      | Yes       | Long   | File size.                                     |
| fileId    | No        | String | File ID, which is used only for log recording. |

## Response Parameters

Status code: 200

**Table 4-206** Response body parameters

| Parameter | Type                                       | Description           |
|-----------|--|-----------------------|
| code      | String                                     | Response code.        |
| msg       | String                                     | Response information. |
| data      | <a href="#">FcaListAuditDataDto</a> object | Response data.        |

**Table 4-207** FcaListAuditDataDto

| Parameter | Type   | Description                     |
|-----------|--|---------------------------------|
| auditList | Array of <a href="#">BatchGetAudit</a> objects | Content moderation record list. |

**Table 4-208** BatchGetAudit

| Parameter   | Type    | Description  |
|-------------|---------|--|
| sha256      | String  | SHA-256 fingerprint of a file.   |
| size        | Long    | File size.   |
| auditLevel  | Integer | Moderation level. 10: machine moderation; 20: manual moderation; 30: machine + manual moderation; 99: appeal moderation. |
| auditResult | Integer | File moderation result. 1: normal file; 2: low-sensitivity file; 3: high-sensitivity file.                               |
| auditDetail | String  | Moderation result details.   |

## Example Requests

```
/koodrive/ose/v1/audit/batchGet
{
  "featureList": [
    {
      "sha256": "ef47a6416ddc1f405c4c905e12b29e26d87d316982e04cbccf115f8fff2b8e3e",
      "size": "413774",
      "fileId": "string"
    }
  ]
}
```

## Example Responses

**Status code: 200**

Response to the request for querying content moderation records in batches.

```
{
  "data": {
    "auditList": [
      {
        "sha256": "c553002b64c4613d8e93c209afefcd8d7c341358036008dccf7fddd005985d62",
        "size": 461179,
        "auditLevel": 10,
        "auditResult": 1,
        "auditDetail": "ACCEPT"
      }
    ],
    "code": 0,
    "msg": "success"
  }
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Response to the request for querying content moderation records in batches. |

## 4.11 Cloud Decompression

### 4.11.1 Listing Directories in a Compressed Package

#### Function

List file directories in a compressed package.

#### URI

POST /koodrive/ose/v1/archive/listFile

## Request Parameters

**Table 4-209** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-210** Request body parameters

| Parameter   | Mandatory | Type   | Description                  |
|-------------|-----------|--------|------------------------------|
| containerId | Yes       | String | Space ID.                    |
| fileId      | Yes       | String | File ID.                     |
| pwd         | No        | String | Compressed package password. |

## Response Parameters

Status code: 200

**Table 4-211** Response body parameters

| Parameter | Type               | Description   |
|-----------|--------------------|---|
| code      | String             | Response code.  |
| msg       | String             | Response message.   |
| data      | <b>data</b> object | Response for listing directories in a compressed package. |

**Table 4-212** data

| Parameter            | Type                                   | Description  |
|----------------------|--|--|
| uncompressedFileList | <b>UncompressedFileInfoList</b> object | List of files in the compressed package, including all sub-files and sub-directories.<br><br>This parameter is returned in synchronous mode. |
| taskKey              | String                                 | Asynchronous task key.   |
| taskValue            | Object                                 | Returned in asynchronous mode.   |
| progress             | Integer                                | Task progress, which is a percentage.  |
| taskId               | String                                 | Task ID, which is returned in asynchronous mode.   |

**Table 4-213** UncompressedFileInfoList

| Parameter | Type   | Description                                   |
|-----------|--------|---|
| code      | String | Error code.                                   |
| name      | String | File name.                                    |
| type      | String | File type. 1: content; 2: directory           |
| updateAt  | String | File modification timestamp, in milliseconds. |
| fileSize  | String | Size of a file or folder, in bytes.           |

Status code: 400

**Table 4-214** Response body parameters

| Parameter | Type   | Description  |
|-----------|--------|--------------|
| code      | String | Error code.  |
| msg       | String | Description. |

## Example Requests

Lists file directories in a compressed package.

```
POST /ose/v1/archive/listFile
Authorization: Bearer+10f88*****4791e9ff
{
  "containerId": "IAADfsBFCO6WtAtuAe3ab00aac61c45e18b0896269d5efb",
  "fileId": "FvW8flQFZmz6Fu-lZ-7pKt6wtJISsW0C-",
  "pwd": ""
}
```

## Example Responses

**Status code: 200**

Response for listing directories in a compressed package.

```
{
  "data": {
    "taskId": "1428103989525998336"
  },
  "code": 0,
  "msg": "OK"
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Response for listing directories in a compressed package. |
| 400         | Error response  |

# 4.12 Batch Task Operations

## 4.12.1 Listing Batch Tasks

### Function

List batch tasks.

## URI

GET /koodrive/ose/v1/jobs

**Table 4-215** Query Parameters

| Parameter | Mandatory | Type    | Description  |
|-----------|-----------|---------|--|
| type      | No        | Integer | Task type. <ul style="list-style-type: none"><li>• <b>1:</b> batch replication.</li><li>• <b>2:</b> batch deletion.</li><li>• <b>3:</b> batch relocation.</li><li>• <b>4:</b> batch restoration of recycle bin data.</li><li>• <b>5:</b> cloud decompression.</li><li>• <b>6:</b> package download.</li><li>• <b>7:</b> recycle bin clearance.<br/>(This function is available only to whitelisted users.)</li></ul> |
| status    | No        | Integer | Task status. <ul style="list-style-type: none"><li>• 0: to be processed</li><li>• 1: being processed</li><li>• 2: completed</li><li>• 3: canceled</li></ul>  |
| offset    | Yes       | Integer | Offset. Minimum value: 0.  |
| limit     | Yes       | Integer | Maximum number of records to be returned. Value range: 1 to 100.   |

## Request Parameters

**Table 4-216** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

Status code: 200

**Table 4-217** Response body parameters

| Parameter | Type   | Description       |
|-----------|--------|-------------------|
| code      | String | Response code.    |
| msg       | String | Response message. |

| Parameter | Type                                     | Description      |
|-----------|--|------------------|
| data      | Array of <a href="#">JobInfo</a> objects | Batch task list. |

**Table 4-218 JobInfo**

| Parameter      | Type    | Description   |
|----------------|---------|---|
| taskId         | String  | Task ID.  |
| taskType       | Integer | Task type.  |
| actionType     | Integer | Operation type.   |
| status         | Integer | Task status. <ul style="list-style-type: none"><li>• 0: to be processed</li><li>• 1: being processed</li><li>• 2: completed</li><li>• 3: canceled</li></ul> |
| taskresultCode | Integer | Task result. <ul style="list-style-type: none"><li>• 1: all succeeded</li><li>• 2: partially failed</li><li>• 3: all failed</li></ul>                       |
| resultCode     | Integer | Task result code.   |
| contentNum     | Integer | Number of request files.  |
| containerId    | String  | Target space ID in cross-space scenarios.   |
| tenantId       | String  | Tenant ID.  |
| beginTime      | String  | Task start time.  |
| endTime        | String  | Task end time.  |
| createTime     | String  | Time creation time.   |

**Status code: 400****Table 4-219 Response body parameters**

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response description. |

**Status code: 401****Table 4-220** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response description. |

**Status code: 500****Table 4-221** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response description. |

## Example Requests

Request for listing batch tasks.

```
GET /koodrive/ose/v1/jobs?offset=0&limit=2
Authorization: Bearer+10f88*****5a544791e9ff
```

## Example Responses

**Status code: 200**

Returns the queried task list.

```
{
  "data": [
    {
      "taskId": "1320279189273965056",
      "taskType": 2,
      "actionType": 201,
      "status": 2,
      "taskresultCode": 1,
      "contentNum": 1,
      "containerId": "IAADfsBFCO6WtAtuA9add2fea594e4e75b8feb8474ef236",
      "beginTime": "20231227151904",
      "endTime": "20231227151904",
      "createTime": "20231227151904"
    },
    {
      "taskId": "1320279092268104960",
      "taskType": 2,
      "actionType": 201,
      "status": 2,
      "taskresultCode": 1,
      "contentNum": 4,
      "containerId": "IAADfsBFCO6WtAtuA9add2fea594e4e75b8feb8474ef236",
      "beginTime": "20231227151852",
      "endTime": "20231227151852",
      "createTime": "20231227151852"
    }
  ]
}
```

```
"code" : 0,  
"msg" : "OK"  
}
```

## Status Codes

| Status Code | Description                    |
|-------------|--------------------------------|
| 200         | Returns the queried task list. |
| 400         | Bad Request                    |
| 401         | Unauthorized                   |
| 500         | Internal Server Error          |

## 4.12.2 Creating a Batch Task

### Function

Create a batch task.

### URI

POST /koodrive/ose/v1/jobs

### Request Parameters

**Table 4-222** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| Host      | Yes       | String | Address, which is used for app authentication.   |
| X-Traceid | No        | String | Message log trace ID. The value contains 58 bits.  |
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |

**Table 4-223** Request body parameters

| Parameter | Mandatory | Type    | Description   |
|-----------|-----------|---------|---|
| taskType  | Yes       | Integer | <p>Task type.</p> <ul style="list-style-type: none"><li>● <b>1:</b> batch replication.</li><li>● <b>2:</b> batch deletion.</li><li>● <b>3:</b> batch relocation.</li><li>● <b>4:</b> batch restoration of recycle bin data.</li><li>● <b>5:</b> cloud decompression.</li><li>● <b>6:</b> package download.</li><li>● <b>7:</b> recycle bin clearance.<br/>(This function is available only to whitelisted users.)</li></ul> |

| Parameter      | Mandatory | Type                                     | Description   |
|----------------|-----------|--|---|
| actionType     | No        | Integer                                  | Operation type, which is a subdivision of <b>taskType</b> . This parameter is used only when <b>taskType</b> is set to 1, 2, or 3. <ul style="list-style-type: none"><li>• 101: replication and dumping.</li><li>• 201: logical deletion (moved to the recycle bin).</li><li>• 202: permanent deletion.</li><li>• 301: common relocation.</li><li>• 501: compressed package preview.</li><li>• 502: full decompression.</li><li>• 503: partial decompression.</li><li>• 701: recycle bin clearance. (This function is available only to whitelisted users.)</li></ul> |
| taskInfo       | Yes       | <a href="#">CreateTaskInfoReq</a> object | Request for creating a batch task.  |
| dstContainerId | Yes       | String                                   | Target space ID.  |
| password       | No        | String                                   | Compressed package password.  |

**Table 4-224 CreateTaskInfoReq**

| Parameter           | Mandatory | Type                                      | Description   |
|---------------------|-----------|---|---|
| fileInfo            | Yes       | Array of <a href="#">fileInfo</a> objects | File/Directory ID (optional when <b>taskType</b> is set to 7).                |
| newFilePath         | No        | String                                    | New path of the file (optional when <b>taskType</b> is set to 7).             |
| srcContainerId      | Yes       | String                                    | Source space ID.  |
| uncompressFilePaths | No        | Array of strings                          | List of full paths of partially decompressed files in the compressed package. |

**Table 4-225 fileInfo**

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| fileId    | No        | String | File ID (optional for recycle bin clearance).  |
| filePath  | No        | String | Full path of the file, including the file ID. (This parameter is mandatory for logical deletion, that is, moving the file to the recycle bin, which affects the restoration function.) |

## Response Parameters

**Status code: 200**

**Table 4-226 Response body parameters**

| Parameter | Type   | Description    |
|-----------|--------|----------------|
| code      | String | Error code.    |
| msg       | String | Error message. |
| data      | String | Task ID.       |

**Status code: 400**

**Table 4-227 Response body parameters**

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response description. |

**Status code: 401**

**Table 4-228 Response body parameters**

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response description. |

**Status code: 500****Table 4-229** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response description. |

## Example Requests

Request for copying files.

```
POST /koodrive/ose/v1/jobs
Authorization: Bearer+10f88d07fa*****44791e9ff
{
    "taskType":1 ,
    "actionType":101 ,
    "dstContainerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4" ,
    "taskInfo": {
        "srcContainerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
        "newFilePath": "Fm9UdqBNTAQDOS6l1xPlFnIqXJg2-UdqA" ,
        "fileInfo": [
            {
                "fileId": "FuZmQ66CF0DdpKRG1Y29lwajbq04Nhwu3"
            }
        ]
    }
}
```

## Example Responses

**Status code: 200**

Basic response. Only the error code and error information are returned.

```
{
    "data": "1309243162258308352"
    "code": 0,
    "msg": "success"
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Basic response. Only the error code and error information are returned. |
| 400         | Bad Request   |
| 401         | Unauthorized  |
| 500         | Internal Server Error   |

## 4.12.3 Querying Details About a Batch Task

### Function

Query details about a batch task.

### URI

GET /koodrive/ose/v1/{job\_id}

**Table 4-230** Path Parameters

| Parameter | Mandatory | Type   | Description    |
|-----------|-----------|--------|----------------|
| job_id    | Yes       | String | Batch task ID. |

### Request Parameters

**Table 4-231** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |

## Response Parameters

Status code: 200

**Table 4-232** Response body parameters

| Parameter | Type                        | Description       |
|-----------|-----------------------------|-------------------|
| code      | String                      | Response code.    |
| msg       | String                      | Response message. |
| data      | <a href="#">data object</a> | Task details.     |

**Table 4-233** data

| Parameter            | Type  | Description  |
|----------------------|---|--|
| jobInfo              | <a href="#">JobDetailInfo</a> object                  | Task information.                                  |
| taskInfos            | Array of <a href="#">TaskInfo</a> objects             | Task details list.                                 |
| uncompressedFileList | Array of <a href="#">UncompressedFileInfo</a> objects | Information about files in the compressed package. |

**Table 4-234** JobDetailInfo

| Parameter | Type    | Description      |
|-----------|---------|------------------|
| taskId    | String  | Task ID.         |
| taskName  | String  | Task name.       |
| userId    | String  | Task creator ID. |
| taskType  | Integer | Task type.       |

| Parameter      | Type    | Description   |
|----------------|---------|---|
| actionType     | Integer | Operation type.   |
| status         | Integer | Task status. <ul style="list-style-type: none"><li>• 0: to be processed</li><li>• 1: being processed</li><li>• 2: completed</li><li>• 3: canceled</li></ul> |
| taskresultCode | Integer | Task result. <ul style="list-style-type: none"><li>• 1: all succeeded</li><li>• 2: partially failed</li><li>• 3: all failed</li></ul>                       |
| resultCode     | Integer | Task result code.   |
| progress       | Integer | Task progress. This parameter is returned in an asynchronous task, for example, a package download task.  |
| downloadUrl    | String  | Download link. This parameter is used only when the task type is package download.  |
| contentNum     | Integer | Number of request files.  |
| containerId    | String  | Target space ID in cross-space scenarios.   |
| tenantId       | String  | Tenant ID.  |
| beginTime      | String  | Task start time.  |
| endTime        | String  | Task end time.  |
| createTime     | String  | Time creation time.   |

**Table 4-235 TaskInfo**

| Parameter | Type   | Description  |
|-----------|--------|--|
| id        | String | Task ID.   |
| fileId    | String | File/Directory ID.                                       |
| filePath  | String | Full path of a file or directory, including the file ID. |

| Parameter      | Type   | Description  |
|----------------|--------|--|
| status         | String | Task processing status. <ul style="list-style-type: none"><li>● <b>0</b>: pending.</li><li>● <b>1</b>: successful.</li><li>● <b>2</b>: failed.</li></ul> |
| newFileId      | String | New ID after operation.  |
| newFilePath    | String | New path.  |
| srcContainerId | String | Source container ID (source space ID corresponding to <b>fileId</b> ). This parameter is mandatory only for batch replication across spaces.             |
| resultCode     | String | File operation result code.  |
| resultDesc     | String | File operation result description.   |
| tenantId       | String | Tenant ID.   |
| createTime     | String | Task creation time.  |

**Table 4-236 UncompressedFileInfo**

| Parameter   | Type  | Description  |
|-------------|---|--|
| containerId | String                                      | Space ID after decompression. This parameter is returned only for decompression.   |
| fileId      | String                                      | ID of the decompressed file. This parameter is returned only for decompression.  |
| name        | String                                      | Full path of the file or folder in the compressed package.   |
| fileSize    | Long  | File size, in bytes.   |
| type        | Integer                                     | For details, see the definition of <b>fileType</b> . <ul style="list-style-type: none"><li>● <b>1</b>: content.</li><li>● <b>2</b>: directory.</li></ul> |
| updatedAt   | Long  | Millisecond timestamp of file modification.  |
| subFileList | <a href="#">UncompressedFileInfo</a> object | List of sub-files and sub-directories (expanded only for directories).   |
| reason      | String                                      | Failure cause. If the operation is successful, this parameter is null.   |

| Parameter       | Type                | Description     |
|-----------------|---------------------|-----------------|
| code            | String              | Error code.     |
| reservationInfo | Map<String, Object> | Reserved field. |

**Status code: 400****Table 4-237** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response description. |

**Status code: 401****Table 4-238** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response description. |

**Status code: 500****Table 4-239** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response description. |

## Example Requests

Queries details about a batch task.

```
GET /koodrive/ose/v1/1309243162258308352
```

```
Authorization:Bearer+10f8*****a544791e9ff
```

## Example Responses

**Status code: 200**

Returns queried task details.

```
{  
  "data": {  
    "jobInfo": {  
      "taskId": "1309243162258308352",  
      "userId": "40086000004871666-369528171409614001",  
      "taskType": 1,  
      "actionType": 101,  
      "status": 2,  
      "progress": 100,  
      "taskresultCode": 1,  
      "contentNum": 1,  
      "containerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",  
      "tenantId": "40086000004871666",  
      "beginTime": "20231212095227",  
      "endTime": "20231212095227",  
      "createTime": "20231212095227"  
    },  
    "taskInfos": [ {  
      "fileId": "FuZmQ66CF0DdpKRG1Y29lwajbq04Nhwu3",  
      "status": "1",  
      "new fileId": "FtEXHCpfqHueAHFbEmWZNkqUH_K866MVn",  
      "srcContainerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"  
    } ]  
  },  
  "code": 0,  
  "msg": "OK"  
}
```

## Status Codes

| Status Code | Description                   |
|-------------|-------------------------------|
| 200         | Returns queried task details. |
| 400         | Bad Request                   |
| 401         | Unauthorized                  |
| 500         | Internal Server Error         |

## 4.12.4 Cancelling a Batch Task

### Function

Cancel a batch task whose status is **0** (to be processed) or **1** (processing). After the task is canceled, the task scheduling module ignores its record.

### URI

POST /koodrive/ose/v1/cancel

## Request Parameters

**Table 4-240** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-241** Request body parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| jobId     | Yes       | String | Task ID.    |

## Response Parameters

Status code: 200

**Table 4-242** Response body parameters

| Parameter | Type   | Description                   |
|-----------|--------|-------------------------------|
| data      | String | Response service information. |

**Status code: 400****Table 4-243** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response description. |

**Status code: 401****Table 4-244** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response description. |

**Status code: 500****Table 4-245** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response description. |

## Example Requests

Cancels a batch task.

```
POST /koodrive/ose/v1/cancel
Authorization:Bearer+10f*****791e9ff
{
    "jobId":"1289250105886769024"
}
```

## Example Responses

### Status code: 200

Basic response. Only the error code and error information are returned.

```
{  
    "code" : 0,  
    "msg" : "OK"  
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Basic response. Only the error code and error information are returned. |
| 400         | Bad Request   |
| 401         | Unauthorized  |
| 500         | Internal Server Error   |

## 4.13 Basic Task Operations

### 4.13.1 Creating a Task

#### Function

Create a task (such as a transfer task).

#### URI

POST /koodrive/ose/v1/task/create

## Request Parameters

**Table 4-246** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | No        | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-Traceid     | No        | String | Message log tracing ID (58 bits).  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-247** Request body parameters

| Parameter | Mandatory | Type    | Description   |
|-----------|-----------|---------|---|
| taskType  | No        | Integer | Task type. 0: transfer and deletion; 1: batch import                              |
| srcUserId | No        | String  | Source user ID. This field is mandatory when <b>taskType</b> is set to <b>0</b> . |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| dstUserId | No        | String | Target user ID. This field is mandatory when <b>taskType</b> is set to <b>0</b> .    |
| resultId  | No        | String | Result ID. This field is filled when <b>taskType</b> is set to <b>1</b> .            |
| orgId     | No        | String | Organization ID. This field is mandatory when <b>taskType</b> is set to <b>1</b> .   |
| orgUserId | No        | String | Creator orgUserId. This field is mandatory when <b>taskType</b> is set to <b>1</b> . |

## Response Parameters

Status code: 200

**Table 4-248** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| taskId    | String | Task ID.              |
| code      | String | Response code.        |
| msg       | String | Response information. |

## Example Requests

Creates a task.

```
POST /koodrive/ose/v1/task/create
Authorization: Bearer+dsadasd*****4ad83c8f'
{
  "taskType": 0,
  "srcUserId": "139768722724455008",
  "dstUserId": "1507947856550550784"
}
```

## Example Responses

Status code: 200

Response for creating a task.

```
{
  "taskId" : "1534087020903704704",
  "code" : 0,
  "msg" : "Success."
}
```

## Status Codes

| Status Code | Description                   |
|-------------|-------------------------------|
| 200         | Response for creating a task. |

## 4.13.2 Listing Tasks

### Function

List tasks.

### URI

GET /koodrive/ose/v1/task/list

### Request Parameters

**Table 4-249** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | No        | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-Traceid     | No        | String | Message log tracing ID (58 bits).  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| X-Date    | Yes       | String | Date, which is used for app authentication.    |
| Host      | Yes       | String | Address, which is used for app authentication. |

**Table 4-250** Request body parameters

| Parameter  | Mandatory | Type              | Description  |
|------------|-----------|-------------------|--|
| taskType   | No        | Integer           | Task type. <b>0</b> : transfer task.   |
| status     | No        | Array of integers | Task status. <b>0</b> : NEW; <b>1</b> : EXECUTING; <b>2</b> : SUCCESS; <b>3</b> : FAILED.  |
| pageSize   | No        | Integer           | Number of records to be returned on each page.<br>Default and maximum value: <b>100</b> . It is possible that partial or empty result pages are returned before the end of the result list has been reached. |
| pageCursor | No        | Long              | Current page cursor, which is obtained from <b>nextCursor</b> of the previous response.  |

## Response Parameters

Status code: 200

**Table 4-251** Response body parameters

| Parameter  | Type                                      | Description   |
|------------|---|---|
| taskList   | Array of <a href="#">TaskInfo</a> objects | Task list.  |
| code       | String                                    | Response code.  |
| msg        | String                                    | Response information.   |
| nextCursor | String                                    | Pagination cursor. If the cursor does not exist, the last record has been returned. |

**Table 4-252 TaskInfo**

| Parameter  | Type    | Description         |
|------------|---------|---------------------|
| taskId     | String  | Task ID.            |
| taskName   | String  | Task name.          |
| taskType   | Integer | Task type.          |
| tenantId   | String  | Tenant ID.          |
| userId     | String  | User ID.            |
| status     | Integer | Task status.        |
| initParams | String  | Extended field.     |
| locale     | String  | User country.       |
| resultCode | String  | Task result.        |
| createTime | String  | Time creation time. |
| startTime  | String  | Task start time.    |
| endTime    | String  | Task end time.      |

## Example Requests

Queries the task list.

```
GTE /koodrive/ose/v1/task/list?taskType=0&status=2&pageSize=10&pageCursor
```

```
Authorization: Bearer+dsadasd*****4ad83c8f'
```

## Example Responses

**Status code: 200**

Response for listing tasks.

```
{
  "taskListDtos": [
    {
      "taskId": "1486254586942472064",
      "taskName": "ceshi1111",
      "taskType": 0,
      "status": 2,
      "createTime": "2024-08-12T07:22:33.000Z"
    },
    {
      "taskId": "1486368980720435072",
      "taskName": "ceshi4",
      "taskType": 0,
      "status": 2,
      "createTime": "2024-08-12T11:09:50.000Z"
    }
  ],
  "nextCursor": 1723549107000,
  "code": 0,
  "msg": "Success."
}
```

## Status Codes

| Status Code | Description                 |
|-------------|-----------------------------|
| 200         | Response for listing tasks. |

## 4.13.3 Obtaining Task Details

### Function

Obtain task details.

### URI

GET /koodrive/ose/v1/task/{task\_id}

**Table 4-253** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| task_id   | Yes       | String | Task ID.    |

### Request Parameters

**Table 4-254** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |
| X-Traceid | No        | String | Message log tracing ID (58 bits).  |
| X-User-Id | Yes       | String | User ID, which is used for app authentication.   |
| X-Date    | Yes       | String | Date, which is used for app authentication.  |
| Host      | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-255** Response body parameters

| Parameter  | Type    | Description  |
|------------|---------|--|
| taskId     | String  | Task ID.   |
| taskName   | String  | Task name.   |
| taskType   | Integer | Task type. <b>0</b> : transfer and deletion.   |
| tenantId   | String  | Tenant ID.   |
| userId     | String  | Internal user ID.  |
| status     | Integer | Task status. <b>0</b> : NEW; <b>1</b> : EXECUTING; <b>2</b> : SUCCESS; <b>3</b> : FAILED.                        |
| resultCode | String  | Result code.<br><i>18xxxxxx</i> : specific errors. (This parameter is not returned when the task is successful.) |
| code       | String  | Response code.   |
| msg        | String  | Response information.  |

## Example Requests

Obtains task details.

```
GET /koodrive/ose/v1/task/1534087020903704704
```

```
Authorization: Bearer+dsadasd*****4ad83c8f
```

## Example Responses

**Status code: 200**

Response for obtaining task details.

```
{
  "taskId" : "1534087020903704704",
  "taskName" : "lym0412normal",
  "taskType" : 0,
  "tenantId" : "d5ac574bd2934a69baa4f23c55daa8d4",
  "userId" : "1395497048157130881",
  "status" : 3,
  "resultCode" : "18000205",
  "code" : 0,
  "msg" : "Success."
}
```

## Status Codes

| Status Code | Description                          |
|-------------|--------------------------------------|
| 200         | Response for obtaining task details. |

## 4.13.4 Obtains the information about the handover recipient.

### Function

Obtains the recipient information based on the transferor ID.

### URI

```
GET /koodrive/ose/v1/task/dstUserInfo/{src_user_id}
```

**Table 4-256 Path Parameters**

| Parameter   | Mandatory | Type   | Description                       |
|-------------|-----------|--------|-----------------------------------|
| src_user_id | Yes       | String | ID of the user to be handed over. |

## Request Parameters

**Table 4-257** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-Traceid     | No        | String | Message log tracing ID (58 bits).  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-258** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response information. |
| id        | String | Recipient ID.         |

| Parameter | Type   | Description         |
|-----------|--------|---------------------|
| name      | String | Recipient username. |

## Example Requests

Obtains the recipient information.

```
GET /koodrive/ose/v1/task/dstUserInfo/1397687227244555008
```

```
Authorization: Bearer+dsadasd*****4ad83c8f
```

## Example Responses

**Status code: 200**

Response body for obtaining the user information of the handover recipient.

```
{
  "id" : "1507947856550550784",
  "name" : "zujian2",
  "code" : 0,
  "msg" : "Success."
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Response body for obtaining the user information of the handover recipient. |

## 4.13.5 Queries the task result.

### Function

Queries the task result.

### URI

```
GET /koodrive/ose/v1/task/result
```

**Table 4-259** Query Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| taskId    | No        | String | Task ID.    |

## Request Parameters

**Table 4-260** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-Traceid     | No        | String | Message log tracing ID (58 bits).  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-261** Response body parameters

| Parameter | Type                           | Description               |
|-----------|--------------------------------|---------------------------|
| data      | <b>UserImportResult</b> object | Batch user import result. |

**Table 4-262** UserImportResultDto

| Parameter    | Type   | Description   |
|--------------|--|---|
| successCount | Integer  | Number of successful records.                             |
| failCount    | Integer  | Number of failed records.                                 |
| failInfoList | Array of<br><a href="#">UserImportFailInfo</a> objects | Information about the failure to import users in batches. |

**Table 4-263** UserImportFailInfo

| Parameter | Type   | Description  |
|-----------|--------|--------------|
| userName  | String | Username.    |
| desc      | String | Description. |

## Example Requests

Queries the task result.

```
GET /koodrive/ose/v1/task/result?taskid=1215215
```

```
Authorization: Bearer+dsadasd*****4ad83c8f
```

## Example Responses

**Status code: 200**

Response to the request for querying the task result.

```
{  
    "data": {  
        "successCount": 1  
        "failCount": 1  
        "failInfoList": [  
            {"userName": "ss"}  
        ]  
    },  
    "code": 0,  
    "msg": "Successful"  
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Response to the request for querying the task result. |

## 4.14 File List Query

### 4.14.1 Listing Files in the Individual Space

#### Function

List files in the individual space.

#### URI

POST /koodrive/ose/v1/files/{type}

**Table 4-264** Path Parameters

| Parameter | Mandatory | Type   | Description   |
|-----------|-----------|--------|---|
| type      | Yes       | String | <ul style="list-style-type: none"><li>• 0: individual space.</li><li>• 1: individual recycle bin.</li></ul> |

#### Request Parameters

**Table 4-265** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| X-Traceid | No        | String | Message log trace ID. The value contains 58 bits.  |
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |

**Table 4-266** Request body parameters

| Parameter    | Mandatory | Type                                | Description   |
|--------------|-----------|-------------------------------------|---|
| pageInfo     | No        | <a href="#">PageInfo</a> object     | Pagination information.   |
| sortInfo     | No        | <a href="#">FileSortInfo</a> object | Classification information.   |
| containerId  | Yes       | String                              | Space ID.   |
| parentFileId | Yes       | String                              | Parent directory of the file. <ul style="list-style-type: none"><li>● <b>root</b>: root directory of the common file system.</li><li>● <b>sbox</b>: root directory of the safe file system.</li></ul>   |
| fileType     | No        | String                              | File type. <ul style="list-style-type: none"><li>● <b>10</b>: folder.</li><li>● <b>11</b>: smart folder (available only to whitelisted users).</li><li>● <b>15</b>: image.</li><li>● <b>20</b>: video.</li><li>● <b>26</b>: Word file.</li><li>● <b>27</b>: Excel file.</li><li>● <b>28</b>: PowerPoint file.</li><li>● <b>30</b>: audio.</li><li>● <b>35</b>: compressed file.</li><li>● <b>40</b>: application.</li><li>● <b>45</b>: other.</li></ul> |
| imageProcess | No        | String                              | Image operation, which can be used to specify the thumbnail size.   |

| Parameter | Mandatory | Type    | Description   |
|-----------|-----------|---------|---|
| hidden    | No        | Boolean | Whether hidden files are queried. (This function is available only to whitelisted users.) |

**Table 4-267 PageInfo**

| Parameter  | Mandatory | Type    | Description                                       |
|------------|-----------|---------|---|
| pageSize   | No        | Integer | Number of files on each page. Default value: 100. |
| pageCursor | No        | String  | Pagination start cursor.                          |

**Table 4-268 FileSortInfo**

| Parameter     | Mandatory | Type    | Description   |
|---------------|-----------|---------|---|
| sortType      | No        | Integer | Sorting field. <ul style="list-style-type: none"><li>• 1: by file name.</li><li>• 2: by file size.</li><li>• 3: by creation time.</li><li>• 4: by modification time.</li><li>• 5: by recycling time (only for recycled files).</li><li>• 6: by file format.</li></ul> |
| sortDirection | No        | Integer | Sorting order. <ul style="list-style-type: none"><li>• 1: ascending.</li><li>• 2: descending.</li></ul>   |

## Response Parameters

Status code: 200

**Table 4-269 Response body parameters**

| Parameter | Type   | Description  |
|-----------|--------|--|
| category  | String | Resource type. The value is fixed to <b>drive#fileList</b> . |

| Parameter       | Type  | Description   |
|-----------------|---|---|
| nextCursor      | String  | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| searchCompleted | Boolean   | Whether the search is complete.   |
| files           | Array of <a href="#">FileListMetadata</a> objects | File list.  |
| code            | String  | Response code.  |
| msg             | String  | Response information.   |

**Table 4-270** FileListMetadata

| Parameter    | Type                                  | Description   |
|--------------|---------------------------------------|---|
| id           | String                                | File ID.  |
| fileName     | String                                | File name, which contains up to 250 characters.   |
| fileType     | String                                | File type, which is input externally.   |
| contentType  | String                                | Content type.   |
| favorite     | Boolean                               | Whether the file is added to favorites.   |
| recycled     | Boolean                               | Whether the file is moved to the recycle bin.   |
| recycledTime | String                                | Time when the file is moved to the recycle bin. This parameter is returned when the file is recycled.   |
| parentFolder | Array of strings                      | ID of the parent directory IDs. Currently, only the first ID is used.   |
| properties   | Map<String, String>                   | Common user-defined attributes of the file. The number of key-value pairs cannot exceed 30. A single key-value pair can contain up to 124 characters. |
| containers   | Array of strings                      | Space ID.   |
| createdTime  | String                                | UTC time when the file is created.  |
| editedTime   | String                                | UTC time when the file is modified.   |
| owners       | Array of <a href="#">User</a> objects | Owner.  |
| lastEditor   | <a href="#">User</a> object           | Last editor.  |

| Parameter        | Type                                       | Description   |
|------------------|--|---|
| fileSuffix       | String                                     | File name extension, which is the last character string of <b>fullFileExtension</b> . |
| size             | Integer                                    | File size.  |
| attachments      | Array of <b>FileListAttachment</b> objects | Attachment.   |
| downloadLinks    | Array of <b>downLoadLinks</b> objects      | Link for downloading FileProxy files.   |
| userProperties   | Array of <b>PrivateProperties</b> objects  | User attributes.  |
| sha256           | String                                     | SHA256 value of the file.   |
| userCapabilities | <b>userCapabilities</b> object             | User permissions.   |
| hidden           | Boolean                                    | Whether it is hidden.   |
| directlyRecycled | Boolean                                    | Whether it is directly deleted.   |
| idPath           | String                                     | ID path of the file or folder.  |

**Table 4-271** User

| Parameter    | Type    | Description                            |
|--------------|---------|--|
| category     | String  | Type. The value is <b>drive#user</b> . |
| userId       | String  | Huawei user ID.                        |
| displayName  | String  | Display name of the user.              |
| me           | Boolean | Whether you are the user.              |
| permissionId | String  | Permission ID.                         |

**Table 4-272** fileListAttachment

| Parameter | Type   | Description   |
|-----------|--------|---|
| usage     | String | Default usage: <b>content</b> or <b>thumbnail</b> . This parameter is customizable. |
| hash      | String | Hash of the resource associated with the asset.                                     |

| Parameter | Type                                 | Description                                       |
|-----------|--------------------------------------|---|
| sha256    | String                               | SHA256 of the resource associated with the asset. |
| asset     | <a href="#">FileListAsset</a> object | Asset.  |

**Table 4-273** [FileListAsset](#)

| Parameter | Type                                    | Description |
|-----------|---|-------------|
| resource  | <a href="#">FileListResource</a> object | Resource.   |
| mimeType  | String                                  | MIME type   |

**Table 4-274** [FileListResource](#)

| Parameter | Type                                       | Description  |
|-----------|--|--|
| object    | <a href="#">FileListSliceObject</a> object | Part object, which is applicable when <b>type</b> is set to <b>0</b> or <b>3</b> . |

**Table 4-275** [FileListSliceObject](#)

| Parameter   | Type                                       | Description  |
|-------------|--|--|
| id          | String                                     | Part ID.   |
| start       | Long                                       | Start position of a part, which is not applicable when <b>type</b> is set to <b>12</b> . |
| downloadUrl | <a href="#">EndpointURLMetadata</a> object | Download URL.  |
| image       | Array of <a href="#">Images</a> objects    | Thumbnail information.   |

**Table 4-276** [Images](#)

| Parameter   | Type                                       | Description                                |
|-------------|--|--|
| process     | String                                     | File resource name.                        |
| downloadUrl | <a href="#">EndpointURLMetadata</a> object | URL structure for file upload or download. |

**Table 4-277** EndpointURLMetadata

| Parameter | Type   | Description |
|-----------|--------|-------------|
| url       | String | URL         |
| method    | String | http method |

**Table 4-278** downLoadLinks

| Parameter    | Type   | Description  |
|--------------|--------|--|
| usage        | String | Usage. The value can be <b>thumbnail</b> or <b>content</b> . |
| downloadLink | String | Image address.   |

**Table 4-279** PrivateProperties

| Parameter  | Type                 | Description  |
|------------|----------------------|--|
| attributes | Map<String, Object>  | Type attributes (The size of a single attribute is not limited, but the total size cannot exceed 16 KB.)     |
| properties | Map<String, String > | Extended attributes (The size of a single attribute is not limited, but the total size cannot exceed 16 KB.) |

**Table 4-280** userCapabilities

| Parameter                 | Type    | Description   |
|---------------------------|---------|---|
| addChildNodePermission    | Boolean | Whether the user can add sub-directories or sub-files.  |
| copyPermission            | Boolean | Whether the user can copy files.                        |
| deletePermission          | Boolean | Whether the user can delete files.                      |
| downloadPermission        | Boolean | Whether the user can download content.                  |
| editPermission            | Boolean | Whether the user can edit files.                        |
| listChildNodePermission   | Boolean | Whether the user can list sub-directories or sub-files. |
| removeChildNodePermission | Boolean | Whether the user can move sub-directories.              |

| Parameter            | Type    | Description                         |
|----------------------|---------|-------------------------------------|
| renameFilePermission | Boolean | Whether the user can rename files.  |
| shareFilePermission  | Boolean | Whether the user can share files.   |
| uploadPermission     | Boolean | Whether the user can upload files.  |
| viewPermission       | Boolean | Whether the user can preview files. |

**Status code: 400****Table 4-281** Response body parameters

| Parameter | Type                         | Description    |
|-----------|------------------------------|----------------|
| error     | <a href="#">Error</a> object | Error message. |

**Table 4-282** Error

| Parameter   | Type                                      | Description  |
|-------------|---|--|
| errorData   | <a href="#">errorData</a> object          | Extended data returned to visitors when an exception occurs. |
| errorDetail | Array of <a href="#">ErrorMsg</a> objects | Error chain.   |
| code        | Integer                                   | HTTP status code.  |
| description | String                                    | HTTP status information.                                     |

**Table 4-283** errorData

| Parameter       | Type   | Description          |
|-----------------|--------|----------------------|
| conflict fileId | String | Conflicting file ID. |

**Table 4-284** ErrorMsg

| Parameter | Type   | Description  |
|-----------|--------|--------------|
| domain    | String | Domain.      |
| reason    | String | Error cause. |

| Parameter   | Type   | Description   |
|-------------|--------|---|
| errorCode   | String | Internal system error code. For details, see the error code specifications. |
| description | String | Error message.  |
| errorPos    | String | Error position type.  |
| errorParam  | String | Error position.   |

## Example Requests

Lists files in the root directory of individual space  
**IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b.**

```
POST /koodrive/ose/v1/files/0
Authorization:Bearer+10f88*****4791e9ff
{
  "pageInfo": {
    "pageSize": "10",
    "pageCursor": ""
  },
  "sortInfo": {
    "sortType": "",
    "sortDirection": ""
  },
  "containerId": "IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b",
  "parentFileId": "root",
  "fileType": "",
  "fileName": ""
}
```

## Example Responses

**Status code: 200**

Returns the file list.

```
{
  "category" : "drive#fileList",
  "nextCursor" : "0|[9-1-0,11-0-1]
[JzlwMjMtMTItMTNUMDM6MzA6NTkuNTU4Wi=,J0ZpQk02VHhsS2JiSEx4LW54X3FaT2M1bFJBZXewU0xZeC
c=]",
  "searchCompleted" : false,
  "files" : [ {
    "id" : "Fk0n_L_3nVynllxGSUdLkYILxIZQ5Yyp",
    "fileName" : "AI Test",
    "mimeType" : "application/vnd.huawei-apps.folder",
    "fileSuffix" : "",
    "recycled" : false,
    "parentFolder" : [ "DEUI7pa0C24ArootIAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b" ],
    "containers" : [ "IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b" ],
    "properties" : {
      "srcFileId" : "Fuyt9uELO9mny6vLWnWpIDqppRh3vzC3p",
      "createUser" : "369528171409614001",
      "lastEditUser" : "369528171409614001"
    },
    "owners" : [ {
      "category" : "drive#user",
      "me" : true,
    }
  }
]
```

```
        "permissionId" : "1243622029865966464",
        "userId" : "NDEzMmA4NjAwMDAwMjc0MTY2NS00MDA4NjAwMDAwNDg3MTY2Ng",
        "displayName" : "Tenant Administrator"
    },
    "lastEditor" : {
        "category" : "drive#user",
        "me" : true,
        "permissionId" : "1243622029865966464",
        "userId" : "NDEzMmA4NjAwMDAwMjc0MTY2NS00MDA4NjAwMDAwNDg3MTY2Ng",
        "displayName" : "Tenant Administrator"
    },
    "fileType" : "10",
    "createdTime" : "2023-12-11T09:17:25.529Z",
    "editedTime" : "2023-12-11T09:17:25.529Z",
    "favorite" : false
},
"code" : 0,
"msg" : "OK"
}
```

## Status Codes

| Status Code | Description            |
|-------------|------------------------|
| 200         | Returns the file list. |
| 400         | Bad request            |

## 4.14.2 Listing Files in a Group or Department Space

### Function

List files in a group or department space.

### URI

POST /koodrive/ose/v1/files/{groupId}/{type}

**Table 4-285** Path Parameters

| Parameter | Mandatory | Type   | Description   |
|-----------|-----------|--------|---|
| groupId   | Yes       | String | Team ID.  |
| type      | Yes       | String | Type.<br>• 0: team space.<br>• 1: team recycle bin. |

**Table 4-286** Query Parameters

| Parameter | Mandatory | Type    | Description   |
|-----------|-----------|---------|---|
| team_type | No        | Integer | (Optional) Team type.<br>If this parameter is not carried, the default value <b>0</b> is used.<br><b>0</b> : department.<br><b>2</b> : group. |

## Request Parameters

**Table 4-287** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-288** Request body parameters

| Parameter    | Mandatory | Type                                | Description   |
|--------------|-----------|-------------------------------------|---|
| pageInfo     | No        | <a href="#">PageInfo</a> object     | Pagination information.   |
| sortInfo     | No        | <a href="#">FileSortInfo</a> object | Classification information.   |
| containerId  | Yes       | String                              | Space ID.   |
| parentFileId | Yes       | String                              | Parent directory of the file. <ul style="list-style-type: none"><li>● <b>root</b>: root directory of the common file system.</li><li>● <b>sbox</b>: root directory of the safe file system.</li></ul>   |
| fileType     | No        | String                              | File type. <ul style="list-style-type: none"><li>● <b>10</b>: folder.</li><li>● <b>11</b>: smart folder (available only to whitelisted users).</li><li>● <b>15</b>: image.</li><li>● <b>20</b>: video.</li><li>● <b>26</b>: Word file.</li><li>● <b>27</b>: Excel file.</li><li>● <b>28</b>: PowerPoint file.</li><li>● <b>30</b>: audio.</li><li>● <b>35</b>: compressed file.</li><li>● <b>40</b>: application.</li><li>● <b>45</b>: other.</li></ul> |
| imageProcess | No        | String                              | Image operation, which can be used to specify the thumbnail size.   |
| hidden       | No        | Boolean                             | Whether hidden files are queried. (This function is available only to whitelisted users.)   |

**Table 4-289** PageInfo

| Parameter  | Mandatory | Type    | Description                                       |
|------------|-----------|---------|---|
| pageSize   | No        | Integer | Number of files on each page. Default value: 100. |
| pageCursor | No        | String  | Pagination start cursor.                          |

**Table 4-290** FileSortInfo

| Parameter     | Mandatory | Type    | Description   |
|---------------|-----------|---------|---|
| sortType      | No        | Integer | Sorting field. <ul style="list-style-type: none"><li>● 1: by file name.</li><li>● 2: by file size.</li><li>● 3: by creation time.</li><li>● 4: by modification time.</li><li>● 5: by recycling time (only for recycled files).</li><li>● 6: by file format.</li></ul> |
| sortDirection | No        | Integer | Sorting order. <ul style="list-style-type: none"><li>● 1: ascending.</li><li>● 2: descending.</li></ul>   |

## Response Parameters

Status code: 200

**Table 4-291** Response body parameters

| Parameter       | Type                                     | Description   |
|-----------------|--|---|
| category        | String                                   | Resource type. The value is fixed to <b>drive#fileList</b> .                        |
| nextCursor      | String                                   | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| searchCompleted | Boolean                                  | Whether the search is complete.   |
| files           | Array of <b>FileListMetadata</b> objects | File list.  |
| code            | String                                   | Response code.  |
| msg             | String                                   | Response information.   |

**Table 4-292** FileListMetadata

| Parameter | Type   | Description |
|-----------|--------|-------------|
| id        | String | File ID.    |

| Parameter        | Type  | Description   |
|------------------|---|---|
| fileName         | String  | File name, which contains up to 250 characters.   |
| fileType         | String  | File type, which is input externally.   |
| contentType      | String  | Content type.   |
| favorite         | Boolean   | Whether the file is added to favorites.   |
| recycled         | Boolean   | Whether the file is moved to the recycle bin.   |
| recycledTime     | String  | Time when the file is moved to the recycle bin. This parameter is returned when the file is recycled.   |
| parentFolder     | Array of strings                                    | ID of the parent directory IDs. Currently, only the first ID is used.   |
| properties       | Map<String, String>                                 | Common user-defined attributes of the file. The number of key-value pairs cannot exceed 30. A single key-value pair can contain up to 124 characters. |
| containers       | Array of strings                                    | Space ID.   |
| createdTime      | String  | UTC time when the file is created.  |
| editedTime       | String  | UTC time when the file is modified.   |
| owners           | Array of <a href="#">User</a> objects               | Owner.  |
| lastEditor       | <a href="#">User</a> object                         | Last editor.  |
| fileSuffix       | String  | File name extension, which is the last character string of <b>fullFileExtension</b> .   |
| size             | Integer   | File size.  |
| attachments      | Array of <a href="#">FileListAttachment</a> objects | Attachment.   |
| downloadLinks    | Array of <a href="#">downLoadLinks</a> objects      | Link for downloading FileProxy files.   |
| userProperties   | Array of <a href="#">PrivateProperties</a> objects  | User attributes.  |
| sha256           | String  | SHA256 value of the file.   |
| userCapabilities | <a href="#">userCapabilities</a> object             | User permissions.   |

| Parameter        | Type    | Description                     |
|------------------|---------|---------------------------------|
| hidden           | Boolean | Whether it is hidden.           |
| directlyRecycled | Boolean | Whether it is directly deleted. |
| idPath           | String  | ID path of the file or folder.  |

**Table 4-293 User**

| Parameter    | Type    | Description                            |
|--------------|---------|--|
| category     | String  | Type. The value is <b>drive#user</b> . |
| userId       | String  | Huawei user ID.                        |
| displayName  | String  | Display name of the user.              |
| me           | Boolean | Whether you are the user.              |
| permissionId | String  | Permission ID.                         |

**Table 4-294 fileListAttachment**

| Parameter | Type                                    | Description   |
|-----------|---|---|
| usage     | String                                  | Default usage: <b>content</b> or <b>thumbnail</b> . This parameter is customizable. |
| hash      | String                                  | Hash of the resource associated with the asset.                                     |
| sha256    | String                                  | SHA256 of the resource associated with the asset.                                   |
| asset     | <a href="#">FileListAsset</a><br>object | Asset.  |

**Table 4-295 fileListAsset**

| Parameter | Type                                       | Description |
|-----------|--|-------------|
| resource  | <a href="#">FileListResource</a><br>object | Resource.   |
| mimeType  | String                                     | MIME type   |

**Table 4-296** fileListResource

| Parameter | Type                       | Description  |
|-----------|----------------------------|--|
| object    | FileListSliceObject object | Part object, which is applicable when <b>type</b> is set to <b>0</b> or <b>3</b> . |

**Table 4-297** fileListSliceObject

| Parameter   | Type                       | Description  |
|-------------|----------------------------|--|
| id          | String                     | Part ID.   |
| start       | Long                       | Start position of a part, which is not applicable when <b>type</b> is set to <b>12</b> . |
| downloadUrl | EndpointURLMetadata object | Download URL.  |
| image       | Array of Images objects    | Thumbnail information.   |

**Table 4-298** Images

| Parameter   | Type                       | Description                                |
|-------------|----------------------------|--|
| process     | String                     | File resource name.                        |
| downloadUrl | EndpointURLMetadata object | URL structure for file upload or download. |

**Table 4-299** EndpointURLMetadata

| Parameter | Type   | Description |
|-----------|--------|-------------|
| url       | String | URL         |
| method    | String | http method |

**Table 4-300** downLoadLinks

| Parameter    | Type   | Description  |
|--------------|--------|--|
| usage        | String | Usage. The value can be <b>thumbnail</b> or <b>content</b> . |
| downloadLink | String | Image address.   |

**Table 4-301** PrivateProperties

| Parameter  | Type                | Description  |
|------------|---------------------|--|
| attributes | Map<String, Object> | Type attributes (The size of a single attribute is not limited, but the total size cannot exceed 16 KB.)     |
| properties | Map<String, String> | Extended attributes (The size of a single attribute is not limited, but the total size cannot exceed 16 KB.) |

**Table 4-302** userCapabilities

| Parameter                 | Type    | Description   |
|---------------------------|---------|---|
| addChildNodePermission    | Boolean | Whether the user can add sub-directories or sub-files.  |
| copyPermission            | Boolean | Whether the user can copy files.                        |
| deletePermission          | Boolean | Whether the user can delete files.                      |
| downloadPermission        | Boolean | Whether the user can download content.                  |
| editPermission            | Boolean | Whether the user can edit files.                        |
| listChildNodePermission   | Boolean | Whether the user can list sub-directories or sub-files. |
| removeChildNodePermission | Boolean | Whether the user can move sub-directories.              |
| renameFilePermission      | Boolean | Whether the user can rename files.                      |
| shareFilePermission       | Boolean | Whether the user can share files.                       |
| uploadPermission          | Boolean | Whether the user can upload files.                      |
| viewPermission            | Boolean | Whether the user can preview files.                     |

**Status code: 400****Table 4-303** Response body parameters

| Parameter | Type         | Description    |
|-----------|--------------|----------------|
| error     | Error object | Error message. |

**Table 4-304** Error

| Parameter   | Type                                      | Description  |
|-------------|---|--|
| errorData   | <a href="#">errorData</a> object          | Extended data returned to visitors when an exception occurs. |
| errorDetail | Array of <a href="#">ErrorMsg</a> objects | Error chain.   |
| code        | Integer                                   | HTTP status code.  |
| description | String                                    | HTTP status information.                                     |

**Table 4-305** errorData

| Parameter      | Type   | Description          |
|----------------|--------|----------------------|
| conflictFileId | String | Conflicting file ID. |

**Table 4-306** ErrorMsg

| Parameter   | Type   | Description   |
|-------------|--------|---|
| domain      | String | Domain.   |
| reason      | String | Error cause.  |
| errorCode   | String | Internal system error code. For details, see the error code specifications. |
| description | String | Error message.  |
| errorPos    | String | Error position type.  |
| errorParam  | String | Error position.   |

## Example Requests

Lists files in the root directory of team space **IAAB\_BRGQ-MajA2WAf81df00a3443452aa3dd54e35245bc**.

```
POST /koodrive/ose/v1/files/1269529595850261633/0
```

```
Authorization:Bearer+10f88*****4791e9ff
```

```
{
  "pageInfo": {
    "pageSize": "10",
    "pageCursor": ""
  },
  "sortInfo": {
    "sortType": "",
    "sortDirection": ""
  }
},
```

```
"containerId": "IAAB_BRGQ-MajA2WAf81df00a3443452aa3dd54e35245bc",
"parentFileId": "root",
"fileType": "",
"fileName": ""
}
```

## Example Responses

### Status code: 200

Returns the queried file list.

```
{
  "category" : "drive#fileList",
  "nextCursor" : "0|[9-1-0,11-0-1]
[1zlwMjMtMTItMTNUMDM6MzA6NTkuNTU4Wi=,J0ZpQk02VHhsS2jISEx4LW54X3FaT2M1bFJBZXewU0xZeC
c=]",
  "searchCompleted" : false,
  "files" : [ {
    "id" : "Fk0n_L_3nVynllxGSUdLkYILxIZQ5Yyp",
    "fileName" : "AI Test",
    "mimeType" : "application/vnd.huawei-apps.folder",
    "fileSuffix" : "",
    "recycled" : false,
    "parentFolder" : [ "DEUI7pa0C24ArootIAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b" ],
    "containers" : [ "IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b" ],
    "properties" : {
      "srcFileId" : "Fuyt9uELO9mny6vLWnWpIDqppRh3vzC3p",
      "createUser" : "369528171409614001",
      "lastEditUser" : "369528171409614001"
    },
    "owners" : [ {
      "category" : "drive#user",
      "me" : true,
      "permissionId" : "1243622029865966464",
      "userId" : "NDEzMDA4NjAwMDAwMjc0MTY2NS00MDA4NjAwMDAwNDg3MTY2Ng",
      "displayName" : "Tenant Administrator"
    }],
    "lastEditor" : {
      "category" : "drive#user",
      "me" : true,
      "permissionId" : "1243622029865966464",
      "userId" : "NDEzMDA4NjAwMDAwMjc0MTY2NS00MDA4NjAwMDAwNDg3MTY2Ng",
      "displayName" : "Tenant Administrator"
    },
    "fileType" : "10",
    "createdTime" : "2023-12-11T09:17:25.529Z",
    "editedTime" : "2023-12-11T09:17:25.529Z",
    "favorite" : false
  }],
  "code" : 0,
  "msg" : "OK"
}
```

## Status Codes

| Status Code | Description                    |
|-------------|--------------------------------|
| 200         | Returns the queried file list. |
| 400         | Bad request                    |

## 4.15 File Management

### 4.15.1 Obtaining File Details

#### Function

Obtain file details, such as the file size, name, and modification time.

#### URI

POST /koodrive/ose/v1/files/{fileId}/detail

**Table 4-307** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| fileId    | Yes       | String | File ID.    |

#### Request Parameters

**Table 4-308** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |

**Table 4-309** Request body parameters

| Parameter    | Mandatory | Type   | Description   |
|--------------|-----------|--------|---|
| containerId  | Yes       | String | Space ID.   |
| imageProcess | No        | String | Image operation, which can be used to specify the thumbnail size. |

## Response Parameters

Status code: 200

**Table 4-310** Response body parameters

| Parameter    | Type                | Description   |
|--------------|---------------------|---|
| id           | String              | File ID.  |
| fileName     | String              | File name, which contains up to 250 characters.   |
| fileType     | String              | File type, which is input externally.   |
| contentType  | String              | Content type.   |
| recycled     | Boolean             | Whether the file is moved to the recycle bin.   |
| parentFolder | Array of strings    | ID of the parent directory IDs. Currently, only the first ID is used.   |
| properties   | Map<String, String> | Common user-defined attributes of the file. The number of key-value pairs cannot exceed 30. A single key-value pair can contain up to 124 characters. |
| containers   | Array of strings    | Space ID.   |
| createdTime  | String              | UTC time when the file is created.  |

| Parameter        | Type  | Description   |
|------------------|---|---|
| editedTime       | String  | UTC time when the file is modified.   |
| owners           | Array of <a href="#">User</a> objects               | Owner.  |
| lastEditor       | <a href="#">User</a> object                         | Last editor.  |
| fileSuffix       | String  | File name extension, which is the last character string of <b>fullFileExtension</b> . |
| size             | Integer   | File size.  |
| attachments      | Array of <a href="#">AttachmentMetadata</a> objects | Attachment.   |
| userCapabilities | <a href="#">userCapabilities</a> object             | User permissions.   |
| code             | String  | Response code.  |
| msg              | String  | Response information.   |
| sha256           | String  | SHA256 value of the file.   |
| downloadLinks    | Map<String, <a href="#">downLoadLinks</a> >         | Download link.  |

**Table 4-311 User**

| Parameter    | Type    | Description                            |
|--------------|---------|--|
| category     | String  | Type. The value is <b>drive#user</b> . |
| userId       | String  | Huawei user ID.                        |
| displayName  | String  | Display name of the user.              |
| me           | Boolean | Whether you are the user.              |
| permissionId | String  | Permission ID.                         |

**Table 4-312 AttachmentMetadata**

| Parameter | Type   | Description   |
|-----------|--------|---|
| usage     | String | Default usage: <b>content</b> or <b>thumbnail</b> . This parameter is customizable. |
| hash      | String | Hash of the resource associated with the asset.                                     |

| Parameter | Type                        | Description                                       |
|-----------|-----------------------------|---|
| sha256    | String                      | SHA256 of the resource associated with the asset. |
| asset     | <b>AssetMetadata</b> object | Asset.  |

**Table 4-313 AssetMetadata**

| Parameter    | Type                           | Description  |
|--------------|--------------------------------|--|
| id           | String                         | Asset ID   |
| versionId    | String                         | Asset version ID.  |
| version      | Long                           | Version number.  |
| contentType  | String                         | MIME type  |
| state        | Integer                        | Data status. <ul style="list-style-type: none"><li>• <b>0</b>: available.</li><li>• <b>1</b>: unavailable.</li><li>• <b>2</b>: temporary.</li><li>• <b>3</b>: retained (flash upload unsupported).</li><li>• <b>4</b>: to be cut over.</li></ul> |
| createdTime  | String                         | UTC time when data is created.   |
| modifiedTime | String                         | UTC time when data is last modified.   |
| resource     | <b>ResourceMetadata</b> object | Resource.  |
| attributes   | Map<String, Object>            | Type attributes. A key consists of letters and digits and starts with a letter. A value cannot contain emojis. The size of an attribute is not limited, but the total size cannot exceed 16 KB.  |

**Table 4-314 ResourceMetadata**

| Parameter | Type   | Description                                    |
|-----------|--------|--|
| id        | String | ID of the file resource.                       |
| length    | Long   | Size of the file resource.                     |
| sha256    | String | SHA256 of the file (used for integrity check). |

| Parameter | Type   | Description  |
|-----------|--|--|
| objects   | Array of <a href="#">SliceObjectMetadata</a> objects | Part object, which is applicable when <b>type</b> is set to <b>0</b> or <b>3</b> . |

**Table 4-315** SliceObjectMetadata

| Parameter   | Type                                       | Description  |
|-------------|--|--|
| id          | String                                     | Part ID.   |
| start       | Long                                       | Start position of a part, which is not applicable when <b>type</b> is set to <b>12</b> . |
| downloadUrl | <a href="#">EndpointURLMetadata</a> object | Download URL.  |
| images      | Map<String, <a href="#">Images</a> >       | Thumbnail.   |

**Table 4-316** Images

| Parameter   | Type                                       | Description                                |
|-------------|--|--|
| process     | String                                     | File resource name.                        |
| downloadUrl | <a href="#">EndpointURLMetadata</a> object | URL structure for file upload or download. |

**Table 4-317** EndpointURLMetadata

| Parameter | Type   | Description |
|-----------|--------|-------------|
| url       | String | URL         |
| method    | String | http method |

**Table 4-318** userCapabilities

| Parameter              | Type    | Description  |
|------------------------|---------|--|
| addChildNodePermission | Boolean | Whether the user can add sub-directories or sub-files. |
| copyPermission         | Boolean | Whether the user can copy files.                       |
| deletePermission       | Boolean | Whether the user can delete files.                     |

| Parameter                 | Type    | Description   |
|---------------------------|---------|---|
| downloadPermission        | Boolean | Whether the user can download content.                  |
| editPermission            | Boolean | Whether the user can edit files.                        |
| listChildNodePermission   | Boolean | Whether the user can list sub-directories or sub-files. |
| removeChildNodePermission | Boolean | Whether the user can move sub-directories.              |
| renameFilePermission      | Boolean | Whether the user can rename files.                      |
| shareFilePermission       | Boolean | Whether the user can share files.                       |
| uploadPermission          | Boolean | Whether the user can upload files.                      |
| viewPermission            | Boolean | Whether the user can preview files.                     |

**Table 4-319** downLoadLinks

| Parameter    | Type   | Description  |
|--------------|--------|--|
| usage        | String | Usage. The value can be <b>thumbnail</b> or <b>content</b> . |
| downloadLink | String | Image address.   |

## Example Requests

Checks file details.

```
POST /koodrive/ose/v1/files/FqNZrzGgSKHkfGmwjf7dLgLlGkwrLEU35/detail
Authorization: Bearer+10f88*****4791e9ff
{
  "containerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"
```

## Example Responses

**Status code: 200**

File details.

```
{
  "id": "FtSCRFXCYtFjo315lPfRHeKRiqrDdmm_Y",
  "fileName": "Download_20231213_160540.png",
  "mimeType": "image/png",
  "fileSuffix": "png",
  "recycled": false,
```

```
"size": 81243,
"parentFolder": [
    "DEUI7pa0C24ArootIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"
],
"containers": [
    "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"
],
"properties": {
    "localCreatedAt": "",
    "localUpdatedAt": "",
    "createUser": "369528171409614001",
    "lastEditUser": "369528171409614001"
},
"attachments": [
    {
        "asset": {
            "id": "1310155787561278720",
            "versionId": "1310155787561278721",
            "version": 612304,
            "mimeType": "image/png",
            "state": 0,
            "createdTime": "2023-12-13T08:05:40.655ZVGltZQ==",
            "modifiedTime": "2023-12-13T08:05:40.655ZVGltZQ==",
            "resource": {
                "id": "1275457496273837312",
                "length": 81243,
                "sha256": "f08b00d63f9109fda252e45cc70e2762347907aba7c5dea4de7eb179ddad1ab2",
                "object": {
                    "id": "b91e8df8afba4145a310dde1bfb9f8c5086",
                    "start": 0,
                    "downloadUrl": {
                        "url": "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/b91e8df8afba4145a310dde1bfb9f8c5086?response-content-disposition=attachment%3B%20filename%3D%22%25E4%25B8%258B%25E8%25BD%25BD_20231213_160540.png%22&X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-Date=20231227T073619Z&X-Amz-SignedHeaders=host&X-Amz-Expires=10000&X-Amz-Credential=MIKRISPBZAJWFHNB5WLB%2F20231227%2Fcidec-rp-2006%2Fs3%2Faws4_request&X-Amz-Signature=6fc56f74a9478e088e1e044f453c33f8cc7b403f4478d3aef923449349373e4",
                        "method": "GET"
                    }
                }
            },
            "attributes": {
                "fileName": "Download.png",
                "localCreatedAt": "",
                "createdBy": "40086000004871666",
                "resource": {
                    "id": "1275457496273837312",
                    "object": {
                        "bucket": "b10-obs-ykj-uat-01",
                        "objectId": "b91e8df8afba4145a310dde1bfb9f8c5086"
                    }
                },
                "localUpdatedAt": ""
            }
        },
        "hash": "f08b00d63f9109fda252e45cc70e2762347907aba7c5dea4de7eb179ddad1ab2",
        "usage": "content",
        "sha256": "f08b00d63f9109fda252e45cc70e2762347907aba7c5dea4de7eb179ddad1ab2"
    }
],
"owners": [
    {
        "category": "drive#user",
        "me": true,
        "permissionId": "1243622029865966464",
        "userId": "NDEzMjA4NjAwMDAwMjc0MTY2NS00MDA4NjAwMDAwNDg3MTY2Ng",
        "displayName": "Tenant Administrator"
    }
],
```

```
"lastEditor": {  
    "category": "drive#user",  
    "me": true,  
    "permissionId": "1243622029865966464",  
    "userId": "NDEzMjA4NjAwMDAwMj0MTY2NS00MDA4NjAwMDAwNDg3MTY2Ng",  
    "displayName": "Tenant Administrator"  
},  
"fileType": "15",  
"createdTime": "2023-12-13T08:05:40.601ZVGltZQ==",  
"editedTime": "2023-12-13T08:05:41.054ZVGltZQ==",  
"userCapabilities": {  
    "addChildNodePermission": true,  
    "copyPermission": true,  
    "deletePermission": false,  
    "downloadPermission": true,  
    "editPermission": true,  
    "listChildNodePermission": true,  
    "removeChildNodePermission": true,  
    "renameFilePermission": true,  
    "shareFilePermission": true,  
    "uploadPermission": true,  
    "viewPermission": true  
}  
}  
"code": 0,  
"msg": "Success."  
}
```

## Status Codes

| Status Code | Description   |
|-------------|---------------|
| 200         | File details. |

## 4.15.2 Adding a File Directory

### Function

Add a file directory.

### URI

POST /koodrive/ose/v1/directory

## Request Parameters

**Table 4-320** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |

**Table 4-321** Request body parameters

| Parameter   | Mandatory | Type   | Description   |
|-------------|-----------|--------|---|
| createdTime | No        | String | Time when the file is created. Format: yyyy-MM-ddTHH:mm:ss.sssZ   |
| description | No        | String | File description. The value contains up to 512 characters and cannot contain invalid characters such as emojis. |

| Parameter       | Mandatory | Type  | Description   |
|-----------------|-----------|---|---|
| mimeType        | No        | String  | Resource type.  |
| editedTime      | No        | String  | File modification time.   |
| fileName        | Yes       | String  | File name. The value cannot contain the following characters: '<> :"*? /', cannot be '.', '..', and can contain up to 250 characters.   |
| fileType        | Yes       | String  | File type, which is input externally.<br>The value is fixed at <b>10</b> .  |
| parentFolder    | No        | Array of strings                                  | List of parent directory IDs. The first directory is used as the parent directory.<br>If this parameter is null, the file is created in the root directory.   |
| containerId     | Yes       | String  | Space ID.   |
| renameMode      | No        | Integer   | Duplicate name policy. <ul style="list-style-type: none"><li>• <b>2</b>: Forcibly renames a file with an existing name by adding a timestamp to the end of the file name.</li><li>• <b>3</b>: Rejects files with the same name. A file with an existing name cannot be created.</li></ul> |
| hidden          | No        | Boolean   | Whether the directory is hidden. (This function is available only to whitelisted users.)  |
| smartFolderAttr | No        | Array of <a href="#">SmartFolder Attr</a> objects | Smart folder attributes. (This function is available only to whitelisted users.)  |

**Table 4-322 SmartFolderAttr**

| Parameter | Mandatory | Type    | Description      |
|-----------|-----------|---------|------------------|
| name      | No        | Integer | Attribute name.  |
| type      | No        | Integer | Attribute type.  |
| value     | No        | String  | Attribute value. |

| Parameter | Mandatory | Type    | Description    |
|-----------|-----------|---------|----------------|
| sort      | No        | Integer | Sorting value. |

## Response Parameters

**Status code: 200**

**Table 4-323** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| id        | String | File ID.              |
| fileName  | String | File name.            |
| mimeType  | String | File format.          |
| code      | String | Response code.        |
| msg       | String | Response information. |

## Example Requests

Creates a folder in the root directory of the space

**IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4.**

```
POST /koodrive/ose/v1/directory
Authorization: Bearer+10f88*****4791e9ff
{
  "createdTime": "",
  "editedTime": "",
  "description": "222",
  "mimeType": "application/vnd.huawei-apps.folder",
  "fileName": "ttgg",
  "fileType": "10",
  "parentFolder": [
    "root"
  ],
  "containerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
  "renameMode": "2"
}
```

## Example Responses

**Status code: 200**

Information returned after the directory is created.

```
{
  "id": "FqAHbpps7uJEDpvh2MbpLj7lD4AM2OWMR",
  "fileName": "ttgg",
  "mimeType": "application/vnd.huawei-apps.folder",
  "code": 0,
  "msg": "success"
}
```

## Status Codes

| Status Code | Description  |
|-------------|--|
| 200         | Information returned after the directory is created. |

## 4.15.3 Creating File Metadata

### Function

Create the metadata of the uploaded file. If flash upload is not hit, the upload process is triggered. If flash upload is hit, the file upload is complete.

### URI

POST /koodrive/ose/v1/files/create

### Request Parameters

**Table 4-324** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |

**Table 4-325** Request body parameters

| Parameter    | Mandatory | Type             | Description   |
|--------------|-----------|------------------|---|
| createdTime  | No        | String           | Time when the file is created. The format is yyyy-MM-dd'T'HH:mm:ss'Z', for example, 2023-08-18T05:43:49Z.   |
| description  | No        | String           | File description.   |
| mimeType     | No        | String           | Resource type.  |
| fileName     | Yes       | String           | File name, which cannot contain the following characters: '<> :"*? /', cannot be '.', '..', ', and can contain up to 250 characters.  |
| fileType     | Yes       | String           | File type, which is customizable.   |
| parentFolder | Yes       | Array of strings | Parent directory ID list. If the target directory is a root directory, the value is <b>root</b> . Currently, only one parent directory is supported. If multiple parent directory IDs are passed, only the first one is used. |
| sha256       | No        | String           | Complete file digest calculated using SHA256.   |
| length       | Yes       | Long             | File size, in bytes.<br>If <b>uploadMode</b> is set to <b>multipart</b> , the value must be less than or equal to 200 GB.   |

| Parameter   | Mandatory | Type   | Description  |
|-------------|-----------|--|--|
| uploadMode  | Yes       | String   | Upload mode. <ul style="list-style-type: none"><li>• <b>multipart</b>: multipart upload.</li></ul>   |
| uploadType  | Yes       | Integer  | Upload type. <ul style="list-style-type: none"><li>• <b>0</b>: common upload (not supported yet).</li><li>• <b>1</b>: multipart upload.</li><li>• <b>2</b>: versioning upload (not supported yet).</li></ul>   |
| autoRename  | Yes       | Integer  | Duplicate name policy. <ul style="list-style-type: none"><li>• <b>2</b>: Forcibly renames a file with an existing name by adding a timestamp to the end of the file name.</li><li>• <b>3</b>: Rejects files with the same name. A file with an existing name cannot be created.</li><li>• <b>4</b>: Does not create a file if files with the same name have the same SHA256 value, or, uses the forcible renaming logic.</li></ul> |
| multiParts  | No        | Array of <a href="#">MultiPartInfo</a> objects | Part information list.   |
| containerId | Yes       | String   | ID of the target space to which the file is uploaded.  |
| preHash     | No        | String   | Digest of the first 1 KB of the file calculated using SHA256.  |
| proofCode   | No        | String   | Storage signature, generated using the binary data of the file and used to prevent credential stuffing.  |
| hidden      | No        | Boolean  | Whether the file is hidden.<br>(This function is available only to whitelisted users.)   |

**Table 4-326 MultiPartInfo**

| Parameter  | Mandatory | Type           | Description   |
|------------|-----------|----------------|---|
| partNumber | Yes       | Integer        | Part No.  |
| partSize   | Yes       | Long           | Part length. The value range is [5,242,880, 5,368,709,120]. The value range of the last part is [0, 5,368,709,120]. Minimum value: 0. Maximum value: 5,368,709,120.   |
| partOffset | No        | Long           | Total length (in bytes) to the last data block. This parameter is valid only during concurrent multipart upload. The size of all parts except the last one must be a multiple of 64 bytes.  |
| hashCtx    | No        | Array of longs | Context used to iteratively calculate SHA256. This field is valid only during concurrent multipart upload. For SHA1, the value is the first to fifth 32-bit variables of the SHA1 of the previous data block. For SHA256, the value is the first to eighth 32-bit variables of the SHA256 of the previous data block.<br><br>This parameter is mandatory for all parts except the first one in concurrent multipart upload. |
| uploadUrl  | No        | String         | URL for uploading a file, which is a return parameter. The PUT method is required for uploading a file.   |
| partId     | No        | String         | Part object ID.   |

## Response Parameters

**Status code: 200**

**Table 4-327** Response body parameters

| Parameter      | Type   | Description   |
|----------------|--|---|
| fileId         | String   | File ID.  |
| rapidUpload    | Boolean  | Whether flash upload is hit. <b>true</b> indicates that flash upload is hit.  |
| containerId    | String   | ID of the space where the file is located.  |
| fileName       | String   | Name of the uploaded file. If the file is not renamed, the value is the same as the file name in the request parameter.   |
| uploadId       | String   | File upload ID.   |
| parentFolder   | Array of strings                               | ID of the parent directory where the uploaded file is located.  |
| exist          | Boolean  | Whether the file exists. This parameter is used only when the input parameter <b>autoRename</b> is set to <b>4</b> . If the file names and SHA256 values are the same, <b>true</b> is returned. |
| multiParts     | Array of <a href="#">MultiPartInfo</a> objects | Part information, which is returned during multipart upload (when <b>uploadMode</b> is set to <b>multipart</b> ).   |
| matchedPreHash | Boolean  | Whether a matching prehash exists.  |
| code           | String   | Response code.  |
| msg            | String   | Response information.   |

**Table 4-328** MultiPartInfo

| Parameter  | Type    | Description   |
|------------|---------|---|
| partNumber | Integer | Part No.  |
| partSize   | Long    | Part length. The value range is [5,242,880, 5,368,709,120]. The value range of the last part is [0, 5,368,709,120].<br>Minimum value: 0.<br>Maximum value: 5,368,709,120.                     |
| partOffset | Long    | Total length (in bytes) to the last data block. This parameter is valid only during concurrent multipart upload.<br>The size of all parts except the last one must be a multiple of 64 bytes. |

| Parameter | Type           | Description   |
|-----------|----------------|---|
| hashCtx   | Array of longs | Context used to iteratively calculate SHA256. This field is valid only during concurrent multipart upload. For SHA1, the value is the first to fifth 32-bit variables of the SHA1 of the previous data block. For SHA256, the value is the first to eighth 32-bit variables of the SHA256 of the previous data block.<br><br>This parameter is mandatory for all parts except the first one in concurrent multipart upload. |
| uploadUrl | String         | URL for uploading a file, which is a return parameter. The PUT method is required for uploading a file.   |
| partId    | String         | Part object ID.   |

## Example Requests

Creates file metadata in multipart upload mode. In this example, a part is specified. The upload link of the part is returned in the subsequent response. The part needs to be uploaded through a PUT request.

```
POST /koodrive/ose/v1/files/create
Authorization: Bearer+10f88*****4791e9ff

{
  "containerId": "IAADfsBFCO6WtAtuA9add2fea594e4e75b8feb8474ef236",
  "parentFolder": [
    "root"
  ],
  "createdTime": "2020-05-18T01:43:49Z",
  "mimeType": "application/x-zip-compressed",
  "fileType": 35,
  "fileName": "demo.zip",
  "sha256": "08a784aeb181506391c20c6355f881dc363d8c3e0739d295e5d6f410d05dbc69",
  "length": 22106481,
  "uploadMode": "multipart",
  "uploadType": 1,
  "autoRename": 2,
  "multiParts": [
    {
      "partNumber": 1,
      "partOffset": 0,
      "partSize": 22106481
    }
  ],
  "description": ""
}
```

## Example Responses

Status code: 200

Information returned after the first step of uploading a file is complete.

```
{  
    "fileId" : "FnkL1QhXj8muHBuSWCHtFFY8Azue44Snr",  
    "containerId" : "IAADfsBFCO6WtAtuA9add2fea594e4e75b8feb8474ef236",  
    "fileName" : "test_20240104_105403.zip",  
    "uploadId" : "0000018CD26464022026422966B8879A",  
    "parentFolder" : [ "DEUI7pa0C24ArootIAADfsBFCO6WtAtuA9add2fea594e4e75b8feb8474ef236" ],  
    "exist" : false,  
    "multiParts" : [ {  
        "partNumber" : 1,  
        "partSize" : 22106481,  
        "partOffset" : 0,  
        "uploadUrl" : "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/  
ff6b221b4b474c829c1cd5037f1504ca086?  
partNumber=1&uploadId=0000018CD26464022026422966B8879A&X-Amz-Algorithm=AWS4-HMAC-  
SHA256&X-Amz-Date=20240104T025403Z&X-Amz-SignedHeaders=content-length%3Bhost&X-Amz-  
Expires=3600&X-Amz-Credential=MKRISPBZAJWFHNB5WLB%2F20240104%2Fcfdc-  
rp-2006%2Fs3%2Faws4_request&X-Amz-  
Signature=39b9b620c8de901682675059cfca9902a13fb5c6ab38fe1451763feb6a8323c"  
    } ],  
    "code" : 0,  
    "msg" : "Success."  
}
```

## Status Codes

| Status Code | Description  |
|-------------|--|
| 200         | Information returned after the first step of uploading a file is complete. |

## 4.15.4 Obtains the upload link.

### Function

Generate the upload link of a file part for multipart upload.

### URI

POST /koodrive/ose/v1/files/multipart/uploadUrl

## Request Parameters

**Table 4-329** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permissions. When an API is called, the token is added to the request header to obtain the operation permissions. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-330** Request body parameters

| Parameter  | Mandatory | Type                                  | Description            |
|------------|-----------|---------------------------------------|------------------------|
| fileId     | Yes       | String                                | File ID.               |
| multiParts | Yes       | Array of <b>MultiPartInfo</b> objects | Part information list. |

**Table 4-331 MultiPartInfo**

| Parameter  | Mandatory | Type           | Description   |
|------------|-----------|----------------|---|
| partNumber | Yes       | Integer        | Part No.  |
| partSize   | Yes       | Long           | Part length. The value range is [5,242,880, 5,368,709,120]. The value range of the last part is [0, 5,368,709,120]. Minimum value: 0. Maximum value: 5,368,709,120.   |
| partOffset | No        | Long           | Total length (in bytes) to the last data block. This parameter is valid only during concurrent multipart upload. The size of all parts except the last one must be a multiple of 64 bytes.  |
| hashCtx    | No        | Array of longs | Context used to iteratively calculate SHA256. This field is valid only during concurrent multipart upload. For SHA1, the value is the first to fifth 32-bit variables of the SHA1 of the previous data block. For SHA256, the value is the first to eighth 32-bit variables of the SHA256 of the previous data block.<br><br>This parameter is mandatory for all parts except the first one in concurrent multipart upload. |
| uploadUrl  | No        | String         | URL for uploading a file, which is a return parameter. The PUT method is required for uploading a file.   |
| partId     | No        | String         | Part object ID.   |

## Response Parameters

**Status code: 200**

**Table 4-332** Response body parameters

| Parameter  | Type   | Description            |
|------------|--|------------------------|
| multiParts | Array of<br><a href="#">MultiPartInfo</a><br>objects | Multipart information. |
| code       | Integer  | Response code.         |
| msg        | String   | Response message.      |

**Table 4-333** MultiPartInfo

| Parameter  | Type           | Description   |
|------------|----------------|---|
| partNumber | Integer        | Part No.  |
| partSize   | Long           | Part length. The value range is [5,242,880, 5,368,709,120]. The value range of the last part is [0, 5,368,709,120].<br>Minimum value: 0.<br>Maximum value: 5,368,709,120.   |
| partOffset | Long           | Total length (in bytes) to the last data block. This parameter is valid only during concurrent multipart upload. The size of all parts except the last one must be a multiple of 64 bytes.  |
| hashCtx    | Array of longs | Context used to iteratively calculate SHA256. This field is valid only during concurrent multipart upload. For SHA1, the value is the first to fifth 32-bit variables of the SHA1 of the previous data block. For SHA256, the value is the first to eighth 32-bit variables of the SHA256 of the previous data block.<br>This parameter is mandatory for all parts except the first one in concurrent multipart upload. |
| uploadUrl  | String         | URL for uploading a file, which is a return parameter. The PUT method is required for uploading a file.   |
| partId     | String         | Part object ID.   |

## Example Requests

Creates file metadata in multipart upload mode. In this example, a file is divided into 46 to 50 parts. The upload link of the part is returned in the subsequent response. The part needs to be uploaded through a PUT request.

```
POST /koodrive/ose/v1/files/multipart/uploadUrl
Authorization:Bearer+10f88*****4791e9ff
{
  "fileId": "Fqo2kYHmsgWg5whxzYZL7mebXbBr1no",
  "multiParts": [
    {
      "hashCtx": [
        1748048713,
        2644528514,
        4267727253,
        2252747490,
        4036182088,
        2253856463,
        526139147,
        2194267752
      ],
      "partNumber": 46,
      "partOffset": 471859200,
      "partSize": 10485760
    },
    {
      "hashCtx": [
        1606212,
        1743131457,
        2392241618,
        605997363,
        3054356113,
        673008609,
        3509469858,
        2186398707
      ],
      "partNumber": 47,
      "partOffset": 482344960,
      "partSize": 10485760
    },
    {
      "hashCtx": [
        3734586607,
        1407828785,
        3243195625,
        3451635323,
        4031416500,
        3005674269,
        2829389145,
        3478923465
      ],
      "partNumber": 48,
      "partOffset": 492830720,
      "partSize": 10485760
    },
    {
      "hashCtx": [
        3677016828,
        906610338,
        3389225168,
        2507561547,
        1134075905,
        3951513567,
        1673174790,
        3034719756
      ],
      "partNumber": 49,
```

```
        "partOffset": 503316480,
        "partSize": 10485760
    },
    {
        "hashCtx": [
            1827691250,
            2956926651,
            1801460777,
            4119662276,
            4162375117,
            187866976,
            1789369655,
            278284511
        ],
        "partNumber": 50,
        "partOffset": 513802240,
        "partSize": 10485760
    }
]
```

## Example Responses

### Status code: 200

Upload information of the corresponding part.

```
{
    "multiParts" : [ {
        "partNumber" : 46,
        "partSize" : 10485760,
        "partOffset" : 471859200,
        "hashCtx" : [ 1748048713, 2644528514, 4267727253, 2252747490, 4036182088, 2253856463,
526139147, 2194267752 ],
        "uploadUrl" : "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/
4e8108ee15fa471cbe5f18f03e8b555b086?"
partNumber=46&uploadId=0000019039E1E8520006EBE63B492EDB&X-Amz-Algorithm=AWS4-HMAC-
SHA256&X-Amz-Date=20240621T082041Z&X-Amz-SignedHeaders=content-length%3Bhost&X-Amz-
Expires=3600&X-Amz-Credential=MKRISPBZAJWFHNB5WLB%2F20240621%2Fcide-
rp-2006%2Fs3%2Faws4_request&X-Amz-Iteration-Hash-
Ctx=eyJtZF9sZW4iOjMyLCJudW0iOjAsImgiOlsxNzQ4MDQ4NzEzLDI2NDQ1Mjg1MTQsNDI2NzcyNzI1MywyMj
UyNzQ3NDkwLDQwMzYxODlwODgsMj1lMzg1NjQ2Myw1MjYxMzkxNDcsMjE5NDI2Nzc1Ml0sIm5oIjowLCJub
Ci6Mzc3NDg3MzYwMCviaGFzaF90eXBlljoic2hhMjU2ln0%3D&X-Amz-
Signature=d3e7f60f45c8fd3960e697c57bb7d1c386dd20940b860fd976ba77425767d65e"
    }, {
        "partNumber" : 47,
        "partSize" : 10485760,
        "partOffset" : 482344960,
        "hashCtx" : [ 1606212, 1743131457, 2392241618, 605997363, 3054356113, 673008609, 3509469858,
2186398707 ],
        "uploadUrl" : "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/
4e8108ee15fa471cbe5f18f03e8b555b086?"
partNumber=47&uploadId=0000019039E1E8520006EBE63B492EDB&X-Amz-Algorithm=AWS4-HMAC-
SHA256&X-Amz-Date=20240621T082041Z&X-Amz-SignedHeaders=content-length%3Bhost&X-Amz-
Expires=3600&X-Amz-Credential=MKRISPBZAJWFHNB5WLB%2F20240621%2Fcide-
rp-2006%2Fs3%2Faws4_request&X-Amz-Iteration-Hash-
Ctx=eyJtZF9sZW4iOjMyLCJudW0iOjAsImgiOlsxNjA2MjEyLDE3NDMxMzE0NTcsMjM5MjI0MTYxOCw2MDU5O
TczNjMsMzA1NDM1NjExMyw2NzMwMDg2MDksMzUwOTQ2OTg1OCwyMTg2Mzk4NzA3XSwibmgijOjAsIm5s
IjozODU4NzU5NjgwLCJoYXNoX3R5cGUiOjzaGEyNTYifQ%3D%3D&X-Amz-
Signature=38980d3be00e528ee11c366ae69e950d673528203f3869a26f39dae42b4dabb"
    }, {
        "partNumber" : 48,
        "partSize" : 10485760,
        "partOffset" : 492830720,
        "hashCtx" : [ 3734586607, 1407828785, 3243195625, 3451635323, 4031416500, 3005674269,
2829389145, 3478923465 ],
        "uploadUrl" : "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/
4e8108ee15fa471cbe5f18f03e8b555b086?"
partNumber=48&uploadId=0000019039E1E8520006EBE63B492EDB&X-Amz-Algorithm=AWS4-HMAC-
```

```
SHA256&X-Amz-Date=20240621T082041Z&X-Amz-SignedHeaders=content-length%3Bhost&X-Amz-Expires=3600&X-Amz-Credential=MKRISPBZAJWFHNB5WLB%2F20240621%2Fcide-rp-2006%2Fs3%2Faws4_request&X-Amz-Iteration-Hash-Ctx=eyJtZF9sZW4iOjMyLCJudW0iOjAslmgIolszNzM0NTg2NjA3LDE0MDc4Mjg3ODUsMzI0MzE5NTYyNSwzNDUxNjM1MzizLDQwMzE0MTY1MDAsMzAwNTY3NDI2OSwyODI5Mzg5MTQ1LDM0Nzg5MjM0NjVdLCJuaCI6MCwibmwiOjM5NDI2NDU3NjAslmhgc2hfdHlwZSI6InNoYTI1NiJ9&X-Amz-Signature=d5608f38d6afdfree117be1243870b63f46ff11676633e0630d122f0c4145e8ae"
}, {
    "partNumber" : 49,
    "partSize" : 10485760,
    "partOffset" : 503316480,
    "hashCtx" : [ 3677016828, 906610338, 3389225168, 2507561547, 1134075905, 3951513567, 1673174790, 3034719756 ],
    "uploadUrl" : "https://b10-obs-ykj-uat-01.obs.cide-rp-2006.joint.cmecloud.cn/4e8108ee15fa471cbe5f18f03e8b555b086?"
partNumber=49&uploadId=0000019039E1E8520006EBE63B492EDB&X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-Date=20240621T082041Z&X-Amz-SignedHeaders=content-length%3Bhost&X-Amz-Expires=3600&X-Amz-Credential=MKRISPBZAJWFHNB5WLB%2F20240621%2Fcide-rp-2006%2Fs3%2Faws4_request&X-Amz-Iteration-Hash-Ctx=eyJtZF9sZW4iOjMyLCJudW0iOjAslmgIolszNjc3MDE2ODI4LDkwNjYxMDMzOCwzMzg5MjI1MTY4LDI1MDc1NjE1NDcsMTEzNDA3NTkwNSwzOTUxNTEzNTY3LDE2NzMxNzQ3OTAsMzAzNDcxOTc1Nl0slm5oljowLCJubCI6NDAyNjUzMTg0MCwiaGFzaF90eXBljoc2hhMjU2In0%3D&X-Amz-Signature=52eb71278fc9310f13a5b92641b5a726d0006be8dd89a242f9c4ce09c360e1f7"
}, {
    "partNumber" : 50,
    "partSize" : 10485760,
    "partOffset" : 513802240,
    "hashCtx" : [ 1827691250, 2956926651, 1801460777, 4119662276, 4162375117, 187866976, 1789369655, 278284511 ],
    "uploadUrl" : "https://b10-obs-ykj-uat-01.obs.cide-rp-2006.joint.cmecloud.cn/4e8108ee15fa471cbe5f18f03e8b555b086?"
partNumber=50&uploadId=0000019039E1E8520006EBE63B492EDB&X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-Date=20240621T082041Z&X-Amz-SignedHeaders=content-length%3Bhost&X-Amz-Expires=3600&X-Amz-Credential=MKRISPBZAJWFHNB5WLB%2F20240621%2Fcide-rp-2006%2Fs3%2Faws4_request&X-Amz-Iteration-Hash-Ctx=eyJtZF9sZW4iOjMyLCJudW0iOjAslmgIolsxODI3NjkxMjUwLDI5NTY5MjY2NTEsMTgwMTQ2MDc3Nyw0MTE5NjYmjc2LDQxNjIzNzUxMTcsMTg3ODY2OTc2LDE3ODkzNjk2NTUsMjc4Mjg0NTEsXSwibmgiOjAslmsljo0MTEwNDE3OTIwLCJoYXNoX3R5cGUiOjzaGEyNTYifQ%3D%3D&X-Amz-Signature=154bcd4ad7774f20e196666d403bf3d4359dd151b9cb1cc1f604c6517c4a287b"
}], "code" : 0,
"msg" : "Success."
}
```

## Status Codes

| Status Code | Description                                   |
|-------------|---|
| 200         | Upload information of the corresponding part. |

## 4.15.5 Checking Whether File Upload Is Completed

### Function

Check the file integrity after the service uploads the complete data of a file. If the file passes the check, the file upload is complete.

### URI

POST /koodrive/ose/v1/files/complete

## Request Parameters

**Table 4-334** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |

**Table 4-335** Request body parameters

| Parameter | Mandatory | Type   | Description                                   |
|-----------|-----------|--------|---|
| fileId    | Yes       | String | ID of the uploaded file.                      |
| sha256    | No        | String | Complete file digest calculated using SHA256. |

## Response Parameters

Status code: 200

**Table 4-336** Response body parameters

| Parameter | Type   | Description       |
|-----------|--------|-------------------|
| code      | String | Response code.    |
| msg       | String | Response message. |

## Example Requests

Combines parts and checks file integrity after the binary data of a file is uploaded.

```
POST /koodrive/ose/v1/files/complete
Authorization: Bearer+10f88*****4791e9ff
{
  "fileId": "FiqNTAYdzXtKhenh29A9EXJvhaKQqcYVS"
}
```

## Example Responses

### Status code: 200

Information returned after the upload is complete.

```
{
  "code" : 0,
  "msg" : "success."
}
```

## Status Codes

| Status Code | Description  |
|-------------|--|
| 200         | Information returned after the upload is complete. |

## 4.15.6 Obtaining Download Links

### Function

Obtain the download links of files.

### URI

```
POST /koodrive/ose/v1/files/download
```

## Request Parameters

**Table 4-337** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |

**Table 4-338** Request body parameters

| Parameter   | Mandatory | Type             | Description   |
|-------------|-----------|------------------|---|
| containerId | Yes       | String           | ID of the space where the files to be obtained are located. |
| fileIds     | Yes       | Array of strings | File ID list. Up to 100 file IDs are allowed.               |

## Response Parameters

Status code: 200

**Table 4-339** Response body parameters

| Parameter | Type   | Description  |
|-----------|--|--|
| code      | Integer  | Response code.   |
| msg       | String   | Response information.  |
| batchCode | Integer  | Response code. <ul style="list-style-type: none"><li>● <b>0</b>: partially successful.</li><li>● <b>1</b>: all successful.</li><li>● <b>2</b>: all failed.</li></ul> |
| downloads | Array of<br><a href="#">DownloadInfoResponse</a> objects | Download link information.   |

**Table 4-340** DownloadInfoResponse

| Parameter | Type   | Description                                   |
|-----------|--------|---|
| fileId    | String | File ID.                                      |
| fileName  | String | File name.                                    |
| url       | String | Download link.                                |
| code      | String | Response code of a single download record.    |
| msg       | String | Response message of a single download record. |

## Example Requests

Obtains the download links of files.

```
POST /koodrive/ose/v1/files/download
Authorization:Bearer+10f88*****4791e9ff
{
  "containerId": "IAADfsBFCO6WtAtuA9add2fea594e4e75b8feb8474ef236",
  "fileIds": [
    "Fn1bTLIOomJkTCAe9DEVBRY4U6IkuqkMZ"
  ]
}
```

## Example Responses

### Status code: 200

Response to the request for obtaining the file download links.

```
{  
    "downloads" : [ {  
        "fileId" : "Fn1bTLIOomJkTCAe9DEVBR4U6IkuqkMZ",  
        "url" : "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/  
5e3fc0c5d4fa45338f44db7177579c2c087?response-content-disposition=attachment%3B%20filename%3D  
%622%25E5%258F%2591%25E7%25A5%25A81.pdf%22&X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-  
Date=20231227T072939Z&X-Amz-SignedHeaders=host&X-Amz-Expires=3600&X-Amz-  
Credential=MKRISPBZAJWFHNB5WLB%2F20231227%2Fcidec-rp-2006%2Fs3%2Faws4_request&X-Amz-  
Signature=9d06798af17e2f1082b720f43af29a32b3154da4ddee4f10025a758b599728a",  
        "fileName" : "Invoice 1.pdf",  
        "code" : "0",  
        "msg" : "success"  
    } ],  
    "batchCode" : 1,  
    "code" : 0,  
    "msg" : "Success."  
}
```

## Status Codes

| Status Code | Description  |
|-------------|--|
| 200         | Response to the request for obtaining the file download links. |

## 4.15.7 Renaming a File

### Function

Rename a file.

### URI

POST /koodrive/ose/v1/files/rename/{fileId}

**Table 4-341** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| fileId    | Yes       | String | File ID.    |

## Request Parameters

**Table 4-342** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-343** Request body parameters

| Parameter   | Mandatory | Type   | Description  |
|-------------|-----------|--------|--|
| containerId | Yes       | String | Space ID.  |
| name        | Yes       | String | New file name, which cannot contain the following characters: '<> :"*? /\', cannot be .. or ., and can contain up to 250 characters. |

| Parameter  | Mandatory | Type    | Description   |
|------------|-----------|---------|---|
| renameMode | Yes       | Integer | Duplicate name policy. <ul style="list-style-type: none"><li>• <b>2:</b> Forcibly renames a file with an existing name by adding a timestamp to the end of the file name.</li><li>• <b>3:</b> Rejects files with the same name. A file with an existing name cannot be created.</li></ul> |

## Response Parameters

**Status code: 200**

**Table 4-344** Response body parameters

| Parameter | Type   | Description       |
|-----------|--------|-------------------|
| code      | String | Response code.    |
| msg       | String | Response message. |

## Example Requests

Renames a file whose ID is **FtSCRFXYtFjo315lPfRHeKRiqrDdmm\_Y** under the space whose ID is **IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4** to **Download**.

```
POST /koodrive/ose/v1/files/rename/FtSCRFXYtFjo315lPfRHeKRiqrDdmm_Y
Authorization: Bearer+10f88*****4791e9ff
{
  "name": "Download",
  "containerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
  "renameMode": 2
}
```

## Example Responses

**Status code: 200**

Information returned after a file is renamed.

```
{
  "code": 0,
  "msg": "success"
}
```

## Status Codes

| Status Code | Description                                   |
|-------------|---|
| 200         | Information returned after a file is renamed. |

## 4.15.8 Clearing the Recycle Bin

### Function

Create an asynchronous task to clear all files in the recycle bin of the space.

### URI

POST /koodrive/ose/v1/files/recycle

### Request Parameters

**Table 4-345** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| X-Date    | Yes       | String | Date, which is used for app authentication.    |
| Host      | Yes       | String | Address, which is used for app authentication. |

**Table 4-346** Request body parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| container | Yes       | String | Space ID.   |

## Response Parameters

**Status code: 200**

**Table 4-347** Response body parameters

| Parameter | Type   | Description       |
|-----------|--------|-------------------|
| code      | String | Response code.    |
| msg       | String | Response message. |

## Example Requests

Clears the files in the recycle bin of the space whose ID is **IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4**.

```
POST /koodrive/ose/v1/files/recycle
Authorization: Bearer+10f88*****4791e9ff
{
  "containerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"
}
```

## Example Responses

**Status code: 200**

Information returned after the recycle bin is cleared.

```
{
  "code": 0,
  "msg": "success"
}
```

## Status Codes

| Status Code | Description  |
|-------------|--|
| 200         | Information returned after the recycle bin is cleared. |

## 4.15.9 Retrieving Files Using Search Engine Capabilities

### Function

Search for files in a space by conditions such as search scope, parent directory, file name, file size range, update time range, and owner. Common users and department administrators can search for their individual and team space. Tenant administrators can search for all team spaces of the tenant.

### URI

POST /koodrive/ose/v1/files/search

### Request Parameters

**Table 4-348** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |

**Table 4-349** Request body parameters

| Parameter    | Mandatory | Type                            | Description  |
|--------------|-----------|---------------------------------|--|
| searchType   | Yes       | String                          | Query type. <ul style="list-style-type: none"><li>• personal: individual space</li><li>• team: team space</li></ul>  |
| pageInfo     | Yes       | <a href="#">pageInfo object</a> | Pagination information.  |
| filter       | No        | <a href="#">filter object</a>   | Filter.  |
| sortInfo     | No        | <a href="#">sortInfo object</a> | Sorting information.   |
| recycled     | No        | Boolean                         | Whether to query the recycle bin. The default value is false. The options are as follows: <ul style="list-style-type: none"><li>• <b>true</b>: Queries files in the recycle bin.</li><li>• <b>false</b>: Queries other files in the space.</li></ul> |
| recursived   | No        | Boolean                         | Whether files in sub-directories are queried recursively. Default value: false.  |
| imageProcess | No        | String                          | Image operation, which can be used to specify the thumbnail size.  |

**Table 4-350** pageInfo

| Parameter | Mandatory | Type    | Description   |
|-----------|-----------|---------|---|
| pageSize  | Yes       | Integer | Size of each page. The value ranges from <b>1</b> to <b>100</b> . |

| Parameter  | Mandatory | Type   | Description  |
|------------|-----------|--------|--|
| pageCursor | Yes       | String | Start cursor. If this parameter is null, the query starts from the first page. |

**Table 4-351 filter**

| Parameter    | Mandatory | Type   | Description   |
|--------------|-----------|--------|---|
| keyWord      | No        | String | File name. Fuzzy match is supported. The value contains up to 80 characters.  |
| containerId  | No        | String | Space ID. This parameter is mandatory when the parent directory is specified. |
| parentFolder | No        | String | Parent directory.   |

| Parameter       | Mandatory | Type   | Description  |
|-----------------|-----------|--------|--|
| fileType        | No        | String | File type. Enumerated values:<br>/**<br>* Folder<br>/ FOLDER("10"), /*<br>* Smart folder (available only<br>to whitelisted users)<br>/ SMART_FOLDER("11"), /*<br>* Image<br>/ PICTURE("15"), /*<br>* Video<br>/ VIDEO("20"), /*<br>* Word file<br>/ WORD("26"), /*<br>* Excel file<br>/ EXCEL("27"), /*<br>* PowerPoint file<br>/ PPT("28"), /*<br>* Audio<br>/ AUDIO("30"), /*<br>* Compressed file<br>/ ARCHIVE("35"), /*<br>* Application<br>/ APPLICATION("40"), /*<br>* Other<br>*/<br>OTHER("45"); |
| updateTimeRange | No        | String | Update time range.   |
| ownerId         | No        | String | File owner.  |

**Table 4-352 sortInfo**

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| sortType      | No        | String | Enumerated values:<br><ul style="list-style-type: none"><li>• <b>fileName</b>: file name.</li><li>• <b>size</b>: file size.<br/>-** type**: file format.</li><li>• <b>updateTime</b>: update time.</li><li>• <b>createTime</b>: creation time.</li><li>• <b>recycledTime</b>: deletion time.</li><li>• <b>fileSuffix</b>: file sub-category.</li></ul> |
| sortDirection | No        | String | Enumerated values:<br><ul style="list-style-type: none"><li>• <b>desc</b>: descending order.</li><li>• <b>asc</b>: ascending order.</li></ul>  |

## Response Parameters

**Status code: 200**

**Table 4-353 Response body parameters**

| Parameter      | Type                          | Description   |
|----------------|-------------------------------|---|
| code           | Integer                       | Response code. <b>0</b> indicates success. Other values indicate failure. |
| msg            | String                        | Success and error information.  |
| files          | Array of <b>files</b> objects | Search results  |
| total          | Integer                       | Total number of records.  |
| nextPageCursor | String                        | Start cursor of the next page. It is null for the last page.              |

**Table 4-354 files**

| Parameter  | Type   | Description  |
|------------|--------|--------------|
| id         | String | File ID.     |
| fileSuffix | String | File suffix. |
| fileName   | String | File name.   |

| Parameter     | Type   | Description   |
|---------------|--|---|
| fileType      | String   | File type.  |
| size          | String   | File size.  |
| updateTime    | String   | Update time.  |
| namePath      | String   | Full name path.   |
| idPath        | String   | Full ID path.   |
| downloadLinks | Array of<br><a href="#">downLoadLinks</a><br>objects | Thumbnail link, which is returned for an image.   |
| teamName      | String   | Department name or group space name returned for the team space.  |
| teamId        | String   | Group ID, that is, department ID or group ID.   |
| containerId   | String   | Space ID.   |
| containerType | String   | <b>0:</b> department space; <b>1:</b> individual space; <b>2:</b> group space.  |
| favorite      | Boolean  | Whether the file returned by the individual space or team space is added to favorites by the current user.  |
| owner         | String   | Owner name returned for the team space.   |
| attachments   | <a href="#">Attachment</a><br>object                 | Attachment.   |
| createTime    | String   | Creation time.  |
| editTime      | String   | Editing time.   |
| lastEditor    | <a href="#">User</a> object                          | Last editor.  |
| contentType   | String   | Content type.<br>Content type.  |
| ownerId       | String   | Owner ID.   |
| owners        | Array of <a href="#">User</a><br>objects             | Owner.  |
| parentFolder  | Array of strings                                     | List of the parent directory IDs. Currently, only the first ID is used.   |
| properties    | Map<String, String<br>>                              | Common user-defined attributes of the file. The number of key-value pairs cannot exceed 30. A single key-value pair can contain up to 124 characters. |

| Parameter        | Type  | Description                                   |
|------------------|---|---|
| recycled         | Boolean   | Whether the file is moved to the recycle bin. |
| sha256           | String  | sha256  |
| userCapabilities | <a href="#">userCapabilities</a> object                     | User permissions.                             |
| userProperties   | Array of <a href="#">FileListPrivate-Properties</a> objects | Extended user attributes.                     |

**Table 4-355** downLoadLinks

| Parameter    | Type   | Description  |
|--------------|--------|--|
| usage        | String | Usage. The value can be <b>thumbnail</b> or <b>content</b> . |
| downloadLink | String | Image address.   |

**Table 4-356** Attachment

| Parameter    | Type                         | Description   |
|--------------|------------------------------|---|
| usage        | String                       | Default usage: <b>content</b> or <b>thumbnail</b> . This parameter is customizable. |
| assetId      | String                       | Asset ID  |
| length       | Long                         | File size.  |
| versionId    | String                       | Asset version ID.   |
| contentType  | String                       | MIME type.  |
| hash         | String                       | Hash of the resource associated with the asset.                                     |
| sha256       | String                       | SHA256 of the resource associated with the asset.                                   |
| createdTime  | String                       | Time when the data is created.  |
| modifiedTime | String                       | Time when the data is last modified.  |
| attributes   | Map<String, Object>          | Type attributes.  |
| asset        | <a href="#">Asset</a> object | Asset.  |

**Table 4-357 Asset**

| Parameter         | Type                            | Description  |
|-------------------|---------------------------------|--|
| id                | String                          | Asset ID   |
| versionId         | String                          | Asset version ID.  |
| version           | Long                            | Version number.  |
| mimeType          | String                          | MIME type  |
| keepPolicy        | Integer                         | Storage policy of historical versions. <ul style="list-style-type: none"><li>● <b>0:</b> automatic clearance. Two versions are retained. The earliest version is deleted when the third version is added. (This prevents obtaining failures in concurrent scenarios.)</li><li>● <b>1:</b> permanent storage.</li></ul> |
| state             | Integer                         | Data status. <ul style="list-style-type: none"><li>● <b>0:</b> available.</li><li>● <b>1:</b> unavailable.</li><li>● <b>2:</b> temporary.</li><li>● <b>3:</b> retained (flash upload unsupported).</li><li>● <b>4:</b> to be cut over.</li></ul>   |
| createdTime       | String                          | Time when the data is created.   |
| modifiedTime      | String                          | Time when the data is last modified.   |
| lastModifyingUser | String                          | UPID of the user that last modifies the data.  |
| resource          | <a href="#">Resource object</a> | Resource.  |
| cipher            | <a href="#">Cipher object</a>   | Cipher.  |

| Parameter  | Type                | Description  |
|------------|---------------------|--|
| attributes | Map<String, Object> | Type attributes. A key consists of letters and digits and starts with a letter. A value cannot contain emojis. The size of an attribute is not limited, but the total size cannot exceed 16 KB.<br>Attribute options: <ul style="list-style-type: none"><li>• <b>pictureMetadata</b>: image attribute data. For details, see the definition of <b>PictureMetadata</b>.</li><li>• <b>videoMetadata</b>: video attribute data. For details, see the definition of <b>VideoMetadata</b>.</li><li>• <b>audioMetadata</b>: audio attribute data. For details, see the definition of <b>AudioMetadata</b>.</li><li>• <b>contentDisposition</b>: used when <b>response-content-disposition</b> is not specified for the downloaded attachment (valid when <b>resource.type</b> is set to 12).</li></ul> |
| properties | Map<String, String> | Extended attributes.   |

**Table 4-358** Resource

| Parameter | Type    | Description   |
|-----------|---------|---|
| id        | String  | ID of the file resource.  |
| hash      | String  | Hash of the file resource.  |
| length    | Long    | Size of the file resource.  |
| sha256    | String  | SHA256 of the file (used for integrity check).  |
| type      | Integer | Resource type. <ul style="list-style-type: none"><li>• 0: ciphertext multipart file.</li><li>• 3: plaintext multipart file.</li><li>• 12: plaintext single-part file.</li></ul> |

| Parameter    | Type                                | Description  |
|--------------|-------------------------------------|--|
| state        | Integer                             | Data status. <ul style="list-style-type: none"><li>● <b>0</b>: available.</li><li>● <b>1</b>: unavailable.</li><li>● <b>2</b>: temporary.</li><li>● <b>3</b>: retained (flash upload unsupported).</li><li>● <b>4</b>: to be cut over.</li></ul> |
| sliceSize    | Long                                | Part size.   |
| hfek         | String                              | Hash of the FEK of the encrypted file. This parameter is applicable when <b>type</b> is set to <b>0</b> .  |
| iv           | String                              | IV of the encrypted file. This parameter is applicable when <b>type</b> is set to <b>0</b> .   |
| createdTime  | String                              | Time when the data is created.   |
| modifiedTime | String                              | Time when the data is last modified.   |
| objects      | Array of <b>SliceObject</b> objects | Part object, which is applicable when <b>type</b> is set to <b>0</b> or <b>3</b> .   |
| attributes   | Map<String, Object>                 | Type attributes.   |
| properties   | Map<String, String >                | Extended attributes.   |

**Table 4-359 SliceObject**

| Parameter | Type    | Description  |
|-----------|---------|--|
| id        | String  | Part ID.   |
| number    | Integer | Part No., starting from 0. This parameter is not applicable when <b>type</b> is set to <b>12</b> . |
| start     | Long    | Start position of a part, which is not applicable when <b>type</b> is set to <b>12</b> .           |
| sha256    | String  | SHA256 of the part (or SHA256 of the ciphertext if the part is encrypted.)                         |
| length    | Long    | Part length (or ciphertext length if the part is encrypted).                                       |
| bucket    | String  | OBS bucket information.  |

| Parameter    | Type                                    | Description   |
|--------------|---|---|
| createdTime  | String                                  | Time when the data is created.  |
| modifiedTime | String                                  | Time when the data is last modified.  |
| uploadUrl    | <a href="#">EndpointURL</a> object      | Upload URL.   |
| downloadUrl  | <a href="#">EndpointURL</a> object      | Download URL.   |
| uploadId     | String                                  | Multipart upload ID. This parameter is applicable when <b>type</b> is set to <b>12</b> and <b>uploadMode</b> is set to <b>multipart</b> . |
| attributes   | Map<String, Object>                     | Type attributes.  |
| properties   | Map<String, String >                    | Extended attributes.  |
| images       | Array of <a href="#">Images</a> objects | Thumbnail.  |

**Table 4-360** EndpointURL

| Parameter | Type                 | Description  |
|-----------|----------------------|--|
| url       | String               | URL  |
| method    | String               | http method  |
| headers   | Map<String, String > | http headers   |
| forms     | Map<String, String > | Form parameter, which is applicable when <b>type</b> is set to <b>12</b> and <b>uploadMode</b> is set to <b>post</b> .           |
| partId    | String               | Multipart parameter, which is applicable when <b>type</b> is set to <b>12</b> and <b>uploadMode</b> is set to <b>multipart</b> . |

**Table 4-361** Images

| Parameter   | Type                               | Description                                |
|-------------|------------------------------------|--|
| process     | String                             | File resource name.                        |
| downloadUrl | <a href="#">EndpointURL</a> object | URL structure for file upload or download. |

**Table 4-362** EndpointURLMetadata

| Parameter | Type   | Description |
|-----------|--------|-------------|
| url       | String | URL         |
| method    | String | http method |

**Table 4-363** Cipher

| Parameter | Type                             | Description   |
|-----------|----------------------------------|---|
| algorithm | String                           | Encryption algorithm.   |
| hfek      | String                           | Hash of the FEK of the encrypted file. This parameter is applicable when <b>type</b> is set to <b>0</b> or <b>4</b> . |
| iv        | String                           | IV of the encrypted file. This parameter is applicable when <b>type</b> is set to <b>0</b> or <b>4</b> .              |
| dataType  | Integer                          | Data type. <ul style="list-style-type: none"><li>• <b>11:</b> sync drive.</li></ul>                                   |
| keychains | Array of <b>Keychain</b> objects | Keychain.   |

**Table 4-364** Keychain

| Parameter | Type    | Description   |
|-----------|---------|---|
| id        | String  | Key UUID.   |
| type      | Integer | Key type. <ul style="list-style-type: none"><li>• <b>1:</b> efek.</li><li>• <b>2:</b> zfek.</li><li>• <b>3:</b> sfek.</li></ul> |
| algorithm | String  | Encryption algorithm.   |
| ekey      | String  | Encrypted key.  |

**Table 4-365** User

| Parameter | Type   | Description                            |
|-----------|--------|--|
| category  | String | Type. The value is <b>drive#user</b> . |
| userId    | String | Huawei user ID.                        |

| Parameter    | Type    | Description               |
|--------------|---------|---------------------------|
| displayName  | String  | Display name of the user. |
| me           | Boolean | Whether you are the user. |
| permissionId | String  | Permission ID.            |

**Table 4-366** userCapabilities

| Parameter                 | Type    | Description   |
|---------------------------|---------|---|
| addChildNodePermission    | Boolean | Whether the user can add sub-directories or sub-files.  |
| copyPermission            | Boolean | Whether the user can copy files.                        |
| deletePermission          | Boolean | Whether the user can delete files.                      |
| downloadPermission        | Boolean | Whether the user can download content.                  |
| editPermission            | Boolean | Whether the user can edit files.                        |
| listChildNodePermission   | Boolean | Whether the user can list sub-directories or sub-files. |
| removeChildNodePermission | Boolean | Whether the user can move sub-directories.              |
| renameFilePermission      | Boolean | Whether the user can rename files.                      |
| shareFilePermission       | Boolean | Whether the user can share files.                       |
| uploadPermission          | Boolean | Whether the user can upload files.                      |
| viewPermission            | Boolean | Whether the user can preview files.                     |

**Table 4-367** FileListPrivateProperties

| Parameter  | Type                | Description  |
|------------|---------------------|--|
| properties | Map<String, String> | Extended attributes (The size of a single attribute is not limited, but the total size cannot exceed 16 KB.) |

## Example Requests

Example request for searching for a file.

```
POST /koodrive/ose/v1/files/search

Authorization:Bearer+10f88*****4791e9ff
{
  "searchType" : " personal/team",
  "pageInfo" : {
    "pageSize" : 100,
    "pageCursor" : 1
  },
  "filter" : {
    "keyWord" : "Material",
    "containerId" : "123456",
    "parentFolder" : "1",
    "fileType" : "1",
    "sizeRang" : "1024,2048",
    "updateTimeRange" : "2023-11-02,2023-11-21",
    "ownerId" : "Owner ID"
  }
}
```

## Example Responses

**Status code: 200**

Search results

```
{
  "files" : [ {
    "id" : "Fu2A5BQZ1qUk3h1tU6ZIAS66swzlN9mnJ",
    "sha256" : "57eafb818ad716aa11b443fb9fc2c1f23875f0c8da49035a8ca98136e4525632",
    "fileName" : "KooDrive Service Overview.docx",
    "fileSuffix" : "docx",
    "fileType" : "26",
    "size" : "705395",
    "updateTime" : "2024-12-25T06:41:22.873Z",
    "idPath" : "DFCz6PEuDwlArootIAAFWbRXM-jxLg8CA1578177668157825025",
    "downloadLinks" : [ {
      "usage" : "content",
      "downloadLink" : "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/18ad967c9af047fd8b909ed163c0fdb6086?response-content-disposition=attachment%3B%20filename%2A%3DUTF-8%27%27KooDrive%25E6%259C%258D%25E5%258A%25A1%25E4%25BB%258B%25E7%25BB%258D.docx&X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-Date=20250103T023324Z&X-Amz-SignedHeaders=host&X-Amz-Expires=3600&X-Amz-Credential=MKRISPBZAJWFHNB5WLB%2F20250103%2Fcide-rp-2006%2Fs3%2Faws4_request&X-Amz-Signature=e518a982307ef9b6d6e4bd8788e421d3488f58f3ed79eb3ab42702ac5c3d7513",
      "usage" : "thumbnail",
      "downloadLink" : "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/18ad967c9af047fd8b909ed163c0fdb6086?x-image-process=image%2Fresize%2Cm_lfit%2Ch_128%2Cw_128&response-content-disposition=attachment%3B%20filename%2A%3DUTF-8%27%27KooDrive%25E6%259C%258D%25E5%258A%25A1%25E4%25BB%258B%25E7%25BB%258D.docx&X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-Date=20250103T023324Z&X-Amz-SignedHeaders=host&X-Amz-Expires=3600&X-Amz-Credential=MKRISPBZAJWFHNB5WLB%2F20250103%2Fcide-rp-2006%2Fs3%2Faws4_request&X-Amz-Signature=ad55a09e66ddd32c6f9b3cce08c7c9a867c7a579a41200f415fb2918de1ab473"
    } ],
    "teamName" : "fdsgdsf",
    "teamId" : "1578175198769733633",
    "containerId" : "IAAFWbRXM-jxLg8CA1578177668157825025",
    "containerType" : "0",
    "favorite" : false,
    "owner" : "hid42638091",
    "ownerId" : "1568722386902108288",
    "properties" : {
      "localCreatedAt" : "",
      "localUpdatedAt" : "",
      "createUser" : "1568722386902108288",
      "lastEditUser" : "1568722386902108288",
      "auditResult" : "{\"auditDetail\":\"{}\",\"auditLevel\":10,\"auditResult\":1}"
    }
  } ]
```

```
        },
        "attachments" : [ {
            "assetId" : "1584078561541652992",
            "asset" : {
                "id" : "1584078561541652992",
                "versionId" : "1584078561541652993",
                "version" : 49923,
                "mimeType" : "application/vnd.openxmlformats-officedocument.wordprocessingml.document",
                "state" : 0,
                "createdTime" : "2024-12-25T06:41:20.050Z",
                "modifiedTime" : "2024-12-25T06:41:20.050Z",
                "resource" : {
                    "id" : "1584078561810055808",
                    "length" : 705395,
                    "sha256" : "57eafb818ad716aa11b443fb9fc2c1f23875f0c8da49035a8ca98136e4525632",
                    "object" : {
                        "id" : "18ad967c9af047fd8b909ed163c0fdb6086",
                        "start" : 0,
                        "downloadUrl" : {
                            "url" : "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/
18ad967c9af047fd8b909ed163c0fdb6086?response-content-disposition=attachment%3B%20filename%2A
%3DUTF-8%27%27KooDrive%25E6%259C%258D%25E5%258A%25A1%25E4%25BB%258B%25E7%25BB
%258D.docx&X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-Date=20250103T023324Z&X-Amz-
SignedHeaders=host&X-Amz-Expires=3600&X-Amz-Credential=MKRISPBZAJWFHNB5WLB
%2F20250103%2Fcidec-rp-2006%2Fs3%2Faws4_request&X-Amz-
Signature=e518a982307ef9b6d6e4bd8788e421d3488f58f3ed79eb3ab42702ac5c3d7513",
                            "method" : "GET"
                        },
                        "images" : [ {
                            "process" : "image/resize,m_lfit,h_128,w_128",
                            "downloadUrl" : {
                                "url" : "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/
18ad967c9af047fd8b909ed163c0fdb6086?x-image-process=image%2Fresize%2Cm_lfit
%2Ch_128%2Cw_128&response-content-disposition=attachment%3B%20filename%2A
%3DUTF-8%27%27KooDrive%25E6%259C%258D%25E5%258A%25A1%25E4%25BB%258B%25E7%25BB
%258D.docx&X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-Date=20250103T023324Z&X-Amz-
SignedHeaders=host&X-Amz-Expires=3600&X-Amz-Credential=MKRISPBZAJWFHNB5WLB
%2F20250103%2Fcidec-rp-2006%2Fs3%2Faws4_request&X-Amz-
Signature=ad55a09e66ddd32c6f9b3cce08c7c9a867c7a579a41200f415fb2918de1ab473",
                            "method" : "GET"
                        }
                    }
                }
            }
        }
    ],
    "attributes" : {
        "fileName" : "KooDrive Service Overview.docx",
        "localCreatedAt" : "",
        "createdBy" : "667706171d1c4ef2a4d7464f3656066c",
        "resource" : {
            "id" : "1584078561810055808",
            "object" : {
                "bucket" : "b10-obs-ykj-uat-01",
                "objectId" : "18ad967c9af047fd8b909ed163c0fdb6086"
            }
        },
        "localUpdatedAt" : ""
    }
},
"versionId" : "1584078561541652993",
"attributes" : {
    "fileName" : "KooDrive Service Overview.docx",
    "localCreatedAt" : "",
    "createdBy" : "667706171d1c4ef2a4d7464f3656066c",
    "resource" : {
        "id" : "1584078561810055808",
        "object" : {
            "bucket" : "b10-obs-ykj-uat-01",
            "objectId" : "18ad967c9af047fd8b909ed163c0fdb6086"
        }
    }
}
```

```
        },
        "localUpdatedAt" : "",
    },
    "hash" : "57eafb818ad716aa11b443fb9fc2c1f23875f0c8da49035a8ca98136e4525632",
    "length" : 705395,
    "mimeType" : "application/vnd.openxmlformats-officedocument.wordprocessingml.document",
    "usage" : "content",
    "sha256" : "57eafb818ad716aa11b443fb9fc2c1f23875f0c8da49035a8ca98136e4525632",
    "createdTime" : "2024-12-25T06:41:20.050Z",
    "modifiedTime" : "2024-12-25T06:41:20.050Z"
} ],
"createdTime" : "2024-12-25T06:41:19.794Z",
"editedTime" : "2024-12-25T06:41:22.873Z",
"lastEditor" : {
    "category" : "drive#user",
    "me" : true,
    "permissionId" : "1570905506917367936",
    "userId" :
"NDEzMmA4NjAwMDAwMjc0MTY2NS02Njc3MDYxNzFkMWM0ZWYyYTRkNzQ2NGYzNjU2MDY2Yw",
    "displayName" : "hid42638091"
},
"mimeType" : "application/vnd.openxmlformats-officedocument.wordprocessingml.document",
"owners" : [ {
    "category" : "drive#user",
    "me" : true,
    "permissionId" : "1570905506917367936",
    "userId" :
"NDEzMmA4NjAwMDAwMjc0MTY2NS02Njc3MDYxNzFkMWM0ZWYyYTRkNzQ2NGYzNjU2MDY2Yw"
} ],
"parentFolder" : [ "DFcz6PEuDwlArootIAAFWbRXM-jxLg8CA1578177668157825025" ],
"recycled" : false,
"userProperties" : {
    "properties" : {
        "hidden" : "false"
    }
},
"userCapabilities" : {
    "addChildNodePermission" : true,
    "copyPermission" : true,
    "deletePermission" : true,
    "downloadPermission" : true,
    "editPermission" : true,
    "listChildNodePermission" : true,
    "removeChildNodePermission" : true,
    "renameFilePermission" : true,
    "shareFilePermission" : true,
    "uploadPermission" : true,
    "viewPermission" : true
}
},
"total" : 1,
"code" : 0,
"msg" : "Successful."
}
```

## Status Codes

| Status Code | Description    |
|-------------|----------------|
| 200         | Search results |

## 4.15.10 Collecting Folder Statistics

### Function

Collect statistics on the number of directories, number of files, and total file size in a folder.

### URI

GET /koodrive/ose/v1/files/statsDir

**Table 4-368** Query Parameters

| Parameter   | Mandatory | Type    | Description   |
|-------------|-----------|---------|---|
| fileId      | Yes       | String  | Directory ID.   |
| containerId | Yes       | String  | ID of the space to which the directory belongs.                 |
| recursive   | No        | Boolean | Whether to recursively upload files. The default value is true. |

### Request Parameters

**Table 4-369** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permissions. When an API is called, the token is added to the request header to obtain the operation permissions. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |

| Parameter | Mandatory | Type   | Description  |
|-----------|-----------|--------|--|
| Host      | Yes       | String | Address, which is used for app authentication.   |
| language  | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default. |

## Response Parameters

Status code: 200

**Table 4-370** Response body parameters

| Parameter | Type                    | Description           |
|-----------|-------------------------|-----------------------|
| code      | String                  | Response code.        |
| msg       | String                  | Response information. |
| data      | <b>StatsData</b> object | Data.                 |

**Table 4-371** StatsData

| Parameter    | Type   | Description                     |
|--------------|--------|---------------------------------|
| totalSize    | String | Total file size.                |
| subDirCount  | String | Total number of subdirectories. |
| subFileCount | String | Total number of subfiles.       |

## Example Requests

Query the number of directories, number of files, and total file size in directory FnNGsBnXUdIW7AycSK4ZCTlPJ6JO1\_sF.

```
POST /koodrive/ose/v1/files/statsDir?  
fileId=FnNGsBnXUdIW7AycSK4ZCTlPJ6JO1_sF&containerId=IAAGvmhWei6Q7A4-  
A1557836058161393920&recursive=true
```

```
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

### Status code: 200

Search results.

```
{  
  "code" : 0,  
  "msg" : "success",  
  "data" : {  
    "totalSize" : 0,  
    "subDirCount" : 1,  
    "subFileCount" : 0  
  }  
}
```

## Status Codes

| Status Code | Description     |
|-------------|-----------------|
| 200         | Search results. |

## 4.15.11 Obtaining the Full Name and ID Paths of a File

### Function

Obtain the full name and ID paths of a file.

### URI

GET /koodrive/ose/v1/files/path

**Table 4-372** Query Parameters

| Parameter   | Mandatory | Type   | Description |
|-------------|-----------|--------|-------------|
| fileId      | Yes       | String | File ID.    |
| containerId | Yes       | String | Space ID.   |

## Request Parameters

**Table 4-373** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-374** Response body parameters

| Parameter  | Type   | Description               |
|------------|--------|---------------------------|
| code       | String | Response code.            |
| msg        | String | Response message.         |
| fileIdPath | String | Full path of the file ID. |

| Parameter | Type   | Description                 |
|-----------|--------|-----------------------------|
| namePath  | String | Full path of the file name. |

## Example Requests

Queries the full directory path of a file.

```
GET /koodrive/ose/v1/files/path?  
fileId=FqS6hLLy_DkjIWdfOnEdCErhsmokRvdXI&containerId=IAADfsBFCO6WtAtuA315074383680425b8aa9a1  
30cba2d4  
  
Authorization:Bearer+10f88*****4791e9ff
```

## Example Responses

**Status code: 200**

Full path information.

```
{  
    "filePath" : "/DEUI7pa0C24ArootIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4/  
FkbdCAceMj89bprz5xLJASID1eaRqjlRP/FqlAmBlz7ovbThxeUBIOpbnCHaP_MTUL/  
FqS6hLLy_DkjIWdfOnEdCErhsmokRvdXI",  
    "namePath" : "/rootIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4/007/001/Batch Task Test",  
    "code" : 0,  
    "msg" : "OK"  
}
```

## Status Codes

| Status Code | Description            |
|-------------|------------------------|
| 200         | Full path information. |

## 4.16 File Favorites

### 4.16.1 Adding Files to Favorites

#### Function

Add files to favorites or remove files from favorites. Up to 100 files are supported.

#### URI

POST /koodrive/ose/v1/star/batch

## Request Parameters

**Table 4-375** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-376** Request body parameters

| Parameter      | Mandatory | Type   | Description                           |
|----------------|-----------|--|---------------------------------------|
| starred        | Yes       | Boolean  | Whether files are added to favorites. |
| subRequestList | Yes       | Array of <a href="#">StarFileRequest</a> objects | Files to be added to favorites.       |

**Table 4-377** StarFileRequest

| Parameter   | Mandatory | Type   | Description                    |
|-------------|-----------|--------|--------------------------------|
| containerId | Yes       | String | Space ID.                      |
| fileId      | Yes       | String | File ID, which must be unique. |

## Response Parameters

**Status code: 200**

**Table 4-378** Response body parameters

| Parameter       | Type                                      | Description   |
|-----------------|---|---|
| status          | Integer                                   | Response status. <b>0</b> : all successful; <b>1</b> : partially successful; <b>2</b> : all failed. |
| subResponseList | Array of<br><b>SubResponse</b><br>objects | Sub-response list.  |
| code            | String                                    | Response code.  |
| msg             | String                                    | Response information.   |

**Table 4-379** SubResponse

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| fileId    | String | File ID.              |
| code      | String | Response code.        |
| message   | String | Response information. |

## Example Requests

```
{  
    "starred": true,  
    "subRequestList": [ {  
        "containerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",  
        "fileId": "Fn1bTLIOomJkTCAe9DEVBRY4U6IkuqkMZ"  
    } ]  
}
```

## Example Responses

**Status code: 200**

OK

```
{  
    "status": 0,  
    "subResponseList": [ {  
        "fileId": "Fn1bTLIOomJkTCAe9DEVBRY4U6IkuqkMZ",  
        "code": "0",  
        "message": "success"  
    } ]  
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.16.2 Listing Files in Favorites

### Function

List files in favorites. Up to 100 files are supported each time.

### URI

GET /koodrive/ose/v1/star/files

**Table 4-380** Query Parameters

| Parameter     | Mandatory | Type    | Description   |
|---------------|-----------|---------|---|
| pageSize      | No        | Integer | Number of records to be returned on each page. Default and maximum value: 100. It is possible that partial or empty result pages are returned before the end of the result list has been reached. |
| pageCursor    | No        | String  | Current page cursor, which is obtained from <b>nextCursor</b> of the previous response.   |
| sortType      | No        | Integer | Sorting type. <b>1</b> : by the time when a file is added to favorites (default).   |
| sortDirection | No        | Integer | Sorting order. <b>1</b> : ascending; <b>2</b> : descending (default).   |

| Parameter    | Mandatory | Type   | Description   |
|--------------|-----------|--------|---|
| fileType     | No        | String | File type. <ul style="list-style-type: none"><li>● <b>10</b>: folder.</li><li>● <b>11</b>: smart folder (available only to whitelisted users).</li><li>● <b>15</b>: image.</li><li>● <b>20</b>: video.</li><li>● <b>26</b>: Word file.</li><li>● <b>27</b>: Excel file.</li><li>● <b>28</b>: PowerPoint file.</li><li>● <b>30</b>: audio.</li><li>● <b>35</b>: compressed file.</li><li>● <b>40</b>: application.</li><li>● <b>45</b>: other.</li></ul> |
| imageProcess | No        | String | Image operation, which can be used to specify the thumbnail size.   |

## Request Parameters

**Table 4-381** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| Host      | Yes       | String | Address, which is used for app authentication. |

## Response Parameters

Status code: 200

**Table 4-382** Response body parameters

| Parameter   | Type  | Description  |
|-------------|---|--|
| nextCursor  | String  | Pagination cursor. If the cursor does not exist, the last record has been returned.  |
| autoDeleted | Integer   | Number of automatically deleted files (original files have been physically deleted). |
| starFiles   | Array of<br><a href="#">StarFileInfo</a><br>objects | Favorite file information.   |
| code        | String  | Response code.   |
| msg         | String  | Response information.  |

**Table 4-383** StarFileInfo

| Parameter    | Type             | Description   |
|--------------|------------------|---|
| category     | String           | Type. The value is <b>drive#file</b> .                              |
| id           | String           | File ID.  |
| fileName     | String           | File name, which contains up to 250 characters.                     |
| fileType     | String           | File type, which is input externally.                               |
| mimeType     | String           | Content type.   |
| favorite     | Boolean          | Whether the file is added to favorites.                             |
| recycled     | Boolean          | Whether the file is moved to the recycle bin.                       |
| parentFolder | Array of strings | List of parent directory IDs. Currently, only the first ID is used. |

| Parameter      | Type  | Description   |
|----------------|---|---|
| properties     | Map<String, String>                           | Common user-defined attributes of the file. The number of key-value pairs cannot exceed 30. A single key-value pair can contain up to 124 characters.                               |
| containers     | Array of strings                              | Space ID.   |
| createdTime    | String  | File creation time.   |
| editedTime     | String  | File modification time.   |
| editedByMe     | Boolean                                       | Whether the file is modified by you.  |
| owners         | Array of <a href="#">User</a> objects         | Owner.  |
| lastEditor     | <a href="#">User</a> object                   | Last editor.  |
| fullFileSuffix | String  | Complete file name extension, which is the characters following the first period (.) in the name.   |
| fileSuffix     | String  | File name extension, which is the last character string of <b>fullFileExtension</b> .   |
| size           | Integer                                       | File size.  |
| sha256         | String  | SHA256 of the file.   |
| attachments    | Array of <a href="#">Attachment</a> objects   | Attachment (purpose and attachment). Only the app ID of the risk control service is returned.   |
| downloadLinks  | Array of <a href="#">DownloadLink</a> objects | Link for downloading FileProxy files.   |
| userProperties | <a href="#">PrivateProperties</a> object      | User attributes.  |
| starredTime    | String  | Time when the file is added to favorites.   |
| filePath       | String  | File location, specific to the team name.   |
| spaceType      | String  | Space type. <ul style="list-style-type: none"><li>● 1: individual space.</li><li>● 2: team space.</li><li>● 3: recycle bin.</li><li>● 4: space without access permission.</li></ul> |
| invalid        | Integer                                       | Whether the file has expired. *0: normal; 1: expired.   |

| Parameter        | Type                                    | Description                 |
|------------------|---|-----------------------------|
| hidden           | Boolean                                 | Whether the file is hidden. |
| userCapabilities | <a href="#">userCapabilities</a> object | User permissions.           |

**Table 4-384** User

| Parameter    | Type    | Description                            |
|--------------|---------|--|
| category     | String  | Type. The value is <b>drive#user</b> . |
| userId       | String  | Huawei user ID.                        |
| displayName  | String  | Display name of the user.              |
| me           | Boolean | Whether you are the user.              |
| permissionId | String  | Permission ID.                         |

**Table 4-385** Attachment

| Parameter    | Type                         | Description   |
|--------------|------------------------------|---|
| usage        | String                       | Default usage: <b>content</b> or <b>thumbnail</b> . This parameter is customizable. |
| assetId      | String                       | Asset ID  |
| length       | Long                         | File size.  |
| versionId    | String                       | Asset version ID.   |
| mimeType     | String                       | MIME type.  |
| hash         | String                       | Hash of the resource associated with the asset.                                     |
| sha256       | String                       | SHA256 of the resource associated with the asset.                                   |
| createdTime  | String                       | Time when the data is created.  |
| modifiedTime | String                       | Time when the data is last modified.  |
| attributes   | Map<String, Object>          | Type attributes.  |
| asset        | <a href="#">Asset</a> object | Asset.  |

**Table 4-386 Asset**

| Parameter         | Type                            | Description  |
|-------------------|---------------------------------|--|
| id                | String                          | Asset ID   |
| versionId         | String                          | Asset version ID.  |
| version           | Long                            | Version number.  |
| mimeType          | String                          | MIME type  |
| keepPolicy        | Integer                         | Storage policy of historical versions. <ul style="list-style-type: none"><li>● <b>0:</b> automatic clearance. Two versions are retained. The earliest version is deleted when the third version is added. (This prevents obtaining failures in concurrent scenarios.)</li><li>● <b>1:</b> permanent storage.</li></ul> |
| state             | Integer                         | Data status. <ul style="list-style-type: none"><li>● <b>0:</b> available.</li><li>● <b>1:</b> unavailable.</li><li>● <b>2:</b> temporary.</li><li>● <b>3:</b> retained (flash upload unsupported).</li><li>● <b>4:</b> to be cut over.</li></ul>   |
| createdTime       | String                          | Time when the data is created.   |
| modifiedTime      | String                          | Time when the data is last modified.   |
| lastModifyingUser | String                          | UPID of the user that last modifies the data.  |
| resource          | <a href="#">Resource object</a> | Resource.  |
| cipher            | <a href="#">Cipher object</a>   | Cipher.  |

| Parameter  | Type                | Description  |
|------------|---------------------|--|
| attributes | Map<String, Object> | Type attributes. A key consists of letters and digits and starts with a letter. A value cannot contain emojis. The size of an attribute is not limited, but the total size cannot exceed 16 KB.<br>Attribute options: <ul style="list-style-type: none"><li>• <b>pictureMetadata</b>: image attribute data. For details, see the definition of <b>PictureMetadata</b>.</li><li>• <b>videoMetadata</b>: video attribute data. For details, see the definition of <b>VideoMetadata</b>.</li><li>• <b>audioMetadata</b>: audio attribute data. For details, see the definition of <b>AudioMetadata</b>.</li><li>• <b>contentDisposition</b>: used when <b>response-content-disposition</b> is not specified for the downloaded attachment (valid when <b>resource.type</b> is set to 12).</li></ul> |
| properties | Map<String, String> | Extended attributes.   |

**Table 4-387** Resource

| Parameter | Type    | Description   |
|-----------|---------|---|
| id        | String  | ID of the file resource.  |
| hash      | String  | Hash of the file resource.  |
| length    | Long    | Size of the file resource.  |
| sha256    | String  | SHA256 of the file (used for integrity check).  |
| type      | Integer | Resource type. <ul style="list-style-type: none"><li>• 0: ciphertext multipart file.</li><li>• 3: plaintext multipart file.</li><li>• 12: plaintext single-part file.</li></ul> |

| Parameter    | Type                                | Description  |
|--------------|-------------------------------------|--|
| state        | Integer                             | Data status. <ul style="list-style-type: none"><li>● <b>0</b>: available.</li><li>● <b>1</b>: unavailable.</li><li>● <b>2</b>: temporary.</li><li>● <b>3</b>: retained (flash upload unsupported).</li><li>● <b>4</b>: to be cut over.</li></ul> |
| sliceSize    | Long                                | Part size.   |
| hfek         | String                              | Hash of the FEK of the encrypted file. This parameter is applicable when <b>type</b> is set to <b>0</b> .  |
| iv           | String                              | IV of the encrypted file. This parameter is applicable when <b>type</b> is set to <b>0</b> .   |
| createdTime  | String                              | Time when the data is created.   |
| modifiedTime | String                              | Time when the data is last modified.   |
| objects      | Array of <b>SliceObject</b> objects | Part object, which is applicable when <b>type</b> is set to <b>0</b> or <b>3</b> .   |
| attributes   | Map<String, Object>                 | Type attributes.   |
| properties   | Map<String, String >                | Extended attributes.   |

**Table 4-388 SliceObject**

| Parameter | Type    | Description  |
|-----------|---------|--|
| id        | String  | Part ID.   |
| number    | Integer | Part No., starting from 0. This parameter is not applicable when <b>type</b> is set to <b>12</b> . |
| start     | Long    | Start position of a part, which is not applicable when <b>type</b> is set to <b>12</b> .           |
| sha256    | String  | SHA256 of the part (or SHA256 of the ciphertext if the part is encrypted.)                         |
| length    | Long    | Part length (or ciphertext length if the part is encrypted).                                       |
| bucket    | String  | OBS bucket information.  |

| Parameter    | Type                                    | Description   |
|--------------|---|---|
| createdTime  | String                                  | Time when the data is created.  |
| modifiedTime | String                                  | Time when the data is last modified.  |
| uploadUrl    | <a href="#">EndpointURL</a> object      | Upload URL.   |
| downloadUrl  | <a href="#">EndpointURL</a> object      | Download URL.   |
| uploadId     | String                                  | Multipart upload ID. This parameter is applicable when <b>type</b> is set to <b>12</b> and <b>uploadMode</b> is set to <b>multipart</b> . |
| attributes   | Map<String, Object>                     | Type attributes.  |
| properties   | Map<String, String >                    | Extended attributes.  |
| images       | Array of <a href="#">Images</a> objects | Thumbnail.  |

**Table 4-389** EndpointURL

| Parameter | Type                 | Description  |
|-----------|----------------------|--|
| url       | String               | URL  |
| method    | String               | http method  |
| headers   | Map<String, String > | http headers   |
| forms     | Map<String, String > | Form parameter, which is applicable when <b>type</b> is set to <b>12</b> and <b>uploadMode</b> is set to <b>post</b> .           |
| partId    | String               | Multipart parameter, which is applicable when <b>type</b> is set to <b>12</b> and <b>uploadMode</b> is set to <b>multipart</b> . |

**Table 4-390** Images

| Parameter   | Type  | Description                                |
|-------------|---|--|
| process     | String  | File resource name.                        |
| downloadUrl | <a href="#">EndpointURL</a> <b>adata</b> object | URL structure for file upload or download. |

**Table 4-391** EndpointURLMetadata

| Parameter | Type   | Description |
|-----------|--------|-------------|
| url       | String | URL         |
| method    | String | http method |

**Table 4-392** Cipher

| Parameter | Type                             | Description   |
|-----------|----------------------------------|---|
| algorithm | String                           | Encryption algorithm.   |
| hfek      | String                           | Hash of the FEK of the encrypted file. This parameter is applicable when <b>type</b> is set to <b>0</b> or <b>4</b> . |
| iv        | String                           | IV of the encrypted file. This parameter is applicable when <b>type</b> is set to <b>0</b> or <b>4</b> .              |
| dataType  | Integer                          | Data type. <ul style="list-style-type: none"><li>• <b>11</b>: sync drive.</li></ul>                                   |
| keychains | Array of <b>Keychain</b> objects | Keychain.   |

**Table 4-393** Keychain

| Parameter | Type    | Description   |
|-----------|---------|---|
| id        | String  | Key UUID.   |
| type      | Integer | Key type. <ul style="list-style-type: none"><li>• <b>1</b>: efek.</li><li>• <b>2</b>: zfek.</li><li>• <b>3</b>: sfek.</li></ul> |
| algorithm | String  | Encryption algorithm.   |
| ekey      | String  | Encrypted key.  |

**Table 4-394** DownloadLink

| Parameter | Type   | Description   |
|-----------|--------|---|
| usage     | String | Default usage: <b>content</b> or <b>thumbnail</b> . This parameter is customizable. |

| Parameter    | Type    | Description               |
|--------------|---------|---------------------------|
| downloadLink | String  | Attachment download link. |
| version      | Integer | Attachment version.       |

**Table 4-395** PrivateProperties

| Parameter  | Type                 | Description  |
|------------|----------------------|--|
| attributes | Map<String, Object>  | Type attributes (The size of a single attribute is not limited, but the total size cannot exceed 16 KB.)     |
| properties | Map<String, String > | Extended attributes (The size of a single attribute is not limited, but the total size cannot exceed 16 KB.) |

**Table 4-396** userCapabilities

| Parameter                 | Type    | Description   |
|---------------------------|---------|---|
| addChildNodePermission    | Boolean | Whether the user can add sub-directories or sub-files.  |
| copyPermission            | Boolean | Whether the user can copy files.                        |
| deletePermission          | Boolean | Whether the user can delete files.                      |
| downloadPermission        | Boolean | Whether the user can download content.                  |
| editPermission            | Boolean | Whether the user can edit files.                        |
| listChildNodePermission   | Boolean | Whether the user can list sub-directories or sub-files. |
| removeChildNodePermission | Boolean | Whether the user can move sub-directories.              |
| renameFilePermission      | Boolean | Whether the user can rename files.                      |
| shareFilePermission       | Boolean | Whether the user can share files.                       |
| uploadPermission          | Boolean | Whether the user can upload files.                      |
| viewPermission            | Boolean | Whether the user can preview files.                     |

## Example Requests

None

## Example Responses

None

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

# 4.17 Sharing Management - Shared by You

## 4.17.1 Sharing a File

### Function

Share a file.

### URI

POST /koodrive/ose/v1/share

### Request Parameters

**Table 4-397** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| X-User-Id | Yes       | String | User ID, which is used for app authentication. |
| X-Date    | Yes       | String | Date, which is used for app authentication.    |
| Host      | Yes       | String | Address, which is used for app authentication. |

**Table 4-398** Request body parameters

| Parameter   | Mandatory | Type                                   | Description   |
|-------------|-----------|--|---|
| scope       | Yes       | Integer                                | Sharing scope. <b>1</b> : users who receive the link (only for whitelisted users); <b>2</b> : only enterprise users; <b>3</b> : specified enterprise users. |
| deptIds     | No        | Array of strings                       | Department ID list.   |
| groupIds    | No        | Array of strings                       | List of user group IDs.   |
| userIds     | No        | Array of strings                       | User ID list.   |
| fileIds     | Yes       | Array of strings                       | File ID list.   |
| containerId | Yes       | String                                 | Space ID.   |
| permission  | No        | <a href="#">SharePermission</a> object | Sharing permission (supported in the future).   |
| extractCode | No        | String                                 | Access code.  |
| expireTime  | No        | String                                 | Expiration time.  |
| comment     | No        | String                                 | Sharing message.  |
| validDays   | Yes       | Integer                                | Sharing validity period. Value range: 1 to 365 days.  |
| expiredType | No        | String                                 | Invalidation type.  |

**Table 4-399 SharePermission**

| Parameter | Mandatory | Type    | Description          |
|-----------|-----------|---------|----------------------|
| preview   | No        | Boolean | Preview permission.  |
| edit      | No        | Boolean | Editing permission.  |
| download  | No        | Boolean | Download permission. |

## Response Parameters

Status code: 200

**Table 4-400 Response body parameters**

| Parameter | Type                             | Description               |
|-----------|----------------------------------|---------------------------|
| code      | String                           | Response code.            |
| msg       | String                           | Response information.     |
| shareLink | <a href="#">shareLink object</a> | Sharing link information. |

**Table 4-401 shareLink**

| Parameter   | Type   | Description         |
|-------------|--------|---------------------|
| shareId     | String | Sharing ID.         |
| shortUrl    | String | Sharing short code. |
| linkUrl     | String | Sharing link.       |
| extractCode | String | Access code.        |
| comment     | String | Message.            |
| expireTime  | String | Expiration time.    |

## Example Requests

```
POST /koodrive/ose/v1/share
Authorization:Bearer+10f88*****4791e9ff
{
  "scope": 0,
  "deptIds": [
    "string"
  ],
  "groupIds": [
    "string"
  ],
  "userIds": [
```

```
        "string"
    ],
    "filelds": [
        "string"
    ],
    "containerId": "string",
    "permission": {
        "preview": true,
        "edit": true,
        "download": true
    },
    "extractCode": "string",
    "expireTime": "2024-06-03T01:54:57.288Z",
    "comment": "string",
    "validDays": 0
}
```

## Example Responses

**Status code: 200**

OK

```
{
    "shareLink": {
        "shareId": "1537770199275722240",
        "shortUrl": "1537770199275722241",
        "linkUrl": "https://kdconsole-test-gray.hwcloudtest.cn:8080/cloudfile/#/sharelink/i/1537770199275722241",
        "extractCode": "",
        "comment": "",
        "expireTime": "2024-10-29T09:14:52.948Z"
    },
    "code": 0,
    "msg": "success"
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.17.2 Listing Files Shared by You

### Function

List files shared by you. One sharing record occupies one line. When multiple files are shared, a folder with the first file name is displayed. When a single file is shared, the file information is displayed.

### URI

GET /koodrive/ose/v1/share

**Table 4-402** Query Parameters

| Parameter     | Mandatory | Type    | Description   |
|---------------|-----------|---------|---|
| pageSize      | No        | Integer | Number of records to be returned on each page. Default and maximum value: 100. It is possible that partial or empty result pages are returned before the end of the result list has been reached. |
| pageCursor    | No        | String  | Current page cursor, which is obtained from <b>nextCursor</b> of the previous response. Default value: <b>0</b> .   |
| sortType      | No        | Integer | Sorting type. <b>4</b> : by sharing time (default).   |
| sortDirection | No        | Integer | Sorting order. <b>1</b> : ascending; <b>2</b> : descending (default).   |
| displayName   | No        | String  | Fuzzy match by display name is supported.   |
| imageProcess  | No        | String  | Image operation, which can be used to specify the thumbnail size.   |

## Request Parameters

**Table 4-403** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| X-User-Id | Yes       | String | User ID, which is used for app authentication. |
| X-Date    | Yes       | String | Date, which is used for app authentication.    |
| Host      | Yes       | String | Address, which is used for app authentication. |

## Response Parameters

Status code: 200

**Table 4-404** Response body parameters

| Parameter  | Type   | Description   |
|------------|--|---|
| code       | String   | Response code.  |
| msg        | String   | Response information.   |
| nextCursor | String   | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| shareLinks | Array of<br><a href="#">ShareByMeLink</a><br>objects | Sharing link list.  |

**Table 4-405** ShareByMeLink

| Parameter | Type   | Description   |
|-----------|--|---|
| shareId   | String   | Sharing ID.   |
| shortUrl  | String   | Sharing short code.   |
| linkUrl   | String   | Sharing link.   |
| shareTime | String   | Time when the file is shared.   |
| scope     | Integer  | Sharing scope. 1: users who receive the link (only for whitelisted users); 2: only enterprise users; 3: specified enterprise users. |
| files     | Array of<br><a href="#">ShareFileInfo</a><br>objects | List of shared files.   |

| Parameter     | Type    | Description   |
|---------------|---------|---|
| displayName   | String  | Display name.   |
| expireTime    | String  | Expiration time.  |
| status        | Integer | Sharing status. <b>0</b> : determined based on the expiration time. <b>1</b> : The file has been deleted. <b>2</b> : expired. |
| comment       | String  | Sharing message.  |
| viewCnt       | Integer | Number of views.  |
| downloadCnt   | Integer | Number of download times (supported in the future).   |
| saveCnt       | Integer | Number of dump times (supported in the future).   |
| containerId   | String  | ID of the space to which the shared file belongs.   |
| containerName | String  | Space to which the shared file belongs.   |

**Table 4-406 ShareFileInfo**

| Parameter     | Type   | Description   |
|---------------|--|---|
| id            | String   | *File ID.   |
| fileName      | String   | *File name, which contains up to 160 bytes.   |
| fileType      | String   | File type, which is entered externally. The value contains up to 250 characters.      |
| mimeType      | String   | *Content type.  |
| size          | Integer  | File size.  |
| parentFolder  | Array of strings                                     | List of parent directory IDs. Currently, only the first ID is used.                   |
| fileSuffix    | String   | File name extension, which is the last character string of <b>fullFileExtension</b> . |
| containers    | Array of strings                                     | Space ID.   |
| downloadLinks | Array of<br><a href="#">downloadLinks</a><br>objects | Download link.  |
| recycled      | Boolean  | Whether the file is in the recycle bin.   |

**Table 4-407** downloadLinks

| Parameter    | Type   | Description   |
|--------------|--------|---|
| usage        | String | Default usage: <b>content</b> or <b>thumbnail</b> . This parameter is customizable. |
| downloadLink | String | Download link.  |

## Example Requests

```
GET /koodrive/ose/v1/share?pageSize=&pageCursor=0&sortType=2&sortDirection=4&displayName=
Authorization:Bearer+10f88*****5a544791e9ff
```

## Example Responses

**Status code: 200**

OK

```
{
  "code" : "string",
  "msg" : "string",
  "nextCursor" : "string",
  "shareLinks" : [ {
    "shareId" : "string",
    "shortUrl" : "string",
    "linkUrl" : "string",
    "shareTime" : "2024-06-03T01:58:35.419Z",
    "scope" : 0,
    "files" : [ {
      "id" : "string",
      "fileName" : "string",
      "fileType" : "string",
      "mimeType" : "string",
      "size" : 0,
      "parentFolder" : [ "string" ],
      "fileSuffix" : "string",
      "containers" : [ "string" ]
    }],
    "displayName" : "string",
    "permission" : {
      "preview" : true,
      "edit" : true,
      "download" : true
    },
    "extractCode" : "string",
    "expireTime" : "2024-06-03T01:58:35.419Z",
    "status" : 0,
    "comment" : "string",
    "viewCnt" : 0,
    "downloadCnt" : 0,
    "saveCnt" : 0,
    "containerId" : "string",
    "containerName" : "string"
  }]
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.17.3 Obtaining Sharing Details

### Function

Obtain sharing details.

### URI

GET /koodrive/ose/v1/share/{shareId}

**Table 4-408** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| shareId   | Yes       | String | Sharing ID. |

### Request Parameters

**Table 4-409** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| X-Date    | Yes       | String | Date, which is used for app authentication.    |
| Host      | Yes       | String | Address, which is used for app authentication. |

## Response Parameters

Status code: 200

**Table 4-410** Response body parameters

| Parameter | Type                                       | Description                     |
|-----------|--|---------------------------------|
| code      | String                                     | Response code.                  |
| msg       | String                                     | Response information.           |
| shareLink | <a href="#">ShareByMeLinkDetail object</a> | Details about the sharing link. |

**Table 4-411** ShareByMeLinkDetail

| Parameter   | Type                                       | Description   |
|-------------|--|---|
| shareId     | String                                     | Sharing ID.   |
| shortUrl    | String                                     | Sharing short code.   |
| linkUrl     | String                                     | Sharing link.   |
| shareTime   | String                                     | Time when the file is shared.   |
| scope       | Integer                                    | Sharing scope. <b>1</b> : users who receive the link (only for whitelisted users); <b>2</b> : only enterprise users; <b>3</b> : specified enterprise users. |
| deps        | Array of <a href="#">DeptInfo</a> objects  | Department list.  |
| groups      | Array of <a href="#">GroupInfo</a> objects | User group list.  |
| users       | Array of <a href="#">UserInfo</a> objects  | User list.  |
| displayName | String                                     | Display name.   |
| permission  | <a href="#">SharePermission</a> object     | Sharing permission (supported in the future).   |

| Parameter   | Type    | Description   |
|-------------|---------|---|
| extractCode | String  | Access code.  |
| expireTime  | String  | Expiration time.  |
| status      | Integer | Sharing status. <b>0</b> : determined based on the expiration time. <b>1</b> : The file has been deleted. <b>2</b> : expired. |
| comment     | String  | Sharing message.  |

**Table 4-412 DeptInfo**

| Parameter | Type   | Description      |
|-----------|--------|------------------|
| id        | String | Department ID.   |
| name      | String | Department name. |

**Table 4-413 GroupInfo**

| Parameter | Type   | Description      |
|-----------|--------|------------------|
| id        | String | User group ID.   |
| name      | String | User group name. |

**Table 4-414 UserInfo**

| Parameter | Type   | Description |
|-----------|--------|-------------|
| id        | String | User ID.    |
| name      | String | Username.   |

**Table 4-415 SharePermission**

| Parameter | Type    | Description          |
|-----------|---------|----------------------|
| preview   | Boolean | Preview permission.  |
| edit      | Boolean | Editing permission.  |
| download  | Boolean | Download permission. |

## Example Requests

```
GET /koodrive/ose/v1/share/{shareId}  
Authorization:Bearer+10f88*****5a544791e9ff
```

## Example Responses

**Status code: 200**

OK

```
{  
  "code" : "string",  
  "msg" : "string",  
  "shareLink" : {  
    "shareId" : "string",  
    "shortUrl" : "string",  
    "linkUrl" : "string",  
    "shareTime" : "2024-06-03T01:59:05.324Z",  
    "scope" : 0,  
    "depts" : [ {  
      "id" : "string",  
      "name" : "string"  
    } ],  
    "groups" : [ {  
      "id" : "string",  
      "name" : "string"  
    } ],  
    "users" : [ {  
      "id" : "string",  
      "name" : "string"  
    } ],  
    "displayName" : "string",  
    "permission" : {  
      "preview" : true,  
      "edit" : true,  
      "download" : true  
    },  
    "extractCode" : "string",  
    "expireTime" : "2024-06-03T01:59:05.324Z",  
    "status" : 0,  
    "comment" : "string"  
  }  
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.17.4 Modifying Sharing Settings

### Function

Modify sharing settings.

## URI

PUT /koodrive/ose/v1/share/{shareId}

**Table 4-416** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| shareId   | Yes       | String | Sharing ID. |

## Request Parameters

**Table 4-417** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-418** Request body parameters

| Parameter | Mandatory | Type             | Description             |
|-----------|-----------|------------------|-------------------------|
| deptIds   | No        | Array of strings | Department ID list.     |
| groupIds  | No        | Array of strings | List of user group IDs. |

| Parameter   | Mandatory | Type                                   | Description  |
|-------------|-----------|--|--|
| userIds     | No        | Array of strings                       | User ID list.  |
| permission  | No        | <a href="#">SharePermission object</a> | Sharing permission (supported in the future).                                      |
| expireTime  | No        | String                                 | Expiration time.   |
| extractCode | No        | String                                 | Access code.   |
| comment     | No        | String                                 | Sharing message.   |
| validDays   | Yes       | Integer                                | Sharing validity period, ranging from 0 to 365 days. <b>0</b> indicates no change. |

**Table 4-419 SharePermission**

| Parameter | Mandatory | Type    | Description          |
|-----------|-----------|---------|----------------------|
| preview   | No        | Boolean | Preview permission.  |
| edit      | No        | Boolean | Editing permission.  |
| download  | No        | Boolean | Download permission. |

## Response Parameters

Status code: 200

**Table 4-420 Response body parameters**

| Parameter | Type                             | Description               |
|-----------|----------------------------------|---------------------------|
| code      | String                           | Response code.            |
| msg       | String                           | Response information.     |
| shareLink | <a href="#">shareLink object</a> | Sharing link information. |

**Table 4-421 shareLink**

| Parameter   | Type   | Description   |
|-------------|--------|---------------|
| shareId     | String | Sharing ID.   |
| shortUrl    | String | Sharing link. |
| extractCode | String | Access code.  |

| Parameter   | Type    | Description                   |
|-------------|---------|-------------------------------|
| createTime  | String  | Creation time.                |
| updateTime  | String  | Modification time.            |
| expireTime  | String  | Expiration time.              |
| linkUrl     | String  | Sharing link.                 |
| shareTime   | String  | Time when the file is shared. |
| scope       | Integer | Scope.                        |
| displayName | String  | Display name.                 |
| status      | Integer | Status.                       |
| viewCnt     | String  | Number of views.              |
| downloadCnt | String  | Download times.               |
| saveCnt     | String  | Save times.                   |

## Example Requests

```
PUT /koodrive/ose/v1/share/{shareId}

{
  "deptIds" : [ "string" ],
  "groupIds" : [ "string" ],
  "userIds" : [ "string" ],
  "permission" : {
    "preview" : true,
    "edit" : true,
    "download" : true
  },
  "expireTime" : "2024-06-03T02:00:39.952Z",
  "extractCode" : "string",
  "comment" : "string",
  "validDays" : 0
}
```

## Example Responses

**Status code: 200**

OK

```
{
  "code" : "string",
  "msg" : "string",
  "shareLink" : {
    "shareId" : "string",
    "shortUrl" : "string",
    "extractCode" : "string",
    "createTime" : "2024-06-03T02:00:39.953Z",
    "updateTime" : "2024-06-03T02:00:39.953Z",
    "expireTime" : "2024-06-03T02:00:39.953Z"
  }
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.17.5 Stopping Sharing Files

### Function

Stop sharing files.

### URI

POST /koodrive/ose/v1/share/cancel

### Request Parameters

**Table 4-422 Request header parameters**

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-423** Request body parameters

| Parameter | Mandatory | Type             | Description   |
|-----------|-----------|------------------|---|
| shareIds  | No        | Array of strings | List of IDs for canceling sharing. Up to 100 IDs can be canceled at a time. |

## Response Parameters

Status code: 200

**Table 4-424** Response body parameters

| Parameter       | Type                              | Description           |
|-----------------|-----------------------------------|-----------------------|
| code            | String                            | Response code.        |
| msg             | String                            | Response information. |
| subResponseList | Array of ShareSubResponse objects | Sub-response list.    |

**Table 4-425** ShareSubResponse

| Parameter | Type    | Description           |
|-----------|---------|-----------------------|
| code      | Integer | Sub-response code.    |
| msg       | String  | Sub-response message. |

## Example Requests

```
POST /koodrive/ose/v1/share/cancel
{
    "shareIds" : [ "string" ]
}
```

## Example Responses

Status code: 200

OK

```
{
    "code" : "string",
    "msg" : "string",
    "subResponseList" : [ {
        "shareId" : "string",
        "code" : "string",
        "msg" : "string"
    }
]
```

```
    } ]
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.18 Sharing Management - Shared with You

### 4.18.1 Listing Files Shared with You

#### Function

List files shared with you.

#### URI

GET /koodrive/ose/v1/share/received

**Table 4-426** Query Parameters

| Parameter     | Mandatory | Type    | Description   |
|---------------|-----------|---------|---|
| pageSize      | No        | Integer | Number of records to be returned on each page. Default and maximum value: 100. It is possible that partial or empty result pages are returned before the end of the result list has been reached. |
| pageCursor    | No        | String  | Current page cursor, which is obtained from <b>nextCursor</b> of the previous response. Default value: <b>0</b> .   |
| sortType      | No        | Integer | Sorting type. <b>4</b> : by sharing time (default).   |
| sortDirection | No        | Integer | Sorting order. <b>1</b> : ascending; <b>2</b> : descending (default).   |
| displayName   | No        | String  | Fuzzy match by display name is supported.   |
| imageProcess  | No        | String  | Image operation, which can be used to specify the thumbnail size.   |

## Request Parameters

**Table 4-427** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

Status code: 200

**Table 4-428** Response body parameters

| Parameter  | Type  | Description   |
|------------|---|---|
| code       | Integer   | Response code.  |
| msg        | String  | Response information.   |
| nextCursor | String  | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| shareLinks | Array of<br><b>ShareWithMeLin<br/>k</b> objects | Sharing link list.  |

**Table 4-429** ShareWithMeLink

| Parameter   | Type   | Description   |
|-------------|--|---|
| shareId     | String   | Sharing ID.   |
| shortUrl    | String   | Sharing short code.   |
| linkUrl     | String   | Sharing link.   |
| shareTime   | String   | Time when the file is shared.   |
| ownerId     | String   | Sharer ID.  |
| ownerName   | String   | Sharer name.  |
| displayName | String   | Display name.   |
| files       | Array of<br><a href="#">ShareFileInfo</a><br>objects | List of shared files.   |
| permission  | <a href="#">SharePermission</a><br>object            | Sharing permission (supported in the future).   |
| expireTime  | String   | Expiration time.  |
| status      | Integer  | Sharing status. <b>0</b> : determined based on the expiration time. <b>1</b> : The file has been deleted. <b>2</b> : expired. |
| comment     | String   | Sharing message.  |
| containerId | String   | Space ID.   |
| downloadCnt | Integer  | Download times.   |
| saveCnt     | Integer  | Save times.   |
| scope       | String   | Scope.  |
| updateTime  | String   | Update time.  |
| viewCnt     | String   | Number of views.  |

**Table 4-430** ShareFileInfo

| Parameter | Type   | Description  |
|-----------|--------|--|
| id        | String | *File ID.  |
| fileName  | String | *File name, which contains up to 160 bytes.                                      |
| fileType  | String | File type, which is entered externally. The value contains up to 250 characters. |

| Parameter     | Type   | Description   |
|---------------|--|---|
| mimeType      | String   | *Content type.  |
| size          | Integer  | File size.  |
| parentFolder  | Array of strings                                     | List of parent directory IDs. Currently, only the first ID is used.                   |
| fileSuffix    | String   | File name extension, which is the last character string of <b>fullFileExtension</b> . |
| containers    | Array of strings                                     | Space ID.   |
| downloadLinks | Array of<br><a href="#">downloadLinks</a><br>objects | Download link.  |
| recycled      | Boolean  | Whether the file is in the recycle bin.   |

**Table 4-431** downloadLinks

| Parameter    | Type   | Description   |
|--------------|--------|---|
| usage        | String | Default usage: <b>content</b> or <b>thumbnail</b> . This parameter is customizable. |
| downloadLink | String | Download link.  |

**Table 4-432** SharePermission

| Parameter | Type    | Description          |
|-----------|---------|----------------------|
| preview   | Boolean | Preview permission.  |
| edit      | Boolean | Editing permission.  |
| download  | Boolean | Download permission. |

## Example Requests

```
GET /koodrive/ose/v1/share/received?  
pageSize=&pageCursor=0&sortType=2&sortDirection=4&displayName=&tenantId=String  
Authorization:Bearer+10f88*****5a544791e9ff
```

## Example Responses

Status code: 200

OK

```
{  
  "code" : "string",
```

```
"msg" : "string",
"nextCursor" : "string",
"shareLinks" : [ {
  "shareId" : "string",
  "shortUrl" : "string",
  "linkUrl" : "string",
  "shareTime" : "2024-06-03T02:02:00.797Z",
  "ownerId" : "string",
  "ownerName" : "string",
  "displayName" : "string",
  "files" : [ {
    "id" : "string",
    "fileName" : "string",
    "fileType" : "string",
    "mimeType" : "string",
    "size" : 0,
    "parentFolder" : [ "string" ],
    "fileSuffix" : "string",
    "containers" : [ "string" ]
  }],
  "permission" : {
    "preview" : true,
    "edit" : true,
    "download" : true
  },
  "expireTime" : "2024-06-03T02:02:00.797Z",
  "status" : 0,
  "comment" : "string"
} ]
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.18.2 Obtain Sharing Details

### Function

Obtain sharing details.

### URI

GET /koodrive/ose/v1/share/received/{shareId}

**Table 4-433** Path Parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| shareId   | Yes       | String | Sharing ID. |

## Request Parameters

**Table 4-434** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-435** Response body parameters

| Parameter | Type                                | Description                                 |
|-----------|-------------------------------------|---|
| code      | Integer                             | Response code.                              |
| msg       | String                              | Response information.                       |
| shareLink | <b>ShareWithMeLinkDetail</b> object | Information about the link shared with you. |

**Table 4-436** ShareWithMeLinkDetail

| Parameter | Type   | Description |
|-----------|--------|-------------|
| shareId   | String | Sharing ID. |

| Parameter   | Type                             | Description                                   |
|-------------|----------------------------------|---|
| shortUrl    | String                           | Sharing short code.                           |
| linkUrl     | String                           | Sharing link.                                 |
| shareTime   | String                           | Time when the file is shared.                 |
| ownerId     | String                           | Sharer ID.                                    |
| ownerName   | String                           | Sharer name.                                  |
| displayName | String                           | Display name.                                 |
| permission  | <b>SharePermission</b><br>object | Sharing permission (supported in the future). |
| expireTime  | String                           | Expiration time.                              |
| status      | Integer                          | Sharing status. 1: The file has been deleted. |
| comment     | String                           | Sharing message.                              |

**Table 4-437 SharePermission**

| Parameter | Type    | Description          |
|-----------|---------|----------------------|
| preview   | Boolean | Preview permission.  |
| edit      | Boolean | Editing permission.  |
| download  | Boolean | Download permission. |

## Example Requests

```
GET /koodrive/ose/v1/share/received/{shareId}  
Authorization:Bearer+10f88*****5a544791e9ff
```

## Example Responses

**Status code: 200**

OK

```
{  
  "code" : "string",  
  "msg" : "string",  
  "shareLink" : {  
    "shareId" : "string",  
    "shortUrl" : "string",  
    "linkUrl" : "string",  
    "shareTime" : "string",  
    "ownerId" : "string",  
    "ownerName" : "string",  
    "displayName" : "string",  
    "permission" : {  
      "read" : "string",  
      "write" : "string",  
      "execute" : "string",  
      "list" : "string",  
      "create" : "string",  
      "update" : "string",  
      "delete" : "string",  
      "download" : "string",  
      "comment" : "string",  
      "share" : "string",  
      "cancel" : "string",  
      "other" : "string"  
    }  
  }  
}
```

```
        "preview" : true,  
        "edit" : true,  
        "download" : true  
    },  
    "expireTime" : "2024-06-03T02:18:51.520Z",  
    "status" : 0,  
    "comment" : "string"  
}  
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.18.3 Removing Yourself from Shared Files

### Function

Remove yourself from shared files.

### URI

POST /koodrive/ose/v1/share/exit

### Request Parameters

**Table 4-438** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| X-Date    | Yes       | String | Date, which is used for app authentication.    |
| Host      | Yes       | String | Address, which is used for app authentication. |

**Table 4-439** Request body parameters

| Parameter | Mandatory | Type             | Description                         |
|-----------|-----------|------------------|-------------------------------------|
| shareIds  | Yes       | Array of strings | List of IDs of target shared files. |

## Response Parameters

Status code: 200

**Table 4-440** Response body parameters

| Parameter       | Type                              | Description           |
|-----------------|-----------------------------------|-----------------------|
| code            | Integer                           | Response code.        |
| msg             | String                            | Response information. |
| subResponseList | Array of ShareSubResponse objects | Sub-response list.    |

**Table 4-441** ShareSubResponse

| Parameter | Type    | Description           |
|-----------|---------|-----------------------|
| code      | Integer | Sub-response code.    |
| msg       | String  | Sub-response message. |

## Example Requests

```
POST /koodrive/ose/v1/share/exit
{
  "shareIds" : [ "string" ]
}
```

## Example Responses

**Status code: 200**

OK

```
{  
  "code" : "string",  
  "msg" : "string",  
  "subResponseList" : [ {  
    "code" : "string",  
    "message" : "string"  
  } ]  
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.19 Sharing Management - Access Links

### 4.19.1 Accessing a Sharing Link.

#### Function

Access a sharing link.

#### URI

GET /koodrive/ose/v1/share/visit

**Table 4-442** Query Parameters

| Parameter | Mandatory | Type   | Description         |
|-----------|-----------|--------|---------------------|
| shortUrl  | Yes       | String | Sharing short code. |

## Request Parameters

**Table 4-443** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200****Table 4-444** Response body parameters

| Parameter | Type    | Description           |
|-----------|---------|-----------------------|
| code      | Integer | Response code.        |
| msg       | String  | Response information. |

## Example Requests

```
GET /koodrive/ose/v1/share/visit?shortUrl=String  
Authorization:Bearer+10f88*****5a544791e9ff
```

## Example Responses

**Status code: 200**

OK

```
{  
    "code" : "integer",  
    "msg" : "string"  
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.19.2 Obtaining Sharing Information

### Function

Obtain sharing information.

### URI

GET /koodrive/ose/v1/share/userInfo

**Table 4-445** Query Parameters

| Parameter | Mandatory | Type   | Description         |
|-----------|-----------|--------|---------------------|
| shortUrl  | Yes       | String | Sharing short code. |

### Request Parameters

**Table 4-446** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| X-Traceid | No        | String | Service trace ID, which contains 58 bits.      |
| X-User-Id | Yes       | String | User ID, which is used for app authentication. |
| X-Date    | Yes       | String | Date, which is used for app authentication.    |
| Host      | Yes       | String | Address, which is used for app authentication. |

## Response Parameters

Status code: 200

**Table 4-447** Response body parameters

| Parameter | Type                   | Description                            |
|-----------|------------------------|--|
| code      | Integer                | Response code.                         |
| msg       | String                 | Response information.                  |
| link      | CommonShareLink object | Public information of the access link. |

**Table 4-448** CommonShareLink

| Parameter  | Type                   | Description   |
|------------|------------------------|---|
| shareId    | String                 | Sharing ID.   |
| shortUrl   | String                 | Sharing short code.   |
| shareTime  | String                 | Time when the file is shared.   |
| ownerId    | String                 | Sharer ID.  |
| ownerName  | String                 | Sharer name.  |
| permission | SharePermission object | Sharing permission (supported in the future).   |
| expireTime | String                 | Expiration time.  |
| status     | Integer                | Sharing status. 0: determined based on the expiration time. 1: The file has been deleted. 2: expired. |
| expireDate | String                 | Validity period.  |

**Table 4-449 SharePermission**

| Parameter | Type    | Description          |
|-----------|---------|----------------------|
| preview   | Boolean | Preview permission.  |
| edit      | Boolean | Editing permission.  |
| download  | Boolean | Download permission. |

## Example Requests

```
GET /koodrive/ose/v1/share/userInfo?shortUrl=String
```

```
Authorization: Bearer+10f88*****5a544791e9ff
```

## Example Responses

**Status code: 200**

OK

```
{
  "code" : "string",
  "msg" : "string",
  "link" : {
    "shareId" : "string",
    "shortUrl" : "string",
    "shareTime" : "2024-06-03T02:20:24.274Z",
    "ownerId" : "string",
    "ownerName" : "string",
    "permission" : {
      "preview" : true,
      "edit" : true,
      "download" : true
    },
    "expireTime" : "2024-06-03T02:20:24.274Z",
    "expireDate" : "3",
    "status" : 0
  }
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.19.3 Verifying a Sharing Access Code

### Function

Verify a sharing access code.

## URI

POST /koodrive/ose/v1/share/verify

## Request Parameters

**Table 4-450** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-451** Request body parameters

| Parameter   | Mandatory | Type   | Description         |
|-------------|-----------|--------|---------------------|
| shortUrl    | Yes       | String | Sharing short link. |
| extractCode | Yes       | String | Sharing code.       |

## Response Parameters

**Status code: 200**

**Table 4-452** Response body parameters

| Parameter | Type    | Description           |
|-----------|---------|-----------------------|
| code      | Integer | Response code.        |
| msg       | String  | Response information. |
| kdstoken  | String  | Temporary token.      |

## Example Requests

```
POST /koodrive/ose/v1/share/verify
{
    "shortUrl" : "string",
    "extractCode" : "string"
}
```

## Example Responses

**Status code: 200**

OK

```
{
    "code" : "integer",
    "msg" : "string",
    "kdstoken" : "string"
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.19.4 Listing Files Shared with You

### Function

List shared files.

### URI

```
POST /koodrive/ose/v1/share/files
```

## Request Parameters

**Table 4-453** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-454** Request body parameters

| Parameter    | Mandatory | Type    | Description   |
|--------------|-----------|---------|---|
| shortUrl     | Yes       | String  | Sharing short code.   |
| parentFolder | No        | String  | Parent directory ID.  |
| pageSize     | No        | Integer | Number of records to be returned on each page. Default and maximum value: 100. It is possible that partial or empty result pages are returned before the end of the result list has been reached. |
| pageCursor   | No        | String  | Current page cursor, which is obtained from <b>nextCursor</b> of the previous response.   |

| Parameter     | Mandatory | Type    | Description  |
|---------------|-----------|---------|--|
| sortType      | No        | Integer | Sorting type. <b>1</b> : by file name; <b>2</b> : by file size; <b>4</b> : by modification time (default). |
| sortDirection | No        | Integer | Sorting order. <b>1</b> : ascending; <b>2</b> : descending (default).                                      |
| kdstoken      | No        | String  | Temporary token for sharing.   |
| refreshCount  | No        | Boolean | Whether this API call is counted as a file view.   |
| fileName      | No        | String  | File name.   |
| imageProcess  | No        | String  | Image operation, which can be used to specify the thumbnail size.  |

## Response Parameters

Status code: 200

**Table 4-455** Response body parameters

| Parameter  | Type                                       | Description   |
|------------|--|---|
| code       | Integer                                    | Response code.  |
| msg        | String                                     | Response information.   |
| nextCursor | String                                     | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| link       | <a href="#">CommonShareLink object</a>     | Public information of the access link.  |
| files      | Array of <a href="#">ShareFile objects</a> | List of shared files.   |

**Table 4-456** CommonShareLink

| Parameter | Type   | Description                   |
|-----------|--------|-------------------------------|
| shareId   | String | Sharing ID.                   |
| shortUrl  | String | Sharing short code.           |
| shareTime | String | Time when the file is shared. |
| ownerId   | String | Sharer ID.                    |

| Parameter  | Type                          | Description   |
|------------|-------------------------------|---|
| ownerName  | String                        | Sharer name.  |
| permission | <b>SharePermission</b> object | Sharing permission (supported in the future).   |
| expireTime | String                        | Expiration time.  |
| status     | Integer                       | Sharing status. <b>0</b> : determined based on the expiration time. <b>1</b> : The file has been deleted. <b>2</b> : expired. |
| expireDate | String                        | Validity period.  |

**Table 4-457 SharePermission**

| Parameter | Type    | Description          |
|-----------|---------|----------------------|
| preview   | Boolean | Preview permission.  |
| edit      | Boolean | Editing permission.  |
| download  | Boolean | Download permission. |

**Table 4-458 ShareFile**

| Parameter     | Type                               | Description   |
|---------------|------------------------------------|---|
| id            | String                             | *File ID.   |
| fileName      | String                             | *File name, which contains up to 250 bytes.   |
| fileType      | String                             | File type, which is input externally.   |
| parentFolder  | Array of strings                   | List of parent directory IDs. Currently, only the first ID is used.                   |
| fileSuffix    | String                             | File name extension, which is the last character string of <b>fullFileExtension</b> . |
| size          | Integer                            | File size.  |
| containers    | Array of strings                   | Space ID.   |
| downloadLinks | Map<String, <b>downloadLinks</b> > | Download link.  |
| editedTime    | String                             | File modification time.   |

**Table 4-459** downloadLinks

| Parameter    | Type   | Description   |
|--------------|--------|---|
| usage        | String | Default usage: <b>content</b> or <b>thumbnail</b> . This parameter is customizable. |
| downloadLink | String | Download link.  |

## Example Requests

```
POST /koodrive/ose/v1/share/files
```

```
{
  "shortUrl" : "string",
  "parentFolder" : "string",
  "pageSize" : 0,
  "pageCursor" : "string",
  "sortType" : 0,
  "sortDirection" : 0,
  "kdstoken" : "string",
  "refreshCount" : true,
  "fileName" : "string"
}
```

## Example Responses

**Status code: 200**

OK

```
{
  "code" : "string",
  "msg" : "string",
  "nextCursor" : "string",
  "link" : {
    "shareId" : "string",
    "shortUrl" : "string",
    "shareTime" : "2024-06-03T02:23:40.607Z",
    "ownerId" : "string",
    "ownerName" : "string",
    "permission" : {
      "preview" : true,
      "edit" : true,
      "download" : true
    },
    "expireTime" : "2024-06-03T02:23:40.607Z",
    "expireDate" : "3",
    "status" : 0
  },
  "files" : [ {
    "id" : "string",
    "fileName" : "string",
    "fileType" : "string",
    "parentFolder" : [ "string" ],
    "fileSuffix" : "string",
    "size" : 0,
    "containers" : [ "string" ],
    "editedTime" : "2024-06-03T02:23:40.607Z"
  } ]
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.19.5 Downloading a File

### Function

Download a file.

### URI

POST /koodrive/ose/v1/share/download

### Request Parameters

**Table 4-460** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-461** Request body parameters

| Parameter | Mandatory | Type   | Description                  |
|-----------|-----------|--------|------------------------------|
| shareId   | Yes       | String | Sharing ID.                  |
| fileId    | Yes       | String | File ID.                     |
| kdstoken  | No        | String | Temporary token for sharing. |

## Response Parameters

**Status code: 200**

**Table 4-462** Response body parameters

| Parameter   | Type    | Description           |
|-------------|---------|-----------------------|
| code        | Integer | Response code.        |
| msg         | String  | Response information. |
| downloadUrl | String  | Download link.        |

## Example Requests

```
POST /koodrive/ose/v1/share/download
{
  "shareId" : "string",
  "fileId" : "string",
  "kdstoken" : "string"
}
```

## Example Responses

**Status code: 200**

OK

```
{
  "code" : "integer",
  "msg" : "string",
  "downloadUrl" : "string"
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.19.6 Creating an Asynchronous Sharing Task

### Function

Create an asynchronous sharing task.

### URI

POST /koodrive/ose/v1/share/tasks

### Request Parameters

**Table 4-463** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-464** Request body parameters

| Parameter   | Mandatory | Type    | Description                                      |
|-------------|-----------|---------|--|
| taskType    | Yes       | Integer | Batch operation task type. 1: download; 2: dump. |
| containerId | Yes       | String  | Space where the file is located.                 |

| Parameter    | Mandatory | Type                   | Description  |
|--------------|-----------|------------------------|--|
| filelds      | Yes       | Array of strings       | File ID list.  |
| targetFileId | No        | <b>FileInfo</b> object | Destination directory, which should be specified during dumping.   |
| zipName      | No        | String                 | Compressed package name, which is the same as that of the package created for download in File Management. |
| shareId      | Yes       | String                 | Sharing ID.  |
| kdstoken     | No        | String                 | Temporary token for sharing.   |

**Table 4-465 FileInfo**

| Parameter   | Mandatory | Type   | Description |
|-------------|-----------|--------|-------------|
| fileId      | Yes       | String | File ID.    |
| containerId | Yes       | String | Space ID.   |

## Response Parameters

Status code: 200

**Table 4-466 Response body parameters**

| Parameter | Type    | Description           |
|-----------|---------|-----------------------|
| code      | Integer | Response code.        |
| msg       | String  | Response information. |
| taskId    | String  | Task ID.              |

## Example Requests

POST /koodrive/ose/v1/share/tasks

```
{  
    "taskType" : 0,  
    "containerId" : "string",  
    "filelds" : [ "string" ],  
    "targetFileId" : {  
        "fileId" : "string",  
        "containerId" : "string"  
    },
```

```
"zipName" : "string",
"shareId" : "string",
"kdstoken" : "string"
}
```

## Example Responses

**Status code: 200**

OK

```
{
  "code" : "integer",
  "msg" : "string",
  "taskId" : "string"
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.19.7 Querying an Asynchronous Task

### Function

Query details about an asynchronous task.

### URI

POST /koodrive/ose/v1/share/taskDetail

### Request Parameters

**Table 4-467** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| X-Traceid | No        | String | Service trace ID, which contains 58 bits.      |
| X-User-Id | Yes       | String | User ID, which is used for app authentication. |
| X-Date    | Yes       | String | Date, which is used for app authentication.    |
| Host      | Yes       | String | Address, which is used for app authentication. |

**Table 4-468** Request body parameters

| Parameter | Mandatory | Type   | Description |
|-----------|-----------|--------|-------------|
| taskId    | Yes       | String | Task ID.    |
| shareId   | Yes       | String | Sharing ID. |
| kdstoken  | No        | String | token       |

## Response Parameters

Status code: 200

**Table 4-469** Response body parameters

| Parameter | Type                            | Description           |
|-----------|---------------------------------|-----------------------|
| code      | Integer                         | Response code.        |
| msg       | String                          | Response information. |
| jobInfo   | <a href="#">JobInfo object</a>  | Work information.     |
| taskInfos | <a href="#">TaskInfo object</a> | Task information.     |

**Table 4-470** JobInfo

| Parameter | Type    | Description |
|-----------|---------|-------------|
| userId    | String  | User ID.    |
| taskId    | String  | Task ID.    |
| taskType  | Integer | Task type.  |

| Parameter      | Type    | Description   |
|----------------|---------|---|
| taskStatus     | Integer | Task status. <b>0</b> : to be processed; <b>1</b> : being processed; <b>2</b> : completed; <b>3</b> : canceled. |
| taskresultCode | Integer | Task result. <b>1</b> : all succeeded; <b>2</b> : partially failed; <b>3</b> : all failed.                      |
| createTime     | String  | Task creation time. The value is a 14-digit timestamp in yyyyMMddHHmmss format.                                 |
| startTime      | String  | Task start time. The value is a 14-digit timestamp in yyyyMMddHHmmss format.                                    |
| endTime        | String  | Task end time. The value is a 14-digit timestamp in yyyyMMddHHmmss format.                                      |
| progress       | Integer | Task progress, in percentage. For example, if the progress is 70%, the returned value is <b>70</b> .            |
| downloadUrl    | String  | Download link of the compressed package.  |

**Table 4-471 TaskInfo**

| Parameter      | Type   | Description      |
|----------------|--------|------------------|
| fileId         | String | Old file ID.     |
| status         | String | Status.          |
| newFileId      | String | New file ID.     |
| srcContainerId | String | Source space ID. |

## Example Requests

```
POST /koodrive/ose/v1/share/taskDetail
```

```
{
  "taskId" : "string",
  "shareId" : "string",
  "kdtoken" : "string"
}
```

## Example Responses

**Status code: 200**

OK

```
{  
    "jobInfo" : {  
        "userId" : "0929b397a3424384b32cf8f96d9f35e4|1465814559892958208",  
        "taskId" : "1521827471237047552",  
        "taskType" : 1,  
        "taskStatus" : 2,  
        "taskresultCode" : 1,  
        "createTime" : "20240930091932",  
        "startTime" : "20240930091932",  
        "endTime" : "20240930091933",  
        "progress" : 100  
    },  
    "taskInfos" : [ {  
        "fileId" : "FmvP8my7yGTvCmKhweL1BoY6kWjRt83A7",  
        "status" : "1",  
        "new fileId" : "FmvlhS-VxkVrHr0vRwydKgo9-x-SmcPha",  
        "srcContainerId" : "IAACk0hRXpq9DAWkA1465823622533999616"  
    }, {  
        "fileId" : "FulYbSXt1ovCywA4qda1Fe64BveY4dMvw",  
        "status" : "1",  
        "new fileId" : "FjRrf91UdjQnffuMcw-xlJJlNeVgWHEwJ",  
        "srcContainerId" : "IAACk0hRXpq9DAWkA1465823622533999616"  
    } ],  
    "code" : 0,  
    "msg" : "Success."  
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.20 Collaboration Portal

### 4.20.1 Listing Related Files

#### Function

List files related to you.

#### URI

GET /koodrive/ose/v1/related

**Table 4-472** Query Parameters

| Parameter     | Mandatory | Type    | Description   |
|---------------|-----------|---------|---|
| pageSize      | No        | Integer | Number of records to be returned on each page. Default and maximum value: 100. It is possible that partial or empty result pages are returned before the end of the result list has been reached. |
| pageCursor    | No        | String  | Current page cursor, which is obtained from <b>nextCursor</b> of the previous response. Default value: <b>0</b> .   |
| sortType      | No        | Integer | Sorting type. <b>1</b> : by operation time (default).   |
| sortDirection | No        | Integer | Sorting order. <b>1</b> : ascending; <b>2</b> : descending (default).   |
| displayName   | No        | String  | Fuzzy match by display name is supported.   |
| relatedType   | No        | String  | Related file type. <b>0</b> : all; <b>1</b> : shared with you. If this parameter is null or set to <b>0</b> , all types are queried.  |
| imageProcess  | No        | String  | Image operation, which can be used to specify the thumbnail size.   |

## Request Parameters

**Table 4-473** Request header parameters

| Parameter | Mandatory | Type   | Description                               |
|-----------|-----------|--------|---|
| X-Traceid | No        | String | Service trace ID, which contains 58 bits. |

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

Status code: 200

**Table 4-474** Response body parameters

| Parameter        | Type   | Description   |
|------------------|--|---|
| code             | String                                       | Response code.  |
| msg              | String                                       | Response information.   |
| nextCursor       | String                                       | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| relatedToMeInfos | Array of<br><b>RelatedToMeRecord</b> objects | Sharing link list.  |

| Parameter | Type | Description              |
|-----------|------|--------------------------|
| total     | Long | Total number of records. |

**Table 4-475** RelatedToMeRecord

| Parameter   | Type                                      | Description  |
|-------------|---|--|
| operator    | String                                    | Operator name.   |
| operateType | Integer                                   | Operation type. 1: sharing.  |
| operateTime | String                                    | Operation time.  |
| id          | String                                    | Record ID. If the operation type is sharing, the value is the sharing ID.  |
| displayName | String                                    | Display name.  |
| files       | Array of <a href="#">FileInfo</a> objects | File list.   |
| expireTime  | String                                    | Expiration time.   |
| status      | Integer                                   | 0: determined based on the expiration time. 1: The file has been deleted. 2: The space has expired (the space has been disabled or deleted or you do not have the space permission). |
| operatorId  | String                                    | Operator ID.   |
| containerId | String                                    | Space ID.  |
| tenantId    | String                                    | Tenant ID.   |

**Table 4-476** FileInfo

| Parameter     | Type  | Description   |
|---------------|---|---|
| id            | String  | File ID.  |
| size          | String  | File size.  |
| fileType      | String  | File type.  |
| downloadLinks | Array of <a href="#">DownloadLink</a> objects | Required by the image type (when <b>fileType</b> is set to 15). |
| recycled      | Boolean                                       | Whether the file is in the recycle bin.                         |

**Table 4-477** DownloadLink

| Parameter    | Type   | Description   |
|--------------|--------|---|
| usage        | String | Default usage: <b>content</b> or <b>thumbnail</b> . This parameter is customizable. |
| downloadLink | String | Attachment download link.   |

## Example Requests

Lists files related to you.

```
GET /koodrive/ose/v1/related?  
sortType=1&sortDirection=2&pageSize=2&pageCursor=&displayName=&relatedType=1  
  
{  
    "total" : 1,  
    "relatedToMeInfos" : [ {  
        "id" : "1427677119873431808",  
        "operator" : "zujian1",  
        "operatorId" : "1395664261493231745",  
        "operateType" : 1,  
        "operateTime" : "2024-05-23T11:39:35.000Z",  
        "displayName" : "Content Not Reviewed.docx",  
        "files" : [ {  
            "id" : "Fv54zG8ha44HX2XRlrQlM76zD4KAN2uOB",  
            "size" : 50383,  
            "fileType" : "26",  
            "recycled" : false,  
            "downloadLinks" : [ {  
                "usage" : "content",  
                "downloadLink" : "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/  
6957916206ce4407ac9436567b14d719086?response-content-disposition=attachment%3B%20filename%2A  
%3DUTF-8%27%27%25E5%2586%2585%25E5%25AE%25B9%25E6%259C%25AA%25E5%25AE  
%25A1%25E6%25A0%25B8.docx&X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-  
Date=20240523T113937Z&X-Amz-SignedHeaders=host&X-Amz-Expires=3600&X-Amz-  
Credential=MKRISPBZAJWFHNB5WLB%2F20240523%2Fcidec-rp-2006%2Fs3%2Faws4_request&X-Amz-  
Signature=e130a202a80157e63583bd7597452eb1d30a70c610db86be6871754114e2bd0"  
}, {  
                "usage" : "thumbnail",  
                "downloadLink" : "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/  
6957916206ce4407ac9436567b14d719086?x-image-process=image%2Fresize%2Cm_lfit  
%2Ch_128%2Cw_128&response-content-disposition=attachment%3B%20filename%2A  
%3DUTF-8%27%27%25E5%2586%2585%25E5%25AE%25B9%25E6%259C%25AA%25E5%25AE  
%25A1%25E6%25A0%25B8.docx&X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-  
Date=20240523T113937Z&X-Amz-SignedHeaders=host&X-Amz-Expires=3600&X-Amz-  
Credential=MKRISPBZAJWFHNB5WLB%2F20240523%2Fcidec-rp-2006%2Fs3%2Faws4_request&X-Amz-  
Signature=e78515818612dbb024bf14300bd63bbb340e7f7476b988143089ce6d92d6d9f9"  
} ]  
    } ],  
    "expireTime" : "2024-05-30T11:39:35.000Z",  
    "status" : 0,  
    "containerId" : "IAAFFyRN07vFgAAA1395504262720721025",  
    "tenantId" : "d5ac574bd2934a69baa4f23c55daa8d4"  
},  
    "code" : 0,  
    "msg" : "OK"  
}
```

## Example Responses

Status code: 200

OK

```
{  
    "code": "string",  
    "msg": "string",  
    "nextCursor": "string",  
    "relatedToMeInfos": [ {  
        "operator": "string",  
        "operateType": 0,  
        "operateTime": "2024-06-03T02:25:41.085Z",  
        "id": "string",  
        "displayName": "string",  
        "files": [ {  
            "id": "string",  
            "size": "string",  
            "fileType": "string",  
            "downloadLinks": [ {  
                "usage": "string",  
                "downloadLink": "string"  
            } ],  
            "recycled": true  
        } ],  
        "expireTime": "2024-06-03T02:25:41.085Z",  
        "status": 0,  
        "operatorId": "string",  
        "containerId": "string",  
        "tenantId": "string"  
    } ],  
    "total": 0  
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.20.2 Listing Recently Visited Files

### Function

List files that you recently visited.

### URI

GET /koodrive/ose/v1/access

**Table 4-478** Query Parameters

| Parameter    | Mandatory | Type   | Description   |
|--------------|-----------|--------|---|
| imageProcess | No        | String | Image operation, which can be used to specify the thumbnail size. |

## Request Parameters

**Table 4-479** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| X-Traceid     | No        | String | Service trace ID, which contains 58 bits.  |
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

Status code: 200

**Table 4-480** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response information. |

| Parameter | Type  | Description                     |
|-----------|---|---------------------------------|
| list      | Array of<br><a href="#">RecentlyAccess</a><br>objects | List of recently visited files. |

**Table 4-481** RecentlyAccess

| Parameter   | Type                                     | Description  |
|-------------|--|--|
| operateTime | String                                   | Operation time.  |
| operateType | Integer                                  | Operation type. <b>1</b> : view; <b>2</b> : edit; <b>3</b> : share; <b>4</b> : dump; <b>5</b> : upload (only for whitelisted users); <b>6</b> : share and dump (only for whitelisted users). |
| file        | <a href="#">AccessFileInfo</a><br>object | Basic file information.  |
| status      | Integer                                  | Status. <b>1</b> : The file has been deleted. <b>2</b> : The space has expired (the space has been disabled or deleted or you do not have the space permission).                             |

**Table 4-482** AccessFileInfo

| Parameter       | Type   | Description  |
|-----------------|--------|--|
| id              | String | File ID.   |
| containerId     | String | Space ID.  |
| name            | String | File name.   |
| collaboratorId  | String | Co-author ID.  |
| collaborator    | String | Co-author name.  |
| collaborateTime | String | Collaboration time.  |
| collaborateType | String | Collaboration type. <b>2</b> : editing; <b>3</b> : sharing; <b>4</b> : saving to the individual space. |

| Parameter     | Type    | Description   |
|---------------|---------|---|
| fileType      | String  | File type. /*<br>* Folder<br>/* FOLDER = "10", /*<br>* Image<br>/* PICTURE = "15", /*<br>* Video<br>/* VIDEO = "20", /*<br>* Word file<br>/* WORD = "26", /*<br>* Excel file<br>/* EXCEL = "27", /*<br>* PowerPoint file<br>/* PPT = "28", /*<br>* Audio<br>/* AUDIO = "30", /*<br>* Compressed file<br>/* ARCHIVE = "35", /*<br>* Application<br>/* APPLICATION = "40", /*<br>* Other<br>*/<br>OTHER = "45", |
| owner         | String  | File owner.   |
| containerName | String  | For an individual space, this parameter is null. For a department space, the value is the department name.  |
| containerType | Integer | <b>0</b> : department space; <b>1</b> : individual space; <b>2</b> : group space.   |
| favorite      | Boolean | <b>true</b> : The file is added to favorites.<br><b>false</b> : The file is not added to favorites.   |
| teamId        | String  | For an individual space, this parameter is null. For a department space, the value is the department ID. For a group space, the value is the group ID.  |

## Example Requests

GET /koodrive/ose/v1/access

## Example Responses

**Status code: 200**

OK

```
{  
    "code" : "string",  
    "msg" : "string",  
    "list" : [ {  
        "operateTime" : "2024-06-03T02:26:45.897Z",  
        "operType" : 0,  
        "file" : {  
            "id" : "string",  
            "containerId" : "string",  
            "name" : "string",  
            "collaboratorId" : "string",  
            "collaborator" : "string",  
            "collaborateTime" : "2024-06-03T02:26:45.897Z",  
            "collaborateType" : "string",  
            "fileType" : "string",  
            "owner" : "string",  
            "containerName" : "string",  
            "containerType" : 0,  
            "favorite" : true,  
            "teamId" : "string"  
        },  
        "status" : 0  
    } ]  
}
```

## Status Codes

| Status Code | Description |
|-------------|-------------|
| 200         | OK          |

## 4.21 Message Notifications

### 4.21.1 Obtaining the Number of Unread Messages

#### Function

Obtain the number of unread messages.

#### URI

GET /koodrive/ose/v1/message/unreadCount

## Request Parameters

**Table 4-483** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-484** Response body parameters

| Parameter | Type    | Description                |
|-----------|---------|----------------------------|
| code      | String  | Response code.             |
| msg       | String  | Response information.      |
| count     | Integer | Number of unread messages. |

## Example Requests

None

## Example Responses

None

## Status Codes

| Status Code | Description  |
|-------------|--|
| 200         | Response body for obtaining the number of unread messages. |

## 4.21.2 Listing Messages

### Function

List messages.

### URI

GET /koodrive/ose/v1/message/list

**Table 4-485** Query Parameters

| Parameter  | Mandatory | Type    | Description   |
|------------|-----------|---------|---|
| pageSize   | No        | Integer | Number of records to be returned on each page. Default and maximum value: 100. It is possible that partial or empty result pages are returned before the end of the result list has been reached. |
| pageCursor | No        | String  | Current page cursor, which is obtained from <b>nextCursor</b> of the previous response. Default value: 0.   |
| filterType | No        | String  | Filter type.<br><b>000</b> : sharing messages.<br><b>001</b> : team messages.<br><b>002</b> : system messages.<br><b>003</b> : management messages.   |
| state      | No        | Integer | Message status. 0: unread; 1: read.   |

## Request Parameters

**Table 4-486** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

Status code: 200

**Table 4-487** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response information. |

| Parameter  | Type                               | Description   |
|------------|------------------------------------|---|
| nextCursor | String                             | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| messages   | <a href="#">MessageInfo object</a> | Message object.   |

**Table 4-488 MessageInfo**

| Parameter  | Type    | Description             |
|------------|---------|-------------------------|
| id         | String  | Message ID.             |
| sender     | String  | Message sender.         |
| type       | String  | Message type.           |
| context    | String  | Message body.           |
| state      | Integer | Message status.         |
| createTime | String  | Message receiving time. |

## Example Requests

None

## Example Responses

None

## Status Codes

| Status Code | Description                                   |
|-------------|---|
| 200         | Response body for obtaining the message list. |

## 4.21.3 Marking Messages as Read in Batches

### Function

Mark messages as read in batches.

### URI

POST /koodrive/ose/v1/message/batchRead

## Request Parameters

**Table 4-489** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

**Table 4-490** Request body parameters

| Parameter | Mandatory | Type             | Description |
|-----------|-----------|------------------|-------------|
| ids       | Yes       | Array of strings | Message ID. |

## Response Parameters

Status code: 200

**Table 4-491** Response body parameters

| Parameter | Type  | Description                            |
|-----------|---|--|
| messages  | Array of<br><a href="#">UpdateMessageStateResponse</a><br>objects | Response for modifying message status. |

**Table 4-492** UpdateMessageStateResponse

| Parameter | Type    | Description          |
|-----------|---------|----------------------|
| id        | String  | Message ID.          |
| changed   | Boolean | Modification result. |

## Example Requests

None

## Example Responses

None

## Status Codes

| Status Code | Description  |
|-------------|--|
| 200         | Response body for marking messages as read in batches. |

## 4.21.4 Batch Message Deletion

### Function

Delete selected messages in batches.

### URI

DELETE /koodrive/ose/v1/message/batchDelete

## Request Parameters

**Table 4-493** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

**Status code: 200**

**Table 4-494** Response body parameters

| Parameter | Type  | Description                            |
|-----------|---|--|
| messages  | Array of <b>UpdateMessageStatusResponse</b> objects | Response for modifying message status. |

**Table 4-495** UpdateMessageStateResponse

| Parameter | Type    | Description          |
|-----------|---------|----------------------|
| id        | String  | Message ID.          |
| changed   | Boolean | Modification result. |

## Example Requests

None

## Example Responses

None

## Status Codes

| Status Code | Description                                    |
|-------------|--|
| 200         | Response body for deleting messages in batches |

## 4.21.5 Modify message status (marks all unread messages as read or deletes all messages).

### Function

Modify message status (marks all unread messages as read or deletes all messages).

### URI

POST /koodrive/ose/v1/message/specific

**Table 4-496** Query Parameters

| Parameter | Mandatory | Type    | Description   |
|-----------|-----------|---------|---|
| operate   | Yes       | Integer | Operation of modifying message status. <b>0</b> : marks unread messages as read. <b>1</b> : deletes all messages. |

## Request Parameters

**Table 4-497** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is <b>Bearer+{access_token}</b> . |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en-US</b> indicates English (United States). English (United States) is used by default.   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |
| Host          | Yes       | String | Address, which is used for app authentication.   |

## Response Parameters

Status code: 200

**Table 4-498** Response body parameters

| Parameter | Type   | Description           |
|-----------|--------|-----------------------|
| code      | String | Response code.        |
| msg       | String | Response information. |

## Example Requests

None

## Example Responses

None

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Response body for modifying the message status of a user. |

## 4.22 Refined Authorization

### 4.22.1 Obtaining the User Permissions List

#### Function

Obtain the user permissions list.

#### URI

GET /koodrive/ose/v1/permission/userList

**Table 4-499** Query Parameters

| Parameter   | Mandatory | Type    | Description   |
|-------------|-----------|---------|---|
| templatelId | No        | String  | Permissions template ID. <ul style="list-style-type: none"><li>• <b>-1</b>: anonymous template.</li><li>• Other values: ID of a named template.</li></ul> |
| spaceType   | Yes       | Integer | Space type. <ul style="list-style-type: none"><li>• <b>0</b>: department.</li><li>• <b>1</b>: group.</li></ul>  |
| groupId     | No        | String  | Group ID (mandatory when the space type is set to <b>1</b> ).   |
| deptId      | No        | String  | Department ID (mandatory when the space type is set to <b>0</b> ).  |
| count       | No        | Integer | Number of records to be returned. Maximum value: 100.   |

| Parameter   | Mandatory | Type   | Description   |
|-------------|-----------|--------|---|
| cursor      | No        | String | Cursor, which is not transferred for the first call. (For subsequent calls, obtain the cursor from the previous response body to return results starting from the user next to the last user in the previous response.) |
| containerId | Yes       | String | Space ID.   |
| userName    | No        | String | Username.   |
| fileId      | No        | String | File ID.  |

## Request Parameters

**Table 4-500** Request header parameters

| Parameter     | Mandatory | Type   | Description  |
|---------------|-----------|--------|--|
| Authorization | Yes       | String | 1. The format is <b>Bearer {app_access_token}</b> . The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using <b>clientid</b> and <b>clientSecret</b> obtained during application creation.<br>2. The application is the KooDrive server. |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.  |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en_us</b> indicates English (United States).   |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.   |
| X-Date        | Yes       | String | Date, which is used for app authentication.  |

| Parameter | Mandatory | Type   | Description                                    |
|-----------|-----------|--------|--|
| Host      | No        | String | Address, which is used for app authentication. |

## Response Parameters

Status code: 200

**Table 4-501** Response body parameters

| Parameter          | Type  | Description            |
|--------------------|---|------------------------|
| userPermissontList | Array of<br><a href="#">userPermissont</a><br>objects | User permissions list. |
| code               | String  | Response code.         |
| msg                | String  | Response message.      |
| nextCursor         | String  | Cursor.                |

**Table 4-502** userPermissont

| Parameter    | Type    | Description  |
|--------------|---------|--|
| userName     | String  | Username.  |
| mobile       | String  | Mobile number.   |
| deptName     | String  | Department name.   |
| deptId       | String  | Department ID.   |
| templatelId  | String  | Template ID.   |
| groupName    | String  | Group name.  |
| description  | String  | Permissions description returned when an anonymous template is used. |
| userId       | String  | User ID.   |
| templateName | String  | Template name.   |
| deptRole     | Integer | Role in the department (under the transferred <b>deptId</b> ).       |
| groupRole    | Integer | Role in the group (under the transferred <b>group</b> ).             |

| Parameter    | Type                                       | Description        |
|--------------|--|--------------------|
| capabilities | Array of<br><b>Capabilities</b><br>objects | Permissions value. |

**Table 4-503** Capabilities

| Parameter                 | Type    | Description   |
|---------------------------|---------|---|
| addChildNodePermission    | Boolean | Permission to create a file or folder. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| copyPermission            | Boolean | Copy permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                       |
| deletePermission          | Boolean | Delete permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                     |
| downloadPermission        | Boolean | Download permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                   |
| editPermission            | Boolean | Edit permissions. <b>true</b> : granted; <b>false</b> : not granted (editing is not supported.)   |
| listChildNodePermission   | Boolean | Permission to view the list. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| removeChildNodePermission | Boolean | Move permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                       |
| renameFilePermission      | Boolean | Rename permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                     |
| shareFilePermission       | Boolean | Share permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                      |

| Parameter        | Type    | Description  |
|------------------|---------|--|
| uploadPermission | Boolean | Upload permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.  |
| viewPermission   | Boolean | Preview permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |

## Example Requests

Example request for obtaining the user permissions list.

```
/koodrive/ose/v1/permission/userList?  
spaceType=0&deptId=1570902****4673&count=100&containerId=IAAFW*****054209
```

```
Authorization:Bearer+7b8d5d009443187d149432249b2482fbc87d1be0c1dd3f6f
```

## Example Responses

**Status code: 200**

Response to the request for obtaining the user permissions list.

```
{  
    "userPermissionList" : [ {  
        "userName" : "111",  
        "userId" : "15842*****45888",  
        "mobile" : "0086137***6060",  
        "deptName" : "ce**i-1",  
        "templateId" : "1568195451952301579",  
        "capabilities" : {  
            "addChildNodePermission" : true,  
            "copyPermission" : true,  
            "deletePermission" : false,  
            "downloadPermission" : true,  
            "editPermission" : true,  
            "listChildNodePermission" : true,  
            "removeChildNodePermission" : true,  
            "renameFilePermission" : true,  
            "shareFilePermission" : true,  
            "uploadPermission" : true,  
            "viewPermission" : true  
        },  
        "templateName" : "Unable to Delete",  
        "deptRole" : 1  
    } ],  
    "code" : 0,  
    "msg" : "Successful."  
}
```

## Status Codes

| Status Code | Description  |
|-------------|--|
| 200         | Response to the request for obtaining the user permissions list. |

## 4.22.2 Updating Permissions in Batches

### Function

Update permissions in batches.

### URI

PUT /koodrive/ose/v1/permission/batchupdate

### Request Parameters

**Table 4-504** Request header parameters

| Parameter     | Mandatory | Type   | Description   |
|---------------|-----------|--------|---|
| Authorization | Yes       | String | The format is <b>Bearer {app_access_token}</b> . The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using <b>clientid</b> and <b>clientSecret</b> obtained during application creation. |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.   |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en_us</b> indicates English (United States).  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.  |
| X-Date        | Yes       | String | Date, which is used for app authentication.   |
| Host          | No        | String | Address, which is used for app authentication.  |

**Table 4-505** Request body parameters

| Parameter     | Mandatory | Type  | Description  |
|---------------|-----------|---|--|
| amendModRoles | Yes       | Array of <a href="#">AmendModRole</a> objects | Roles to be modified.  |
| type          | Yes       | Integer                                       | Type. <b>0</b> : team space; <b>1</b> : group space.                               |
| container     | Yes       | String  | Space ID.  |
| fileId        | No        | String  | File ID (If a file ID is specified, the permissions for the resource are granted.) |

**Table 4-506** AmendModRole

| Parameter    | Mandatory | Type                                | Description  |
|--------------|-----------|-------------------------------------|--|
| userId       | Yes       | Long                                | User ID.   |
| template     | Yes       | Long                                | Permission template ID. For an anonymous template, set this parameter to <b>-1</b> . (This parameter is optional when members are added to or deleted from a user group in batches.) |
| capabilities | No        | <a href="#">Capabilities</a> object | Permission value (transferred when a template is customized).  |

**Table 4-507** Capabilities

| Parameter              | Mandatory | Type    | Description   |
|------------------------|-----------|---------|---|
| addChildNodePermission | Yes       | Boolean | Permission to create a file or folder. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| copyPermission         | Yes       | Boolean | Copy permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                       |

| Parameter                 | Mandatory | Type    | Description   |
|---------------------------|-----------|---------|---|
| deletePermission          | Yes       | Boolean | Delete permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| downloadPermission        | Yes       | Boolean | Download permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.         |
| editPermission            | Yes       | Boolean | Edit permissions. <b>true</b> : granted; <b>false</b> : not granted (editing is not supported.)   |
| listChildNodePermission   | Yes       | Boolean | Permission to view the list. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| removeChildNodePermission | Yes       | Boolean | Move permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.             |
| renameFilePermission      | Yes       | Boolean | Rename permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| shareFilePermission       | Yes       | Boolean | Share permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.            |
| uploadPermission          | Yes       | Boolean | Upload permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| viewPermission            | Yes       | Boolean | Preview permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.          |

## Response Parameters

**Status code: 200**

**Table 4-508** Response body parameters

| Parameter | Type    | Description    |
|-----------|---------|----------------|
| code      | Integer | Error code.    |
| msg       | String  | Error message. |

## Example Requests

```
/koodrive/ose/v1/permission/batchupdate

{
  "amendModRoles" : [ {
    "userId" : "*****",
    "template" : "*****",
    "capabilities" : {
      "addChildNodePermission" : true,
      "copyPermission" : false,
      "deletePermission" : false,
      "downloadPermission" : true,
      "editPermission" : false,
      "listChildNodePermission" : true,
      "removeChildNodePermission" : false,
      "renameFilePermission" : false,
      "shareFilePermission" : false,
      "uploadPermission" : true,
      "viewPermission" : true
    }
  }],
  "type" : 0,
  "container" : "*****",
  "fileId" : "*****"
}
```

## Example Responses

**Status code: 200**

Response for updating permissions in batches.

```
{
  "code" : 0,
  "msg" : "success"
}
```

## Status Codes

| Status Code | Description                                   |
|-------------|---|
| 200         | Response for updating permissions in batches. |

## 4.22.3 Querying Initial Permissions of a Member

### Function

Query initial permissions of a member.

### URI

GET /koodrive/ose/v1/permission/member/initial/{spaceId}

**Table 4-509** Path Parameters

| Parameter | Mandatory | Type | Description          |
|-----------|-----------|------|----------------------|
| spaceId   | Yes       | Long | Group/Department ID. |

### Request Parameters

**Table 4-510** Request header parameters

| Parameter     | Mandatory | Type   | Description   |
|---------------|-----------|--------|---|
| Authorization | Yes       | String | The format is <b>Bearer {app_access_token}</b> . The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using <b>clientId</b> and <b>clientSecret</b> obtained during application creation. |
| X-Traceid     | No        | String | Message log trace ID. The value contains 58 bits.   |
| language      | No        | String | Language code, which complies with the internationalization specifications. For example, <b>en_us</b> indicates English (United States).  |
| X-User-Id     | Yes       | String | User ID, which is used for app authentication.  |
| X-Date        | Yes       | String | Date, which is used for app authentication.   |
| Host          | No        | String | Address, which is used for app authentication.  |

## Response Parameters

Status code: 200

**Table 4-511** Response body parameters

| Parameter | Type   | Description                 |
|-----------|--|-----------------------------|
| code      | Integer  | Response code.              |
| msg       | String   | Response information.       |
| data      | <a href="#">MemberInitialPermission object</a> | Initial member permissions. |

**Table 4-512** MemberInitialPermission

| Parameter    | Type                                | Description          |
|--------------|-------------------------------------|----------------------|
| userId       | Long                                | User ID.             |
| spaceId      | Long                                | Group/Department ID. |
| containerId  | String                              | Space ID.            |
| spaceType    | Integer                             | Space type.          |
| templateId   | String                              | Template ID.         |
| templateName | String                              | Template name.       |
| capabilities | <a href="#">Capabilities object</a> | User permissions.    |

**Table 4-513** Capabilities

| Parameter              | Type    | Description   |
|------------------------|---------|---|
| addChildNodePermission | Boolean | Permission to create a file or folder. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| copyPermission         | Boolean | Copy permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                       |
| deletePermission       | Boolean | Delete permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.                     |

| Parameter                 | Type    | Description   |
|---------------------------|---------|---|
| downloadPermission        | Boolean | Download permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.         |
| editPermission            | Boolean | Edit permissions. <b>true</b> : granted; <b>false</b> : not granted (editing is not supported.)   |
| listChildNodePermission   | Boolean | Permission to view the list. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted. |
| removeChildNodePermission | Boolean | Move permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.             |
| renameFilePermission      | Boolean | Rename permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| shareFilePermission       | Boolean | Share permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.            |
| uploadPermission          | Boolean | Upload permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.           |
| viewPermission            | Boolean | Preview permission. The value <b>true</b> indicates that the permission is granted, and the value <b>false</b> indicates that the permission is not granted.          |

## Example Requests

```
/koodrive/ose/v1/permission/member/initial/15*****01
```

```
Authorization:Bearer+7b8d5d009443187d149432249b2482fbc87d1be0c1dd3f6f
```

## Example Responses

**Status code: 200**

Response body for querying initial administrator permissions.

```
{  
    "data": {  
        "userId": "****",  
        "spaceId": "****",  
        "permissions": {  
            "download": true,  
            "edit": false,  
            "list": true,  
            "move": true,  
            "rename": true,  
            "share": true,  
            "upload": true,  
            "view": true  
        }  
    }  
}
```

```
"containerId": "*****",
"spaceType": 0,
"templateId": "*****",
"templateName": "Upload",
"capabilities": {
    "addChildNodePermission": true,
    "copyPermission": false,
    "deletePermission": false,
    "downloadPermission": true,
    "editPermission": false,
    "listChildNodePermission": true,
    "removeChildNodePermission": false,
    "renameFilePermission": false,
    "shareFilePermission": false,
    "uploadPermission": true,
    "viewPermission": true
},
"code": 0,
"msg": "success"
}
```

## Status Codes

| Status Code | Description   |
|-------------|---|
| 200         | Response body for querying initial administrator permissions. |

# 5 Appendixes

## 5.1 Status Codes

[Table 5-1](#) describes common status codes.

**Table 5-1** Status codes

| Status Code | Message               | Description   |
|-------------|-----------------------|---|
| 200         | OK                    | The request has succeeded.  |
| 400         | Bad Request           | Authentication failed.  |
| 401         | Unauthorized          | Unauthorized.   |
| 500         | Internal Server Error | The server encountered an unexpected condition that prevented it from fulfilling the request. |

## 5.2 Error Codes

If an error code starting with APIGW is returned after you call an API, rectify the fault by referring to the instructions provided in [API Gateway Error Codes](#).

| Status Code | Error Codes | Error Message             | Description               | Solution            |
|-------------|-------------|---------------------------|---------------------------|---------------------|
| 400         | 13000102    | Verify parameters failed. | Verify parameters failed. | Check parameters.   |
| 400         | 13000301    | Space not found.          | Space not found.          | Check space status. |

| Status Code | Error Codes | Error Message  | Description  | Solution   |
|-------------|-------------|--|--|--|
| 400         | 13000302    | File is not in the specified space.  | File is not in the specified space.  | Check the space where the file is located.                         |
| 400         | 13000303    | This operation cannot be performed because the file is not in the recycle bin. | This operation cannot be performed because the file is not in the recycle bin. | Move the file to the recycle bin.                                  |
| 400         | 13000304    | Target directory is abnormal.  | Target directory is abnormal.  | Try again later. If the fault persists, contact technical support. |
| 400         | 13000305    | Target directory is in the recycle bin.  | Target directory is in the recycle bin.  | Remove the directory from the recycle bin.                         |
| 400         | 13000306    | File is in the recycle bin.  | File is in the recycle bin.  | Restore the file from the recycle bin.                             |
| 400         | 13000307    | Nested directories.  | Nested directories.  | Try again later. If the fault persists, contact technical support. |
| 400         | 13000308    | File metadata error.   | File metadata error.   | Try again later. If the fault persists, contact technical support. |
| 400         | 13000309    | Resource not found.  | Resource not found.  | Try again later. If the fault persists, contact technical support. |
| 400         | 13000310    | Max. levels exceeded.  | Max. levels exceeded.  | Delete a level.  |
| 400         | 13000311    | Insufficient space.  | Insufficient space.  | Contact the administrator to expand capacity.                      |
| 400         | 13000312    | File already in the target folder.   | File already in the target folder.   | No operation required.   |

| Status Code | Error Codes | Error Message                                     | Description                                       | Solution   |
|-------------|-------------|---|---|--|
| 400         | 13000401    | Upload task not found.                            | Upload task not found.                            | Try again later. If the fault persists, contact technical support. |
| 400         | 13000402    | File upload incomplete.                           | File upload incomplete.                           | Try again later. If the fault persists, contact technical support. |
| 400         | 13000403    | Change file status failed.                        | Change file status failed.                        | Try again later. If the fault persists, contact technical support. |
| 400         | 13000404    | Parent directory is in the recycle bin.           | Parent directory is in the recycle bin.           | Remove the directory from the recycle bin.                         |
| 400         | 13000405    | Duplicate file name.                              | Duplicate file name.                              | Enter a unique file name.  |
| 400         | 13000406    | This operation cannot be performed on the folder. | This operation cannot be performed on the folder. | Check the folder.  |
| 400         | 13000407    | File download address not found.                  | File download address not found.                  | Try again later. If the fault persists, contact technical support. |
| 400         | 13000408    | Download file failed.                             | Download file failed.                             | Try again later. If the fault persists, contact technical support. |
| 400         | 13000409    | Upload file failed.                               | Upload file failed.                               | Try again later. If the fault persists, contact technical support. |
| 400         | 13000410    | No permission to perform operations on space {0}. | No permission to perform operations on space {0}. | Check permissions.   |
| 400         | 13000411    | File {0} is not in space {1}                      | File {0} is not in space {1}                      | Check the space where the file is located.                         |

| Status Code | Error Codes | Error Message   | Description   | Solution   |
|-------------|-------------|---|---|--|
| 400         | 13000412    | Space {0} is not activated.                                       | Space {0} is not activated.                                       | Activate the space.  |
| 400         | 13000413    | Unsupported operation type: {0}                                   | Unsupported operation type: {0}                                   | Enter a correct search type.                                       |
| 400         | 13000414    | Search type cannot be blank.                                      | Search type cannot be blank.                                      | Enter a search type.   |
| 400         | 13000415    | Space does not match the team.                                    | Space does not match the team.                                    | Check the space and team.  |
| 400         | 13000417    | File name: Max. 250 characters.                                   | File name: Max. 250 characters.                                   | Shorten the file name to max. 250 characters.                      |
| 400         | 13000419    | The fileName can not contain '<> :\\"*?/\\", cannot equal .. or . | The fileName can not contain '<> :\\"*?/\\", cannot equal .. or . | Enter a correct file name.   |
| 401         | 13000202    | Invalid sign-in information.                                      | Invalid sign-in information.                                      | Check authentication.  |
| 500         | 13000201    | Call internal server failed. Please try again later.              | Call internal server failed. Please try again later.              | Try again later. If the fault persists, contact technical support. |