

KooDrive

API Reference

Issue 01
Date 2024-07-30



Copyright © Huawei Cloud Computing Technologies Co., Ltd. 2024. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Cloud Computing Technologies Co., Ltd.

Trademarks and Permissions



HUAWEI and other Huawei trademarks are the property of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei Cloud and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Contents

| | |
|--|-----------|
| 1 Before You Start..... | 1 |
| 1.1 Overview..... | 1 |
| 1.2 API Calling..... | 1 |
| 1.3 Endpoints..... | 1 |
| 1.4 Constraints..... | 1 |
| 1.5 Concepts..... | 2 |
| 2 API Overview..... | 3 |
| 3 Calling APIs..... | 5 |
| 3.1 Making an API Request..... | 5 |
| 3.2 Authentication..... | 7 |
| 3.3 Response..... | 8 |
| 4 API..... | 10 |
| 4.1 Batch Task Operations..... | 10 |
| 4.1.1 Listing Batch Tasks..... | 10 |
| 4.1.2 Creating a Batch Task..... | 14 |
| 4.1.3 Querying Details About a Batch Task..... | 18 |
| 4.1.4 Cancelling a Batch Task..... | 23 |
| 4.2 Department Management..... | 25 |
| 4.2.1 Listing Departments..... | 26 |
| 4.2.2 Querying a Department..... | 28 |
| 4.2.3 Creating a Department..... | 30 |
| 4.2.4 Modifying a Department..... | 32 |
| 4.2.5 Deleting a Department..... | 34 |
| 4.3 User Management..... | 36 |
| 4.3.1 Listing Users..... | 36 |
| 4.3.2 Querying Information About a User..... | 39 |
| 4.3.3 Counting Members in an Organization or Department..... | 42 |
| 4.3.4 Creating a User..... | 43 |
| 4.3.5 Modifying a User..... | 45 |
| 4.3.6 Deleting a User..... | 47 |
| 4.3.7 Querying the Mobile Number of a User..... | 49 |
| 4.4 Space Management..... | 51 |

| | |
|--|-----|
| 4.4.1 Listing Departments Spaces..... | 51 |
| 4.4.2 Querying Space Information..... | 55 |
| 4.4.3 Creating a Space for a Department or Individual..... | 58 |
| 4.4.4 Modifying Space Information..... | 60 |
| 4.4.5 Deleting a Space..... | 62 |
| 4.4.6 Querying Space Details by Space ID..... | 64 |
| 4.4.7 Querying Information About a Team Space..... | 67 |
| 4.4.8 Creating a Group Space..... | 70 |
| 4.4.9 Listing Group Spaces in an Enterprise..... | 72 |
| 4.4.10 Dismissing a Team Space..... | 76 |
| 4.4.11 Listing User Spaces..... | 78 |
| 4.5 Group Management..... | 81 |
| 4.5.1 Creating a User Group..... | 81 |
| 4.5.2 Listing User Groups..... | 83 |
| 4.5.3 Modifying Group Information..... | 86 |
| 4.5.4 Deleting a Group..... | 88 |
| 4.5.5 Listing Members in a User Group..... | 90 |
| 4.5.6 Adding Members to a User Group..... | 93 |
| 4.5.7 Deleting Members from a User Group..... | 95 |
| 4.6 Session Management..... | 97 |
| 4.6.1 Checking Whether a User Session Is Invalid Based on Token Information..... | 97 |
| 4.6.2 Obtaining the URL of an OrgID Authorization Code for KooDrive..... | 100 |
| 4.6.3 Initializing and Creating a Session..... | 101 |
| 4.6.4 Refreshing a Session..... | 103 |
| 4.6.5 Signing In and Signing Out..... | 105 |
| 4.7 Service Subscription..... | 106 |
| 4.7.1 Obtaining the Subscription Status..... | 106 |
| 4.7.2 Querying Service Usage..... | 109 |
| 4.8 Enterprise Settings..... | 111 |
| 4.8.1 Setting the Expiration Time of a Compressed Package..... | 111 |
| 4.9 Cloud Decompression..... | 113 |
| 4.9.1 Listing Directories in a Compressed Package..... | 113 |
| 4.10 File List Query..... | 116 |
| 4.10.1 Listing Files in the Individual Space..... | 116 |
| 4.10.2 Listing Files in a Group or Department Space..... | 124 |
| 4.11 File Management..... | 133 |
| 4.11.1 Obtaining File Details..... | 133 |
| 4.11.2 Adding a File Directory..... | 139 |
| 4.11.3 Creating File Metadata..... | 142 |
| 4.11.4 Checking Whether File Upload Is Completed..... | 148 |
| 4.11.5 Obtaining Download Links..... | 150 |
| 4.11.6 Renaming a File..... | 153 |

| | |
|---|------------|
| 4.11.7 Clearing the Recycle Bin..... | 155 |
| 4.11.8 Retrieving Files Using Search Engine Capabilities..... | 157 |
| 4.11.9 Obtaining the Full Name and ID Paths of a File..... | 164 |
| 4.12 File Favorites..... | 166 |
| 4.12.1 Adding Files to Favorites..... | 166 |
| 4.12.2 Listing Files in Favorites..... | 168 |
| 4.13 Sharing Management - Shared by You..... | 183 |
| 4.13.1 Sharing a File..... | 183 |
| 4.13.2 Listing Files Shared by You..... | 188 |
| 4.13.3 Obtaining Sharing Details..... | 192 |
| 4.13.4 Modifying Sharing Settings..... | 196 |
| 4.13.5 Stopping Sharing Files..... | 199 |
| 4.14 Sharing Management - Shared with You..... | 200 |
| 4.14.1 Listing Files Shared with You..... | 201 |
| 4.14.2 Obtain Sharing Details..... | 205 |
| 4.14.3 Removing Yourself from Shared Files..... | 207 |
| 4.15 Sharing Management - Access Links..... | 209 |
| 4.15.1 Accessing a Sharing Link..... | 209 |
| 4.15.2 Obtaining Sharing Information..... | 211 |
| 4.15.3 Verifying a Sharing Access Code..... | 213 |
| 4.15.4 Listing Files Shared with You..... | 215 |
| 4.15.5 Downloading a File..... | 219 |
| 4.15.6 Creating an Asynchronous Sharing Task..... | 221 |
| 4.15.7 Querying an Asynchronous Task..... | 223 |
| 4.16 Collaboration Portal..... | 225 |
| 4.16.1 Listing Related Files..... | 225 |
| 4.16.2 Listing Recently Visited Files..... | 230 |
| 5 Appendixes..... | 234 |
| 5.1 Status Codes..... | 234 |
| 5.2 Error Codes..... | 234 |
| 6 Change History..... | 236 |

1 Before You Start

1.1 Overview

KooDrive is an online service provided by Huawei Cloud for government and enterprise customers. It provides functions such as data storage, access, synchronization, management, and collaboration. It is a one-stop digital content center for enterprises and enables efficient knowledge collaboration.

This document describes how to use application programming interfaces (APIs) to perform operations on KooDrive, such as adding file directories, obtaining file details, and renaming files. For details about all supported operations, see [API Overview](#).

If you plan to access KooDrive through an API, ensure that you are familiar with KooDrive concepts. For details, see [Service Overview](#).

1.2 API Calling

KooDrive supports Representational State Transfer (REST) APIs, allowing you to call APIs using HTTPS. For details about API calling, see [Calling APIs](#).

1.3 Endpoints

An endpoint is the request address for calling an API. Endpoints vary depending on services and regions. Currently, KooDrive is deployed only in the **AP-Singapore** region, and the endpoint is **intl.myhuaweicloud-koodrive.com**.

1.4 Constraints

None

1.5 Concepts

- **Account**

An account is created upon successful registration with Huawei Cloud. The account has full access permissions for all of its cloud services and resources. It can be used to reset user passwords and grant user permissions. The account is a payment entity and should not be directly used to perform routine management. For security purposes, create Identity and Access Management (IAM) users and grant them permissions for routine management.
- **User**

A KooDrive user is created by the tenant administrator (also called system administrator) in the [KooDrive service plane](#). After a KooDrive user logs in to the service system, an Access-Token (AT) is generated. The AT is used for verification and authentication of subsequent API calling.
- **Region**

Regions are divided based on geographical location and network latency. Public services, such as Elastic Cloud Server (ECS), Elastic Volume Service (EVS), Object Storage Service (OBS), Virtual Private Cloud (VPC), Elastic IP (EIP), and Image Management Service (IMS), are shared within the same region. Regions are classified into universal regions and dedicated regions. A universal region provides universal cloud services for common tenants. A dedicated region provides specific services for specific tenants.

For details, see [Region and AZ](#).
- **AZ**

An AZ contains one or more physical data centers. Each AZ has independent cooling, fire extinguishing, moisture-proof, and electricity facilities. Within an AZ, computing, network, storage, and other resources are logically divided into multiple clusters. AZs within a region are interconnected using high-speed optical fibers to support cross-AZ high-availability systems.

2 API Overview

Table 2-1 describes the KooDrive APIs.

Table 2-1 API overview

| Type | Description |
|------------------------------|---|
| Batch Task Operations | Manage batch tasks, including creating a batch task, canceling a batch task, and listing batch tasks. |
| Department Management | Manage departments, including creating, modifying, deleting, and querying a department. |
| User Management | Manage users, including creating, modifying, deleting, and querying a user. |
| Space Management | Manage spaces, including creating, modifying, deleting, and querying a space. |
| Group Management | Manage groups, including creating and deleting a user group. |
| Session Management | Manage sessions, including session creation and update, sign-in, and sign-out. |
| Service Subscription | Obtain the subscription status of the management and control service. |
| Enterprise Settings | Set the time for deleting expired compressed packages generated during package download. |
| Cloud Decompression | List compressed package directories. |
| File List Query | List files in the individual space and department space. |
| File Management | Manage files, including obtaining details about a file, adding a file directory, uploading a file, and renaming a file. |
| File Favorites | Manage files in favorites, including adding files to favorites and listing files in favorites. |

| Type | Description |
|--|--|
| Sharing Management - Shared by You | Manage files shared by you, including sharing a file, obtaining sharing details, and modifying sharing. |
| Sharing Management - Shared with You | Manage files shared with you, including obtaining sharing details and removing yourself from shared files. |
| Sharing Management - Access Links | Manage access links, including obtaining sharing details and verifying a sharing code. |
| Collaboration Portal | Query files related to you and files that you recently visited. |

3 Calling APIs

3.1 Making an API Request

This section describes the structure of a REST API request, and uses the KooDrive API for processing files as an example to demonstrate how to call an API.

Request URI

A request URI is in the following format:

{URI-scheme}://{Endpoint}/{resource-path}?{query-string}

Although a request URI is included in the request header, most programming languages or frameworks require the request URI to be transmitted separately.

Table 3-1 URI parameters

| Parameter | Description |
|---------------|---|
| URI-scheme | Protocol used to transmit requests. All KooDrive APIs use HTTPS. |
| Endpoint | Domain name or IP address of the server bearing the REST service. The endpoint varies between services in different regions. Currently, KooDrive is deployed only in the AP-Singapore region, and the endpoint is intl.myhuaweicloud-koodrive.com . |
| resource-path | Access path of an API. Obtain the path from the URI of an API. For example, the resource-path of the API used to create a batch task is /koodrive/ose/v1/jobs . |
| query-string | This optional parameter is used to query the data of a parameter. Ensure that a question mark (?) is included before each query parameter that is in the format of <i>Parameter name=Parameter value</i> . For example, ?limit=10 indicates that a maximum of 10 data records will be displayed. |

For example, to create a batch task in the **AP-Singapore** region, obtain the endpoint of KooDrive (**intl.myhuaweicloud-koodrive.com**) for this region and the **resource-path** (**/koodrive/ose/v1/jobs**) in the URI of the API used to create a batch task. Then, construct the URI as follows:

```
https://intl.myhuaweicloud-koodrive.com/koodrive/ose/v1/jobs
```

 **NOTE**

To simplify URI display, only the **resource-path** and request method are displayed. The **URI-scheme** of all APIs is **HTTPS**, and the endpoints of all APIs in the same region are identical.

Request Methods

The HTTP protocol defines the following request methods that can be used to send a request to the server:

Table 3-2 HTTP methods

| Method | Description |
|--------|---|
| GET | Request the server to return specified resources. |
| POST | Request the server to add resources or perform special operations. |
| DELETE | Request the server to delete specified resources, for example, an object. |
| PUT | Request the server to update specified resources. |

For example, in the case of the API used to create a batch task, the request method is POST. The request is as follows:

```
POST https://intl.myhuaweicloud-koodrive.com/koodrive/ose/v1/jobs
```

Request Header

- **Content-Type:** (optional) request body type or format. The default value is **application/json**. Other values of this field will be provided for specific APIs if any.
- **Authorization:** authentication.

Request header example:

```
POST https://intl.myhuaweicloud-koodrive.com/koodrive/ose/v1/jobs
Content-Type: application/json
Authorization: xxx
```

Request Body

The body of a request is often sent in a structured format as specified in the **Content-Type** header field. The request body transfers content except the request header.

The request body varies between APIs. Some APIs do not require the request body, such as the APIs requested using the GET and DELETE methods.

For the API used to process files, an example of the request body is as follows:

```
{
  "taskType":1
  "actionType":101
  "dstContainerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"
  "taskInfo": {
    "srcContainerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"
    "newFilePath": "Fm9UdqBNTAQDos6l1xPlFnIqXJg2-UdqA"
    "fileInfo": [
      {
        "fileId": "FuZmQ66CF0DdpKRG1Y29Iwajbq04Nhwu3"
      }
    ]
  }
}
```

If all data required for the API request is available, you can send the request to call the API through [curl](#), [Postman](#), or coding.

3.2 Authentication

Currently, KooDrive uses token-based authentication.

Requests are authenticated using a token.

Token-based Authentication

NOTE


A token is valid for 20 minutes. If an API is called within the validity period of the token, the validity period is reset. If no operation is performed within the validity period, the token becomes invalid.

Ensure that the token is valid when you use it. Using a token that will soon expire may cause API calling failures.

A token specifies temporary permissions in a computer system. During API authentication using a token, the token is added to requests to get permissions for calling the API.

A token is obtained from the cookies after you log in to the service frontend. As shown in [Figure 3-1](#), the value of **Authorization** is the AT to be obtained.

Figure 3-1 Obtaining a token



After a token is obtained, the **Authorization** header field must be added to requests to specify the token when calling other APIs. For example, if the token is **ABCDEFJ....**, **Authorization: ABCDEFJ....** can be added to a request as follows:

```
POST https://intl.myhuaweicloud-koodrive.com/koodrive/ose/v1/files/batch
Content-Type: application/json
Authorization: xxx
```

3.3 Response

Status Code

After sending a request, you will receive a response, including a status code, response header, and response body.

A status code is a group of digits, ranging from 1xx to 5xx. It indicates the status of a request. For more information, see [Status Codes](#).

For example, if status code **0** is returned for calling the API used to process files, the request is successful.

Response Header

Similar to a request, a response also has a header, for example, **Content-Type**.

[Figure 3-2](#) shows the response header of the API used to process files.

Figure 3-2 Response header

| Key | Value |
|------------------|---------------------------------|
| Content-Type ⓘ | application/json; charset=utf-8 |
| content-length ⓘ | 127 |

Response Body

The body of a response is often returned in structured format as specified in the **Content-Type** header field. The response body transfers content except the response header.

The following is part of the response body for the API used to process files.

```
{
  "data": "1309243162258308352"
  "code": 0,
  "msg": "success"
}
```

If an error occurs during API calling, an error code and a message will be displayed. The following shows an error response body.

```
{
  "code": 13000201,
  "msg": "inner server invoke failure"
}
```

In the response body, **code** is an error code, and **msg** provides information about the error.

4 API

4.1 Batch Task Operations

4.1.1 Listing Batch Tasks

Function

List batch tasks.

URI

GET /koodrive/ose/v1/jobs

Table 4-1 Query Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|---------|--|
| type | No | Integer | Task type. |
| status | No | Integer | Task status. |
| offset | Yes | Integer | Offset. Minimum value: 0. |
| limit | Yes | Integer | Maximum number of records to be returned. Value range: 1 to 100. |

Request Parameters

Table 4-2 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-3 Response body parameters

| Parameter | Type | Description |
|-----------|---------------------------------|-------------------|
| code | String | Response code. |
| msg | String | Response message. |
| data | Array of JobInfo objects | Batch task list. |

Table 4-4 JobInfo

| Parameter | Type | Description |
|----------------|---------|---|
| taskId | String | Task ID. |
| taskName | String | Task name. |
| userId | String | Task creator ID. |
| taskType | Integer | Task type. |
| actionType | Integer | Operation type. |
| status | Integer | Task status. |
| taskResultCode | Integer | Task result. |
| resultCode | Integer | Task result code. |
| contentNum | Integer | Number of request files. |
| containerId | String | Target space ID in cross-space scenarios. |
| tenantId | String | Tenant ID. |
| beginTime | String | Task start time. |
| endTime | String | Task end time. |
| createTime | String | Time creation time. |

Status code: 400**Table 4-5** Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response description. |

Status code: 401**Table 4-6** Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response description. |

Status code: 500

Table 4-7 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response description. |

Example Requests

Request for listing batch tasks.

```
GET /koodrive/ose/v1/jobs?offset=0&limit=2
Authorization:Bearer+10f88*****5a544791e9ff
```

Example Responses

Status code: 200

Returns the queried task list.

```
{
  "data" : [ {
    "taskId" : "1320279189273965056",
    "taskType" : 2,
    "actionType" : 201,
    "status" : 2,
    "taskResultCode" : 1,
    "contentNum" : 1,
    "containerId" : "IAADfsBFCO6WtAtuA9add2fea594e4e75b8feb8474ef236",
    "beginTime" : "20231227151904",
    "endTime" : "20231227151904",
    "createTime" : "20231227151904"
  }, {
    "taskId" : "1320279092268104960",
    "taskType" : 2,
    "actionType" : 201,
    "status" : 2,
    "taskResultCode" : 1,
    "contentNum" : 4,
    "containerId" : "IAADfsBFCO6WtAtuA9add2fea594e4e75b8feb8474ef236",
    "beginTime" : "20231227151852",
    "endTime" : "20231227151852",
    "createTime" : "20231227151852"
  } ],
  "code" : 0,
  "msg" : "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|--------------------------------|
| 200 | Returns the queried task list. |
| 400 | Bad Request |

| Status Code | Description |
|-------------|-----------------------|
| 401 | Unauthorized |
| 500 | Internal Server Error |

4.1.2 Creating a Batch Task

Function

Create a batch task.

URI

POST /koodrive/ose/v1/jobs

Request Parameters

Table 4-8 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-9 Request body parameters

| Parameter | Mandatory | Type | Description |
|----------------|-----------|--------------------------|---|
| taskType | Yes | Integer | Task type. <ul style="list-style-type: none"> • 1: batch replication. • 2: batch deletion. • 3: batch relocation. • 4: batch restoration of recycle bin data. • 5: cloud decompression. • 6: package download. |
| actionType | No | Integer | Operation type, which is a subdivision of taskType . This parameter is used only when taskType is set to 1, 2, or 3. <ul style="list-style-type: none"> • 101: replication and dumping. • 201: logical deletion (moved to the recycle bin). • 202: permanent deletion. • 301: common relocation. • 501: compressed package preview. • 502: full decompression. • 503: partial decompression. |
| taskInfo | Yes | CreateTaskInfoReq object | Request for creating a batch task. |
| dstContainerId | Yes | String | Target space ID. |
| password | No | String | Compressed package password. |

Table 4-10 CreateTaskInfoReq

| Parameter | Mandatory | Type | Description |
|----------------|-----------|---------------------------|--------------------|
| fileInfo | Yes | Array of fileInfo objects | File/Directory ID. |
| newFilePath | No | String | New file path. |
| srcContainerId | Yes | String | Source space ID. |

| Parameter | Mandatory | Type | Description |
|---------------------|-----------|------------------|---|
| uncompressFilePaths | No | Array of strings | List of full paths of partially decompressed files in the compressed package. |

Table 4-11 fileInfo

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|---|
| fileId | Yes | String | File ID. |
| filePath | No | String | Full file path, including fileId . |

Response Parameters

Status code: 200

Table 4-12 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Error code. |
| msg | String | Error message. |
| data | String | Task ID. |

Status code: 400

Table 4-13 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response description. |

Status code: 401

Table 4-14 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response description. |

Status code: 500

Table 4-15 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response description. |

Example Requests

Request for copying files.

```
POST /koodrive/ose/v1/jobs
Authorization:Bearer+10f88d07fa*****44791e9ff
{
  "taskType":1 ,
  "actionType":101 ,
  "dstContainerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4" ,
  "taskInfo": {
    "srcContainerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
    "newFilePath": "Fm9UdqBNTAQDos6l1xPlFnlqXJg2-UdqA" ,
    "fileInfo": [
      {
        "fileId": "FuZmQ66CF0DdpKRG1Y29Iwajbq04Nhwu3"
      }
    ]
  }
}
```

Example Responses

Status code: 200

Basic response. Only the error code and error information are returned.

```
{
  "data": "1309243162258308352"
  "code": 0,
  "msg": "success"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Basic response. Only the error code and error information are returned. |
| 400 | Bad Request |
| 401 | Unauthorized |
| 500 | Internal Server Error |

4.1.3 Querying Details About a Batch Task

Function

Query details about a batch task.

URI

GET /koodrive/ose/v1/{job_id}

Table 4-16 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|----------------|
| job_id | Yes | String | Batch task ID. |

Request Parameters

Table 4-17 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer +{access_token}. |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-18 Response body parameters

| Parameter | Type | Description |
|-----------|--------------------|-------------------|
| code | String | Response code. |
| msg | String | Response message. |
| data | data object | Task details. |

Table 4-19 data

| Parameter | Type | Description |
|-----------------------|--|--|
| jobInfo | JobDetailInfo object | Task information. |
| taskInfos | Array of TaskInfo objects | Task details list. |
| uncompressed FileList | Array of UncompressedFileInfo objects | Information about files in the compressed package. |

Table 4-20 JobDetailInfo

| Parameter | Type | Description |
|----------------|---------|--|
| taskId | String | Task ID. |
| taskName | String | Task name. |
| userId | String | Task creator ID. |
| taskType | Integer | Task type. |
| actionType | Integer | Operation type. |
| status | Integer | Task status. |
| taskResultCode | Integer | Task result. |
| resultCode | Integer | Task result code. |
| progress | Integer | Task progress. This parameter is returned in an asynchronous task, for example, a package download task. |
| downloadUrl | String | Download link. This parameter is used only when the task type is package download. |

| Parameter | Type | Description |
|-------------|---------|---|
| contentNum | Integer | Number of request files. |
| containerId | String | Target space ID in cross-space scenarios. |
| tenantId | String | Tenant ID. |
| beginTime | String | Task start time. |
| endTime | String | Task end time. |
| createTime | String | Time creation time. |

Table 4-21 TaskInfo

| Parameter | Type | Description |
|----------------|--------|--|
| fileId | String | File/Directory ID. |
| status | String | Task processing status. <ul style="list-style-type: none"> • 0: pending. • 1: successful. • 2: failed. |
| newFileId | String | New ID after operation. |
| srcContainerId | String | Source container ID (source space ID corresponding to fileId). This parameter is mandatory only for batch replication across spaces. |
| resultCode | String | File operation result code. |
| resultDesc | String | File operation result description. |

Table 4-22 UncompressedFileInfo

| Parameter | Type | Description |
|-------------|--------|--|
| containerId | String | Space ID after decompression. This parameter is returned only for decompression. |
| fileId | String | ID of the decompressed file. This parameter is returned only for decompression. |
| name | String | Full path of the file or folder in the compressed package. |
| fileSize | Long | File size, in bytes. |

| Parameter | Type | Description |
|-----------------|-------------------------------------|---|
| type | Integer | For details, see the definition of fileType . <ul style="list-style-type: none"> • 1: content. • 2: directory. |
| updatedAt | Long | Millisecond timestamp of file modification. |
| subFileList | Array of SubFileList objects | List of sub-files and sub-directories (expanded only for directories). |
| reason | String | Failure cause. If the operation is successful, this parameter is null. |
| code | String | Error code. |
| reservationInfo | Object | Reserved field. |

Table 4-23 SubFileList

| Parameter | Type | Description |
|-------------|---------|--------------|
| containerId | String | Space ID. |
| name | String | File name. |
| type | Integer | File type. |
| updatedAt | Integer | Update time. |
| code | String | Error code. |
| fileId | String | File ID. |
| fileSize | Integer | File size. |

Status code: 400

Table 4-24 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response description. |

Status code: 401

Table 4-25 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response description. |

Status code: 500

Table 4-26 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response description. |

Example Requests

Queries details about a batch task.

```
GET /koodrive/ose/v1/1309243162258308352
```

```
Authorization:Bearer+10f8*****a544791e9ff
```

Example Responses

Status code: 200

Returns queried task details.

```
{
  "data" : {
    "jobInfo" : {
      "taskId" : "1309243162258308352",
      "userId" : "40086000004871666-369528171409614001",
      "taskType" : 1,
      "actionType" : 101,
      "status" : 2,
      "progress" : 100,
      "taskResultCode" : 1,
      "contentNum" : 1,
      "containerId" : "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
      "tenantId" : "40086000004871666",
      "beginTime" : "20231212095227",
      "endTime" : "20231212095227",
      "createTime" : "20231212095227"
    },
    "taskInfos" : [ {
      "fileId" : "FuZmQ66CF0DdpKRG1Y29lwajbq04Nhwu3",
      "status" : "1",
      "newFileId" : "FtEXHCpfqHueAHFbEmWZNkqUH_K866MVn",
      "srcContainerId" : "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"
    } ]
  },
  "code" : 0,
  "msg" : "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|-------------------------------|
| 200 | Returns queried task details. |
| 400 | Bad Request |
| 401 | Unauthorized |
| 500 | Internal Server Error |

4.1.4 Cancelling a Batch Task

Function

Cancel a batch task whose status is **0** (to be processed) or **1** (processing). After the task is canceled, the task scheduling module ignores its record.

URI

POST /koodrive/ose/v1/cancel

Request Parameters

Table 4-27 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-28 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| jobId | Yes | String | Task ID. |

Response Parameters

Status code: 200

Table 4-29 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response description. |

Status code: 400

Table 4-30 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response description. |

Status code: 401

Table 4-31 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Response code. |

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| msg | String | Response description. |

Status code: 500

Table 4-32 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response description. |

Example Requests

Cancels a batch task.

```
POST /koodrive/ose/v1/cancel
Authorization:Bearer+10f*****791e9ff
{
  "jobId":"1289250105886769024"
}
```

Example Responses

Status code: 200

Basic response. Only the error code and error information are returned.

```
{
  "code" : 0,
  "msg" : "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Basic response. Only the error code and error information are returned. |
| 400 | Bad Request |
| 401 | Unauthorized |
| 500 | Internal Server Error |

4.2 Department Management

4.2.1 Listing Departments

Function

List sub-departments under an organization or department. Only the top-level sub-departments are returned. To query sub-department of the lowest level, use the caller to perform recursive query.

URI

GET /koodrive/ose/v1/departmentList

Table 4-33 Query Parameters

| Parameter | Mandatory | Type | Description |
|--------------|-----------|--------|---|
| departmentId | No | String | Department ID. If no value is passed, the root department ID is used. |
| keyWord | No | String | Search keyword. You can use name as the search criterion. |

Request Parameters

Table 4-34 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-35 Response body parameters

| Parameter | Type | Description |
|-----------|--|-----------------------|
| code | String | Response code. |
| msg | String | Response information. |
| data | Array of departmentInfo objects | Department list. |

Table 4-36 departmentInfo

| Parameter | Type | Description |
|-----------|--------|--|
| code | String | Response code. |
| msg | String | Response information. |
| id | String | Department ID. |
| orgId | String | ID of the organization created in OrgID. |
| deptId | String | ID of the department created in OrgID. |
| parentId | String | ID of the parent department in KooDrive. |
| name | String | Department name. |
| tenantId | String | Tenant ID. |

Example Requests

Lists sub-departments under department **1245640257345455489**.


```
GET /koodrive/ose/v1/departmentList?departmentId=1245640257345455489
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Returns the list of sub-departments under an organization or department.

```
{
  "list": [ {
    "id": "1248723349513736065",
    "orgId": "9190086000001210958",
    "deptId": "b06f091567064db9a1f6a7dc8d08e8a7",
    "parentId": "1245640257345455489",
    "name": "sub11rt",
    "tenantId": "40086000004871666"
  }, {
    "id": "1252924812435692416",
    "orgId": "9190086000001210958",
    "deptId": "f63c3008420c4c55b3963b6191096e2e",
    "parentId": "1245640257345455489",
    "name": "1234666",
    "tenantId": "40086000004871666"
  } ],
  "code": 0,
  "msg": "success"
}
```

Status Codes

| Status Code | Description |
|-------------|--|
| 200 | Returns the list of sub-departments under an organization or department. |

4.2.2 Querying a Department

Function

Query the information about a department.

URI

GET /koodrive/ose/v1/departments/{department_id}

Table 4-37 Path Parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|----------------|
| department_id | Yes | String | Department ID. |

Request Parameters

Table 4-38 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-39 Response body parameters

| Parameter | Type | Description |
|-----------|--------|--|
| code | String | Response code. |
| msg | String | Response information. |
| id | String | Department ID. |
| orgId | String | ID of the organization created in OrgID. |
| deptId | String | ID of the department created in OrgID. |
| parentId | String | ID of the parent department in KooDrive. |
| name | String | Department name. |
| tenantId | String | Tenant ID. |

Example Requests

Queries information about department **1319678187126486144**.

```
GET /koodrive/ose/v1/departments/1319678187126486144
```

```
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Department information.

```
{
  "id" : "1319678187126486144",
  "orgId" : "9190086000001210958",
  "deptId" : "a4fd0d798f5344ccac2c695646ef66d3",
  "parentId" : "1245640257345455489",
  "name" : "test16",
  "tenantId" : "40086000004871666",
  "code" : 0,
  "msg" : "success"
}
```

Status Codes

| Status Code | Description |
|-------------|-------------------------|
| 200 | Department information. |

4.2.3 Creating a Department

Function

Create a department and allocate a space to the department.

URI

POST /koodrive/ose/v1/departments

Request Parameters

Table 4-40 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-41 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-----------------------|
| name | Yes | String | Department name. |
| parentId | Yes | String | Parent department ID. |

Response Parameters

Status code: 200

Table 4-42 Response body parameters

| Parameter | Type | Description |
|-----------|--------|--------------------|
| code | String | Error code. |
| msg | String | Error description. |

| Parameter | Type | Description |
|------------|------------------|---------------|
| failedList | Array of strings | Failure list. |

Example Requests

Creates a department named **test16** under department whose ID is **1245640257345455489**.

```
POST /koodrive/ose/v1/departments
Authorization:Bearer+10f88*****4791e9ff
{
  "name": "test16",
  "parentId": "1245640257345455489"
}
```

Example Responses

Status code: 200

Department creation result.

```
{
  "code" : 0,
  "msg" : "success"
}
```

Status Codes

| Status Code | Description |
|-------------|-----------------------------|
| 200 | Department creation result. |

4.2.4 Modifying a Department

Function

Modify the information about a department (including the team space).

URI

PUT /koodrive/ose/v1/departments/{department_id}

Table 4-43 Path Parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|----------------|
| department_id | Yes | String | Department ID. |

Request Parameters

Table 4-44 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-45 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-----------------------|
| name | Yes | String | Department name. |
| parentId | Yes | String | Parent department ID. |

Response Parameters

Status code: 200

Table 4-46 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Error code. |
| msg | String | Error message. |

Example Requests

Modifies the information about the department **1319678187126486144**.

```
PUT /koodrive/ose/v1/departments/1319678187126486144
```

```
Authorization:Bearer+10f88*****4791e9ff
```

```
{
  "name" : "test16",
  "parentId" : "1243696974704704000"
}
```

Example Responses

Status code: 200

Basic response. Only the error code and error information are returned.

```
{
  "code" : 0,
  "msg" : "success"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Basic response. Only the error code and error information are returned. |

4.2.5 Deleting a Department

Function

Delete a department and its team space.

URI

```
DELETE /koodrive/ose/v1/departments/{department_id}
```

Table 4-47 Path Parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|----------------|
| department_id | Yes | String | Department ID. |

Request Parameters

Table 4-48 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-49 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Error code. |
| msg | String | Error message. |

Example Requests

Deletes department **1319678187126486144**.

```
DELETE /koodrive/ose/v1/departments/1319678187126486144
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Basic response. Only the error code and error information are returned.

```
{
  "code" : 0,
  "msg" : "success"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Basic response. Only the error code and error information are returned. |

4.3 User Management

4.3.1 Listing Users

Function

List users in a department. If **department_id** is not specified, the user list of the organization to which the current sign-in user belongs is queried.

URI

GET /koodrive/ose/v1/userList

Table 4-50 Query Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|---------|--|
| deptId | No | String | Department ID. |
| isDirect | No | Boolean | Whether the user belongs to the root department. Default value: false. |
| offset | Yes | String | Offset. Minimum value: 0. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| limit | Yes | String | Maximum number of records to be returned. Value range: 1 to 100. |
| keyWord | No | String | Search keyword. You can use name as the search criterion. |

Request Parameters

Table 4-51 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-52 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Response code. |

| Parameter | Type | Description |
|-----------|----------------------------------|-------------------|
| msg | String | Response message. |
| data | Array of userInfo objects | User information. |

Table 4-53 userInfo

| Parameter | Type | Description |
|-----------|---------|----------------------|
| name | String | Name. |
| userId | String | User ID. |
| deptId | String | Department ID. |
| deptName | String | Department name. |
| mobile | String | Mobile number. |
| role | Integer | Role. |
| status | Integer | Status. |
| id | String | Third-party user ID. |

Example Requests

Lists 10 users in department **1243693141656107521**, starting from the first user.

```
GET /koodrive/ose/v1/userList?deptId=1243693141656107521&offset=0&limit=10
```

```
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

User list information.

```
{
  "list": [
    {
      "id": "1316083732377071000VW5TYWZISW50ZWdlcg==",
      "userId": "1008600000293202821",
      "deptId": "1243693141656107500VW5TYWZISW50ZWdlcg==",
      "deptName": "newDept",
      "mobile": "0086181****8439",
      "name": "Sam",
      "role": 1,
      "status": 0,
    },
    {
      "id": "1315783852559526700VW5TYWZISW50ZWdlcg==",
      "userId": "1008600000292227464",
      "deptId": "1243693141656107500VW5TYWZISW50ZWdlcg==",
    }
  ]
}
```

```
"deptName": "newDept",
"mobile": "0086151****8338",
"name": "test123",
"role": 1,
"status": 2
}
],
"total": 2,
"code": 0,
"msg": "success"
}
```

Status Codes

| Status Code | Description |
|-------------|------------------------|
| 200 | User list information. |

4.3.2 Querying Information About a User

Function

Query the information about a user.

URI

GET /koodrive/ose/v1/users/{user_id}

Table 4-54 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| user_id | Yes | String | User ID. |

Request Parameters

Table 4-55 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-56 Response body parameters

| Parameter | Type | Description |
|-----------|------------------------|-------------------|
| code | String | Response code. |
| msg | String | Response message. |
| data | userInfo object | User information. |

Table 4-57 userInfo

| Parameter | Type | Description |
|-----------|---------|----------------------|
| name | String | Name. |
| userId | String | User ID. |
| deptId | String | Department ID. |
| deptName | String | Department name. |
| mobile | String | Mobile number. |
| role | Integer | Role. |
| status | Integer | Status. |
| id | String | Third-party user ID. |

Example Requests

Queries the information about user **1316083732377070977**.

```
GET /koodrive/ose/v1/users/1316083732377070977
```

```
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

User information.

```
{
  "data": {
    "id": "1316083732377070977",
    "orgId": "9190086000001210958",
    "userId": "1008600000293202821",
    "deptId": "1243693141656107521",
    "deptName": "newDept",
    "mobile": "0086181****8439",
    "name": "Sam",
    "role": 1,
    "status": 0,
  },
  "code": 0,
  "msg": "success"
}
```

Status Codes

| Status Code | Description |
|-------------|-------------------|
| 200 | User information. |

4.3.3 Counting Members in an Organization or Department

Function

Count members in a department or organization. If **dept_id** is not specified, the number of all members in the current organization is queried.

URI

GET /koodrive/ose/v1/users/count

Table 4-58 Query Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|----------------|
| deptId | No | String | Department ID. |

Request Parameters

Table 4-59 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-60 Response body parameters

| Parameter | Type | Description |
|-----------|---------|--------------------------|
| code | String | Response code. |
| msg | String | Response information. |
| total | Integer | Total number of records. |

Example Requests

Counts members in the current organization.

```
GET /koodrive/ose/v1/users/count?deptId=
```

```
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Total number of members.

```
{  
  "total" : 218,  
  "code" : 0,  
  "msg" : "success"  
}
```

Status Codes

| Status Code | Description |
|-------------|--------------------------|
| 200 | Total number of members. |

4.3.4 Creating a User

Function

Create a user.

URI

POST /koodrive/ose/v1/users

Request Parameters

Table 4-61 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-62 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| userId | Yes | String | User ID. |

Response Parameters

Status code: 200

Table 4-63 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Error code. |
| msg | String | Error message. |

Example Requests

Creates a user whose **userId** in OrgID is **1008600000029937613**.

```
POST /koodrive/ose/v1/users
Authorization:Bearer+10f88*****4791e9ff
{
  "userId": "1008600000029937613"
}
```

Example Responses

Status code: 200

Basic response. Only the error code and error information are returned.

```
{
  "code" : 0,
  "msg" : "success"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Basic response. Only the error code and error information are returned. |

4.3.5 Modifying a User

Function

Modify the information about a user.

URI

PUT /koodrive/ose/v1/users/{user_id}

Table 4-64 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| user_id | Yes | String | User ID. |

Request Parameters

Table 4-65 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-66 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|---------|---|
| deptId | No | Long | KooDrive department ID. |
| role | No | Integer | Role. <ul style="list-style-type: none"> ● 0: common administrator. ● 1: common user. ● 2: super administrator. |
| status | No | Integer | User account status. Default value: 0. <ul style="list-style-type: none"> ● 0: enabled (can be used for sign-in). ● 1: disabled (cannot be used for sign-in). |

Response Parameters

Status code: 200

Table 4-67 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Error code. |
| msg | String | Error message. |

Example Requests

Modifies the information about user **1289290865663084545**.

```
PUT /koodrive/ose/v1/users/1289290865663084545
```

```
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Basic response. Only the error code and error information are returned.

```
{  
  "code" : 0,  
  "msg" : "success"  
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Basic response. Only the error code and error information are returned. |

4.3.6 Deleting a User

Function

Delete a user and the corresponding resources.

URI

```
DELETE /koodrive/ose/v1/users/{user_id}
```

Table 4-68 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| user_id | Yes | String | User ID. |

Request Parameters

Table 4-69 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-70 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Error code. |
| msg | String | Error message. |

Example Requests

Deletes user **1244780780316557312** and the corresponding resources.

```
DELETE /koodrive/ose/v1/users/1244780780316557312
```

```
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Basic response. Only the error code and error information are returned.

```
{
  "code" : 0,
  "msg" : "success"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Basic response. Only the error code and error information are returned. |

4.3.7 Querying the Mobile Number of a User

Function

Query the mobile number of a user.

URI

```
GET /koodrive/ose/v1/users/mobile/{user_id}
```

Table 4-71 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| user_id | Yes | String | User ID. |

Request Parameters

Table 4-72 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-73 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-------------------|
| code | String | Response code. |
| msg | String | Response message. |
| mobile | String | Mobile number. |

Example Requests

None

Example Responses

None

Status Codes

| Status Code | Description |
|-------------|--------------------------|
| 200 | Mobile number of a user. |

4.4 Space Management

4.4.1 Listing Departments Spaces

Function

List department spaces.

URI

GET /koodrive/ose/v1/space/departmentList

Table 4-74 Query Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| offset | Yes | String | Offset. Minimum value: 0. |
| limit | Yes | String | Maximum number of records to be returned. Value range: 1 to 100. |
| keyWord | No | String | Search keyword. You can use name and administrator as the search criteria. |

Request Parameters

Table 4-75 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-76 Response body parameters

| Parameter | Type | Description |
|-------------|---|-------------------------------|
| code | String | Error code. |
| msg | String | Error message. |
| total | String | Total number of records. |
| departments | Array of departments paceInfo objects | Department space information. |

Table 4-77 departmentSpaceInfo

| Parameter | Type | Description |
|----------------|---------|---|
| id | String | Department ID. |
| parentId | String | ID of the parent department in KooDrive. |
| name | String | Department name. |
| administrators | String | Administrators of the department. |
| status | String | Space status. |
| capacity | Long | Space size. |
| spaceUsed | String | Size of the used space. |
| containerId | String | Space ID. |
| bizRootFileId | String | ID of the KooDrive root directory. |
| tenantId | String | Tenant ID. |
| userNum | Integer | Number of users. |
| createTime | String | Creation time. |
| modifier | String | ID of the user who updated the information. |
| updateTime | String | Update time. |
| ownerId | String | Owner ID. |
| bizSboxFileId | String | ID of the safe root directory. |

Example Requests

Lists the spaces of up to 10 departments.

```
GET /koodrive/cloudfile/v1/space/departmentList?offset=0&limit=10
```

```
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Department space list.

```
{
  "total": 364,
  "departments": [ {
    "tenantId": "40086000004871666",
    "creator": "369528171409614001",
    "createTime": "2023-11-14T20:39:06.000Z",
    "modifier": "369528171409614001",
    "updateTime": "2023-12-26T11:40:08.000Z",
    "ownerId": "1289173668999530369",
    "status": 0,
  }
]
```

```

"capacity" : 1,
"spaceUsed" : 654777,
"containerId" : "IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b",
"bizRootFileId" : "DEUI7pa0C24ArootIAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b",
"bizSboxFileId" : "DEUI7pa0C24AsboxIAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b",
"id" : "1289173668999530369",
"parentId" : "1289171275545118721",
"name" : "Department 1699953477584",
"userNum" : 1
}, {
"tenantId" : "40086000004871666",
"id" : "1289173650183882753",
"parentId" : "1289171275545118721",
"name" : "Department 1699953475619"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173631275960193",
"parentId" : "1289171275545118721",
"name" : "Department 1699953473454"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173612200265729",
"parentId" : "1289171275545118721",
"name" : "Department 1699953470101"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173593258788737",
"parentId" : "1289171275545118721",
"name" : "Department 169995346896"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173574392809473",
"parentId" : "1289171275545118721",
"name" : "Department 1699953466973"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173555140953985",
"parentId" : "1289171275545118721",
"name" : "Department 1699953463567"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173535931041664",
"parentId" : "1289171275545118721",
"name" : "Department 1699953461741"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173517174114305",
"parentId" : "1289171275545118721",
"name" : "Department 1699953459399"
}, {
"tenantId" : "40086000004871666",
"id" : "1289173498115196929",
"parentId" : "1289171275545118721",
"name" : "Department 1699953457405"
}
}],
"code" : 0,
"msg" : "OK"
}

```

Status Codes

| Status Code | Description |
|-------------|------------------------|
| 200 | Department space list. |

4.4.2 Querying Space Information

Function

Query the space information of an individual, department, or group.

URI

GET /koodrive/ose/v1/space/{owner_id}

Table 4-78 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| owner_id | Yes | String | Owner ID. |

Table 4-79 Query Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|---|
| type | Yes | String | Space type. <ul style="list-style-type: none"> • 0: department. • 1: individual. • 2: group. |

Request Parameters

Table 4-80 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-81 Response body parameters

| Parameter | Type | Description |
|-----------|----------------------------------|--------------------|
| code | String | Response code. |
| msg | String | Response message. |
| data | SpaceInfo object | Space information. |

Table 4-82 SpaceInfo

| Parameter | Type | Description |
|---------------|--------|--|
| type | String | Owner type. 0 : department space; 1 : individual space; 2 : group space. |
| status | String | Status. |
| ownerId | String | Space owner. 1. For a department space, the department ID is returned. 2. For an individual space, the user ID is returned. 3. For a group space, the group ID is returned. |
| containerId | String | Space ID. |
| bizRootFileId | String | ID of the service root directory, which stores unencrypted common files. |
| bizSboxFileId | String | ID of the service safe directory, which stores encrypted files. |
| capacity | String | Space size. |

| Parameter | Type | Description |
|----------------|--------|---|
| spaceUsed | String | Size of the used space. |
| administrators | String | 1. For a department space, administrator names are returned. Multiple administrators are separated by commas (.). 2. For a group space, the owner name is returned. |
| tenantId | String | Tenant ID. |
| creator | String | Creator. |
| createTime | String | Creation time. |
| modifier | String | ID of the user who updated the information. |
| updateTime | String | Update time. |
| userNum | String | Number of users. |
| rootFileId | String | ID of the space root directory. |

Example Requests

Queries the space information of user **369528171409614001**.

```
GET /koodrive/ose/v1/space/369528171409614001?type=1
```

```
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Space information.

```
{
  "data": {
    "tenantId": "40086000004871666",
    "creator": "369528171409614001",
    "createTime": "2023-11-07T20:36:35.000Z",
    "modifier": "369528171409614001",
    "updateTime": "2023-12-26T11:40:07.000Z",
    "ownerId": "369528171409614001",
    "type": 1,
    "status": 0,
    "capacity": 800,
    "spaceUsed": 91966408,
    "containerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
    "rootFileId": "HFFdIb642fU51JWKAUIP6mwUVc8oDNKbO",
    "bizRootFileId": "DEUI7pa0C24ArootIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
    "bizSboxFileId": "DEUI7pa0C24AsboxIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"
  },
  "code": 0,
  "msg": "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|--------------------|
| 200 | Space information. |

4.4.3 Creating a Space for a Department or Individual

Function

Create a space for a department or individual.

URI

POST /koodrive/ose/v1/space/{owner_id}

Table 4-83 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| owner_id | Yes | String | Owner ID. |

Request Parameters

Table 4-84 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-85 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|---------|--|
| capacity | Yes | String | Requested space size. |
| type | Yes | Integer | Space type. <ul style="list-style-type: none"> • 0: department. • 1: individual. |

Response Parameters

Status code: 200

Table 4-86 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Error code. |
| msg | String | Error message. |

Example Requests

Creates a space of 1 GB for department **1289173650183882753**.

```
POST /koodrive/ose/v1/space/1289173650183882753
```

```
Authorization:Bearer+10f88*****4791e9ff
```

```
{
  "capacity": 1,
  "type": 0
}
```

Example Responses

Status code: 200

Basic response. Only the error code and error information are returned.


```
{
  "code" : 0,
  "msg" : "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Basic response. Only the error code and error information are returned. |

4.4.4 Modifying Space Information

Function

Modify the space information of a department or individual.

URI

PUT /koodrive/ose/v1/space/{owner_id}

Table 4-87 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| owner_id | Yes | String | Space owner. The value can be a department or a user ID. |

Request Parameters

Table 4-88 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-89 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|---------|---|
| status | No | String | Space status. <ul style="list-style-type: none"> • 0: normal (A space has been allocated and can be used.) • 1: disabled (A space has been allocated, but the used space cannot be accessed.) |
| capacity | No | String | Capacity. |
| type | Yes | Integer | Space type. <ul style="list-style-type: none"> • 0: department. • 1: individual. |

Response Parameters

Status code: 200

Table 4-90 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Error code. |
| msg | String | Error message. |

Example Requests

Updates the space size of department **1289173650183882753** to 1 GB.

```
PUT /koodrive/ose/v1/space/1289173650183882753
Authorization:Bearer+10f88*****4791e9ff
{
  "status": 1,
  "type": 0
}
```

Example Responses

Status code: 200

Basic response. Only the error code and error information are returned.

```
{
  "code" : 0,
  "msg" : "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Basic response. Only the error code and error information are returned. |

4.4.5 Deleting a Space

Function

Delete a space.

URI

DELETE /koodrive/ose/v1/space/{owner_id}

Table 4-91 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| owner_id | Yes | String | Owner ID. |

Table 4-92 Query Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|---------|---|
| type | Yes | Integer | Space type. <ul style="list-style-type: none">• 0: department.• 1: individual. |

Request Parameters

Table 4-93 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-94 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Error code. |
| msg | String | Error message. |

Example Requests

Deletes the space of department **1289173650183882753**.

```
DELETE /koodrive/ose/v1/space/1289173650183882753?type=0
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Basic response. Only the error code and error information are returned.

```
{
  "code" : 0,
  "msg" : "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Basic response. Only the error code and error information are returned. |

4.4.6 Querying Space Details by Space ID

Function

Query space details by space ID. This API applies only to machine-to-machine calling.

URI

GET /koodrive/ose/v1/space/container/{container_id}

Table 4-95 Path Parameters

| Parameter | Mandatory | Type | Description |
|--------------|-----------|--------|-------------|
| container_id | Yes | String | Space ID. |

Request Parameters

Table 4-96 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-97 Response body parameters

| Parameter | Type | Description |
|-----------|-------------------------|--------------------|
| code | String | Response code. |
| msg | String | Response message. |
| data | SpaceInfo object | Space information. |

Table 4-98 SpaceInfo

| Parameter | Type | Description |
|----------------|--------|--|
| type | String | Owner type. 0 : department space; 1 : individual space; 2 : group space. |
| status | String | Status. |
| ownerId | String | Space owner. 1. For a department space, the department ID is returned. 2. For an individual space, the user ID is returned. 3. For a group space, the group ID is returned. |
| containerId | String | Space ID. |
| bizRootFileId | String | ID of the service root directory, which stores unencrypted common files. |
| bizSboxFileId | String | ID of the service safe directory, which stores encrypted files. |
| capacity | String | Space size. |
| spaceUsed | String | Size of the used space. |
| administrators | String | 1. For a department space, administrator names are returned. Multiple administrators are separated by commas (.). 2. For a group space, the owner name is returned. |
| tenantId | String | Tenant ID. |
| creator | String | Creator. |
| createTime | String | Creation time. |
| modifier | String | ID of the user who updated the information. |
| updateTime | String | Update time. |
| userNum | String | Number of users. |
| rootFileId | String | ID of the space root directory. |

Example Requests

Queries details about a space whose ID is IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b.

```
GET /koodrive/ose/v1/space/container/IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b
```

```
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Space details.

```
{
  "data": {
    "tenantId": "40086000004871666",
    "creator": "369528171409614001",
    "createTime": "2023-11-14T20:39:06.000Z",
    "modifier": "369528171409614001",
    "updateTime": "2023-12-27T03:41:49.000Z",
    "ownerId": "1289173668999530369",
    "type": 0,
    "status": 0,
    "capacity": 1,
    "spaceUsed": 654777,
    "containerId": "IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b",
    "rootFileId": "HFaETMi24qYqOM5KQmpNY2ATjKJeAunIK",
    "bizRootFileId": "DEUI7pa0C24ArootIAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b",
    "bizSboxFileId": "DEUI7pa0C24AsboxIAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b"
  },
  "code": 0,
  "msg": "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|----------------|
| 200 | Space details. |

4.4.7 Querying Information About a Team Space

Function

Query information about a team space.

URI

GET /koodrive/ose/v1/space/teamList

Table 4-99 Query Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|---------|--|
| offset | Yes | Integer | Offset. Minimum value: 0. |
| limit | Yes | Integer | Maximum number of records to be returned. Value range: 1 to 100. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| keyWord | No | String | Search keyword. You can use name and ownerName as the search criteria. |

Request Parameters

Table 4-100 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-101 Response body parameters

| Parameter | Type | Description |
|-----------|--------|--------------------------|
| code | String | Error code. |
| msg | String | Error message. |
| total | String | Total number of records. |

| Parameter | Type | Description |
|-----------|--|------------------|
| teams | Array of TeamSpaceInfo objects | Team space list. |

Table 4-102 TeamSpaceInfo

| Parameter | Type | Description |
|---------------|---------|--|
| id | String | ID of the department, user group, or group to which the space belongs. |
| groupName | String | Team space name, which is a department or user group name. |
| status | Integer | Space status. |
| capacity | Integer | Space size. |
| spaceUsed | String | Size of the used space. |
| containerId | String | Space ID. |
| userNum | Integer | Number of users. |
| ownerId | String | Owner ID. |
| ownerName | String | Owner name. |
| tenantId | String | Tenant ID. |
| creator | String | Creator. |
| createTime | String | Creation time. |
| modifier | String | ID of the user who updated the information. |
| updateTime | String | Update time. |
| bizRootFileId | String | ID of the space root directory. |
| bizSboxFileId | String | ID of the space safe directory. |
| iconUrl | String | Icon link. |
| top | Integer | Whether this record is pinned to top. |
| role | Integer | Role. |
| deptNamePath | String | Department location. |

Example Requests

Queries the space information of team **369528171409614001**.

```
GET /koodrive/ose/v1/space/teamList
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Space information.

```
{
  "data" : {
    "tenantId" : "40086000004871666",
    "creator" : "369528171409614001",
    "createTime" : "2023-11-07T20:36:35.000Z",
    "modifier" : "369528171409614001",
    "updateTime" : "2023-12-26T11:40:07.000Z",
    "ownerId" : "369528171409614001",
    "type" : 1,
    "status" : 0,
    "capacity" : 800,
    "spaceUsed" : 91966408,
    "containerId" : "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
    "rootFileId" : "HFFdIb642fU51JWKAUIP6mwUVc8oDNKbO",
    "bizRootFileId" : "DEUI7pa0C24ArootIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
    "bizSboxFileId" : "DEUI7pa0C24AsboxIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"
  },
  "code" : 0,
  "msg" : "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|--------------------|
| 200 | Space information. |

4.4.8 Creating a Group Space

Function

Create a group space.

URI

POST /koodrive/ose/v1/space/group

Request Parameters

Table 4-103 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-104 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|------------------|------------------------|
| name | Yes | String | Space name. |
| userIds | No | Array of strings | Team members. |
| iconUrl | No | String | Space profile picture. |
| capacity | No | Integer | Space size. |

Response Parameters

Status code: 200

Table 4-105 Response body parameters

| Parameter | Type | Description |
|------------|------------------|--------------------|
| code | String | Error code. |
| msg | String | Error description. |
| failedList | Array of strings | Failure list. |

Example Requests

Creates a space of 20 GB for a group.

```
POST /koodrive/ose/v1/space/
Authorization:Bearer+10f88*****4791e9ff
{
  "name": "API Demo",
  "capacity": 20,
  "iconUrl": "1",
  "userIds": []
}
```

Example Responses

Status code: 200

Basic response. Only the error code and error information are returned.

```
{
  "id": "xxx",
  "failedList": [ ],
  "code": 0,
  "msg": "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Basic response. Only the error code and error information are returned. |

4.4.9 Listing Group Spaces in an Enterprise

Function

List group spaces in an enterprise. (Only tenant administrators have the permission to call this API.)

URI

GET /koodrive/ose/v1/space/groupList

Table 4-106 Query Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|---------|--|
| offset | Yes | Integer | Offset. Minimum value: 0. |
| limit | Yes | Integer | Maximum number of records to be returned. Value range: 1 to 100. |
| keyWord | No | String | Search keyword. You can use name and ownerName as the search criteria. |

Request Parameters

Table 4-107 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer +{ <i>access_token</i> }. |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-108 Response body parameters

| Parameter | Type | Description |
|------------------|--|---------------------------|
| code | String | Error code. |
| msg | String | Error message. |
| total | Integer | Total number of records. |
| groupsTotal | Integer | Total number of groups. |
| groupsMax | Integer | Maximum number of groups. |
| assignedCapacity | String | Assigned capacity. |
| maxCapacity | String | Maximum capacity. |
| groups | Array of TeamSpaceInfo objects | Group space information. |

Table 4-109 TeamSpaceInfo

| Parameter | Type | Description |
|-------------|---------|--|
| id | String | ID of the department, user group, or group to which the space belongs. |
| groupName | String | Team space name, which is a department or user group name. |
| status | Integer | Space status. |
| capacity | Integer | Space size. |
| spaceUsed | String | Size of the used space. |
| containerId | String | Space ID. |
| userNum | Integer | Number of users. |
| ownerId | String | Owner ID. |
| ownerName | String | Owner name. |
| tenantId | String | Tenant ID. |
| creator | String | Creator. |
| createTime | String | Creation time. |

| Parameter | Type | Description |
|---------------|---------|---|
| modifier | String | ID of the user who updated the information. |
| updateTime | String | Update time. |
| bizRootFileId | String | ID of the space root directory. |
| bizSboxFileId | String | ID of the space safe directory. |
| iconUrl | String | Icon link. |
| top | Integer | Whether this record is pinned to top. |
| role | Integer | Role. |
| deptNamePath | String | Department location. |

Example Requests

Lists group spaces in an enterprise.

```
GET /koodrive/ose/v1/space/groupList?offset=0&limit=10
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Information about the group space list.

```
{
  "total": 1,
  "groupsTotal": 1,
  "groupsMax": 500,
  "assignedCapacity": 100,
  "maxCapacity": 2048,
  "groups": [
    {
      "tenantId": "cad444830661464d9da88784a96d960c",
      "creator": "1410172329509745795",
      "createTime": "2024-05-10T01:46:22.000Z",
      "modifier": "1410172329509745795",
      "updateTime": "2024-05-10T02:27:23.000Z",
      "ownerId": "1410172329509745795",
      "status": 0,
      "capacity": 20,
      "spaceUsed": 0,
      "containerId": "IAAE49hOR8LulgAAA1417956457328121729",
      "bizRootFileId": "DE5Hwu6WAAArootIAAE49hOR8LulgAAA1417956457328121729",
      "bizSboxFileId": "DE5Hwu6WAAAAsboxIAAE49hOR8LulgAAA1417956457328121729",
      "id": "1417956457311344513",
      "groupName": "api01",
      "iconUrl": "1",
      "ownerName": "hid99522477",
      "userNum": 1
    }
  ],
  "code": 0,
  "msg": "Successful"
}
```


Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Information about the group space list. |

4.4.10 Dismissing a Team Space

Function

Dismiss a team space.

URI

DELETE /koodrive/ose/v1/space/group/{group_id}

Table 4-110 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| group_id | Yes | String | |

Request Parameters

Table 4-111 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-112 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Error code. |
| msg | String | Error message. |

Example Requests

Deletes the space of department **1289173650183882753**.

```
DELETE /koodrive/ose/v1/space/1289173650183882753?type=2
```

```
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Basic response. Only the error code and error information are returned.

```
{
  "code" : 0,
  "msg" : "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Basic response. Only the error code and error information are returned. |

4.4.11 Listing User Spaces

Function

List user spaces in a department. If **department_id** is not specified, the user space list of the organization to which the current sign-in user belongs is queried.

URI

GET /koodrive/ose/v1/space/userList

Table 4-113 Query Parameters

| Parameter | Mandatory | Type | Description |
|-------------|-----------|---------|--|
| deptId | No | String | Department ID. If this parameter is not specified, the user space list of the organization is queried if the current user is a system administrator, and the user space list of the department is queried if the current user is a department administrator. |
| isDirect | No | Boolean | Whether the user belongs to the root department. Default value: false. |
| offset | Yes | String | Offset. Minimum value: 0. |
| limit | Yes | String | Maximum number of records to be returned. Value range: 1 to 100. |
| keyWord | No | String | Search keyword. You can use name and mobile as the search criteria. |
| spaceStatus | No | String | Space status. |

Request Parameters

Table 4-114 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | 1. The format is Bearer <i>{app_access_token}</i> . The application-level token needs to be passed for calling by an application server. The token is obtained by calling an API using clientid and clientSecret obtained during application creation. 2. The application is the KooDrive server. |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en_us indicates English (United States). |

Response Parameters

Status code: 200

Table 4-115 Response body parameters

| Parameter | Type | Description |
|-----------|---------------------------------------|--------------------------|
| code | String | Response code. |
| msg | String | Response message. |
| users | Array of userSpaceInfo objects | User space information. |
| total | String | Total number of records. |

Table 4-116 userSpaceInfo

| Parameter | Type | Description |
|-------------|---------|-------------------------|
| name | String | Username. |
| deptId | String | Department ID. |
| deptName | String | Department name. |
| mobile | String | Mobile number. |
| role | Integer | User role. |
| status | Integer | User account status. |
| containerId | String | Space ID. |
| capacity | Long | Individual space size. |
| spaceUsed | Long | Size of the used space. |
| tenantId | String | Tenant ID. |
| id | String | User space ID. |
| userId | String | User ID. |
| spaceStatus | String | Space status. |

Example Requests

Lists user spaces in a department.

```
GET /koodrive/ose/v1/space/userList?deptId=&isDirect=&offset=0&limit=100&keyWord
```

```
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Information about the user space list.

```
{
  "total" : 1,
  "users" : [ {
    "tenantId" : "cad444830661464d9da88784a96d960c",
    "status" : 0,
    "capacity" : 10,
    "spaceUsed" : 189,
    "containerId" : "IAAE49hOR8LulgAAA1410765425310141185",
    "id" : "1410765364786334592",
    "role" : 1,
    "name" : "xx",
    "deptName" : "xxx",
    "userId" : "1008600000445114904",
    "deptId" : 1410183811475666000,
    "mobile" : "0086147****6900",
    "spaceStatus" : "0"
  } ],
  "code" : 0,
```

```
"msg" : "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|--|
| 200 | Information about the user space list. |

4.5 Group Management

4.5.1 Creating a User Group

Function

Create a user group.

URI

POST /koodrive/ose/v1/usergroups

Request Parameters

Table 4-117 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-118 Request body parameters

| Parameter | Mandatory | Type | Description |
|------------|-----------|---------|---|
| groupName | Yes | String | User group name, which cannot contain <> :"*?/\ or emojis. The value cannot be two periods (..), a period (.), or a space. Minimum: 1 Maximum: 30 |
| sourceType | Yes | Integer | User group type. |

Response Parameters

Status code: 200

Table 4-119 Response body parameters

| Parameter | Type | Description |
|------------|------------------|--------------------|
| code | String | Error code. |
| msg | String | Error description. |
| failedList | Array of strings | Failure list. |

Example Requests

Creates a group.

```
POST /koodrive/ose/v1/usergroups
```

```
Authorization:Bearer+c69b0f40334782d560bb154032cf22ef43d671843c4ffbad
```

```
{
  "capacity": 1,
```

```
"type": 0
}
```

Example Responses

Status code: 200

Basic response. For a successful response, the ID of the created user group is returned. For an error response, only the error code and error information are returned.

```
{
  "code" : 0,
  "msg" : "OK",
  "id" : "xxx"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Basic response. For a successful response, the ID of the created user group is returned. For an error response, only the error code and error information are returned. |

4.5.2 Listing User Groups

Function

List groups that a user joins.

URI

GET /koodrive/ose/v1/usergroups

Table 4-120 Query Parameters

| Parameter | Mandatory | Type | Description |
|------------|-----------|---------|---|
| pageSize | Yes | Integer | Number of records to be returned on each page. Default and maximum value: 100. It is possible that partial or empty result pages are returned before the end of the result list has been reached. |
| pageCursor | Yes | String | Current page cursor, which is obtained from nextCursor of the previous response. |
| groupName | No | String | User group name. |

| Parameter | Mandatory | Type | Description |
|------------|-----------|---------|------------------|
| sourceType | Yes | Integer | User group type. |

Request Parameters

Table 4-121 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-122 Response body parameters

| Parameter | Type | Description |
|------------|--------|---|
| code | String | Response code. |
| msg | String | Response information. |
| nextCursor | String | Pagination cursor. If the cursor does not exist, the last record has been returned. |

| Parameter | Type | Description |
|---------------|--|--------------------------|
| userGroupList | Array of UserGroupInfo objects | User group information. |
| total | Integer | Total number of records. |

Table 4-123 UserGroupInfo

| Parameter | Type | Description |
|-------------|--------|------------------|
| id | String | User group ID. |
| groupName | String | User group name. |
| ownerId | String | Creator ID. |
| createdTime | String | Creation time. |
| updatedTime | String | Update time. |

Example Requests

Lists the groups that a user joins.

```
GET /koodrive/ose/v1/usergroups
```

```
Authorization:Bearer+c69b0f40334782d560bb154032cf22ef43d671843c4ffbad
```

Example Responses

Status code: 200

Group list information.

```
{
  "total": 2,
  "userGroupList": [ {
    "id": "1407237551361847809",
    "groupName": "7",
    "ownerId": "1395476983395324033",
    "createdTime": "2024-04-25T06:49:49.000Z",
    "updatedTime": "2024-04-25T06:49:49.000Z"
  }, {
    "id": "1404926806536180481",
    "groupName": "111",
    "ownerId": "1395476983395324033",
    "createdTime": "2024-04-22T02:18:46.000Z",
    "updatedTime": "2024-04-22T02:18:46.000Z"
  } ],
  "code": 0,
  "msg": "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|-------------------------|
| 200 | Group list information. |

4.5.3 Modifying Group Information

Function

Modify group information.

URI

PUT /koodrive/ose/v1/usergroups/{group_id}

Table 4-124 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| group_id | Yes | String | |

Request Parameters

Table 4-125 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-126 Request body parameters

| Parameter | Mandatory | Type | Description |
|------------|-----------|---------|---|
| groupName | Yes | String | User group name. |
| userId | No | String | User ID. |
| role | No | String | User group role. |
| iconUrl | No | String | Link of the group profile picture. |
| top | No | String | Whether this record is pinned to top. 1 : pinned to top. 0 : displayed in sequence. |
| sourceType | Yes | Integer | User group type. |

Response Parameters

Status code: 200

Table 4-127 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response information. |

Example Requests

Updates the group information of department **1289173650183882753**.

```
PUT /koodrive/ose/v1/usergroup/1289173650183882753
```

```
Authorization:Bearer+c69b0f40334782d560bb154032cf22ef43d671843c4ffbad
```

```
{
  "groupName": "123",
```

```
"sourceType": 0  
}
```

Example Responses

Status code: 200

Response after the modification is successful.

```
{  
  "code" : 0,  
  "msg" : "OK"  
}
```

Status Codes

| Status Code | Description |
|-------------|--|
| 200 | Response after the modification is successful. |

4.5.4 Deleting a Group

Function

Delete a group.

URI

DELETE /koodrive/ose/v1/usergroups/{group_id}

Table 4-128 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| group_id | Yes | String | |

Request Parameters

Table 4-129 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-130 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Error code. |
| msg | String | Error message. |

Example Requests

Deletes group **1289173650183882753**.

```
DELETE /koodrive/ose/v1/usergroup/1289173650183882753
```

```
Authorization:Bearer+c69b0f40334782d560bb154032cf22ef43d671843c4ffbada
```

Example Responses

Status code: 200

Basic response.

```
{
  "code" : 0,
  "msg" : "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|-----------------|
| 200 | Basic response. |

4.5.5 Listing Members in a User Group

Function

List members in a group.

URI

GET /koodrive/ose/v1/usergroups/{group_id}/members

Table 4-131 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| group_id | Yes | String | |

Table 4-132 Query Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|---------|--|
| offset | Yes | Integer | Offset. Minimum value: 0. |
| limit | Yes | Integer | Maximum number of records to be returned. Value range: 1 to 100. |
| keyWord | No | String | Search keyword. You can use name and ownerName as the search criteria. |

Request Parameters

Table 4-133 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-134 Response body parameters

| Parameter | Type | Description |
|----------------------|------------------------------------|--|
| code | String | Response code. |
| msg | String | Response information. |
| total | Integer | Total number of members in a user group. |
| userGroupMemberInfos | Array of MemberInfo objects | Member list. |

Table 4-135 MemberInfo

| Parameter | Type | Description |
|-------------|--------|--------------------------------|
| userId | String | Member user ID. |
| userName | String | Username. |
| deptId | String | Department ID. |
| deptName | String | Department name. |
| mobile | String | Mobile number. |
| createdTime | String | Time when the member is added. |
| updatedTime | String | Update time. |

Example Requests

Lists members in group **369528171409614001**.

```
GET /koodrive/ose/v1/usergroups/369528171409614001/members
```

```
Authorization:Bearer+c69b0f40334782d560bb154032cf22ef43d671843c4ffbada
```

Example Responses

Status code: 200

Group member list.

```
{
  "data" : {
    "tenantId" : "40086000004871666",
    "creator" : "369528171409614001",
    "createTime" : "2023-11-07T20:36:35.000Z",
    "modifier" : "369528171409614001",
    "updateTime" : "2023-12-26T11:40:07.000Z",
    "ownerId" : "369528171409614001",
    "type" : 1,
    "status" : 0,
    "capacity" : 800,
    "spaceUsed" : 91966408,
    "containerId" : "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
    "rootFileId" : "HFFdIb642fU51JWKAUIP6mwUVc8oDNKbO",
    "bizRootFileId" : "DEUI7pa0C24ArootIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
    "bizSboxFileId" : "DEUI7pa0C24AsboxIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"
  },
  "code" : 0,
  "msg" : "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|--------------------|
| 200 | Group member list. |

4.5.6 Adding Members to a User Group

Function

Add members to a user group.

URI

POST /koodrive/ose/v1/usergroups/{group_id}/members/batchAdd

Table 4-136 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| group_id | Yes | String | |

Request Parameters

Table 4-137 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-138 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|------------------|-------------|
| userIds | Yes | Array of strings | User list. |

Response Parameters

Status code: 200

Table 4-139 Response body parameters

| Parameter | Type | Description |
|------------|------------------|---|
| code | String | Response code. |
| msg | String | Response information. |
| status | Integer | Response status. 0 : all successful; 1 : partially successful; 2 : all failed. |
| failedList | Array of strings | Failed response list. |

Example Requests

Adds users to group **369528171409614001**.

```
POST /koodrive/ose/v1/usergroups/369528171409614001/members/batchAdd
```

```
Authorization:Bearer+c69b0f40334782d560bb154032cf22ef43d671843c4ffbad
```

```
{
  "userIds": ["3432423464657862424","132543141414141414"]
}
```

Example Responses

Status code: 200

Response for adding users.

```
{
  "code" : 0,
  "msg" : "OK",
  "id" : "xxx"
}
```

Status Codes

| Status Code | Description |
|-------------|----------------------------|
| 200 | Response for adding users. |

4.5.7 Deleting Members from a User Group

Function

Delete members from a user group.

URI

POST /koodrive/ose/v1/usergroups/{group_id}/members/batchDelete

Table 4-140 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| group_id | Yes | String | |

Request Parameters

Table 4-141 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-142 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|------------------|---------------|
| userIds | Yes | Array of strings | User ID list. |

Response Parameters

Status code: 200

Table 4-143 Response body parameters

| Parameter | Type | Description |
|-----------------|--|---|
| code | String | Response code. |
| msg | String | Response information. |
| status | Integer | Response status. 0 : all successful; 1 : partially successful; 2 : all failed. |
| subResponseList | Array of MemberResponse objects | Sub-response list. |

Table 4-144 MemberResponse

| Parameter | Type | Description |
|-----------|--------|-----------------|
| code | String | Response code. |
| message | String | Response code. |
| userId | String | Member user ID. |

Example Requests

Deletes users from group **369528171409614001**.

```
POST /koodrive/ose/v1/usergroups/369528171409614001/members/batchDelete
Authorization:Bearer+c69b0f40334782d560bb154032cf22ef43d671843c4ffbad

{
  "userIds": ["3432423464657862424","132543141414141414"]
}
```

Example Responses

Status code: 200

Response for deleting users.

```
{
  "code" : 0,
  "msg" : "OK",
  "id" : "xxx"
}
```

Status Codes

| Status Code | Description |
|-------------|------------------------------|
| 200 | Response for deleting users. |

4.6 Session Management

4.6.1 Checking Whether a User Session Is Invalid Based on Token Information

Function

Check whether a user session is invalid based on token information.

URI

GET /koodrive/ose/v1/session/auth

Request Parameters

Table 4-145 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-146 Response body parameters

| Parameter | Type | Description |
|-----------|---------------------------|-------------------|
| code | String | Error code. |
| msg | String | Error message. |
| data | OrgUserInfo object | User information. |

Table 4-147 OrgUserInfo

| Parameter | Type | Description |
|-------------|---------|--|
| role | Integer | Role. <ul style="list-style-type: none"> ● 0: common administrator. ● 1: common user. ● 2: super administrator. |
| innerUserId | String | Internal user ID. |
| userName | Long | Internal user ID. |
| orgId | String | orgId |
| orgName | String | Name in OrgID. |
| tenantId | String | Tenant code, that is, enterprise code. |
| userCount | String | Number of users. |
| deptId | String | Department ID. |

Example Requests

Request for verifying a token.

```
GET /koodrive/ose/v1/session/auth
```

```
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

User information.

```
{
  "data": {
    "role": "2",
    "userName": "Tenant Administrator",
    "innerUserId": "369528171409614001",
    "userId": "1008600000016806899",
    "tenantId": "40086000004871666",
    "orgId": "9190086000001210958",
    "orgName": "KooDrive",
    "deptId": "1395496464656556464",
    "userCount": 7000
  },
  "code": 0,
  "msg": "success"
}
```


Status Codes

| Status Code | Description |
|-------------|-------------------|
| 200 | User information. |

4.6.2 Obtaining the URL of an OrgID Authorization Code for KooDrive

Function

Obtain the URL of an OrgID authorization code for KooDrive.

URI

GET /koodrive/ose/v1/session/authCodeURL

Table 4-148 Query Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-----------------------|
| domain | Yes | String | Frontend domain name. |

Request Parameters

Table 4-149 Request header parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-150 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-------------------------|
| uri | String | Login address of OrgID. |
| orgIdHost | String | Domain host of OrgID. |
| code | String | Response code. |
| msg | String | Response message. |

Example Requests

None

Example Responses

Status code: 200

URL of an OrgID authorization code for KooDrive.

```
{
  "uri" : "https://orgid-beta.ulanqab.huawei.com/oauth2/authorize?
response_type=code&client_id=be93d606a69a214642bf324e147af3366aef98f2cb1eb0b51bf8a27647d135b0&
scope=phone+profile+email&redirect_uri=https://kdconsole-sec.hwcloudtest.cn/cloudfile/index.html",
  "orgIdHost" : "https://orgid-beta.ulanqab.huawei.com",
  "code" : 0,
  "msg" : "success"
}
```

Status Codes

| Status Code | Description |
|-------------|--|
| 200 | URL of an OrgID authorization code for KooDrive. |

4.6.3 Initializing and Creating a Session

Function

Initialize and create a session.

URI

POST /koodrive/ose/v1/session/

Request Parameters

Table 4-151 Request header parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-152 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|---------------------|
| code | Yes | String | Authorization code. |

Response Parameters

Status code: 200

Table 4-153 Response body parameters

| Parameter | Type | Description |
|-------------|--------|---|
| code | String | Response code. |
| msg | String | Response information. |
| accessToken | String | Authorization code required by the service API. |
| userId | String | User ID. |
| userName | String | User account. |

Example Requests

Request for initializing a session.

```
POST /koodrive/ose/v1/session
{
  "code":
  FrbMohdqj86v6sMZIFSSuG3E0_9RsDpL08BIYfNQPhvibLET266cQhDI_WczEXJOAoloKGCdqN2shKX1yfqRvci8nS
```

```
FdMlxjNFhoffVvH93uSzloyFxFk4P7yhY6fDXa
}
```

Example Responses

Status code: 200

Session response information.

```
{
  "accessToken": Bearer+013b4daf12f4099a6eb74e2708000cb7a418409192f3e149,
  "userId": 369528171409614001,
  "userName": Tenant Administrator,
  "code": 0,
  "msg": "success"
}
```

Status Codes

| Status Code | Description |
|-------------|-------------------------------|
| 200 | Session response information. |

4.6.4 Refreshing a Session

Function

Refresh a session.

URI

POST /koodrive/ose/v1/session/refresh

Request Parameters

Table 4-154 Request header parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

| Parameter | Mandatory | Type | Description |
|--------------|-----------|--------|-------------|
| x-session-id | Yes | String | Session ID. |

Response Parameters

Status code: 200

Table 4-155 Response body parameters

| Parameter | Type | Description |
|-------------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response information. |
| accessToken | String | Authentication. |

Example Requests

Request for refreshing a session.

```
POST /koodrive/ose/v1/session/refresh
```

```
Authorization:Bearer+10f88d*****a544791e9ff  
x-session-id:b49*****ee67d90c07be
```

Example Responses

Status code: 200

Session refresh result.

```
{  
  "accessToken": Bearer+013b4daf12f4099a6eb74e2708000cb7a418409192f3e149,  
  "code": 0,  
  "msg": "success"  
}
```

Status Codes

| Status Code | Description |
|-------------|-------------------------|
| 200 | Session refresh result. |

4.6.5 Signing In and Signing Out

Function

Clear session information when a member signs out.

URI

GET /koodrive/ose/v1/session/logoff

Request Parameters

Table 4-156 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | No | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-157 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-------------|
| code | String | Error code. |

| Parameter | Type | Description |
|------------|------------------|--------------------|
| msg | String | Error description. |
| failedList | Array of strings | Failure list. |

Example Requests

Sign-out request.

```
GET /koodrive/ose/v1/session/logoff
```

```
Authorization:Bearer+10f88d0*****a544791e9ff
```

Example Responses

Status code: 200

Basic response. Only the error code and error information are returned.

```
{
  "code" : 0,
  "msg" : "success"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Basic response. Only the error code and error information are returned. |

4.7 Service Subscription

4.7.1 Obtaining the Subscription Status

Function

Obtain the subscription status of the management console service.

URI

```
GET /koodrive/ose/v1/service
```

Request Parameters

Table 4-158 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-159 Response body parameters

| Parameter | Type | Description |
|-----------|-----------------------------|------------------------------------|
| code | String | Response code. |
| msg | String | Response message. |
| data | ServiceStatus object | Cloud service subscription status. |

Table 4-160 ServiceStatus

| Parameter | Type | Description |
|---------------------|---------|---|
| status | Integer | Service status. <ul style="list-style-type: none"> • 0: normal (The cloud service restores, for example, after being unfrozen.) • 1: frozen (Resources and data are reserved but the cloud service cannot be used.) |
| spaceCapacity | Integer | Space quota. |
| userCount | Integer | OrgID user quota. |
| groupSpaceSize | Integer | Default size of the team space. 0 indicates that no space is enabled. |
| personalSpaceSize | Integer | Default size of the individual space. 0 indicates that no space is enabled. |
| organizationName | String | Organization name. |
| organizationId | String | Organization ID. |
| rootDeptCode | String | Root department code generated after the organization is created in OrgID. |
| tenantId | String | Tenant ID. |
| departmentSpaceSize | String | Default size of the department space. 0 indicates that no space is enabled. |
| aiAvailable | String | Whether AI is enabled. |
| wpsAvailable | String | Whether WPS is enabled. |
| productType | String | Product type. |

Example Requests

Request for obtaining the subscription status of the management console service.

```
GET /koodrive/ose/v1/service
```

```
Authorization:Bearer+10f88d*****4791e9ff
```

Example Responses

Status code: 200

Service status.

```
{
  "data": {
    "tenantId": "40086000004871666",
    "status": 0,
  }
}
```

```

"spaceCapacity": 10000,
"userCount": 7000,
"personalSpaceSize": 0,
"groupSpaceSize": 10,
"organizationName": "KooDrive",
"organizationId": "9190086000001210958",
"rootDeptCode": "aed8a3763f9b4177beb2dd8bce1a3885",
"departmentSpaceSize": 0
"productType": "2"
"wpsAvailable": true
"aiAvailable": true
},
"code": 0,
"msg": "Successful"
}

```

Status Codes

| Status Code | Description |
|-------------|-----------------|
| 200 | Service status. |

4.7.2 Querying Service Usage

Function

Query service usage (space and OrgID user quotas).

URI

GET /koodrive/ose/v1/service/quotaUsed

Request Parameters

Table 4-161 Request header parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|---|
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |

Response Parameters

Status code: 200

Table 4-162 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Response code. |

| Parameter | Type | Description |
|-----------|--------------------|-------------------|
| msg | String | Response message. |
| data | data object | |

Table 4-163 data

| Parameter | Type | Description |
|------------------------|--------|---|
| spaceQuotaUsed | String | Used space quota. |
| userCount | String | Number of created OrgID users. |
| spaceCapacity | String | Total space capacity subscribed by the tenant, in GB. |
| userMaxCount | String | User quantity subscribed by the tenant. |
| spaceUsed | String | Used space. |
| deptSpaceQuota | String | Department space quota. |
| personalSpaceQuota | String | Individual space quota. |
| groupSpaceQuota | String | Group space quota. |
| reservedSpaceQuota | String | Reserved space quota. |
| deptSpaceUsed | String | Used department space. |
| deptSpaceQuotaUsed | String | Used department space quota. |
| personalSpaceUsed | String | Used individual space. |
| personalSpaceQuotaUsed | String | Used individual space quota. |
| groupSpaceUsed | String | Used group space. |
| groupSpaceQuotaUsed | String | Used group space quota. |
| packageDownloadExpires | String | Expiration time of package download. |

| Parameter | Type | Description |
|-------------|--------|---------------|
| productType | String | Product type. |

Example Requests

None

Example Responses

Status code: 200

Response for querying service usage.

```
{
  "data": {
    "spaceUsed": 7753298,
    "spaceCapacity": 10240,
    "deptSpaceQuota": 6144,
    "personalSpaceQuota": 2048,
    "groupSpaceQuota": 2048,
    "reservedSpaceQuota": 0,
    "spaceQuotaUsed": 327,
    "deptSpaceUsed": 1975057,
    "deptSpaceQuotaUsed": 42,
    "personalSpaceUsed": 3933426,
    "personalSpaceQuotaUsed": 35,
    "groupSpaceUsed": 1844815,
    "groupSpaceQuotaUsed": 250,
    "userCount": 20,
    "userMaxCount": 100,
    "packageDownloadExpires": 7,
    "productType": "1"
  },
  "code": 0,
  "msg": "success"
}
```

Status Codes

| Status Code | Description |
|-------------|--------------------------------------|
| 200 | Response for querying service usage. |

4.8 Enterprise Settings

4.8.1 Setting the Expiration Time of a Compressed Package

Function

Set the expiration time of a compressed package generated during package download.

URI

POST /koodrive/ose/v1/org/package

Request Parameters

Table 4-164 Request header parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en_us indicates English (United States). |

Table 4-165 Request body parameters

| Parameter | Mandatory | Type | Description |
|------------------------|-----------|---------|---|
| tenantId | No | String | Tenant ID. |
| packageDownloadExpires | Yes | Integer | Time for invalidating and deleting the temporary package generated during package download. Default value: 7. Value range: [1, 30]. |

Response Parameters

Status code: 200

Table 4-166 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Error code. |
| msg | String | Error message. |

Example Requests

None

Example Responses

None

Status Codes

| Status Code | Description |
|-------------|-----------------------------|
| 200 | Department creation result. |

4.9 Cloud Decompression

4.9.1 Listing Directories in a Compressed Package

Function

List file directories in a compressed package.

URI

POST /koodrive/ose/v1/archive/listFile

Request Parameters

Table 4-167 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-168 Request body parameters

| Parameter | Mandatory | Type | Description |
|-------------|-----------|--------|------------------------------|
| containerId | Yes | String | Space ID. |
| fileId | Yes | String | File ID. |
| pwd | No | String | Compressed package password. |

Response Parameters

Status code: 200

Table 4-169 Response body parameters

| Parameter | Type | Description |
|-----------|--------------------|---|
| code | String | Response code. |
| msg | String | Response message. |
| data | data object | Response for listing directories in a compressed package. |

Table 4-170 data

| Parameter | Type | Description |
|-----------------------|--|---|
| uncompressed FileList | Array of UncompressedFileInfo objects | List of files in the compressed package, including all sub-files and sub-directories. This parameter is returned in synchronous mode. |
| taskId | String | Task ID, which is returned in asynchronous mode. |

Table 4-171 UncompressedFileInfo

| Parameter | Type | Description |
|-----------------|--|--|
| containerId | String | Space ID after decompression. This parameter is returned only for decompression. |
| fileId | String | ID of the decompressed file. This parameter is returned only for decompression. |
| name | String | Full path of the file or folder in the compressed package. |
| fileSize | Long | File size, in bytes. |
| type | Integer | For details, see the definition of fileType . 1 : content. 2 : directory. |
| updatedAt | Long | Millisecond timestamp of file modification. |
| subFileList | Array of UncompressedFileInfo objects | List of sub-files and sub-directories (expanded only for directories). |
| reason | String | Failure cause. If the operation is successful, this parameter is null. |
| code | String | Error code. |
| reservationInfo | Object | Reserved field. |

Status code: 400

Table 4-172 Response body parameters

| Parameter | Type | Description |
|------------|--------|--|
| error_code | String | Error code. Minimum: 8 Maximum: 36 |
| error_msg | String | Error description. Minimum: 2 Maximum: 512 |

Example Requests

Lists file directories in a compressed package.

```
POST /ose/v1/archive/listFile
```



```
Authorization:Bearer+10f88*****4791e9ff

{
  "containerId": "IAADfsBFCO6WtAtuAe3ab00aac61c45e18b0896269d5efb",
  "fileId": "FvW8fIQFZmz6Fu-Iz-7pKt6wtJISsW0C-",
  "pwd": " "
}
```

Example Responses

Status code: 200

Response for listing directories in a compressed package.

```
{
  "data": {
    "taskId": "1428103989525998336"
  },
  "code": 0,
  "msg": "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Response for listing directories in a compressed package. |
| 400 | Error response |

4.10 File List Query

4.10.1 Listing Files in the Individual Space

Function

List files in the individual space.

URI

POST /koodrive/ose/v1/files/{type}

Table 4-173 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| type | Yes | String | <ul style="list-style-type: none"> 0: individual space. 1: individual recycle bin. |

Request Parameters

Table 4-174 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-175 Request body parameters

| Parameter | Mandatory | Type | Description |
|--------------|-----------|----------------------------|--|
| pageInfo | No | PageInfo object | Pagination information. |
| sortInfo | No | FileSortInfo object | Classification information. |
| containerId | Yes | String | Space ID. |
| parentFileId | Yes | String | Parent directory of the file. <ul style="list-style-type: none"> root: root directory of the common file system. sbox: root directory of the safe file system. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|---|
| fileType | No | String | File type. <ul style="list-style-type: none"> • 10: folder. • 15: image. • 20: video. • 26: Word file. • 27: Excel file. • 28: PowerPoint file. • 30: audio. • 35: compressed file. • 40: application. • 45: other. |

Table 4-176 PageInfo

| Parameter | Mandatory | Type | Description |
|------------|-----------|---------|--|
| pageSize | No | Integer | Number of files on each page. Default value: 100. |
| pageCursor | No | String | Pagination start cursor. |

Table 4-177 FileSortInfo

| Parameter | Mandatory | Type | Description |
|---------------|-----------|---------|--|
| sortType | No | Integer | Sorting field. <ul style="list-style-type: none"> • 1: by file name. • 2: by file size. • 3: by creation time. • 4: by modification time. • 5: by recycling time (only for recycled files). • 6: by file format. |
| sortDirection | No | Integer | Sorting order. <ul style="list-style-type: none"> • 1: ascending. • 2: descending. |

Response Parameters

Status code: 200

Table 4-178 Response body parameters

| Parameter | Type | Description |
|-----------------|--|---|
| category | String | Resource type. The value is fixed to drive#fileList . |
| nextCursor | String | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| searchCompleted | Boolean | Whether the search is complete. |
| files | Array of FileListMetadata objects | File list. |
| code | String | Response code. |
| msg | String | Response information. |

Table 4-179 FileListMetadata

| Parameter | Type | Description |
|--------------|--------------------|---|
| id | String | File ID. |
| fileName | String | File name, which contains up to 80 characters. |
| fileType | String | File type, which is input externally. |
| mimeType | String | Content type. |
| favorite | Boolean | Whether the file is added to favorites. |
| recycled | Boolean | Whether the file is moved to the recycle bin. |
| recycledTime | String | Time when the file is moved to the recycle bin. This parameter is returned when the file is recycled. |
| parentFolder | Array of strings | ID of the parent directory IDs. Currently, only the first ID is used. |
| properties | Map<String,String> | Common user-defined attributes of the file. The number of key-value pairs cannot exceed 30. A single key-value pair can contain up to 124 characters. |
| containers | Array of strings | Space ID. |
| createdTime | String | UTC time when the file is created. |
| editedTime | String | UTC time when the file is modified. |

| Parameter | Type | Description |
|----------------|--|---|
| owners | Array of User objects | Owner. |
| lastEditor | User object | Last editor. |
| fileSuffix | String | File name extension, which is the last character string of fullFileExtension . |
| size | Integer | File size. |
| attachments | Array of FileListAttachment objects | Attachment. |
| downloadLinks | Array of DownloadLink objects | Link for downloading FileProxy files. |
| userProperties | FileListPrivateProperties object | User attributes. |

Table 4-180 User

| Parameter | Type | Description |
|--------------|---------|--|
| category | String | Type. The value is drive#user . Enumeration values: <ul style="list-style-type: none"> • drive#user |
| userId | String | Huawei user ID. |
| displayName | String | Display name of the user. |
| me | Boolean | Whether you are the user. |
| permissionId | String | Permission ID. |

Table 4-181 FileListAttachment

| Parameter | Type | Description |
|-----------|--------|---|
| usage | String | Default usage: content or thumbnail . This parameter is customizable. |
| hash | String | Hash of the resource associated with the asset. |
| sha256 | String | SHA256 of the resource associated with the asset. |

| Parameter | Type | Description |
|-----------|--------------------------------------|-------------|
| asset | FileListAsset object | Asset. |

Table 4-182 FileListAsset

| Parameter | Type | Description |
|-----------|---|-------------|
| resource | FileListResource object | Resource. |
| mimeType | String | MIME type |

Table 4-183 FileListResource

| Parameter | Type | Description |
|-----------|--|--|
| object | FileListSliceObject object | Part object, which is applicable when type is set to 0 or 3 . |

Table 4-184 FileListSliceObject

| Parameter | Type | Description |
|-------------|---|--|
| id | String | Part ID. |
| start | Long | Start position of a part, which is not applicable when type is set to 12 . |
| downloadUrl | EndpointURL Metadata object | Download URL. |
| image | Array of Images objects | Thumbnail information. |

Table 4-185 Images

| Parameter | Type | Description |
|-------------|---|--|
| process | String | File resource name. |
| downloadUrl | EndpointURL Metadata object | URL structure for file upload or download. |

Table 4-186 EndpointURLMetadata

| Parameter | Type | Description |
|-----------|--------|-------------|
| url | String | URL |
| method | String | http method |

Table 4-187 DownloadLink

| Parameter | Type | Description |
|--------------|--------|---|
| usage | String | Default usage: content or thumbnail . This parameter is customizable. |
| downloadLink | String | Attachment download link. |

Table 4-188 FileListPrivateProperties

| Parameter | Type | Description |
|------------|--------------------|--|
| properties | Map<String,String> | Extended attributes (The size of a single attribute is not limited, but the total size cannot exceed 16 KB.) |

Status code: 400

Table 4-189 Response body parameters

| Parameter | Type | Description |
|-----------|---------------------|----------------|
| error | Error object | Error message. |

Table 4-190 Error

| Parameter | Type | Description |
|-------------|----------------------------------|--|
| errorData | errorData object | Extended data returned to visitors when an exception occurs. |
| errorDetail | Array of ErrorMsg objects | Error chain. |
| code | Integer | HTTP status code. |
| description | String | HTTP status information. |

Table 4-191 errorData

| Parameter | Type | Description |
|----------------|--------|----------------------|
| conflictFileId | String | Conflicting file ID. |

Table 4-192 ErrorMsg

| Parameter | Type | Description |
|-------------|--------|---|
| domain | String | Domain. |
| reason | String | Error cause. |
| errorCode | String | Internal system error code. For details, see the error code specifications. |
| description | String | Error message. |
| errorPos | String | Error position type. |
| errorParam | String | Error position. |

Example Requests

Lists files in the root directory of individual space
IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b.

```
POST /koodrive/ose/v1/files/0
Authorization:Bearer+10f88*****4791e9ff

{
  "pageInfo": {
    "pageSize": "10",
    "pageCursor": ""
  },
  "sortInfo": {
    "sortType": "",
    "sortDirection": ""
  },
  "containerId": "IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b",
  "parentFileId": "root",
  "fileType": "",
  "fileName": ""
}
```

Example Responses

Status code: 200

Returns the file list.

```
{
  "category": "drive#fileList",
  "nextCursor": "0[9-1-0,11-0-1]
[JzIwMjMtMTItMTNUMDM6MzA6NTkuNTU4Wic=,J0ZpQk02VHhsS2JiSEx4LW54X3FaT2M1bFJBZXEwU0xZeCc=]",
  "searchCompleted": false,
```



```

"files" : [ {
  "id" : "Fk0n_l_3nVynllxGSUdLkYILxIZQ5Yyp",
  "fileName" : "AI Test",
  "mimeType" : "application/vnd.huawei-apps.folder",
  "fileSuffix" : "",
  "recycled" : false,
  "parentFolder" : [ "DEUI7pa0C24ArootIAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b" ],
  "containers" : [ "IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b" ],
  "properties" : {
    "srcFileId" : "Fuyt9uELO9mny6vLWnWpIDqppRh3vzC3p",
    "createUser" : "369528171409614001",
    "lastEditUser" : "369528171409614001"
  },
  "owners" : [ {
    "category" : "drive#user",
    "me" : true,
    "permissionId" : "1243622029865966464",
    "userId" : "NDEzMDA4NjAwMDAwMjc0MTY2NS00MDA4NjAwMDAwNDg3MjY2Ng",
    "displayName" : "Tenant Administrator"
  } ],
  "lastEditor" : {
    "category" : "drive#user",
    "me" : true,
    "permissionId" : "1243622029865966464",
    "userId" : "NDEzMDA4NjAwMDAwMjc0MTY2NS00MDA4NjAwMDAwNDg3MjY2Ng",
    "displayName" : "Tenant Administrator"
  },
  "fileType" : "10",
  "createdTime" : "2023-12-11T09:17:25.529Z",
  "editedTime" : "2023-12-11T09:17:25.529Z",
  "favorite" : false
} ],
"code" : 0,
"msg" : "OK"
}

```

Status Codes

| Status Code | Description |
|-------------|------------------------|
| 200 | Returns the file list. |
| 400 | Bad request |

4.10.2 Listing Files in a Group or Department Space

Function

List files in a group or department space.

URI

POST /koodrive/ose/v1/files/{groupId}/{type}

Table 4-193 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| groupId | Yes | String | Team ID. |
| type | Yes | String | Type. <ul style="list-style-type: none"> • 0: team space. • 1: team recycle bin. |

Table 4-194 Query Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|---------|--|
| team_type | No | Integer | (Optional) Team type. If this parameter is not carried, the default value 0 is used. 0 : department. 2 : group. |

Request Parameters

Table 4-195 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-196 Request body parameters

| Parameter | Mandatory | Type | Description |
|--------------|-----------|----------------------------|---|
| pageInfo | No | PageInfo object | Pagination information. |
| sortInfo | No | FileSortInfo object | Classification information. |
| containerId | Yes | String | Space ID. |
| parentFileId | Yes | String | Parent directory of the file. <ul style="list-style-type: none"> ● root: root directory of the common file system. ● sbox: root directory of the safe file system. |
| fileType | No | String | File type. <ul style="list-style-type: none"> ● 10: folder. ● 15: image. ● 20: video. ● 26: Word file. ● 27: Excel file. ● 28: PowerPoint file. ● 30: audio. ● 35: compressed file. ● 40: application. ● 45: other. |

Table 4-197 PageInfo

| Parameter | Mandatory | Type | Description |
|------------|-----------|---------|---|
| pageSize | No | Integer | Number of files on each page. Default value: 100. |
| pageCursor | No | String | Pagination start cursor. |

Table 4-198 FileSortInfo

| Parameter | Mandatory | Type | Description |
|---------------|-----------|---------|--|
| sortType | No | Integer | Sorting field. <ul style="list-style-type: none"> • 1: by file name. • 2: by file size. • 3: by creation time. • 4: by modification time. • 5: by recycling time (only for recycled files). • 6: by file format. |
| sortDirection | No | Integer | Sorting order. <ul style="list-style-type: none"> • 1: ascending. • 2: descending. |

Response Parameters

Status code: 200

Table 4-199 Response body parameters

| Parameter | Type | Description |
|-----------------|---|---|
| category | String | Resource type. The value is fixed to drive#fileList . |
| nextCursor | String | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| searchCompleted | Boolean | Whether the search is complete. |
| files | Array of FileListMetadata objects | File list. |
| code | String | Response code. |
| msg | String | Response information. |

Table 4-200 FileListMetadata

| Parameter | Type | Description |
|-----------|--------|--|
| id | String | File ID. |
| fileName | String | File name, which contains up to 80 characters. |

| Parameter | Type | Description |
|----------------|--|---|
| fileType | String | File type, which is input externally. |
| contentType | String | Content type. |
| favorite | Boolean | Whether the file is added to favorites. |
| recycled | Boolean | Whether the file is moved to the recycle bin. |
| recycledTime | String | Time when the file is moved to the recycle bin. This parameter is returned when the file is recycled. |
| parentFolder | Array of strings | ID of the parent directory IDs. Currently, only the first ID is used. |
| properties | Map<String,String> | Common user-defined attributes of the file. The number of key-value pairs cannot exceed 30. A single key-value pair can contain up to 124 characters. |
| containers | Array of strings | Space ID. |
| createdTime | String | UTC time when the file is created. |
| editedTime | String | UTC time when the file is modified. |
| owners | Array of User objects | Owner. |
| lastEditor | User object | Last editor. |
| fileSuffix | String | File name extension, which is the last character string of fullFileExtension . |
| size | Integer | File size. |
| attachments | Array of FileListAttachment objects | Attachment. |
| downloadLinks | Array of DownloadLink objects | Link for downloading FileProxy files. |
| userProperties | FileListPrivateProperties object | User attributes. |

Table 4-201 User

| Parameter | Type | Description |
|--------------|---------|---|
| category | String | Type. The value is drive#user . Enumeration values: <ul style="list-style-type: none">• drive#user |
| userId | String | Huawei user ID. |
| displayName | String | Display name of the user. |
| me | Boolean | Whether you are the user. |
| permissionId | String | Permission ID. |

Table 4-202 FileListAttachment

| Parameter | Type | Description |
|-----------|--------------------------------------|---|
| usage | String | Default usage: content or thumbnail . This parameter is customizable. |
| hash | String | Hash of the resource associated with the asset. |
| sha256 | String | SHA256 of the resource associated with the asset. |
| asset | FileListAsset object | Asset. |

Table 4-203 FileListAsset

| Parameter | Type | Description |
|-------------|---|-------------|
| resource | FileListResource object | Resource. |
| contentType | String | MIME type |

Table 4-204 FileListResource

| Parameter | Type | Description |
|-----------|--|--|
| object | FileListSliceObject object | Part object, which is applicable when type is set to 0 or 3 . |

Table 4-205 FileListSliceObject

| Parameter | Type | Description |
|-------------|---|--|
| id | String | Part ID. |
| start | Long | Start position of a part, which is not applicable when type is set to 12 . |
| downloadUrl | EndpointURL Metadata object | Download URL. |
| image | Array of Images objects | Thumbnail information. |

Table 4-206 Images

| Parameter | Type | Description |
|-------------|---|--|
| process | String | File resource name. |
| downloadUrl | EndpointURL Metadata object | URL structure for file upload or download. |

Table 4-207 EndpointURLMetadata

| Parameter | Type | Description |
|-----------|--------|-------------|
| url | String | URL |
| method | String | http method |

Table 4-208 DownLoadLink

| Parameter | Type | Description |
|--------------|--------|---|
| usage | String | Default usage: content or thumbnail . This parameter is customizable. |
| downloadLink | String | Attachment download link. |

Table 4-209 FileListPrivateProperties

| Parameter | Type | Description |
|------------|--------------------|--|
| properties | Map<String,String> | Extended attributes (The size of a single attribute is not limited, but the total size cannot exceed 16 KB.) |

Status code: 400

Table 4-210 Response body parameters

| Parameter | Type | Description |
|-----------|---------------------|----------------|
| error | Error object | Error message. |

Table 4-211 Error

| Parameter | Type | Description |
|-------------|----------------------------------|--|
| errorData | errorData object | Extended data returned to visitors when an exception occurs. |
| errorDetail | Array of ErrorMsg objects | Error chain. |
| code | Integer | HTTP status code. |
| description | String | HTTP status information. |

Table 4-212 errorData

| Parameter | Type | Description |
|----------------|--------|----------------------|
| conflictFileId | String | Conflicting file ID. |

Table 4-213 ErrorMsg

| Parameter | Type | Description |
|-----------|--------|---|
| domain | String | Domain. |
| reason | String | Error cause. |
| errorCode | String | Internal system error code. For details, see the error code specifications. |

| Parameter | Type | Description |
|-------------|--------|----------------------|
| description | String | Error message. |
| errorPos | String | Error position type. |
| errorParam | String | Error position. |

Example Requests

Lists files in the root directory of team space **IAAB_BRGQ-MajA2Waf81df00a3443452aa3dd54e35245bc**.

```
POST /koodrive/ose/v1/files/1269529595850261633/0
```

```
Authorization:Bearer+10f88*****4791e9ff
```

```
{
  "pageInfo": {
    "pageSize": "10",
    "pageCursor": ""
  },
  "sortInfo": {
    "sortType": "",
    "sortDirection": ""
  },
  "containerId": "IAAB_BRGQ-MajA2Waf81df00a3443452aa3dd54e35245bc",
  "parentFileId": "root",
  "fileType": "",
  "fileName": ""
}
```

Example Responses

Status code: 200

Returns the queried file list.

```
{
  "category": "drive#fileList",
  "nextCursor": "0|[9-1-0,11-0-1]
[JzIwMjMtMTItMTNUMDM6MzA6NTkuNTU4Wic=,J0ZpQk02VHhsS2JiSEx4LW54X3FaT2M1bFJBZXEwU0xZeC
c=]",
  "searchCompleted": false,
  "files": [ {
    "id": "Fk0n_l_3nVynIlxGSUdLkYILxIZQ5Yyp",
    "fileName": "AI Test",
    "mimeType": "application/vnd.huawei-apps.folder",
    "fileSuffix": "",
    "recycled": false,
    "parentFolder": [ "DEUI7pa0C24ArootIAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b" ],
    "containers": [ "IAADfsBFCO6WtAtuAb7e92cde625843cfb7f4ceba802e0b" ],
    "properties": {
      "srcFileId": "Fuyt9uELO9mny6vLWnWpIDqppRh3vzC3p",
      "createUser": "369528171409614001",
      "lastEditUser": "369528171409614001"
    },
  },
  "owners": [ {
    "category": "drive#user",
    "me": true,
    "permissionId": "1243622029865966464",
    "userId": "NDEzMDA4NjAwMDAwMjc0MTY2NS00MDA4NjAwMDAwNDg3MTY2Ng",
    "displayName": "Tenant Administrator"
  }
]
```

```
    } ],
    "lastEditor" : {
      "category" : "drive#user",
      "me" : true,
      "permissionId" : "1243622029865966464",
      "userId" : "NDEzMDA4NjAwMDAwMjc0MTY2NS00MDA4NjAwMDAwNDg3MTY2Ng",
      "displayName" : "Tenant Administrator"
    },
    "fileType" : "10",
    "createdTime" : "2023-12-11T09:17:25.529Z",
    "editedTime" : "2023-12-11T09:17:25.529Z",
    "favorite" : false
  } ],
  "code" : 0,
  "msg" : "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|--------------------------------|
| 200 | Returns the queried file list. |
| 400 | Bad request |

4.11 File Management

4.11.1 Obtaining File Details

Function

Obtain file details, such as the file size, name, and modification time.

URI

POST /koodrive/ose/v1/files/{fileId}/detail

Table 4-214 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| fileId | Yes | String | File ID. |

Request Parameters

Table 4-215 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-216 Request body parameters

| Parameter | Mandatory | Type | Description |
|-------------|-----------|--------|-------------|
| containerId | Yes | String | Space ID. |

Response Parameters

Status code: 200

Table 4-217 Response body parameters

| Parameter | Type | Description |
|-----------|--------|--|
| id | String | File ID. |
| fileName | String | File name, which contains up to 80 characters. |
| fileType | String | File type, which is input externally. |

| Parameter | Type | Description |
|--------------|---|---|
| contentType | String | Content type. |
| recycled | Boolean | Whether the file is moved to the recycle bin. |
| parentFolder | Array of strings | ID of the parent directory IDs. Currently, only the first ID is used. |
| properties | Map<String,String> | Common user-defined attributes of the file. The number of key-value pairs cannot exceed 30. A single key-value pair can contain up to 124 characters. |
| containers | Array of strings | Space ID. |
| createdTime | String | UTC time when the file is created. |
| editedTime | String | UTC time when the file is modified. |
| owners | Array of User objects | Owner. |
| lastEditor | User object | Last editor. |
| fileSuffix | String | File name extension, which is the last character string of fullFileExtension . |
| size | Integer | File size. |
| attachments | Array of Attachment Metadata objects | Attachment. |
| code | String | Response code. |
| msg | String | Response information. |

Table 4-218 User

| Parameter | Type | Description |
|--------------|---------|--|
| category | String | Type. The value is drive#user . Enumeration values: <ul style="list-style-type: none"> • drive#user |
| userId | String | Huawei user ID. |
| displayName | String | Display name of the user. |
| me | Boolean | Whether you are the user. |
| permissionId | String | Permission ID. |

Table 4-219 AttachmentMetadata

| Parameter | Type | Description |
|-----------|--------------------------------------|---|
| usage | String | Default usage: content or thumbnail . This parameter is customizable. |
| hash | String | Hash of the resource associated with the asset. |
| sha256 | String | SHA256 of the resource associated with the asset. |
| asset | AssetMetadata object | Asset. |

Table 4-220 AssetMetadata

| Parameter | Type | Description |
|--------------|---|---|
| id | String | Asset ID |
| versionId | String | Asset version ID. |
| version | Long | Version number. |
| contentType | String | MIME type |
| state | Integer | Data status. <ul style="list-style-type: none"> • 0: available. • 1: unavailable. • 2: temporary. • 3: retained (flash upload unsupported). • 4: to be cut over. Enumeration values: <ul style="list-style-type: none"> • 0 • 1 • 2 • 3 • 4 |
| createdTime | String | UTC time when data is created. |
| modifiedTime | String | UTC time when data is last modified. |
| resource | ResourceMetadata object | Resource. |
| attributes | Map<String, Object> | Type attributes. A key consists of letters and digits and starts with a letter. A value cannot contain emojis. The size of an attribute is not limited, but the total size cannot exceed 16 KB. |

Table 4-221 ResourceMetadata

| Parameter | Type | Description |
|-----------|--|--|
| id | String | ID of the file resource. |
| length | Long | Size of the file resource. |
| sha256 | String | SHA256 of the file (used for integrity check). |
| objects | Array of SliceObjectMetadata objects | Part object, which is applicable when type is set to 0 or 3 . |

Table 4-222 SliceObjectMetadata

| Parameter | Type | Description |
|-------------|--|--|
| id | String | Part ID. |
| start | Long | Start position of a part, which is not applicable when type is set to 12 . |
| downloadUrl | EndpointURLMetadata object | Download URL. |

Table 4-223 EndpointURLMetadata

| Parameter | Type | Description |
|-----------|--------|-------------|
| url | String | URL |
| method | String | http method |

Example Requests

Checks file details.

```
POST /koodrive/ose/v1/files/FqNZrzGgSKHkfGmwjf7dLgLLGkwrLEU35/detail
Authorization:Bearer+10f88*****4791e9ff
{
  "containerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"
}
```

Example Responses

Status code: 200

File details.

```
{
  "id": "FtSCRFXYtFjo315lPFRHeKRiqrDdmm_Y",
  "fileName": "Download_20231213_160540.png",
  "mimeType": "image/png",
  "fileSuffix": ".png",
  "recycled": false,
  "size": 81243,
  "parentFolder": [ "DEUI7pa0C24ArootIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4" ],
  "containers": [ "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4" ],
  "properties": {
    "localCreatedAt": "",
    "localUpdatedAt": "",
    "createUser": "369528171409614001",
    "lastEditUser": "369528171409614001"
  },
  "attachments": [ {
    "asset": {
      "id": "1310155787561278720",
      "versionId": "1310155787561278721",
      "version": 612304,
      "mimeType": "image/png",
      "state": 0,
      "createdTime": "2023-12-13T08:05:40.655Z",
      "modifiedTime": "2023-12-13T08:05:40.655Z",
      "resource": {
        "id": "1275457496273837312",
        "length": 81243,
        "sha256": "f08b00d63f9109fda252e45cc70e2762347907aba7c5dea4de7eb179ddad1ab2",
        "object": {
          "id": "b91e8df8afba4145a310dde1bfb9f8c5086",
          "start": 0,
          "downloadUrl": {
            "url": "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/b91e8df8afba4145a310dde1bfb9f8c5086?response-content-disposition=attachment%3B%20filename%3D%22%25E4%25B8%258B%25E8%25BD%25BD_20231213_160540.png%22&X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-Date=20231227T073619Z&X-Amz-SignedHeaders=host&X-Amz-Expires=10000&X-Amz-Credential=MKRISPBJAJWFHNB5WLB%2F20231227%2Fcidc-rp-2006%2Fs3%2Faws4_request&X-Amz-Signature=6fc56f74a9478e088e1e044f453c33f8cc7b403f4478d3aefd923449349373e4",
            "method": "GET"
          }
        }
      }
    },
    "attributes": {
      "fileName": "Download.png",
      "localCreatedAt": "",
      "createdBy": "40086000004871666",
      "resource": {
        "id": "1275457496273837312",
        "object": {
          "bucket": "b10-obs-ykj-uat-01",
          "objectId": "b91e8df8afba4145a310dde1bfb9f8c5086"
        }
      },
      "localUpdatedAt": ""
    }
  } ],
  "hash": "f08b00d63f9109fda252e45cc70e2762347907aba7c5dea4de7eb179ddad1ab2",
  "usage": "content",
  "sha256": "f08b00d63f9109fda252e45cc70e2762347907aba7c5dea4de7eb179ddad1ab2"
}],
"owners": [ {
  "category": "drive#user",
  "me": true,
  "permissionId": "1243622029865966464",
  "userId": "NDEzMDA4NjAwMDAwMjc0MTY2NS00MDA4NjAwMDAwNDg3MTY2Ng",
  "displayName": "Tenant Administrator"
} ],
"lastEditor": {
  "category": "drive#user",
```

```

"me" : true,
"permissionId" : "1243622029865966464",
"userId" : "NDEzMDA4NjAwMDAwMjc0MTY2NS00MDA4NjAwMDAwNDg3MTY2Ng",
"displayName" : "Tenant Administrator"
},
"fileType" : "15",
"createdTime" : "2023-12-13T08:05:40.601Z",
"editedTime" : "2023-12-13T08:05:41.054Z",
"code" : 0,
"msg" : "Success."
}

```

Status Codes

| Status Code | Description |
|-------------|---------------|
| 200 | File details. |

4.11.2 Adding a File Directory

Function

Add a file directory.

URI

POST /koodrive/ose/v1/directory

Request Parameters

Table 4-224 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-225 Request body parameters

| Parameter | Mandatory | Type | Description |
|--------------|-----------|------------------|--|
| createdTime | No | String | Time when the file is created. Format: yyyy-MM-ddTHH:mm:ss.sssZ |
| description | No | String | File description. The value contains up to 512 characters and cannot contain invalid characters such as emojis. Maximum: 512 |
| contentType | No | String | Resource type. |
| editedTime | No | String | File modification time. |
| fileName | Yes | String | File name. The value cannot contain <> :"*? /. The value cannot be two periods (..), a period (.), or a space. Maximum: 80 |
| fileType | Yes | String | File type, which is input externally. The value is fixed at 10 . |
| parentFolder | No | Array of strings | List of parent directory IDs. The first directory is used as the parent directory. If this parameter is null, the file is created in the root directory. |
| containerId | Yes | String | Space ID. container , parentAlias , and parentFolder are mutually exclusive. parentFolder is preferred. |

| Parameter | Mandatory | Type | Description |
|------------|-----------|---------|--|
| renameMode | No | Integer | Duplicate name policy. <ul style="list-style-type: none"> • 2: Forcibly renames a file with an existing name by adding a timestamp to the end of the file name. • 3: Rejects files with the same name. A file with an existing name cannot be created. |

Response Parameters

Status code: 200

Table 4-226 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| id | String | File ID. |
| fileName | String | File name. |
| mimeType | String | File format. |
| code | String | Response code. |
| msg | String | Response information. |

Example Requests

Creates a folder in the root directory of the space
IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4.

```
POST /koodrive/ose/v1/directory
```

```
Authorization:Bearer+10f88*****4791e9ff
```

```
{
  "createdTime": "",
  "editedTime": "",
  "description": "222",
  "mimeType": "application/vnd.huawei-apps.folder",
  "fileName": "ttgg",
  "fileType": "10",
  "parentFolder": [
    "root"
  ],
  "containerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
  "renameMode": "2"
}
```

Example Responses

Status code: 200

Information returned after the directory is created.

```
{
  "id" : "FqAHbpps7uJEDpvh2MbpLj7LD4AM2OWMR",
  "fileName" : "ttgg",
  "mimeType" : "application/vnd.huawei-apps.folder",
  "code" : 0,
  "msg" : "success"
}
```

Status Codes

| Status Code | Description |
|-------------|--|
| 200 | Information returned after the directory is created. |

4.11.3 Creating File Metadata

Function

Create the metadata of the uploaded file. If flash upload is not hit, the upload process is triggered. When flash upload is hit, the file upload is complete.

URI

POST /koodrive/ose/v1/files/create

Request Parameters

Table 4-227 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-228 Request body parameters

| Parameter | Mandatory | Type | Description |
|--------------|-----------|------------------|--|
| createdTime | No | String | Time when the file is created. The format is yyyy-MM-dd'T'HH:mm:ss'Z', for example, 2023-08-18T05:43:49Z. |
| description | No | String | File description. Maximum: 512 |
| mimeType | No | String | Resource type. |
| fileName | Yes | String | File name, which cannot contain <> :"*? /. The value cannot be two periods (..), a period (.), or a space. Maximum: 80 |
| fileType | Yes | String | File type, which is customizable. |
| parentFolder | Yes | Array of strings | Parent directory ID list. If the target directory is a root directory, the value is root . Currently, only one parent directory is supported. If multiple parent directory IDs are passed, only the first one is used. |
| sha256 | No | String | Complete file digest calculated using SHA256. |

| Parameter | Mandatory | Type | Description |
|-------------|-----------|---------------------------------------|---|
| length | Yes | Long | File size, in bytes. When uploadMode is set to put , the value must be less than or equal to 5 GB. If uploadMode is set to multipart , the value must be less than or equal to 200 GB. |
| uploadMode | Yes | String | Upload mode. <ul style="list-style-type: none"> • multipart: multipart upload. • put: single file upload. |
| uploadType | Yes | Integer | Upload type. <ul style="list-style-type: none"> • 0: common upload (not supported yet). • 1: multipart upload. • 2: versioning upload (not supported yet). |
| autoRename | Yes | Integer | Duplicate name policy. <ul style="list-style-type: none"> • 2: Forcibly renames a file with an existing name by adding a timestamp to the end of the file name. • 3: Rejects files with the same name. A file with an existing name cannot be created. • 4: Does not create a file if files with the same name have the same SHA256 value, or, uses the forcible renaming logic. |
| multiParts | No | Array of MultiPartInfo objects | Part information list. |
| containerId | Yes | String | ID of the target space to which the file is uploaded. |
| preHash | No | String | Digest of the first 1 KB of the file calculated using SHA256. |

Table 4-229 MultiPartInfo

| Parameter | Mandatory | Type | Description |
|------------|-----------|----------------|---|
| partNumber | Yes | Integer | Part No. Minimum: 1 Maximum: 10000 |
| partSize | Yes | Long | Part length. The value range is [5,242,880, 5,368,709,120]. The value range of the last part is [0, 5,368,709,120]. Minimum value: 0. Maximum value: 5,368,709,120. |
| partOffset | No | Long | Total length (in bytes) to the last data block. This parameter is valid only during concurrent multipart upload. The size of all parts except the last one must be a multiple of 64 bytes. |
| hashCtx | No | Array of longs | Context used to iteratively calculate SHA256. This field is valid only during concurrent multipart upload. For SHA1, the value is the first to fifth 32-bit variables of the SHA1 of the previous data block. For SHA256, the value is the first to eighth 32-bit variables of the SHA256 of the previous data block. This parameter is mandatory for all parts except the first one in concurrent multipart upload. |
| uploadUrl | No | String | URL for uploading a file. This parameter is returned. |
| partId | No | String | Part object ID. |

Response Parameters

Status code: 200

Table 4-230 Response body parameters

| Parameter | Type | Description |
|----------------|---------------------------------------|---|
| fileId | String | File ID. |
| rapidUpload | Boolean | Whether flash upload is hit. true indicates that flash upload is hit. |
| containerId | String | ID of the space where the file is located. |
| fileName | String | Name of the uploaded file. If the file is not renamed, the value is the same as the file name in the request parameter. |
| uploadId | String | File upload ID. |
| parentFolder | Array of strings | ID of the parent directory where the uploaded file is located. |
| exist | Boolean | Whether the file exists. This parameter is used only when the input parameter autoRename is set to 4 . If the file names and SHA256 values are the same, true is returned. |
| multiParts | Array of MultiPartInfo objects | Part information, which is returned during multipart upload (when uploadMode is set to multipart). |
| matchedPreHash | Boolean | Whether a matching prehash exists. |
| code | String | Response code. |
| msg | String | Response information. |

Table 4-231 MultiPartInfo

| Parameter | Type | Description |
|------------|---------|--|
| partNumber | Integer | Part No. Minimum: 1 Maximum: 10000 |
| partSize | Long | Part length. The value range is [5,242,880, 5,368,709,120]. The value range of the last part is [0, 5,368,709,120]. Minimum value: 0. Maximum value: 5,368,709,120. |
| partOffset | Long | Total length (in bytes) to the last data block. This parameter is valid only during concurrent multipart upload. The size of all parts except the last one must be a multiple of 64 bytes. |

| Parameter | Type | Description |
|-----------|----------------|---|
| hashCtx | Array of longs | Context used to iteratively calculate SHA256. This field is valid only during concurrent multipart upload. For SHA1, the value is the first to fifth 32-bit variables of the SHA1 of the previous data block. For SHA256, the value is the first to eighth 32-bit variables of the SHA256 of the previous data block. This parameter is mandatory for all parts except the first one in concurrent multipart upload. |
| uploadUrl | String | URL for uploading a file. This parameter is returned. |
| partId | String | Part object ID. |

Example Requests

Creates file metadata in multipart upload mode. In this example, a part is specified. The upload link of the part is returned in the subsequent response. The part needs to be uploaded through a PUT request.

```
POST /koodrive/ose/v1/files/create
Authorization:Bearer+10f88*****4791e9ff

{
  "containerId": "IAADfsBFCO6WtAtuA9add2fea594e4e75b8feb8474ef236",
  "parentFolder": [
    "root"
  ],
  "createdTime": "2020-05-18T01:43:49Z",
  "mimeType": "application/x-zip-compressed",
  "fileType": 35,
  "fileName": "demo.zip",
  "sha256": "08a784aeb181506391c20c6355f881dc363d8c3e0739d295e5d6f410d05dbc69",
  "length": 22106481,
  "uploadMode": "multipart",
  "uploadType": 1,
  "autoRename": 2,
  "multiParts": [
    {
      "partNumber": 1,
      "partOffset": 0,
      "partSize": 22106481
    }
  ],
  "description": ""
}
```

Example Responses

Status code: 200

Information returned after the first step of uploading a file is complete.

```
{
  "fileId": "FnkL1QhXj8muHBuSWCHtFFY8Azue445nr",
}
```



```

"containerId" : "IAADfsBFCO6WtAtuA9add2fea594e4e75b8feb8474ef236",
"fileName" : "test_20240104_105403.zip",
"uploadId" : "0000018CD26464022026422966B8879A",
"parentFolder" : [ "DEUI7pa0C24ArootIAADfsBFCO6WtAtuA9add2fea594e4e75b8feb8474ef236" ],
"exist" : false,
"multiParts" : [ {
  "partNumber" : 1,
  "partSize" : 22106481,
  "partOffset" : 0,
  "uploadUrl" : "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/
ff6b221b4b474c829c1cd5037f1504ca086?
partNumber=1&uploadId=0000018CD26464022026422966B8879A&X-Amz-Algorithm=AWS4-HMAC-
SHA256&X-Amz-Date=20240104T025403Z&X-Amz-SignedHeaders=content-length%3Bhost&X-Amz-
Expires=3600&X-Amz-Credential=MKRISPBJ5WLB%2F20240104%2Fcidc-
rp-2006%2Fs3%2Faws4_request&X-Amz-
Signature=39b9b620c8de901682675059cfcfa9902a13fb5c6ab38fe1451763feb6a8323c"
} ],
"code" : 0,
"msg" : "Success."
}

```

Status Codes

| Status Code | Description |
|-------------|--|
| 200 | Information returned after the first step of uploading a file is complete. |

4.11.4 Checking Whether File Upload Is Completed

Function

Check the file integrity after the service uploads the complete data of a file. If the file passes the check, the file upload is complete.

URI

POST /koodrive/ose/v1/files/complete

Request Parameters

Table 4-232 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-233 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|---|
| fileId | Yes | String | ID of the uploaded file. |
| sha256 | No | String | Complete file digest calculated using SHA256. |

Response Parameters

Status code: 200

Table 4-234 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Response code. |

| Parameter | Type | Description |
|-----------|--------|-------------------|
| msg | String | Response message. |

Example Requests

Combines parts and checks file integrity after the binary data of a file is uploaded.

```
POST /koodrive/ose/v1/files/complete
Authorization:Bearer+10f88*****4791e9ff
{
  "fileId": "FiqNTAYdzXtKhenh29A9EXJvhaKQqcYVS"
}
```

Example Responses

Status code: 200

Information returned after the upload is complete.

```
{
  "code" : 0,
  "msg" : "success."
}
```

Status Codes

| Status Code | Description |
|-------------|--|
| 200 | Information returned after the upload is complete. |

4.11.5 Obtaining Download Links

Function

Obtain the download links of files.

URI

POST /koodrive/ose/v1/files/download

Request Parameters

Table 4-235 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-236 Request body parameters

| Parameter | Mandatory | Type | Description |
|-------------|-----------|------------------|---|
| containerId | Yes | String | ID of the space where the files to be obtained are located. |
| fileIds | Yes | Array of strings | File ID list. Up to 100 file IDs are allowed. |

Response Parameters

Status code: 200

Table 4-237 Response body parameters

| Parameter | Type | Description |
|-----------|---------|----------------|
| code | Integer | Response code. |

| Parameter | Type | Description |
|-----------|---|---|
| msg | String | Response information. |
| batchCode | Integer | Response code. <ul style="list-style-type: none"> • 0: partially successful. • 1: all successful. • 2: all failed. |
| downloads | Array of DownloadInfoResponse objects | Download link information. |

Table 4-238 DownloadInfoResponse

| Parameter | Type | Description |
|-----------|--------|---|
| fileId | String | File ID. |
| fileName | String | File name. |
| url | String | Download link. |
| code | String | Response code of a single download record. |
| msg | String | Response message of a single download record. |

Example Requests

Obtains the download links of files.

```
POST /koodrive/ose/v1/files/download
Authorization:Bearer+10f88*****4791e9ff

{
  "containerId": "IAADfsBFCO6WtAtuA9add2fea594e4e75b8feb8474ef236",
  "fileIds": [
    "Fn1bTLIOomJkTCAe9DEVBRY4U6IkuqkMZ"
  ]
}
```

Example Responses

Status code: 200

Response to the request for obtaining the file download links.

```
{
  "downloads": [ {
    "fileId": "Fn1bTLIOomJkTCAe9DEVBRY4U6IkuqkMZ",
    "url": "https://b10-obs-ykj-uat-01.obs.cdc-rp-2006.joint.cmecloud.cn/5e3fc0c5d4fa45338f44db7177579c2c087?response-content-disposition=attachment%3B%20filename%3D"
```

```
%22%25E5%258F%2591%25E7%25A5%25A81.pdf%22&X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-Date=20231227T072939Z&X-Amz-SignedHeaders=host&X-Amz-Expires=3600&X-Amz-Credential=MKRISPBJAJWFHNB5WLB%2F20231227%2Fcidc-rp-2006%2Fs3%2Faws4_request&X-Amz-Signature=9d06798af17e2f1082b720f43af29a32b3154da4ddeee4f10025a758b599728a",
  "fileName" : "Invoice 1.pdf",
  "code" : "0",
  "msg" : "success"
}],
"batchCode" : 1,
"code" : 0,
"msg" : "Success."
}
```

Status Codes

| Status Code | Description |
|-------------|--|
| 200 | Response to the request for obtaining the file download links. |

4.11.6 Renaming a File

Function

Rename a file.

URI

POST /koodrive/ose/v1/files/rename/{fileId}

Table 4-239 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| fileId | Yes | String | File ID. |

Request Parameters

Table 4-240 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-241 Request body parameters

| Parameter | Mandatory | Type | Description |
|-------------|-----------|---------|--|
| containerId | Yes | String | Space ID. |
| name | Yes | String | New file name, which cannot contain <> :"*?/\ or be two periods (..) or a period (.). Maximum: 80 |
| renameMode | Yes | Integer | Duplicate name policy. <ul style="list-style-type: none"> • 2: Forcibly renames a file with an existing name by adding a timestamp to the end of the file name. • 3: Rejects files with the same name. A file with an existing name cannot be created. |

Response Parameters

Status code: 200

Table 4-242 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-------------------|
| code | String | Response code. |
| msg | String | Response message. |

Example Requests

Renames a file whose ID is **FtSCRFXCYtFjo315lPFRHeKRiqrDdmm_Y** under the space whose ID is **IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4** to **Download**.

```
POST /koodrive/ose/v1/files/rename/FtSCRFXCYtFjo315lPFRHeKRiqrDdmm_Y
Authorization:Bearer+10f88*****4791e9ff
{
  "name": "Download",
  "containerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
  "renameMode": 2
}
```

Example Responses

Status code: 200

Information returned after a file is renamed.

```
{
  "code" : 0,
  "msg" : "success"
}
```

Status Codes

| Status Code | Description |
|-------------|---|
| 200 | Information returned after a file is renamed. |

4.11.7 Clearing the Recycle Bin

Function

Create an asynchronous task to clear all files in the recycle bin of the space.

URI

POST /koodrive/ose/v1/files/recycle

Request Parameters

Table 4-243 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-244 Request body parameters

| Parameter | Mandatory | Type | Description |
|-------------|-----------|--------|-------------|
| containerId | Yes | String | Space ID. |

Response Parameters

Status code: 200

Table 4-245 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Response code. |

| Parameter | Type | Description |
|-----------|--------|-------------------|
| msg | String | Response message. |

Example Requests

Clears the files in the recycle bin of the space whose ID is **IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4**.

```
POST /koodrive/ose/v1/files/recycle
Authorization:Bearer+10f88*****4791e9ff
{
  "containerId": "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4"
}
```

Example Responses

Status code: 200

Information returned after the recycle bin is cleared.

```
{
  "code" : 0,
  "msg" : "success"
}
```

Status Codes

| Status Code | Description |
|-------------|--|
| 200 | Information returned after the recycle bin is cleared. |

4.11.8 Retrieving Files Using Search Engine Capabilities

Function

Search for files in a space by conditions such as search scope, parent directory, file name, file size range, update time range, and owner. Common users and department administrators can search for their individual and team space. Tenant administrators can search for all team spaces of the tenant.

URI

POST /koodrive/ose/v1/files/search

Request Parameters

Table 4-246 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Table 4-247 Request body parameters

| Parameter | Mandatory | Type | Description |
|------------|-----------|------------------------|--|
| searchType | Yes | String | Query type, which is the individual space or team space. |
| pageInfo | Yes | pageInfo object | Pagination information. |
| filter | No | filter object | Filter. |
| sortInfo | No | sortInfo object | Sorting information. |

| Parameter | Mandatory | Type | Description |
|------------|-----------|---------|--|
| recycled | No | Boolean | Whether files in the recycle bin are queried. <ul style="list-style-type: none">• true: Queries files in the recycle bin.• false: Queries other files in the space. Default: false |
| recursived | No | Boolean | Whether files in sub-directories are queried recursively. Default value: false. |

Table 4-248 pageInfo

| Parameter | Mandatory | Type | Description |
|------------|-----------|---------|--|
| pageSize | Yes | Integer | Number of records on each page. Minimum: 1 Maximum: 100 |
| pageCursor | Yes | String | Start cursor. If this parameter is null, the query starts from the first page. |

Table 4-249 filter

| Parameter | Mandatory | Type | Description |
|--------------|-----------|--------|---|
| keyWord | No | String | File name, which is used for fuzzy match. Minimum: 1 Maximum: 255 |
| containerId | No | String | Space ID. This parameter is mandatory when the parent directory is specified. |
| parentFolder | No | String | Parent directory. |

| Parameter | Mandatory | Type | Description |
|-----------------|-----------|--------|---|
| fileType | No | String | File type. Enumerated values: /** Folder / <i>FOLDER("10")</i> , /* Image / <i>PICTURE("15")</i> , /* Video / <i>VIDEO("20")</i> , /* Word file / <i>WORD("26")</i> , /* Excel file / <i>EXCEL("27")</i> , /* PowerPoint file / <i>PPT("28")</i> , /* Audio / <i>AUDIO("30")</i> , /* Compressed file / <i>ARCHIVE("35")</i> , /* Application / <i>APPLICATION("40")</i> , /* Other */ <i>OTHER("45")</i> ; |
| updateTimeRange | No | String | Update time range. |
| ownerId | No | String | File owner. |

Table 4-250 sortInfo

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| sortType | No | String | Enumerated values: <ul style="list-style-type: none"> ● fileName: file name. ● size: file size. -** type**: file format. ● updateTime: update time. ● createTime: creation time. ● recycledTime: deletion time. ● fileSuffix: file sub-category. |
| sortDirection | No | String | Enumerated values: <ul style="list-style-type: none"> ● desc: descending order. ● asc: ascending order. |

Response Parameters

Status code: 200

Table 4-251 Response body parameters

| Parameter | Type | Description |
|----------------|-------------------------------|---|
| code | Integer | Response code. 0 indicates success. Other values indicate failure. |
| msg | String | Success and error information. |
| files | Array of files objects | Search results |
| total | Integer | Total number of records. |
| nextPageCursor | String | Start cursor of the next page. It is null for the last page. |

Table 4-252 files

| Parameter | Type | Description |
|---------------|--------------------------------------|--|
| id | String | File ID. |
| fileSuffix | String | File suffix. |
| fileName | String | File name. |
| fileType | String | File type. |
| size | String | File size. |
| updateTime | String | Update time. |
| namePath | String | Full name path. |
| idPath | String | Full ID path. |
| downloadLinks | Array of DownloadLink objects | Thumbnail link, which is returned for an image. |
| teamName | String | Department name or group space name returned for the team space. |
| teamId | String | Group ID, that is, department ID or group ID. |
| containerId | String | Space ID. |
| containerType | String | 0 : department space; 1 : individual space; 2 : group space. |
| favorite | Boolean | Whether the file returned by the individual space or team space is added to favorites by the current user. |
| owner | String | Owner name returned for the team space. |

| Parameter | Type | Description |
|-------------------|--------------------------------------|------------------------------|
| metadataAuditInfo | FileAuditInfo object | File moderation information. |
| contentAuditInfo | FileAuditInfo object | File moderation information. |

Table 4-253 DownloadLink

| Parameter | Type | Description |
|--------------|--------|---|
| usage | String | Default usage: content or thumbnail . This parameter is customizable. |
| downloadLink | String | Attachment download link. |

Table 4-254 FileAuditInfo

| Parameter | Type | Description |
|-------------|---------|--|
| auditStatus | Integer | Moderation status. <ul style="list-style-type: none"> • 0: not reviewed. • 1: reviewed. Enumeration values: <ul style="list-style-type: none"> • 0 • 1 |
| auditLevel | Integer | Moderation level. <ul style="list-style-type: none"> • 10: machine moderation. • 20: human moderation. • 30: machine and human moderation. • 99: appeal moderation. Enumeration values: <ul style="list-style-type: none"> • 10 • 20 • 30 • 99 |

| Parameter | Type | Description |
|-------------|---------|--|
| auditResult | Integer | <p>Moderation result.</p> <ul style="list-style-type: none"> • 1: normal file. • 2: file with low-sensitive content. • 3: file with high-sensitive content. • 4: file with sensitive metadata. <p>Enumeration values:</p> <ul style="list-style-type: none"> • 1 • 2 • 3 • 4 |
| auditDetail | String | Moderation details. |

Example Requests

Example request for searching for a file.

```
POST /koodrive/ose/v1/files/search
Authorization:Bearer+10f88*****4791e9ff
{
  "searchType" : " personal/team",
  "pageInfo" : {
    "pageSize" : 100,
    "pageCursor" : 1
  },
  "filter" : {
    "keyWord" : "Material",
    "containerId" : "123456",
    "parentFolder" : "1",
    "fileType" : "1",
    "sizeRang" : "1024,2048",
    "updateTimeRange" : "2023-11-02,2023-11-21",
    "ownerId" : "Owner ID"
  }
}
```

Example Responses

Status code: 200

Search results

```
{
  "code" : 0,
  "msg" : "success",
  "files" : [ {
    "id" : "Abc",
    "fileName" : "Abc",
    "fileType" : "1",
    "size" : "1024",
    "updateTime" : "2023-05-26T02:08:53.683Z",
    "namePath" : "",
    "downloadLinks" : "",
    "deptName" : ""
  }
]
```



```

    }],
    "total" : 1000
  }

```

Status Codes

| Status Code | Description |
|-------------|----------------|
| 200 | Search results |

4.11.9 Obtaining the Full Name and ID Paths of a File

Function

Obtain the full name and ID paths of a file.

URI

GET /koodrive/ose/v1/files/path

Table 4-255 Query Parameters

| Parameter | Mandatory | Type | Description |
|-------------|-----------|--------|-------------|
| fileId | Yes | String | File ID. |
| containerId | Yes | String | Space ID. |

Request Parameters

Table 4-256 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| X-Traceid | No | String | Message log trace ID. The value contains 58 bits. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-257 Response body parameters

| Parameter | Type | Description |
|------------|--------|-----------------------------|
| code | String | Response code. |
| msg | String | Response message. |
| fileIdPath | String | Full path of the file ID. |
| namePath | String | Full path of the file name. |

Example Requests

Queries the full directory path of a file.

```
GET /koodrive/ose/v1/files/path?
fileId=FqS6hLLy_DkjlWdfOnEdCErhmokRvdXI&containerId=IAADfsBFCO6WtAtuA315074383680425b8aa9a1
30cba2d4
Authorization:Bearer+10f88*****4791e9ff
```

Example Responses

Status code: 200

Full path information.

```
{
  "fileIdPath" : "/DEUI7pa0C24ArootIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4/
FkbdCAceMj89bprz5xLJASID1eaRqjLRP/FqIAmBliz7ovbThxeUBlOpbnCHaP_MTUL/
FqS6hLLy_DkjlWdfOnEdCErhmokRvdXI",
  "namePath" : "/rootIAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4/007/001/Batch Task Test",
  "code" : 0,
  "msg" : "OK"
}
```

Status Codes

| Status Code | Description |
|-------------|------------------------|
| 200 | Full path information. |

4.12 File Favorites

4.12.1 Adding Files to Favorites

Function

Add files to favorites or remove files from favorites. Up to 100 files are supported.

URI

POST /koodrive/ose/v1/star/batch

Request Parameters

Table 4-258 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| x-hw-trace-id | No | String | Message log trace ID. The value contains 58 bits. |

Table 4-259 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|---------|---------------------------------------|
| starred | Yes | Boolean | Whether files are added to favorites. |

| Parameter | Mandatory | Type | Description |
|----------------|-----------|---|---------------------------------|
| subRequestList | Yes | Array of StarFileRequest objects | Files to be added to favorites. |

Table 4-260 StarFileRequest

| Parameter | Mandatory | Type | Description |
|-------------|-----------|--------|--------------------------------|
| containerId | Yes | String | Space ID. |
| fileId | Yes | String | File ID, which must be unique. |

Response Parameters

Status code: 200

Table 4-261 Response body parameters

| Parameter | Type | Description |
|-----------------|-------------------------------------|---|
| status | Integer | Response status. 0 : all successful; 1 : partially successful; 2 : all failed. |
| subResponseList | Array of SubResponse objects | Sub-response list. |

Table 4-262 SubResponse

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| fileId | String | File ID. |
| code | String | Response code. |
| message | String | Response information. |

Example Requests

```
{
  "starred" : true,
  "subRequestList" : [ {
    "containerId" : "IAADfsBFCO6WtAtuA315074383680425b8aa9a130cba2d4",
    "fileId" : "Fn1bTLIOomJkTCAe9DEVBRy4U6IkuqkMZ"
  } ]
}
```

Example Responses

Status code: 200

OK

```
{
  "status" : 0,
  "subResponseList" : [ {
    "fileId" : "Fn1bTLIOomJkTCAe9DEVBRy4U6IkuqkMZ",
    "code" : "0",
    "message" : "success"
  } ]
}
```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.12.2 Listing Files in Favorites

Function

List files in favorites. Up to 100 files are supported.

URI

GET /koodrive/ose/v1/star/files

Table 4-263 Query Parameters

| Parameter | Mandatory | Type | Description |
|------------|-----------|---------|---|
| pageSize | No | Integer | Number of records to be returned on each page. Default and maximum value: 100. It is possible that partial or empty result pages are returned before the end of the result list has been reached. Maximum: 100 |
| pageCursor | No | String | Current page cursor, which is obtained from nextCursor of the previous response. |
| sortType | No | Integer | Sorting type. 1 : by the time when a file is added to favorites (default). |

| Parameter | Mandatory | Type | Description |
|---------------|-----------|---------|--|
| sortDirection | No | Integer | Sorting order. 1: ascending; 2: descending (default). |
| fileType | No | String | File type. <ul style="list-style-type: none">• 10: folder.• 15: image.• 20: video.• 26: Word file.• 27: Excel file.• 28: PowerPoint file.• 30: audio.• 35: compressed file.• 40: application.• 45: other. |

Request Parameters

Table 4-264 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| x-hw-trace-id | No | String | Message log trace ID. The value contains 58 bits. |

Response Parameters

Status code: 200

Table 4-265 Response body parameters

| Parameter | Type | Description |
|-------------|---|--|
| nextCursor | String | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| autoDeleted | Integer | Number of automatically deleted files (original files have been physically deleted). |
| starFiles | Array of StarFileInfo objects | |

Table 4-266 StarFileInfo

| Parameter | Type | Description |
|------------------|-----------------------------|---|
| category | String | Type. The value is drive#file . Enumeration values: <ul style="list-style-type: none"> drive#file |
| id | String | File ID. |
| fileName | String | File name, which contains up to 160 bytes. |
| fileType | String | File type, which is input externally. |
| mimeType | String | Content type. |
| description | String | File description. The value contains up to 512 characters and cannot contain emojis or invalid characters. Maximum: 512 |
| favorite | Boolean | Whether the file is added to favorites. |
| recycled | Boolean | Whether the file is moved to the recycle bin. |
| directlyRecycled | Boolean | Whether the file is directly moved to the recycle bin. If the folder containing this file is deleted, the value is false . If the file is directly deleted, the value is true . |
| recyclingUser | User object | User that deletes the file. |
| recycledTime | String | Time when the file is moved to the recycle bin. |
| parentFolder | Array of strings | List of parent directory IDs. Currently, only the first ID is used. |
| properties | Map<String,String> | Common user-defined attributes of the file. The number of key-value pairs cannot exceed 30. A single key-value pair can contain up to 124 characters. |

| Parameter | Type | Description |
|---------------------------------|------------------------------|---|
| appSettings | Map<String,String> | User-defined app attributes. The number of key-value pairs cannot exceed 30. A single key-value pair can contain up to 124 characters. |
| containers | Array of strings | Space ID. |
| version | Integer | Version number. |
| createdTime | String | File creation time. |
| editedTime | String | File modification time. |
| editedByMeTime | String | Time when you modify the file. |
| editedByMe | Boolean | Whether the file is modified by you. |
| sharedWithMeTime | String | Time when the file is shared to you. |
| sharer | User object | User who shares the file. |
| owners | Array of User objects | Owner. |
| lastEditor | User object | Last editor. |
| hasShared | Boolean | Whether the file is shared. |
| ownedByMe | Boolean | Whether the file is uploaded by you. |
| capabilities | Capabilities object | Capabilities. |
| viewersHasCopyContentPermission | Boolean | Whether a viewer can copy content. |
| writerHasCopyPermission | Boolean | Whether the writer permission is required for replication. |
| writersHasSharePermission | Boolean | Whether a user with the write permission can share the file. |
| originalFilename | String | Original file name, which contains up to 80 characters. The value cannot contain <> :"*? \ or emojis. The value cannot be two periods (..), a period (.), or a space. |
| fullFileSuffix | String | Complete file name extension, which is the characters following the first period (.) in the name. |
| fileSuffix | String | File name extension, which is the last character string of fullFileExtension . |

| Parameter | Type | Description |
|----------------------|---|---|
| size | Integer | File size. |
| pictureMetadata | PictureMetadata object | Image metadata. |
| videoMetadata | VideoMetadata object | Video metadata. |
| audioMetadata | AudioMetadata object | Audio metadata. |
| sha256 | String | SHA256 of the file. |
| lastHistoryVersionId | String | ID of the latest historical version. |
| attachments | Array of Attachment objects | Attachment (Usage, Attachment). Only the app ID of the risk control service is returned. |
| iconDownloadLink | String | Icon link. |
| existThumbnail | Boolean | Whether a thumbnail is available. |
| privateKey | String | Special folder ID. The usage rules are as follows: <ul style="list-style-type: none"> • The name cannot be _default. • This parameter can be specified only when the folder is created in the space root directory. • This parameter can be specified only when a folder is created. • The value must be unique in the same space. |
| signedDownloadLink | String | Download link of the FileProxy signature, which is used for online playback. |
| downloadLinks | Array of DownloadLink objects | Link for downloading FileProxy files. |
| localPath | String | ID path of the top-level parent directory during change (the first 10 levels are used). This parameter is returned for change record and file query. |
| sortName | String | Sorting name after filename conversion. |
| userProperties | PrivateProperties object | User attributes. |

| Parameter | Type | Description |
|-------------------|--------------------------------------|--|
| starredTime | String | Time when the file is added to favorites. |
| filePath | String | File location, specific to the team name. |
| spaceType | String | Space type. <ul style="list-style-type: none"> • 1: individual space. • 2: team space. • 3: recycle bin. • 4: space without access permission. |
| invalid | Integer | Whether the file has expired. *0: normal; 1: expired. |
| metadataAuditInfo | FileAuditInfo object | File moderation information. |
| contentAuditInfo | FileAuditInfo object | File moderation information. |

Table 4-267 User

| Parameter | Type | Description |
|--------------|---------|---|
| category | String | Type. The value is drive#user . Enumeration values: <ul style="list-style-type: none"> • drive#user |
| userId | String | Huawei user ID. |
| displayName | String | Display name of the user. |
| me | Boolean | Whether you are the user. |
| permissionId | String | Permission ID. |

Table 4-268 Capabilities

| Parameter | Type | Description |
|-------------------------------|---------|--|
| addChildNodePermission | Boolean | Whether a sub-directory or sub-file can be added. |
| writerHasChangeCopyPermission | Boolean | Whether the write permission is required for change and replication. |
| commentPermission | Boolean | Whether comments can be made. |

| Parameter | Type | Description |
|------------------------------|---------|--|
| copyPermission | Boolean | Whether the file can be copied. |
| deletePermission | Boolean | Whether the file can be deleted. |
| downloadPermission | Boolean | Whether the content can be downloaded. |
| editPermission | Boolean | Whether the file can be edited. |
| listChildNodePermission | Boolean | Whether sub-directories or sub-files can be listed. |
| editContentPermission | Boolean | Whether the content can be modified. |
| readHistoryVersionPermission | Boolean | Whether a backup can be read. |
| removeChildNodePermission | Boolean | Whether a sub-directory can be moved. |
| renameFilePermission | Boolean | Whether the file can be renamed. |
| shareFilePermission | Boolean | Whether the file can be shared. |
| recyclePermission | Boolean | Whether the file can be moved to the recycle bin. |
| unrecyclePermission | Boolean | Whether moving a sub-file to the recycle bin can be withdrawn. |

Table 4-269 PictureMetadata

| Parameter | Type | Description |
|-----------|------------------------|--|
| width | Integer | Photo width. |
| height | Integer | Photo height. |
| rotation | Integer | Photo rotation angle. This parameter is not available currently. |
| location | Location object | Location information. |

| Parameter | Type | Description |
|------------------|---------|--|
| exifTime | String | Time of the photo. The value is an EXIF DateTime. |
| cameraMaker | String | Camera manufacturer. |
| cameraModel | String | Camera model. |
| exposureTime | Float | Exposure time, in seconds. |
| aperture | Float | Aperture f-number. |
| flashUsed | Boolean | Whether the flash is used. |
| focalLength | Float | Focal length, in millimeters. |
| isoSpeed | Integer | ISO speed. |
| meteringMode | String | Metering mode. |
| sensor | String | Sensor type. |
| exposureMode | String | Exposure mode. |
| colorSpace | String | Color space. |
| whiteBalance | String | White balance mode. |
| exposureBias | Float | Exposure bias. The value is an APEX value. |
| maxApertureValue | Float | Maximum aperture. The value is an APEX value. |
| subjectDistance | Integer | Distance to subject, in meters. This parameter is not available currently. |
| lens | String | Lens. |

Table 4-270 Location

| Parameter | Type | Description |
|-----------|--------|-------------|
| latitude | Double | Latitude. |
| longitude | Double | Longitude. |
| altitude | Double | Altitude. |

Table 4-271 VideoMetadata

| Parameter | Type | Description |
|--------------|---------|---|
| width | Integer | Width. |
| height | Integer | Altitude. |
| durationTime | Integer | Duration, in milliseconds. |
| position | String | Longitude and latitude information. The format is "x":"111","y":"222","z":"2222". |
| rotation | Integer | Rotation angle. Value range: 1 to 8. |
| format | String | Video encoding format, for example, H.264, H.265, VP8, VP9, Ogg, and MPEG-4 AVC. |
| dynamicRange | String | SDR or HDR. |
| snapshotTime | String | Shooting time. |

Table 4-272 AudioMetadata

| Parameter | Type | Description |
|--------------|---------|---|
| durationTime | Integer | Duration, in milliseconds. |
| sampleRate | String | Sampling rate, for example, 16,000 or 48,000. |
| encoding | String | Audio encoding format, for example, PCM, AAC, AMR, or AMR-WB. |
| codeRate | Number | Bit rate, in kbit/s. Example: 12.8. |
| rateModel | String | Bit rate mode, for example, CBR. |
| languageCode | String | Language code, for example, en. |

Table 4-273 Attachment

| Parameter | Type | Description |
|-----------|--------|---|
| usage | String | Default usage: content or thumbnail . This parameter is customizable. |
| assetId | String | Asset ID |
| length | Long | File size. |
| versionId | String | Asset version ID. |
| mimeType | String | MIME type. |

| Parameter | Type | Description |
|--------------|---------------------|---|
| hash | String | Hash of the resource associated with the asset. |
| sha256 | String | SHA256 of the resource associated with the asset. |
| createdTime | String | Time when the data is created. |
| modifiedTime | String | Time when the data is last modified. |
| attributes | Map<String, Object> | Type attributes. |
| asset | Asset object | Asset. |

Table 4-274 Asset

| Parameter | Type | Description |
|------------|---------|---|
| id | String | Asset ID |
| versionId | String | Asset version ID. |
| version | Long | Version number. |
| mimeType | String | MIME type |
| keepPolicy | Integer | Storage policy of historical versions. <ul style="list-style-type: none"> ● 0: automatic clearance. Two versions are retained. The earliest version is deleted when the third version is added. (This prevents obtaining failures in concurrent scenarios.) ● 1: permanent storage. Default: 0 |
| state | Integer | Data status. <ul style="list-style-type: none"> ● 0: available. ● 1: unavailable. ● 2: temporary. ● 3: retained (flash upload unsupported). ● 4: to be cut over. Enumeration values: <ul style="list-style-type: none"> ● 0 ● 1 ● 2 ● 3 ● 4 |

| Parameter | Type | Description |
|--------------------|------------------------|---|
| createdTime | String | Time when the data is created. |
| modifiedTime | String | Time when the data is last modified. |
| lastModifying User | String | UPID of the user that last modifies the data. |
| resource | Resource object | Resource. |
| cipher | Cipher object | Cipher. |
| attributes | Map<String, Object> | Type attributes. A key consists of letters and digits and starts with a letter. A value cannot contain emojis. The size of an attribute is not limited, but the total size cannot exceed 16 KB. Attribute options: <ul style="list-style-type: none"> • pictureMetadata: image attribute data. For details, see the definition of PictureMetadata. • videoMetadata: video attribute data. For details, see the definition of VideoMetadata. • audioMetadata: audio attribute data. For details, see the definition of AudioMetadata. • contentDisposition: used when response-content-disposition is not specified for the downloaded attachment (valid when resource.type is set to 12). |
| properties | Map<String, String> | Extended attributes. |

Table 4-275 Resource

| Parameter | Type | Description |
|-----------|---------|--|
| id | String | ID of the file resource. |
| hash | String | Hash of the file resource. |
| length | Long | Size of the file resource. |
| sha256 | String | SHA256 of the file (used for integrity check). |
| type | Integer | Resource type. <ul style="list-style-type: none"> • 0: ciphertext multipart file. • 3: plaintext multipart file. • 12: plaintext single-part file. |

| Parameter | Type | Description |
|--------------|--|---|
| state | Integer | Data status. <ul style="list-style-type: none"> ● 0: available. ● 1: unavailable. ● 2: temporary. ● 3: retained (flash upload unsupported). ● 4: to be cut over. |
| sliceSize | Long | Part size. |
| hfek | String | Hash of the FEK of the encrypted file. This parameter is applicable when type is set to 0 . |
| iv | String | IV of the encrypted file. This parameter is applicable when type is set to 0 . |
| createdTime | String | Time when the data is created. |
| modifiedTime | String | Time when the data is last modified. |
| objects | Array of SliceObject objects | Part object, which is applicable when type is set to 0 or 3 . |
| attributes | Map<String, Object> | Type attributes. |
| properties | Map<String, String> | Extended attributes. |

Table 4-276 SliceObject

| Parameter | Type | Description |
|--------------|---------|--|
| id | String | Part ID. |
| number | Integer | Part No., starting from 0. This parameter is not applicable when type is set to 12 . |
| start | Long | Start position of a part, which is not applicable when type is set to 12 . |
| sha256 | String | SHA256 of the part (or SHA256 of the ciphertext if the part is encrypted.) |
| length | Long | Part length (or ciphertext length if the part is encrypted). |
| bucket | String | OBS bucket information. |
| createdTime | String | Time when the data is created. |
| modifiedTime | String | Time when the data is last modified. |

| Parameter | Type | Description |
|-------------|------------------------------------|---|
| uploadUrl | EndpointURL object | Upload URL. |
| downloadUrl | EndpointURL object | Download URL. |
| uploadId | String | Multipart upload ID. This parameter is applicable when type is set to 12 and uploadMode is set to multipart . |
| attributes | Map<String, Object> | Type attributes. |
| properties | Map<String, String> | Extended attributes. |

Table 4-277 EndpointURL

| Parameter | Type | Description |
|-----------|---------------------|--|
| url | String | URL |
| method | String | http method |
| headers | Map<String, String> | http headers |
| forms | Map<String, String> | Form parameter, which is applicable when type is set to 12 and uploadMode is set to post . |
| partId | String | Multipart parameter, which is applicable when type is set to 12 and uploadMode is set to multipart . |

Table 4-278 Cipher

| Parameter | Type | Description |
|-----------|--------|---|
| algorithm | String | Encryption algorithm. Enumeration values: <ul style="list-style-type: none"> • AES_128_CBC_PKCS5Padding |
| hfek | String | Hash of the FEK of the encrypted file. This parameter is applicable when type is set to 0 or 4 . |
| iv | String | IV of the encrypted file. This parameter is applicable when type is set to 0 or 4 . |

| Parameter | Type | Description |
|-----------|---|--|
| dataType | Integer | Data type. <ul style="list-style-type: none"> • 11: sync drive. Enumeration values: <ul style="list-style-type: none"> • 0 • 1 • 10 • 11 |
| keychains | Array of Keychain objects | Keychain. |

Table 4-279 Keychain

| Parameter | Type | Description |
|-----------|---------|---|
| id | String | Key UUID. Maximum: 128 |
| type | Integer | Key type. <ul style="list-style-type: none"> • 1: efek. • 2: zfek. • 3: sfek. |
| algorithm | String | Encryption algorithm. Enumeration values: <ul style="list-style-type: none"> • AES_128_CBC_PKCS5Padding • AES_256_CBC_PKCS5Padding |
| ekey | String | Encrypted key. Maximum: 512 |

Table 4-280 DownloadLink

| Parameter | Type | Description |
|--------------|---------|---|
| usage | String | Default usage: content or thumbnail . This parameter is customizable. |
| downloadLink | String | Attachment download link. |
| version | Integer | Attachment version. |

Table 4-281 PrivateProperties

| Parameter | Type | Description |
|------------|--------------------|--|
| attributes | Map<String,Object> | Type attributes (The size of a single attribute is not limited, but the total size cannot exceed 16 KB.) |
| properties | Map<String,String> | Extended attributes (The size of a single attribute is not limited, but the total size cannot exceed 16 KB.) |

Table 4-282 FileAuditInfo

| Parameter | Type | Description |
|-------------|---------|--|
| auditStatus | Integer | Moderation status. <ul style="list-style-type: none"> ● 0: not reviewed. ● 1: reviewed. Enumeration values: <ul style="list-style-type: none"> ● 0 ● 1 |
| auditLevel | Integer | Moderation level. <ul style="list-style-type: none"> ● 10: machine moderation. ● 20: human moderation. ● 30: machine and human moderation. ● 99: appeal moderation. Enumeration values: <ul style="list-style-type: none"> ● 10 ● 20 ● 30 ● 99 |
| auditResult | Integer | Moderation result. <ul style="list-style-type: none"> ● 1: normal file. ● 2: file with low-sensitive content. ● 3: file with high-sensitive content. ● 4: file with sensitive metadata. Enumeration values: <ul style="list-style-type: none"> ● 1 ● 2 ● 3 ● 4 |

| Parameter | Type | Description |
|-------------|--------|---------------------|
| auditDetail | String | Moderation details. |

Example Requests

None

Example Responses

None

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.13 Sharing Management - Shared by You

4.13.1 Sharing a File

Function

Share a file.

URI

POST /koodrive/ose/v1/share

Request Parameters

Table 4-283 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Table 4-284 Request body parameters

| Parameter | Mandatory | Type | Description |
|-------------|-----------|--|--|
| scope | Yes | Integer | Sharing scope. 1 : all users who receive the link; 2 : enterprise users only; 3 : specified enterprise users. |
| deptIds | No | Array of strings | Department ID list. |
| groupIds | No | Array of strings | List of user group IDs. |
| userIds | No | Array of strings | User ID list. |
| fileIds | Yes | Array of strings | File ID list. |
| containerId | Yes | String | Space ID. |
| permission | No | SharePermission object | Sharing permission (supported in the future). |
| extractCode | No | String | Access code. |
| expireTime | No | String | Expiration time. |
| comment | No | String | Sharing message. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|---------|--|
| validDays | Yes | Integer | Sharing validity period. Value range: 1 to 365 days. |

Table 4-285 SharePermission

| Parameter | Mandatory | Type | Description |
|-----------|-----------|---------|----------------------|
| preview | No | Boolean | Preview permission. |
| edit | No | Boolean | Editing permission. |
| download | No | Boolean | Download permission. |

Response Parameters

Status code: 200

Table 4-286 Response body parameters

| Parameter | Type | Description |
|-----------|----------------------------------|---------------------------|
| code | String | Response code. |
| msg | String | Response information. |
| shareLink | shareLink object | Sharing link information. |

Table 4-287 shareLink

| Parameter | Type | Description |
|-------------|--------|---------------------|
| shareId | String | Sharing ID. |
| shortUrl | String | Sharing short code. |
| linkUrl | String | Sharing link. |
| extractCode | String | Access code. |
| comment | String | Message. |
| createTime | String | Creation time. |
| expireTime | String | Expiration time. |

Status code: 400

Table 4-288 Response body parameters

| Parameter | Type | Description |
|-----------|------------------------------|-------------|
| error | Error object | |

Table 4-289 Error

| Parameter | Type | Description |
|-------------|---|--|
| errorData | errorData object | Extended data returned to visitors when an exception occurs. |
| errorDetail | Array of ErrorMsg objects | Error chain. |
| code | Integer | HTTP status code. |
| description | String | HTTP status information. |

Table 4-290 errorData

| Parameter | Type | Description |
|----------------|--------|----------------------|
| conflictFileId | String | Conflicting file ID. |

Table 4-291 ErrorMsg

| Parameter | Type | Description |
|-------------|--------|---|
| domain | String | Domain. |
| reason | String | Error cause. |
| errorCode | String | Internal system error code. For details, see the error code specifications. |
| description | String | Error message. |
| errorPos | String | Error position type. |
| errorParam | String | Error position. |

Example Requests

```
POST /koodrive/ose/v1/share
Authorization:Bearer+10f88*****4791e9ff
{
```

```

"scope": 0,
"deptIds": [
  "string"
],
"groupIds": [
  "string"
],
"userIds": [
  "string"
],
"fileIds": [
  "string"
],
"containerId": "string",
"permission": {
  "preview": true,
  "edit": true,
  "download": true
},
"extractCode": "string",
"expireTime": "2024-06-03T01:54:57.288Z",
"comment": "string",
"validDays": 0
}

```

Example Responses

Status code: 200

OK

```

{
  "data" : {
    "taskId" : "1428103989525998336"
  },
  "code" : 0,
  "msg" : "OK"
}

```

Status code: 400

```

{
  "error" : {
    "errorData" : {
      "conflictFileId" : "string"
    },
    "errorDetail" : [ {
      "domain" : "string",
      "reason" : "string",
      "errorCode" : "string",
      "description" : "string",
      "errorPos" : "string",
      "errorParam" : "string"
    } ],
    "code" : 0,
    "description" : "string"
  }
}

```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

| Status Code | Description |
|-------------|-------------|
| 400 | |

4.13.2 Listing Files Shared by You

Function

List files shared by you. One sharing record occupies one line. When multiple files are shared, a folder with the first file name is displayed. When a single file is shared, the file information is displayed.

URI

GET /koodrive/ose/v1/share

Table 4-292 Query Parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|---------|---|
| pageSize | No | Integer | Number of records to be returned on each page. Default and maximum value: 100. It is possible that partial or empty result pages are returned before the end of the result list has been reached. Maximum: 100 |
| pageCursor | No | String | Current page cursor, which is obtained from nextCursor of the previous response. |
| sortType | No | Integer | Sorting type. 4 : by sharing time (default). |
| sortDirection | No | Integer | Sorting order. 1 : ascending; 2 : descending (default). |
| displayName | No | String | Fuzzy match by display name is supported. |

Request Parameters

Table 4-293 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Response Parameters

Status code: 200

Table 4-294 Response body parameters

| Parameter | Type | Description |
|------------|--|---|
| code | String | Response code. |
| msg | String | Response information. |
| nextCursor | String | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| shareLinks | Array of ShareByMeLink objects | Sharing link list. |

Table 4-295 ShareByMeLink

| Parameter | Type | Description |
|-----------|--------|---------------------|
| shareId | String | Sharing ID. |
| shortUrl | String | Sharing short code. |
| linkUrl | String | Sharing link. |

| Parameter | Type | Description |
|---------------|--|--|
| shareTime | String | Time when the file is shared. |
| scope | Integer | Sharing scope. 1 : all users who receive the link; 2 : enterprise users only; 3 : specified enterprise users. |
| files | Array of ShareFileInfo objects | List of shared files. |
| displayName | String | Display name. |
| permission | SharePermission object | Sharing permission (supported in the future). |
| extractCode | String | Access code. |
| expireTime | String | Expiration time. |
| status | Integer | Sharing status. 0 : determined based on the expiration time. 1 : The file has been deleted. 2 : expired. |
| comment | String | Sharing message. |
| viewCnt | Integer | Number of views. |
| downloadCnt | Integer | Number of download times (supported in the future). |
| saveCnt | Integer | Number of dump times (supported in the future). |
| containerId | String | ID of the space to which the shared file belongs. |
| containerName | String | Space to which the shared file belongs. |

Table 4-296 ShareFileInfo

| Parameter | Type | Description |
|-----------|---------|---|
| id | String | *File ID. |
| fileName | String | *File name, which contains up to 160 bytes. |
| fileType | String | File type, which is input externally. |
| mimeType | String | *Content type. |
| size | Integer | File size. |

| Parameter | Type | Description |
|--------------|------------------|---|
| parentFolder | Array of strings | List of parent directory IDs. Currently, only the first ID is used. |
| fileSuffix | String | File name extension, which is the last character string of fullFileExtension . |
| containers | Array of strings | Space ID. |

Table 4-297 SharePermission

| Parameter | Type | Description |
|-----------|---------|----------------------|
| preview | Boolean | Preview permission. |
| edit | Boolean | Editing permission. |
| download | Boolean | Download permission. |

Example Requests

```
GET /koodrive/ose/v1/share?pageSize=&pageCursor=0&sortType=2&sortDirection=4&displayName=
Authorization:Bearer+10f88*****5a544791e9ff
```

Example Responses

Status code: 200

OK

```
{
  "code" : "string",
  "msg" : "string",
  "nextCursor" : "string",
  "shareLinks" : [ {
    "shareId" : "string",
    "shortUrl" : "string",
    "linkUrl" : "string",
    "shareTime" : "2024-06-03T01:58:35.419Z",
    "scope" : 0,
    "files" : [ {
      "id" : "string",
      "fileName" : "string",
      "fileType" : "string",
      "mimeType" : "string",
      "size" : 0,
      "parentFolder" : [ "string" ],
      "fileSuffix" : "string",
      "containers" : [ "string" ]
    } ],
    "displayName" : "string",
    "permission" : {
      "preview" : true,
      "edit" : true,
      "download" : true
    }
  } ],
}
```

```

    "extractCode" : "string",
    "expireTime" : "2024-06-03T01:58:35.419Z",
    "status" : 0,
    "comment" : "string",
    "viewCnt" : 0,
    "downloadCnt" : 0,
    "saveCnt" : 0,
    "containerId" : "string",
    "containerName" : "string"
  } ]
}

```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.13.3 Obtaining Sharing Details

Function

Obtain sharing details.

URI

GET /koodrive/ose/v1/share/{shareId}

Table 4-298 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| shareId | Yes | String | Sharing ID. |

Request Parameters

Table 4-299 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Response Parameters

Status code: 200

Table 4-300 Response body parameters

| Parameter | Type | Description |
|-----------|--|---------------------------------|
| code | String | Response code. |
| msg | String | Response information. |
| shareLink | ShareByMeLinkDetail object | Details about the sharing link. |

Table 4-301 ShareByMeLinkDetail

| Parameter | Type | Description |
|-----------|--------|-------------------------------|
| shareId | String | Sharing ID. |
| shortUrl | String | Sharing short code. |
| linkUrl | String | Sharing link. |
| shareTime | String | Time when the file is shared. |

| Parameter | Type | Description |
|-------------|-----------------------------------|--|
| scope | Integer | Sharing scope. 1 : all users who receive the link; 2 : enterprise users only; 3 : specified enterprise users. |
| depts | Array of DeptInfo objects | Department list. |
| groups | Array of GroupInfo objects | User group list. |
| users | Array of UserInfo objects | User list. |
| displayName | String | Display name. |
| permission | SharePermission object | Sharing permission (supported in the future). |
| extractCode | String | Access code. |
| expireTime | String | Expiration time. |
| status | Integer | Sharing status. 0 : determined based on the expiration time. 1 : The file has been deleted. 2 : expired. |
| comment | String | Sharing message. |

Table 4-302 DeptInfo

| Parameter | Type | Description |
|-----------|--------|------------------|
| id | String | Department ID. |
| name | String | Department name. |

Table 4-303 GroupInfo

| Parameter | Type | Description |
|-----------|--------|------------------|
| id | String | User group ID. |
| name | String | User group name. |

Table 4-304 UserInfo

| Parameter | Type | Description |
|-----------|--------|-------------|
| id | String | User ID. |
| name | String | Username. |

Table 4-305 SharePermission

| Parameter | Type | Description |
|-----------|---------|----------------------|
| preview | Boolean | Preview permission. |
| edit | Boolean | Editing permission. |
| download | Boolean | Download permission. |

Example Requests

```
GET /koodrive/ose/v1/share/{shareId}
Authorization:Bearer+10f88*****5a544791e9ff
```

Example Responses

Status code: 200

OK

```
{
  "code" : "string",
  "msg" : "string",
  "shareLink" : {
    "shareId" : "string",
    "shortUrl" : "string",
    "linkUrl" : "string",
    "shareTime" : "2024-06-03T01:59:05.324Z",
    "scope" : 0,
    "depts" : [ {
      "id" : "string",
      "name" : "string"
    } ],
    "groups" : [ {
      "id" : "string",
      "name" : "string"
    } ],
    "users" : [ {
      "id" : "string",
      "name" : "string"
    } ],
    "displayName" : "string",
    "permission" : {
      "preview" : true,
      "edit" : true,
      "download" : true
    }
  },
  "extractCode" : "string",
  "expireTime" : "2024-06-03T01:59:05.324Z",
  "status" : 0,
}
```



```
"comment" : "string"
}
}
```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.13.4 Modifying Sharing Settings

Function

Modify sharing settings.

URI

PUT /koodrive/ose/v1/share/{shareId}

Table 4-306 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| shareId | Yes | String | Sharing ID. |

Request Parameters

Table 4-307 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Table 4-308 Request body parameters

| Parameter | Mandatory | Type | Description |
|-------------|-----------|--|--|
| deptIds | No | Array of strings | Department ID list. |
| groupIds | No | Array of strings | List of user group IDs. |
| userIds | No | Array of strings | User ID list. |
| permission | No | SharePermission object | Sharing permission (supported in the future). |
| expireTime | No | String | Expiration time. |
| extractCode | No | String | Access code. |
| comment | No | String | Sharing message. |
| validDays | Yes | Integer | Sharing validity period, ranging from 0 to 365 days. 0 indicates no change. |

Table 4-309 SharePermission

| Parameter | Mandatory | Type | Description |
|-----------|-----------|---------|----------------------|
| preview | No | Boolean | Preview permission. |
| edit | No | Boolean | Editing permission. |
| download | No | Boolean | Download permission. |

Response Parameters

Status code: 200

Table 4-310 Response body parameters

| Parameter | Type | Description |
|-----------|----------------------------------|---------------------------|
| code | String | Response code. |
| msg | String | Response information. |
| shareLink | shareLink object | Sharing link information. |

Table 4-311 shareLink

| Parameter | Type | Description |
|-------------|--------|--------------------|
| shareId | String | Sharing ID. |
| shortUrl | String | Sharing link. |
| extractCode | String | Access code. |
| createTime | String | Creation time. |
| updateTime | String | Modification time. |
| expireTime | String | Expiration time. |

Example Requests

```
PUT /koodrive/ose/v1/share/{shareId}
{
  "deptIds" : [ "string" ],
  "groupIds" : [ "string" ],
  "userIds" : [ "string" ],
  "permission" : {
    "preview" : true,
    "edit" : true,
    "download" : true
  },
  "expireTime" : "2024-06-03T02:00:39.952Z",
  "extractCode" : "string",
  "comment" : "string",
  "validDays" : 0
}
```

Example Responses

Status code: 200

OK

```
{
  "code" : "string",
  "msg" : "string",
  "shareLink" : {
    "shareId" : "string",
    "shortUrl" : "string",
    "extractCode" : "string",
    "createTime" : "2024-06-03T02:00:39.953Z",
    "updateTime" : "2024-06-03T02:00:39.953Z",
    "expireTime" : "2024-06-03T02:00:39.953Z"
  }
}
```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.13.5 Stopping Sharing Files

Function

Stop sharing files.

URI

POST /koodrive/ose/v1/share/cancel

Request Parameters

Table 4-312 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Table 4-313 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|------------------|--|
| shareids | No | Array of strings | List of IDs of files whose sharing is to be stopped. |

Response Parameters

Status code: 200

Table 4-314 Response body parameters

| Parameter | Type | Description |
|-----------|--------|----------------|
| code | String | Response code. |

| Parameter | Type | Description |
|-----------------|---|-----------------------|
| msg | String | Response information. |
| subResponseList | Array of ShareSubResponse objects | Sub-response list. |

Table 4-315 ShareSubResponse

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| shareId | String | Sharing ID. |
| code | String | Sub-response code. |
| message | String | Sub-response message. |

Example Requests

```
POST /koodrive/ose/v1/share/cancel
```

```
{
  "shareIds": [ "string" ]
}
```

Example Responses

Status code: 200

OK

```
{
  "code": "string",
  "msg": "string",
  "subResponseList": [ {
    "shareId": "string",
    "code": "string",
    "message": "string"
  } ]
}
```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.14 Sharing Management - Shared with You

4.14.1 Listing Files Shared with You

Function

List files shared with you.

URI

GET /koodrive/ose/v1/share/received

Table 4-316 Query Parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|---------|---|
| pageSize | No | Integer | Number of records to be returned on each page. Default and maximum value: 100. It is possible that partial or empty result pages are returned before the end of the result list has been reached. Maximum: 100 |
| pageCursor | No | String | Current page cursor, which is obtained from nextCursor of the previous response. |
| sortType | No | Integer | Sorting type. 4 : by sharing time (default). |
| sortDirection | No | Integer | Sorting order. 1 : ascending; 2 : descending (default). |
| displayName | No | String | Fuzzy match by display name is supported. |

Request Parameters

Table 4-317 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Response Parameters

Status code: 200

Table 4-318 Response body parameters

| Parameter | Type | Description |
|------------|--|---|
| code | String | Response code. |
| msg | String | Response information. |
| nextCursor | String | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| shareLinks | Array of ShareWithMeLink objects | Sharing link list. |

Table 4-319 ShareWithMeLink

| Parameter | Type | Description |
|-----------|--------|---------------------|
| shareId | String | Sharing ID. |
| shortUrl | String | Sharing short code. |
| linkUrl | String | Sharing link. |

| Parameter | Type | Description |
|-------------|--|---|
| shareTime | String | Time when the file is shared. |
| ownerId | String | Sharer ID. |
| ownerName | String | Sharer name. |
| displayName | String | Display name. |
| files | Array of ShareFileInfo objects | List of shared files. |
| permission | SharePermission object | Sharing permission (supported in the future). |
| expireTime | String | Expiration time. |
| status | Integer | Sharing status. 0 : determined based on the expiration time. 1 : The file has been deleted. 2 : expired. |
| comment | String | Sharing message. |

Table 4-320 ShareFileInfo

| Parameter | Type | Description |
|--------------|------------------|---|
| id | String | *File ID. |
| fileName | String | *File name, which contains up to 160 bytes. |
| fileType | String | File type, which is input externally. |
| mimeType | String | *Content type. |
| size | Integer | File size. |
| parentFolder | Array of strings | List of parent directory IDs. Currently, only the first ID is used. |
| fileSuffix | String | File name extension, which is the last character string of fullFileExtension . |
| containers | Array of strings | Space ID. |

Table 4-321 SharePermission

| Parameter | Type | Description |
|-----------|---------|---------------------|
| preview | Boolean | Preview permission. |

| Parameter | Type | Description |
|-----------|---------|----------------------|
| edit | Boolean | Editing permission. |
| download | Boolean | Download permission. |

Example Requests

```
GET /koodrive/ose/v1/share/received?
pageSize=&pageCursor=0&sortType=2&sortDirection=4&displayName=&tenantId=String
Authorization:Bearer+10f88*****5a544791e9ff
```

Example Responses

Status code: 200

OK

```
{
  "code" : "string",
  "msg" : "string",
  "nextCursor" : "string",
  "shareLinks" : [ {
    "shareId" : "string",
    "shortUrl" : "string",
    "linkUrl" : "string",
    "shareTime" : "2024-06-03T02:02:00.797Z",
    "ownerId" : "string",
    "ownerName" : "string",
    "displayName" : "string",
    "files" : [ {
      "id" : "string",
      "fileName" : "string",
      "fileType" : "string",
      "mimeType" : "string",
      "size" : 0,
      "parentFolder" : [ "string" ],
      "fileSuffix" : "string",
      "containers" : [ "string" ]
    } ],
    "permission" : {
      "preview" : true,
      "edit" : true,
      "download" : true
    },
    "expireTime" : "2024-06-03T02:02:00.797Z",
    "status" : 0,
    "comment" : "string"
  } ]
}
```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.14.2 Obtain Sharing Details

Function

Obtain sharing details.

URI

GET /koodrive/ose/v1/share/received/{shareId}

Table 4-322 Path Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| shareId | Yes | String | Sharing ID. |

Request Parameters

Table 4-323 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Response Parameters

Status code: 200

Table 4-324 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response information. |

| Parameter | Type | Description |
|-----------|--|---|
| shareLink | ShareWithMeLinkDetail object | Information about the link shared with you. |

Table 4-325 ShareWithMeLinkDetail

| Parameter | Type | Description |
|-------------|--|---|
| shareId | String | Sharing ID. |
| shortUrl | String | Sharing short code. |
| linkUrl | String | Sharing link. |
| shareTime | String | Time when the file is shared. |
| ownerId | String | Sharer ID. |
| ownerName | String | Sharer name. |
| displayName | String | Display name. |
| permission | SharePermission object | Sharing permission (supported in the future). |
| expireTime | String | Expiration time. |
| status | Integer | Sharing status. 0 : determined based on the expiration time. 1 : The file has been deleted. 2 : expired. |
| comment | String | Sharing message. |

Table 4-326 SharePermission

| Parameter | Type | Description |
|-----------|---------|----------------------|
| preview | Boolean | Preview permission. |
| edit | Boolean | Editing permission. |
| download | Boolean | Download permission. |

Example Requests

```
GET /koodrive/ose/v1/share/received/{shareId}
```

```
Authorization:Bearer+10f88*****5a544791e9ff
```

Example Responses

Status code: 200

OK

```
{
  "code" : "string",
  "msg" : "string",
  "shareLink" : {
    "shareId" : "string",
    "shortUrl" : "string",
    "linkUrl" : "string",
    "shareTime" : "string",
    "ownerId" : "string",
    "ownerName" : "string",
    "displayName" : "string",
    "permission" : {
      "preview" : true,
      "edit" : true,
      "download" : true
    },
    "expireTime" : "2024-06-03T02:18:51.520Z",
    "status" : 0,
    "comment" : "string"
  }
}
```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.14.3 Removing Yourself from Shared Files

Function

Remove yourself from shared files.

URI

POST /koodrive/ose/v1/share/exit

Request Parameters

Table 4-327 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Table 4-328 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|------------------|-------------------------------------|
| shareIds | No | Array of strings | List of IDs of target shared files. |

Response Parameters

Status code: 200

Table 4-329 Response body parameters

| Parameter | Type | Description |
|-----------------|--|-----------------------|
| code | String | Response code. |
| msg | String | Response information. |
| subResponseList | Array of ShareSubResponse objects | Sub-response list. |

Table 4-330 ShareSubResponse

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| shareId | String | Sharing ID. |
| code | String | Sub-response code. |
| message | String | Sub-response message. |

Example Requests

```
POST /koodrive/ose/v1/share/exit
{
  "shareIds": [ "string" ]
}
```

Example Responses

Status code: 200

OK

```
{
  "code": "string",
  "msg": "string",
  "subResponseList": [ {
    "shareId": "string",
    "code": "string",
    "message": "string"
  } ]
}
```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.15 Sharing Management - Access Links

4.15.1 Accessing a Sharing Link.

Function

Access a sharing link.

URI

GET /koodrive/ose/v1/share/visit

Table 4-331 Query Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|---------------------|
| shortUrl | Yes | String | Sharing short code. |

Request Parameters

Table 4-332 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Response Parameters

Status code: 200

Table 4-333 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response information. |

Example Requests

```
GET /koodrive/ose/v1/share/visit?shortUrl=String
Authorization:Bearer+10f88*****5a544791e9ff
```

Example Responses

Status code: 200

OK

```
{
  "code" : "string",
  "msg" : "string"
}
```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.15.2 Obtaining Sharing Information

Function

Obtain sharing information.

URI

GET /koodrive/ose/v1/share/userInfo

Table 4-334 Query Parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|---------------------|
| shortUrl | Yes | String | Sharing short code. |

Request Parameters

Table 4-335 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|---|
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Response Parameters

Status code: 200

Table 4-336 Response body parameters

| Parameter | Type | Description |
|-----------|--|--|
| code | String | Response code. |
| msg | String | Response information. |
| link | CommonShareLink object | Public information of the access link. |

Table 4-337 CommonShareLink

| Parameter | Type | Description |
|------------|--|---|
| shareId | String | Sharing ID. |
| shortUrl | String | Sharing short code. |
| shareTime | String | Time when the file is shared. |
| ownerId | String | Sharer ID. |
| ownerName | String | Sharer name. |
| permission | SharePermission object | Sharing permission (supported in the future). |
| expireTime | String | Expiration time. |
| status | Integer | Sharing status. 0 : determined based on the expiration time. 1 : The file has been deleted. 2 : expired. |

Table 4-338 SharePermission

| Parameter | Type | Description |
|-----------|---------|---------------------|
| preview | Boolean | Preview permission. |
| edit | Boolean | Editing permission. |

| Parameter | Type | Description |
|-----------|---------|----------------------|
| download | Boolean | Download permission. |

Example Requests

```
GET /koodrive/ose/v1/share/userInfo?shortUrl=String
Authorization:Bearer+10f88*****5a544791e9ff
```

Example Responses

Status code: 200

OK

```
{
  "code" : "string",
  "msg" : "string",
  "link" : {
    "shareId" : "string",
    "shortUrl" : "string",
    "shareTime" : "2024-06-03T02:20:24.274Z",
    "ownerId" : "string",
    "ownerName" : "string",
    "permission" : {
      "preview" : true,
      "edit" : true,
      "download" : true
    }
  },
  "expireTime" : "2024-06-03T02:20:24.274Z",
  "status" : 0
}
```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.15.3 Verifying a Sharing Access Code

Function

Verify a sharing access code.

URI

POST /koodrive/ose/v1/share/verify

Request Parameters

Table 4-339 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Table 4-340 Request body parameters

| Parameter | Mandatory | Type | Description |
|-------------|-----------|--------|---------------------|
| shortUrl | Yes | String | Sharing short link. |
| extractCode | Yes | String | Sharing code. |

Response Parameters

Status code: 200

Table 4-341 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response information. |
| kdstoken | String | Temporary token. |

Example Requests

```
POST /koodrive/ose/v1/share/verify
{
  "shortUrl": "string",
```

```
"extractCode" : "string"
}
```

Example Responses

Status code: 200

OK

```
{
  "code" : "string",
  "msg" : "string",
  "kdtoken" : "string"
}
```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.15.4 Listing Files Shared with You

Function

List shared files.

URI

POST /koodrive/ose/v1/share/files

Request Parameters

Table 4-342 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|---|
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Table 4-343 Request body parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|---------|---|
| shortUrl | Yes | String | Sharing short code. |
| parentFolder | No | String | Parent directory ID. |
| pageSize | No | Integer | Number of records to be returned on each page. Default and maximum value: 100. It is possible that partial or empty result pages are returned before the end of the result list has been reached. |
| pageCursor | No | String | Current page cursor, which is obtained from nextCursor of the previous response. |
| sortType | No | Integer | Sorting type. 1 : by file name; 2 : by file size; 4 : by modification time (default). |
| sortDirection | No | Integer | Sorting order. 1 : ascending; 2 : descending (default). |
| kdstoken | No | String | Temporary token for sharing. |
| refreshCount | No | Boolean | Whether this API call is counted as a file view. |
| fileName | No | String | File name. |

Response Parameters

Status code: 200

Table 4-344 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response information. |

| Parameter | Type | Description |
|------------|--|---|
| nextCursor | String | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| link | CommonShareLink object | Public information of the access link. |
| files | Array of ShareFile objects | List of shared files. |

Table 4-345 CommonShareLink

| Parameter | Type | Description |
|------------|--|---|
| shareId | String | Sharing ID. |
| shortUrl | String | Sharing short code. |
| shareTime | String | Time when the file is shared. |
| ownerId | String | Sharer ID. |
| ownerName | String | Sharer name. |
| permission | SharePermission object | Sharing permission (supported in the future). |
| expireTime | String | Expiration time. |
| status | Integer | Sharing status. 0 : determined based on the expiration time. 1 : The file has been deleted. 2 : expired. |

Table 4-346 SharePermission

| Parameter | Type | Description |
|-----------|---------|----------------------|
| preview | Boolean | Preview permission. |
| edit | Boolean | Editing permission. |
| download | Boolean | Download permission. |

Table 4-347 ShareFile

| Parameter | Type | Description |
|-----------|--------|-------------|
| id | String | *File ID. |

| Parameter | Type | Description |
|--------------|------------------|---|
| fileName | String | *File name, which contains up to 160 bytes. |
| fileType | String | File type, which is input externally. |
| mimeType | String | *Content type. |
| parentFolder | Array of strings | List of parent directory IDs. Currently, only the first ID is used. |
| fileSuffix | String | File name extension, which is the last character string of fullFileExtension . |
| size | Integer | File size. |
| containers | Array of strings | Space ID. |
| createdTime | String | File creation time. |
| editedTime | String | File modification time. |

Example Requests

POST /koodrive/ose/v1/share/files

```
{
  "shortUrl" : "string",
  "parentFolder" : "string",
  "pageSize" : 0,
  "pageCursor" : "string",
  "sortType" : 0,
  "sortDirection" : 0,
  "kdstoken" : "string",
  "refreshCount" : true,
  "fileName" : "string"
}
```

Example Responses

Status code: 200

OK

```
{
  "code" : "string",
  "msg" : "string",
  "nextCursor" : "string",
  "link" : {
    "shareId" : "string",
    "shortUrl" : "string",
    "shareTime" : "2024-06-03T02:23:40.607Z",
    "ownerId" : "string",
    "ownerName" : "string",
    "permission" : {
      "preview" : true,
      "edit" : true,
      "download" : true
    }
  },
  "expireTime" : "2024-06-03T02:23:40.607Z",
  "status" : 0
}
```

```

},
"files" : [ {
  "id" : "string",
  "fileName" : "string",
  "fileType" : "string",
  "mimeType" : "string",
  "parentFolder" : [ "string" ],
  "fileSuffix" : "string",
  "size" : 0,
  "containers" : [ "string" ],
  "createdTime" : "2024-06-03T02:23:40.607Z",
  "editedTime" : "2024-06-03T02:23:40.607Z"
} ]
}

```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.15.5 Downloading a File

Function

Download a file.

URI

POST /koodrive/ose/v1/share/download

Request Parameters

Table 4-348 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Table 4-349 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|------------------------------|
| shareId | Yes | String | Sharing ID. |
| fileId | Yes | String | File ID. |
| kdstoken | Yes | String | Temporary token for sharing. |

Response Parameters

Status code: 200

Table 4-350 Response body parameters

| Parameter | Type | Description |
|-------------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response information. |
| downloadUrl | String | Download link. |

Example Requests

```
POST /koodrive/ose/v1/share/download
```

```
{  
  "shareId" : "string",  
  "fileId" : "string",  
  "kdstoken" : "string"  
}
```

Example Responses

Status code: 200

OK

```
{  
  "code" : "string",  
  "msg" : "string",  
  "downloadUrl" : "string"  
}
```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.15.6 Creating an Asynchronous Sharing Task

Function

Create an asynchronous sharing task.

URI

POST /koodrive/ose/v1/share/tasks

Request Parameters

Table 4-351 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Table 4-352 Request body parameters

| Parameter | Mandatory | Type | Description |
|--------------|-----------|------------------------|--|
| taskType | Yes | Integer | Batch operation task type. 1 : download; 2 : dump. |
| containerId | Yes | String | Space where the file is located. |
| fileIds | Yes | Array of strings | File ID list. |
| targetFileId | No | FileInfo object | File ID information. |

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|--|
| zipName | No | String | Compressed package name, which is the same as that of the package created for download in File Management. |
| shareId | Yes | String | Sharing ID. |
| kdstoken | No | String | Temporary token for sharing. |

Table 4-353 FileIdInfo

| Parameter | Mandatory | Type | Description |
|-------------|-----------|--------|-------------|
| fileId | Yes | String | File ID. |
| containerId | Yes | String | Space ID. |

Response Parameters

Status code: 200

Table 4-354 Response body parameters

| Parameter | Type | Description |
|-----------|--------|-----------------------|
| code | String | Response code. |
| msg | String | Response information. |
| taskId | String | Task ID. |

Example Requests

POST /koodrive/ose/v1/share/tasks

```
{
  "taskType" : 0,
  "containerId" : "string",
  "fileIds" : [ "string" ],
  "targetFileId" : {
    "fileId" : "string",
    "containerId" : "string"
  },
  "zipName" : "string",
  "shareId" : "string",
  "kdstoken" : "string"
}
```

Example Responses

Status code: 200

OK

```
{
  "code" : "string",
  "msg" : "string",
  "taskId" : "string"
}
```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.15.7 Querying an Asynchronous Task

Function

Query details about an asynchronous task.

URI

POST /koodrive/ose/v1/share/taskDetail

Request Parameters

Table 4-355 Request header parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer+{access_token} . |
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

Table 4-356 Request body parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|-------------|
| taskId | Yes | String | Task ID. |
| shareId | Yes | String | Sharing ID. |
| kdtoken | No | String | token |

Response Parameters

Status code: 200

Table 4-357 Response body parameters

| Parameter | Type | Description |
|-----------|---------------------------------|--------------------------------|
| code | String | Response code. |
| msg | String | Response information. |
| taskInfo | TaskInfo object | Asynchronous task information. |

Table 4-358 TaskInfo

| Parameter | Type | Description |
|----------------|---------|---|
| userId | String | User ID. |
| taskId | String | Task ID. |
| taskType | Integer | Task type. |
| taskStatus | Integer | Task status. 0 : to be processed; 1 : being processed; 2 : completed; 3 : canceled. |
| taskResultCode | Integer | Task result. 1 : all succeeded; 2 : partially failed; 3 : all failed. |
| resultCode | Integer | Task content processing result. |
| createTime | String | Task creation time. The value is a 14-digit timestamp in yyyyMMddHHmmss format. |
| startTime | String | Task start time. The value is a 14-digit timestamp in yyyyMMddHHmmss format. |
| endTime | String | Task end time. The value is a 14-digit timestamp in yyyyMMddHHmmss format. |
| progress | Integer | Task progress, in percentage. For example, if the progress is 70%, the returned value is 70 . |

| Parameter | Type | Description |
|-------------|--------|--|
| downloadUrl | String | Download link of the compressed package. |

Example Requests

POST /koodrive/ose/v1/share/taskDetail

```
{
  "taskId" : "string",
  "shareId" : "string",
  "kdstoken" : "string"
}
```

Example Responses

Status code: 200

OK

```
{
  "code" : "string",
  "msg" : "string",
  "taskInfo" : {
    "userId" : "string",
    "taskId" : "string",
    "taskType" : 0,
    "taskStatus" : 0,
    "taskResultCode" : 0,
    "resultCode" : 0,
    "createTime" : "string",
    "startTime" : "string",
    "endTime" : "string",
    "progress" : 0,
    "downloadUrl" : "string"
  }
}
```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.16 Collaboration Portal

4.16.1 Listing Related Files

Function

List files related to you.

URI

GET /koodrive/ose/v1/related

Table 4-359 Query Parameters

| Parameter | Mandatory | Type | Description |
|---------------|-----------|---------|---|
| pageSize | No | Integer | Number of records to be returned on each page. Default and maximum value: 100. It is possible that partial or empty result pages are returned before the end of the result list has been reached. Maximum: 100 |
| pageCursor | No | String | Current page cursor, which is obtained from nextCursor of the previous response. |
| sortType | No | Integer | Sorting type. 1 : by operation time (default). |
| sortDirection | No | Integer | Sorting order. 1 : ascending; 2 : descending (default). |
| displayName | No | String | Fuzzy match by display name is supported. |
| relatedType | No | String | Related file type. 0 : all; 1 : shared with you. If this parameter is null or set to 0 , all types are queried. |

Request Parameters

Table 4-360 Request header parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|---|
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|---|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer + <i>{access_token}</i> . |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-361 Response body parameters

| Parameter | Type | Description |
|------------------|--|---|
| code | String | Response code. |
| msg | String | Response information. |
| nextCursor | String | Pagination cursor. If the cursor does not exist, the last record has been returned. |
| relatedToMembers | Array of RelatedToMeRecord objects | Sharing link list. |
| total | Long | Total number of records. |

Table 4-362 RelatedToMeRecord

| Parameter | Type | Description |
|-----------|--------|----------------|
| operator | String | Operator name. |

| Parameter | Type | Description |
|-------------|---|--|
| operateType | Integer | Operation type. 1 : sharing. |
| operateTime | String | Operation time. |
| id | String | Record ID. If the operation type is sharing, the value is the sharing ID. |
| displayName | String | Display name. |
| files | Array of FileInfo objects | |
| expireTime | String | Expiration time. |
| status | Integer | 0 : determined based on the expiration time. 1 : The file has been deleted. 2 : The space has expired (the space has been disabled or deleted or you do not have the space permission). |
| operatorId | String | Operator ID. |
| containerId | String | Space ID. |
| tenantId | String | Tenant ID. |

Table 4-363 FileInfo

| Parameter | Type | Description |
|---------------|--|---|
| id | String | File ID. |
| size | String | File size. |
| fileType | String | File type. |
| downloadLinks | Array of DownloadLinks objects | Required by the image type (when fileType is set to 15). |
| recycled | Boolean | Whether the file is in the recycle bin. |

Table 4-364 DownloadLink

| Parameter | Type | Description |
|--------------|--------|---|
| usage | String | Default usage: content or thumbnail . This parameter is customizable. |
| downloadLink | String | Attachment download link. |

Example Requests

Lists files related to you.

```
GET /koodrive/ose/v1/related?
sortType=1&sortDirection=2&pageSize=2&pageCursor=&displayName=&relatedType=1

{
  "total": 1,
  "relatedToMeInfos": [ {
    "id": "1427677119873431808",
    "operator": "zujian1",
    "operatorId": "1395664261493231745",
    "operateType": 1,
    "operateTime": "2024-05-23T11:39:35.000Z",
    "displayName": "Content Not Reviewed.docx",
    "files": [ {
      "id": "Fv54zG8ha44HX2XRlrQIM76zD4KAN2uOB",
      "size": 50383,
      "fileType": "26",
      "recycled": false,
      "downloadLinks": [ {
        "usage": "content",
        "downloadLink": "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/
6957916206ce4407ac9436567b14d719086?response-content-disposition=attachment%3B%20filename%2A
%3DUTF-8%27%27%25E5%2586%2585%25E5%25AE%25B9%25E6%259C%25AA%25E5%25AE
%25A1%25E6%25A0%25B8.docx&X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-
Date=20240523T113937Z&X-Amz-SignedHeaders=host&X-Amz-Expires=3600&X-Amz-
Credential=MKRISPBJAJWFHNB5WLB%2F20240523%2Fcidc-rp-2006%2Fs3%2Faws4_request&X-Amz-
Signature=e130a202a80157e63583bd7597452eb1d30a70c610db86be68717541114e2bd0"
      }, {
        "usage": "thumbnail",
        "downloadLink": "https://b10-obs-ykj-uat-01.obs.cidc-rp-2006.joint.cmecloud.cn/
6957916206ce4407ac9436567b14d719086?x-image-process=image%2Fresize%2Cm_lfit
%2Ch_128%2Cw_128&response-content-disposition=attachment%3B%20filename%2A
%3DUTF-8%27%27%25E5%2586%2585%25E5%25AE%25B9%25E6%259C%25AA%25E5%25AE
%25A1%25E6%25A0%25B8.docx&X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-
Date=20240523T113937Z&X-Amz-SignedHeaders=host&X-Amz-Expires=3600&X-Amz-
Credential=MKRISPBJAJWFHNB5WLB%2F20240523%2Fcidc-rp-2006%2Fs3%2Faws4_request&X-Amz-
Signature=e78515818612dbb024bf14300bd63bbb340e7f7476b988143089ce6d92d6d9f9"
      } ]
    } ],
    "expireTime": "2024-05-30T11:39:35.000Z",
    "status": 0,
    "containerId": "IAAFyRNd07vFgAAA1395504262720721025",
    "tenantId": "d5ac574bd2934a69baa4f23c55daa8d4"
  } ],
  "code": 0,
  "msg": "OK"
}
```

Example Responses

Status code: 200

OK

```
{
  "code": "string",
  "msg": "string",
  "nextCursor": "string",
  "relatedToMeInfos": [ {
    "operator": "string",
    "operateType": 0,
    "operateTime": "2024-06-03T02:25:41.085Z",
    "id": "string",
    "displayName": "string",
    "files": [ {
```

```

    "id" : "string",
    "size" : "string",
    "fileType" : "string",
    "downloadLinks" : [ {
      "usage" : "string",
      "downloadLink" : "string"
    } ],
    "recycled" : true
  } ],
  "expireTime" : "2024-06-03T02:25:41.085Z",
  "status" : 0,
  "operatorId" : "string",
  "containerId" : "string",
  "tenantId" : "string"
} ],
"total" : 0
}

```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

4.16.2 Listing Recently Visited Files

Function

List files that you recently visited.

URI

GET /koodrive/ose/v1/access

Request Parameters

Table 4-365 Request header parameters

| Parameter | Mandatory | Type | Description |
|-----------|-----------|--------|---|
| X-Traceid | No | String | Service trace ID, which contains 58 bits. |

| Parameter | Mandatory | Type | Description |
|---------------|-----------|--------|--|
| Authorization | Yes | String | Access token. Token authentication is used to call KooDrive APIs. A token indicates the permission. When an API is called, the token is added to the request header to obtain the operation permission. For details about how to obtain an access token, see the corresponding developer guide. The format is Bearer +{access_token}. |
| language | No | String | Language code, which complies with the internationalization specifications. For example, en-US indicates English (United States). English (United States) is used by default. |

Response Parameters

Status code: 200

Table 4-366 Response body parameters

| Parameter | Type | Description |
|-----------|--|---------------------------------|
| code | String | Response code. |
| msg | String | Response information. |
| list | Array of RecentlyAccess objects | List of recently visited files. |

Table 4-367 RecentlyAccess

| Parameter | Type | Description |
|-------------|------------------------------|---|
| operateTime | String | Operation time. |
| operType | Integer | Operation type. 1 : viewing; 2 : editing. |
| file | AccessFileInfo object | Basic file information. |

| Parameter | Type | Description |
|-----------|---------|--|
| status | Integer | Status. 1 : The file has been deleted. 2 : The space has expired (the space has been disabled or deleted or you do not have the space permission). |

Table 4-368 AccessiFileInfo

| Parameter | Type | Description |
|-----------------|---------|---|
| id | String | File ID. |
| containerId | String | Space ID. |
| name | String | File name. |
| collaboratorId | String | Co-author ID. |
| collaborator | String | Co-author name. |
| collaborateTime | String | Collaboration time. |
| collaborateType | String | Collaboration type. 2 : editing; 3 : sharing; 4 : saving to the individual space. |
| fileType | String | File type. /** Folder / FOLDER = "10", /** Image / PICTURE = "15", /** Video / VIDEO = "20", /** Word file / WORD = "26", /** Excel file / EXCEL = "27", /** PowerPoint file / PPT = "28", /** Audio / AUDIO = "30", /** Compressed file / ARCHIVE = "35", /** Application / APPLICATION = "40", /** Other */ OTHER = "45", |
| owner | String | File owner. |
| containerName | String | For an individual space, this parameter is null. For a department space, the value is the department name. |
| containerType | Integer | 0 : department space; 1 : individual space; 2 : group space. |
| favorite | Boolean | true : The file is added to favorites. false : The file is not added to favorites. |
| teamId | String | For an individual space, this parameter is null. For a department space, the value is the department ID. For a group space, the value is the group ID. |

Example Requests

```
GET /koodrive/ose/v1/access
```

Example Responses

Status code: 200

OK

```
{
  "code" : "string",
  "msg" : "string",
  "list" : [ {
    "operateTime" : "2024-06-03T02:26:45.897Z",
    "operType" : 0,
    "file" : {
      "id" : "string",
      "containerId" : "string",
      "name" : "string",
      "collaboratorId" : "string",
      "collaborator" : "string",
      "collaborateTime" : "2024-06-03T02:26:45.897Z",
      "collaborateType" : "string",
      "fileType" : "string",
      "owner" : "string",
      "containerName" : "string",
      "containerType" : 0,
      "favorite" : true,
      "teamId" : "string"
    },
    "status" : 0
  } ]
}
```

Status Codes

| Status Code | Description |
|-------------|-------------|
| 200 | OK |

5 Appendixes

5.1 Status Codes

[Table 5-1](#) describes common status codes.

Table 5-1 Status codes

| Status Code | Message | Description |
|-------------|-----------------------|---|
| 200 | OK | The request has succeeded. |
| 400 | Bad Request | Authentication failed. |
| 401 | Unauthorized | Unauthorized. |
| 500 | Internal Server Error | The server encountered an unexpected condition that prevented it from fulfilling the request. |

5.2 Error Codes

Table 5-2 Error Codes

| Category | Error Codes | Error Message | Description | Measure |
|--------------|-------------|-------------------|--------------------------------|--------------------------------------|
| Success | 0 | SUCCESS | Successful. | N/A |
| Client error | 13000101 | Bad Request | Request error. | Check and correct input parameters. |
| | 13000102 | PARAMETER_INVALID | Parameter verification failed. | Check and correct output parameters. |

| Category | Error Codes | Error Message | Description | Measure |
|------------------------|-------------|------------------------------------|--|--|
| Server error - general | 13000201 | INNER_INVOKE_FAILURE | Internal calling error. | Rectify the fault based on the error description. |
| Server error - service | 13000301 | CONTAINER_NOT_EXIST_OR_STATE_ERROR | Space not found or its status is abnormal. | Pass the ID of an existing space. |
| | 13000302 | FILE_NOT_IN_SPECIFIED_CONTAINER | File is not in the specified space. | Pass the ID of a file under the space specified by the space ID. |
| | 13000401 | NOT_EXIST_UPLOAD_TASK | Upload task not found. | Create the upload task again. |
| | 13000402 | FILE_COMPLETE_CHECK_FAILURE | File integrity verification failed. | Upload a complete file. |
| | 13000403 | CHANGE_FILE_STATE_FAILURE | Change file status failed. | Call the API again. |

6 Change History

| Released On | Description |
|-------------|---|
| 2024-07-30 | This issue is the first official release. |