

# Simple Message Notification

## API Reference

**Issue** 01  
**Date** 2022-07-08



**Copyright © Huawei Technologies Co., Ltd. 2024. All rights reserved.**

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

## **Trademarks and Permissions**



HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

## **Notice**

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

# Security Declaration

## Vulnerability

Huawei's regulations on product vulnerability management are subject to the *Vul. Response Process*. For details about this process, visit the following web page:

<https://www.huawei.com/en/psirt/vul-response-process>

For vulnerability information, enterprise customers can visit the following web page:

<https://securitybulletin.huawei.com/enterprise/en/security-advisory>

---

# Contents

---

<b>1 Before You Start.....</b>	<b>1</b>
1.1 Overview.....	1
1.2 API Calling.....	1
1.3 Endpoints.....	1
1.4 Notes and Constraints.....	1
1.5 Concepts.....	2
<b>2 API Overview.....</b>	<b>4</b>
<b>3 Calling APIs.....</b>	<b>5</b>
3.1 Making an API Request.....	5
3.2 Authentication.....	9
3.3 Response.....	10
<b>4 Getting Started.....</b>	<b>13</b>
<b>5 APIs.....</b>	<b>15</b>
5.1 Topics.....	15
5.1.1 Querying Topics.....	15
5.1.2 Creating a Topic.....	20
5.1.3 Querying Details About a Topic.....	23
5.1.4 Updating a Topic.....	27
5.1.5 Deleting a Topic.....	30
5.1.6 Querying a Topic Policy.....	33
5.1.7 Deleting All Topic Policies.....	39
5.1.8 Updating a Topic Policy.....	41
5.1.9 Deleting a Specified Topic Policy.....	45
5.2 Subscriptions.....	48
5.2.1 Querying Subscriptions.....	48
5.2.2 Querying Subscriptions of a Specified Topic.....	54
5.2.3 Adding a Subscription.....	59
5.2.4 Deleting a Subscription.....	66
5.2.5 Updating a Subscriber.....	69
5.3 Templates.....	72
5.3.1 Querying Message Templates.....	72
5.3.2 Creating a Message Template.....	77

5.3.3 Querying Details About a Message Template.....	81
5.3.4 Modifying a Message Template.....	83
5.3.5 Deleting a Message Template.....	86
5.4 Message Publishing.....	89
5.4.1 Publishing a Message.....	89
5.5 Tags.....	98
5.5.1 Querying Resources by Tag.....	98
5.5.2 Adding or Deleting Resource Tags in Batches.....	107
5.5.3 Querying Resource Tags.....	111
5.5.4 Adding a Resource Tag.....	115
5.5.5 Querying Project Tags.....	119
5.5.6 Deleting a Resource Tag.....	122
5.6 Version Querying.....	125
5.6.1 Querying All SMN API Versions.....	125
5.6.2 Querying the SMN API v2 Version.....	129
<b>6 Public Parameters.....</b>	<b>133</b>
6.1 General Request Return Code.....	133
6.1.1 Exception Response.....	133
6.1.2 Returned Value.....	133
6.2 Error Codes.....	134
6.3 Obtaining a Project ID.....	151
<b>A Appendix.....</b>	<b>153</b>
A.1 Topic Attribute List.....	153
<b>B Change History.....</b>	<b>154</b>

# 1 Before You Start

---

## 1.1 Overview

Welcome to the *Simple Message Notification API Reference*. Simple Message Notification (SMN) is a reliable and flexible large-scale message notification service. It enables you to efficiently send messages to phone numbers, email addresses and HTTP/HTTPS servers and connect cloud services through notifications, reducing system complexity.

This document describes how to use application programming interfaces (APIs) to perform operations in SMN, such as creating, querying, deleting, and updating resources. For details about all supported operations, see [API Overview](#).

Before you use SMN by calling APIs, please get yourself familiar with basic SMN concepts. For details, see "Service Overview" in the *Simple Message Notification User Guide*.

## 1.2 API Calling

SMN supports Representational State Transfer (REST) APIs, allowing you to call APIs using HTTPS. For details, see [Calling APIs](#).

## 1.3 Endpoints

An endpoint is the **request address** for calling an API. Endpoints vary depending on services and regions. For the endpoints of all services, see [Regions and Endpoints](#).

## 1.4 Notes and Constraints

- The number of SMN resources you can create is determined by quota. To view or increase the quota, see "Quota Adjustment" in the *Simple Message Notification User Guide*.
- For more details, see the constraints described in each API.

## 1.5 Concepts

- **Account**

An account is created upon successful registration. The account has full access permissions for all of its cloud services and resources. It can be used to reset user passwords and grant user permissions. The account is a payment entity, which should not be used directly to perform routine management. For security purposes, create Identity and Access Management (IAM) users and grant them permissions for routine management.
- **User**

An IAM user is created by an account in IAM to use cloud services. Each IAM user has its own identity credentials (password and access keys).


API authentication requires information such as the account name, username, and password.
- **Region**

A region is a geographic area in which cloud resources are deployed. Availability zones (AZs) in the same region can communicate with each other over an intranet, while AZs in different regions are isolated from each other. Deploying cloud resources in different regions can better suit certain user requirements or comply with local laws or regulations.
- **AZ**

An AZ comprises of one or more physical data centers equipped with independent ventilation, fire, water, and electricity facilities. Computing, network, storage, and other resources in an AZ are logically divided into multiple clusters. AZs within a region are interconnected using high-speed optical fibers to allow you to build cross-AZ high-availability systems.
- **Project**

A project corresponds to a region. Default projects are defined to group and physically isolate resources (including computing, storage, and network resources) across regions. Users can be granted permissions in a default project to access all resources under their accounts in the region associated with the project. If you need more refined access control, create subprojects under a default project and create resources in subprojects. Then you can assign users the permissions required to access only the resources in the specific subprojects.

**Figure 1-1** Project isolation model





# 2 API Overview

By calling SMN APIs, you can use all functions provided by SMN, for example, creating a topic and adding a subscription.

**Table 2-1** API description

Category	Description
Topic operations	Create, update, and delete a topic.
Subscription operations	Query the subscription list, add and delete subscriptions.
Template operations	Create, modify, and delete message templates.
Message publishing	Publish a message, publishing a probing message, and obtain the HTTP probing result.
Resource tag operations	Query resources by tag, add resource tags, and query tags.
Version querying	Query SMN API versions and information about the SMN API v2 version.

# 3 Calling APIs

## 3.1 Making an API Request

This section describes the structure of a REST API request, and uses the IAM API for obtaining a user token as an example to demonstrate how to call an API. The obtained token can then be used to authenticate the calling of other APIs.

### Request URI

A request URI is in the following format:

**{URI-scheme}://{Endpoint}/{resource-path}?{query-string}**

Although a request URI is included in the request header, most programming languages or frameworks require the request URI to be transmitted separately.

**Table 3-1** URI parameter description

Parameter	Description
URI-scheme	Protocol used to transmit requests. All APIs use HTTPS.
Endpoint	Domain name or IP address of the server bearing the REST service. The endpoint varies between services in different regions. It can be obtained from <a href="#">Regions and Endpoints</a> .
resource-path	Access path of an API for performing a specified operation. Obtain the path from the URI of an API. For example, the <b>resource-path</b> of the API used to obtain a user token is <b>/v3/auth/tokens</b> .
query-string	Query parameter, which is optional. Ensure that a question mark (?) is included before each query parameter that is in the format of <i>Parameter name=Parameter value</i> . For example, <b>?limit=10</b> indicates that a maximum of 10 data records will be displayed.

 NOTE

To simplify the URI display in this document, each API is provided only with a **resource-path** and a request method. The **URI-scheme** of all APIs is **HTTPS**, and the endpoints of all APIs in the same region are identical.

## Request Methods

The HTTP protocol defines the following request methods that can be used to send a request to the server.

**Table 3-2** HTTP methods

Method	Description
GET	Requests the server to return specified resources.
PUT	Requests the server to update specified resources.
POST	Requests the server to add resources or perform special operations.
DELETE	Requests the server to delete specified resources, for example, an object.
HEAD	Same as GET except that the server must return only the response header.
PATCH	Requests the server to update partial content of a specified resource. If the resource does not exist, a new resource will be created.

For example, in the case of the API used to obtain a user token, the request method is **POST**. The request is as follows:

```
POST https://{{endpoint}}/v3/auth/tokens
```

## Request Header

You can also add additional header fields to a request, such as the fields required by a specified URI or HTTP method. For example, to request for the authentication information, add **Content-Type**, which specifies the request body type.

Common request header fields are as follows.

**Table 3-3** Common request header fields

Parameter	Description	Mandatory	Example Value
Host	Specifies the server domain name and port number of the resources being requested. The value can be obtained from the URL of the service API. The value is in the format of <i>Hostname:Port number</i> . If the port number is not specified, the default port is used. The default port number for <b>https</b> is <b>443</b> .	No This field is mandatory for AK/SK authentication.	code.test.com or code.test.com:443
Content-Type	Specifies the type (or format) of the message body. The default value <b>application/json</b> is recommended. Other values of this field will be provided for specific APIs if any.	Yes	application/json
Content-Length	Specifies the length of the request body. The unit is byte.	No	3495
X-Project-Id	Specifies the project ID. Obtain the project ID by following the instructions in <a href="#">Obtaining a Project ID</a> .	No This field is mandatory for requests that use AK/SK authentication in the Dedicated Cloud (DeC) scenario or multi-project scenario.	e9993fc787d94b6c886cbaa340f9c0f4

Parameter	Description	Mandatory	Example Value
X-Auth-Token	<p>Specifies the user token. It is a response to the API for obtaining a user token (This is the only API that does not require authentication).</p> <p>After the request is processed, the value of <b>X-Subject-Token</b> in the response header is the token value.</p>	<p>No</p> <p>This field is mandatory for token authentication.</p>	<p>The following is part of an example token:</p> <p>MIIPAgYJKoZlhvcNAQcCo...ggg1BBIINPXsidG9rZ</p>

 **NOTE**

In addition to supporting authentication using tokens, APIs support authentication using AK/SK, which uses SDKs to sign a request. During the signature, the **Authorization** (signature authentication) and **X-Sdk-Date** (time when a request is sent) headers are automatically added in the request.

For more details, see "Authentication Using AK/SK" in [Authentication](#).

The API used to obtain a user token does not require authentication. Therefore, only the **Content-Type** field needs to be added to requests for calling the API. An example of such requests is as follows:

```
POST https://{{endpoint}}/v3/auth/tokens
Content-Type: application/json
```

### (Optional) Request Body

This part is optional. The body of a request is often sent in a structured format (for example, JSON or XML) as specified in the **Content-Type** header field. The request body transfers content except the request header.

The request body varies between APIs. Some APIs do not require the request body, such as the APIs requested using the GET and DELETE methods.

In the case of the API used to obtain a user token, the request parameters and parameter description can be obtained from the API request. The following provides an example request with a body included. Replace *username*, *domainname*, *\$ADMIN\_PASS* (login password), and *xxxxxxxxxxxxxxxxxxxx* (project name) with the actual values. Obtain a project name from [Regions and Endpoints](#).

 **NOTE**

The **scope** parameter specifies where a token takes effect. You can set **scope** to an account or a project under an account. In the following example, the token takes effect only for the resources in a specified project. For more information about this API, see "Obtaining a User Token".

```
POST https://{{endpoint}}/v3/auth/tokens
Content-Type: application/json
```

```
{
  "auth": {
    "identity": {
      "methods": [
        "password"
      ],
      "password": {
        "user": {
          "name": "username",
          "password": "$ADMIN_PASS", //You are advised to store it in ciphertext in the
configuration file or an environment variable and decrypt it when needed to ensure security.
          "domain": {
            "name": "domainname"
          }
        }
      }
    },
    "scope": {
      "project": {
        "name": "xxxxxxxxxxxxxxxxxxxxxx"
      }
    }
  }
}
```

If all data required for the API request is available, you can send the request to call the API through [curl](#), [Postman](#), or coding. In the response to the API used to obtain a user token, **X-Subject-Token** is the desired user token. This token can then be used to authenticate the calling of other APIs.

## 3.2 Authentication

Requests for calling an API can be authenticated using either of the following methods:

- Token authentication: Requests are authenticated using tokens.
- AK/SK authentication: Requests are encrypted using AK/SK pairs. AK/SK authentication is recommended because it is more secure than token authentication.

### Token Authentication

#### NOTE

The validity period of a token is 24 hours. When using a token for authentication, cache it to prevent frequently calling the IAM API used to obtain a user token.

A token specifies temporary permissions in a computer system. During API authentication using a token, the token is added to requests to get permissions for calling the API. You can obtain a token by calling the Obtaining User Token API.

IMS is a project-level service. When you call the API, set **auth.scope** in the request body to **project**.

```
{
  "auth": {
    "identity": {
      "methods": [
        "password"
      ],
      "password": {
```

```
    "user": {
      "name": "username", // IAM user name
      "password": $ADMIN_PASS, //IAM user password. You are advised to store it in ciphertext in
the configuration file or an environment variable and decrypt it when needed to ensure security.
      "domain": {
        "name": "domainname" // Name of the account to which the IAM user belongs
      }
    }
  },
  "scope": {
    "project": {
      "name": "xxxxxxxx" // Project name
    }
  }
}
```

After a token is obtained, the **X-Auth-Token** header field must be added to requests to specify the token when calling other APIs. For example, if the token is **ABCDEFJ....**, **X-Auth-Token: ABCDEFJ....** can be added to a request as follows:

```
POST https://{{endpoint}}/v3/auth/projects
Content-Type: application/json
X-Auth-Token: ABCDEFJ....
```

## AK/SK Authentication

### NOTE

AK/SK authentication supports API requests with a body not larger than 12 MB. For API requests with a larger body, token authentication is recommended.

In AK/SK authentication, AK/SK is used to sign requests and the signature is then added to the requests for authentication.

- AK: access key ID, which is a unique identifier used in conjunction with a secret access key to sign requests cryptographically.
- SK: secret access key, which is used in conjunction with an AK to sign requests cryptographically. It identifies a request sender and prevents the request from being modified.

In AK/SK authentication, you can use an AK/SK to sign requests based on the signature algorithm or using the signing SDK. For details about how to sign requests and use the signing SDK, see [API Request Signing Guide](#).

### NOTE

The signing SDK is only used for signing requests and is different from the SDKs provided by services.

## 3.3 Response

### Status Code

After sending a request, you will receive a response, including a status code, response header, and response body.

A status code is a group of digits, ranging from 1xx to 5xx. It indicates the status of a request. For more information, see [Returned Value](#).

For example, if status code **201** is returned for calling the API used to obtain a user token, the request is successful.

## Response Header

Similar to a request, a response also has a header, for example, **Content-Type**.

**Figure 3-1** shows the response header fields for the API used to obtain a user token. The **X-Subject-Token** header field is the desired user token. This token can then be used to authenticate the calling of other APIs.

### NOTE

For security purposes, you are advised to set the token in ciphertext in configuration files or environment variables and decrypt it when using it.

**Figure 3-1** Header fields of the response to the request for obtaining a user token



## (Optional) Response Body

The body of a response is often returned in a structured format (for example, JSON or XML) as specified in the **Content-Type** header field. The response body transfers content except the response header.

The following is part of the response body for the API used to obtain a user token.

```
{
  "token": {
    "expires_at": "2019-02-13T06:52:13.855000Z",
    "methods": [
      "password"
    ],
    "catalog": [
      {
        "endpoints": [
          {
            "region_id": "az-01",
            .....

```



If an error occurs during API calling, an error code and a message will be displayed. The following shows an error response body.

```
{  
  "error_msg": "The request message format is invalid.",  
  "error_code": "IMG.0001"  
}
```

In the response body, **error\_code** is an error code, and **error\_msg** provides information about the error.

# 4 Getting Started

---

## Scenarios

This topic describes how to publish a message to a topic by calling APIs.

For details about how to call APIs, see [Calling APIs](#).

### NOTE

The token obtained from IAM is valid for only 24 hours. If you want to use one token for authentication, you can cache it to avoid frequently calling the IAM API.

## Involved APIs

To use token authentication, you need to obtain a token and add **X-Auth-Token** to the request header of API calls.

- IAM API to obtain a token
- SMN API to create a topic
- SMN API to add subscriptions
- SMN API to publish messages

## Procedure

1. Obtain the token by referring to [Authentication](#).
2. Send a request **POST** `https://{SMN_Endpoint}/v2/{project_id}/notifications/topics` to create a topic.

- a. Add **X-Auth-Token** to the request header.
- b. Specify the following parameters in the request body:

```
{
  "name": "test_topic_v2", // Topic name (mandatory)
  "display_name": "test" // Display name (optional)
}
```

If the request is successful, a request ID (**request\_id**) and topic URN (**topic\_urn**) are returned.

If the request fails, an error code and error information are returned. For details, see [Error Codes](#).

3. Send a request **POST** `https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/{topic_urn}/subscriptions` to add subscriptions.

Set **topic\_urn** based on the response in [2.b](#).

- a. Add **X-Auth-Token** to the request header.
- b. Specify the following parameters in the request body:

```
{  
  "protocol": "email", // Subscription protocol (mandatory)  
  "endpoint": "xxx@xx.com", // Email address (mandatory)  
  "remark": "Subscription" // Description (optional)  
}
```

If the request is successful, a request ID (**request\_id**) and subscription URN (**subscription\_urn**) are returned.

If the request fails, an error code and error information are returned. For details, see [Error Codes](#).

 **NOTE**

You can add multiple kinds of subscriptions to a topic. For details, see [Adding a Subscription](#).

- c. The subscription endpoint receives a confirmation message and must confirm the subscription in the email.
4. Send a request **POST** [https://{SMN\\_Endpoint}/v2/{project\\_id}/notifications/topics/{topic\\_urn}/publish](https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/{topic_urn}/publish) to publish a message.

- a. Add **X-Auth-Token** to the request header.
- b. Specify the following parameters in the request body:

```
{  
  "subject": "test message v2", // Message subject, which is displayed in email messages  
  (optional)  
  "message": "Message test message v2." // Message to be published (mandatory)  
}
```

If the request is successful, a request ID (**request\_id**) and message ID (**message\_id**) are returned.

If the request fails, an error code and error information are returned. For details, see [Error Codes](#).

 **NOTE**

Only confirmed subscription endpoints can receive the message you publish.

# 5 APIs

---

## 5.1 Topics

### 5.1.1 Querying Topics

#### Function

This API is used to query topics by page. The topics are sorted by creation time in descending order. You can specify offset and limit. If no topic has been created, an empty list is returned.

#### Calling Method

For details, see [Calling APIs](#).

#### URI

GET /v2/{project\_id}/notifications/topics

**Table 5-1** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .

**Table 5-2** Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Specifies the offset. If the offset is an integer greater than 0 but less than the number of resources, all resources in excess of this offset will be queried. The default offset is 0. Default: <b>0</b>
limit	No	Integer	Specifies the maximum number of records in each query. The number ranges from 1 to 100 and is generally 10, 20, or 50. Specifies the number of resources returned on each page. The default number is 100. Default: <b>100</b>
enterprise_project_id	No	String	Specifies the enterprise project ID. The default enterprise project ID is 0. Default: <b>0</b>
name	No	String	Specifies the name of the topic to be searched for, which must be fully matched.
fuzzy_name	No	String	Specifies the name of the topic to be searched. Fuzzy matching is used.
topic_id	No	String	Specifies the topic ID for exact search.
fuzzy_display_name	No	String	Specifies the display name of the topic to be searched. Fuzzy matching is used. The display name cannot exceed 192 bytes.

## Request Parameters

**Table 5-3** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

**Status code: 200****Table 5-4** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
topic_count	Integer	Specifies the number of returned topics. No matter what offset and limit values you have set in the request, this API always returns the total number of topics in your account.
topics	Array of <a href="#">ListTopicsItem</a> objects	Specifies the topic structure array.

**Table 5-5** ListTopicsItem

Parameter	Type	Description
topic_urn	String	Specifies the resource identifier of the topic, which is unique.
name	String	Specifies the topic name.
display_name	String	Specifies the topic display name, which is presented as the name of the email sender in email messages.
push_policy	Integer	Specifies the message push policy. 0 indicates that the message sending fails and the message is cached in the queue. 1 indicates that the failed message is discarded.
enterprise_project_id	String	Specifies the enterprise project ID.

Parameter	Type	Description
topic_id	String	Specifies the topic ID.

**Status code: 400****Table 5-6** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-7** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-8** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-9** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.

Parameter	Type	Description
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Querying topics

```
GET https://{SMN_Endpoint}/v2/{project_id}/notifications/topics?offset=0&limit=100
```

```
null
```

## Example Responses

**Status code: 200**

OK

```
{
  "request_id" : "6a63a18b8bab40ffb71ebd9cb80d0085",
  "topic_count" : 1,
  "topics" : [ {
    "topic_urn" : "urn:smn:regionId:8bad8a40e0f7462f8c1676e3f93a8183:test_topic_v2",
    "display_name" : "testtest",
    "name" : "test_topic_v1",
    "push_policy" : 0,
    "enterprise_project_id" : "0",
    "topic_id" : "84698185946d44d08431aa441d8e2cf2"
  } ]
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).



## 5.1.2 Creating a Topic

### Function

This API is used to create a topic. Each user can create up to 3,000 topics. In high-concurrent scenarios, a user may create a few topics more than 3,000. The API is idempotent. It returns a successful result after creating a topic. If a topic of the same name already exists, the status code is 200. Otherwise, the status code is 201.

### Calling Method

For details, see [Calling APIs](#).

### URI

POST /v2/{project\_id}/notifications/topics

**Table 5-10** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .

### Request Parameters

**Table 5-11** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

**Table 5-12** Request body parameters

Parameter	Mandatory	Type	Description
name	Yes	String	Specifies the topic name. Enter 1 to 255 characters. Only letters, digits, hyphens (-), and underscores (_) are allowed. The topic name must start with a letter or digit. Minimum: <b>1</b> Maximum: <b>255</b>
display_name	Yes	String	Specifies the topic display name, which is presented as the name of the email sender in email messages. The display name cannot exceed 192 bytes. display_name is left blank by default. Minimum: <b>1</b> Maximum: <b>192</b>
enterprise_project_id	No	String	Specifies the enterprise project ID. It is required only when the enterprise project function is enabled. Default: <b>0</b>

## Response Parameters

**Status code: 201**

**Table 5-13** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
topic_urn	String	Specifies the resource identifier of the topic, which is unique. To obtain the resource identifier, see [Querying Topics].

**Status code: 400**

**Table 5-14** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-15** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-16** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-17** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Creating a topic with the name of **test\_topic\_v2** and display name of **testtest**

```
POST https://{SMN_Endpoint}/v2/{project_id}/notifications/topics
{
  "name" : "test_topic_v2",
  "display_name" : "testtest"
}
```

## Example Responses

**Status code: 201**

OK

```
{
  "request_id" : "6a63a18b8bab40ffb71ebd9cb80d0085",
  "topic_urn" : "urn:smn:regionId:f96188c7ccaf4ffba0c9aa149ab2bd57:test_topic_v2"
}
```

## Status Codes

Status Code	Description
201	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.1.3 Querying Details About a Topic

### Function

This API is used to query details about a topic.

### Calling Method

For details, see [Calling APIs](#).

### URI

GET /v2/{project\_id}/notifications/topics/{topic\_urn}

**Table 5-18** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
topic_urn	Yes	String	Specifies the resource identifier of the topic, which is unique. To obtain the resource identifier, see <a href="#">Querying Topics</a> .

## Request Parameters

**Table 5-19** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

**Status code: 200**

**Table 5-20** Response body parameters

Parameter	Type	Description
update_time	String	Specifies when the topic was updated. The UTC time is in YYYY-MM-DDTHH:MM:SSZ format.
push_policy	Integer	Specifies the message push policy. 0 indicates that the message sending fails and the message is cached in the queue. 1 indicates that the failed message is discarded.
create_time	String	Specifies when the topic is created. The UTC time is in YYYY-MM-DDTHH:MM:SSZ format.
name	String	Specifies the topic name.
topic_urn	String	It is the unique identifier of a topic. To obtain the resource identifier, see <a href="#">Querying Topics</a> .

Parameter	Type	Description
display_name	String	Specifies the topic display name, which is presented as the name of the email sender in email messages.
request_id	String	Specifies the request ID, which is unique.
enterprise_project_id	String	Specifies the enterprise project ID.
topic_id	String	Specifies the topic ID.

**Status code: 400**

**Table 5-21** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403**

**Table 5-22** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404**

**Table 5-23** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-24** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Example Requests**

Querying details about a topic

```
GET https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/  
urn:smn:regionId:8bad8a40e0f7462f8c1676e3f93a8183:test_create_topic_v2  
  
null
```

**Example Responses****Status code: 200**

OK

```
{  
  "update_time" : "2016-08-01T02:16:38Z",  
  "push_policy" : 0,  
  "create_time" : "2016-08-01T02:16:38Z",  
  "name" : "test_create_topic_v2",  
  "topic_urn" : "urn:smn:regionId:8bad8a40e0f7462f8c1676e3f93a8183:test_create_topic_v2",  
  "display_name" : "test create topic v2",  
  "request_id" : "6837531fd3f54550927b930180a706bf",  
  "enterprise_project_id" : "0",  
  "topic_id" : "84698185946d44d08431aa441d8e2cf2"  
}
```

**Status Codes**

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

**Error Codes**

See [Error Codes](#).

## 5.1.4 Updating a Topic

### Function

This API is used to update the topic display name.

### Calling Method

For details, see [Calling APIs](#).

### URI

PUT /v2/{project\_id}/notifications/topics/{topic\_urn}

**Table 5-25** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
topic_urn	Yes	String	Specifies the resource identifier of the topic, which is unique. To obtain the resource identifier, see <a href="#">Querying Topics</a> .

### Request Parameters

**Table 5-26** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.



**Table 5-27** Request body parameters

Parameter	Mandatory	Type	Description
display_name	Yes	String	Specifies the topic display name, which is presented as the name of the email sender in email messages. The display name cannot exceed 192 bytes. Minimum: <b>1</b> Maximum: <b>192</b>

## Response Parameters

**Status code: 200**

**Table 5-28** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.

**Status code: 400**

**Table 5-29** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403**

**Table 5-30** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404**

**Table 5-31** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500**

**Table 5-32** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Modifying the display name of the topic named **test\_topic\_v2** to **testtest222**

```
PUT https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/urn:smn:regionId:f96188c7ccaf4ffba0c9aa149ab2bd57:test_topic_v2
```

```
{
  "display_name" : "testtest222"
}
```

## Example Responses

**Status code: 200**

OK

```
{
  "request_id" : "6a63a18b8bab40ffb71ebd9cb80d0085"
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request

Status Code	Description
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.1.5 Deleting a Topic

### Function

This API is used to delete a topic.

### Calling Method

For details, see [Calling APIs](#).

### URI

DELETE /v2/{project\_id}/notifications/topics/{topic\_urn}

**Table 5-33** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
topic_urn	Yes	String	Specifies the resource identifier of the topic, which is unique. To obtain the resource identifier, see <a href="#">Querying Topics</a> .

## Request Parameters

**Table 5-34** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

**Status code: 200****Table 5-35** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.

**Status code: 400****Table 5-36** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-37** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404**

**Table 5-38** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-39** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Deleting a topic

```
DELETE https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/  
urn:smn:regionId:f96188c7ccaf4ffba0c9aa149ab2bd57:test_topic_v2  
  
null
```

## Example Responses

**Status code: 200**

OK

```
{  
  "request_id" : "6a63a18b8bab40ffb71ebd9cb80d0085"  
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found

Status Code	Description
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.1.6 Querying a Topic Policy

### Function

This API is used to query a topic policy.

### Calling Method

For details, see [Calling APIs](#).

### URI

GET /v2/{project\_id}/notifications/topics/{topic\_urn}/attributes

**Table 5-40** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
topic_urn	Yes	String	Specifies the resource identifier of the topic, which is unique. To obtain the resource identifier, see <a href="#">Querying Topics</a> .

**Table 5-41** Query Parameters

Parameter	Mandatory	Type	Description
name	Yes	String	Specifies the topic policy name. Only specified policy names are supported. For details, see <a href="#">Topic Attribute List</a> .

## Request Parameters

**Table 5-42** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

**Status code: 200****Table 5-43** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
attributes	<b>TopicAttribute</b> object	Specifies the attribute. Its value can be: - access_policy: specifies the access policy of the topic. - introduction: specifies the introduction to the topic.

**Table 5-44** TopicAttribute

Parameter	Type	Description
access_policy	<b>AccessPolicy</b> object	Specifies the access policy of a topic.
introduction	String	Specifies the introduction to a topic.

**Table 5-45** AccessPolicy

Parameter	Type	Description
Version	String	Specifies the version of the access policy. Only 2016-09-07 is supported.
Id	String	Specifies the unique policy ID. This field cannot be left blank.

Parameter	Type	Description
Statement	Array of <b>Statement</b> objects	You can use statements to configure an access policy. Each access policy may contain one or more statements. You can use statements to grant topic operation permissions to other users or cloud services.

**Table 5-46** Statement

Parameter	Type	Description
Sid	String	Specifies the statement ID. The statement ID must be unique, for example, statement01 or statement02.
Effect	String	Specifies the statement effect. The effect can be Allow or Deny.
Principal	String	Specifies the object the statement is applies to. The following two types of objects are supported: <b>CSP</b> indicates cloud users. <b>Service</b> indicates cloud services. Either the <b>Principal</b> or <b>NotPrincipal</b> must be configured. The format of the <b>CSP</b> is <b>urn:csp:iam::domainId:root</b> or <b>*. domainId</b> indicates the account ID of another user, and <b>*</b> indicates the statement is applied for all users. For <b>Service</b> , you must specify the cloud service names in lower case.
NotPrincipal	String	<b>NotPrincipal</b> indicates the object that the statement is not applied to. The following two types of objects are supported: <b>CSP</b> indicates cloud users. <b>Service</b> indicates cloud services. Either the <b>Principal</b> or <b>NotPrincipal</b> must be configured. The format of the <b>CSP</b> is <b>urn:csp:iam::domainId:root</b> or <b>*. domainId</b> indicates the account ID of another user, and <b>*</b> indicates the statement is applied for all users. For <b>Service</b> , you must specify the cloud service names in lower case.



Parameter	Type	Description
Action	String	Specifies the allowed statement action.You can use a wildcard character to configure a type of actions, for example, SMN:Update* and SMN>Delete*. If you only enter a wildcard character (*) in a statement, all supported actions are configured.Either Action or NotAction must be configured.The following actions are supported:SMN:UpdateTopicSMN>DeleteTopicSMN:QueryTopicDetailSMN:ListTopicAttributesSMN:UpdateTopicAttributeSMN>DeleteTopicAttributeSMN>DeleteTopicAttributeByNameSMN:ListSubscriptionsByTopicSMN:SubscribeSMN:UnsubscribeSMN:Publish
NotAction	String	Specifies the statement action that is not allowed.You can use a wildcard character to configure a type of actions, for example, SMN:Update* and SMN>Delete*. If you only enter a wildcard character (*) in a statement, all supported actions are configured.Either Action or NotAction must be configured.The following actions are supported:SMN:UpdateTopicSMN>DeleteTopicSMN:QueryTopicDetailSMN:ListTopicAttributesSMN:UpdateTopicAttributeSMN>DeleteTopicAttributeSMN>DeleteTopicAttributeByNameSMN:ListSubscriptionsByTopicSMN:SubscribeSMN:UnsubscribeSMN:Publish
Resource	String	Specifies the topic the statement applies to. Either Resource or NotResource must be configured. You need to enter a topic URN.
NotResource	String	Specifies the topic that the statement does not apply to. Either Resource or NotResource must be configured. You need to enter a topic URN.

**Status code: 400**

**Table 5-47** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-48** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-49** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-50** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Querying a topic policy

```
GET https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/  
urn:smn:regionId:8bad8a40e0f7462f8c1676e3f93a8183:test_create_topic_v2/attributes?name=access_policy  
  
null
```

## Example Responses

**Status code: 200**

OK

```
{  
  "request_id" : "6837531fd3f54550927b930180a706bf",  
  "attributes" : {  
    "access_policy" : {  
      "Version" : "2016-09-07",  
      "Id" : "__default_policy_ID",  
      "Statement" : [ {  
        "Sid" : "__user_pub_0",  
        "Effect" : "Allow",  
        "Principal" : [ {  
          "CSP" : [ "urn:csp:iam::93dc1b4697ac493d9b7d089569f86b32:root" ]  
        } ],  
        "Action" : [ "SMN:Publish", "SMN:QueryTopicDetail" ],  
        "Resource" : "urn:smn:regionId:8bad8a40e0f7462f8c1676e3f93a8183:aaa"  
      } ],  
    }, {  
      "Sid" : "__service_pub_0",  
      "Effect" : "Allow",  
      "Principal" : [ {  
        "Service" : [ "obs" ]  
      } ],  
      "Action" : [ "SMN:Publish", "SMN:QueryTopicDetail" ],  
      "Resource" : "urn:smn:regionId:8bad8a40e0f7462f8c1676e3f93a8183:aaa"  
    } ]  
  }  
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.1.7 Deleting All Topic Policies

### Function

This API is used to delete all topic policies.

### Calling Method

For details, see [Calling APIs](#).

### URI

DELETE /v2/{project\_id}/notifications/topics/{topic\_urn}/attributes

**Table 5-51** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
topic_urn	Yes	String	Specifies the resource identifier of the topic, which is unique. To obtain the resource identifier, see <a href="#">Querying Topics</a> .

### Request Parameters

**Table 5-52** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

### Response Parameters

**Status code: 200**

**Table 5-53** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.

**Status code: 400****Table 5-54** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-55** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-56** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500**

**Table 5-57** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Deleting all topic policies

```
DELETE https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/{topic_urn}/attributes
null
```

## Example Responses

**Status code: 200**

OK

```
{
  "request_id" : "6837531fd3f54550927b930180a706bf"
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.1.8 Updating a Topic Policy

### Function

This API is used to update a topic policy.

## Calling Method

For details, see [Calling APIs](#).

## URI

PUT /v2/{project\_id}/notifications/topics/{topic\_urn}/attributes/{name}

**Table 5-58** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
topic_urn	Yes	String	Specifies the resource identifier of the topic, which is unique. To obtain the resource identifier, see <a href="#">Querying Topics</a> .
name	Yes	String	Specifies the topic policy name. Only specified policy names are supported. For details, see <a href="#">Topic Attribute List</a> .

## Request Parameters

**Table 5-59** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

**Table 5-60** Request body parameters

Parameter	Mandatory	Type	Description
value	Yes	String	<ol style="list-style-type: none"><li>1. If you set name to access_policy, value is the topic attribute, and the maximum length of value is 30 KB.</li><li>2. If you set name to introduction, value is the topic introduction, and the maximum length of value is 120 bytes.</li></ol>

## Response Parameters

**Status code: 200**

**Table 5-61** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.

**Status code: 400**

**Table 5-62** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403**

**Table 5-63** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.



**Status code: 404**

**Table 5-64** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500**

**Table 5-65** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Example Requests**

- Updating a topic policy

```
PUT https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/{topic_urn}/attributes/access_policy
{
  "value" : "{ \"Version\": \"2016-09-07\", \"Id\": \"__default_policy_ID\", \"Statement\": [ { \"Sid\": \"__user_pub_0\", \"Effect\": \"Allow\", \"Principal\": { \"CSP\": [ \"urn:csp:iam::{domainID}:root\" ] }, \"Action\": [ \"SMN:Publish\", \"SMN:QueryTopicDetail\" ], \"Resource\": \"{topic_urn}\" }, { \"Sid\": \"__service_pub_0\", \"Effect\": \"Allow\", \"Principal\": { \"Service\": [ \"obs\" ] }, \"Action\": [ \"SMN:Publish\", \"SMN:QueryTopicDetail\" ], \"Resource\": \"{topic_urn}\" } ] }"
```

- Updating a topic policy

```
PUT https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/{topic_urn}/attributes/introduction
{
  "value" : ""
}
```

**Example Responses**

**Status code: 200**

OK

```
{
  "request_id" : "6837531fd3f54550927b930180a706bf"
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.1.9 Deleting a Specified Topic Policy

### Function

This API is used to delete a specified topic policy.

### Calling Method

For details, see [Calling APIs](#).

### URI

DELETE /v2/{project\_id}/notifications/topics/{topic\_urn}/attributes/{name}

**Table 5-66** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
topic_urn	Yes	String	Specifies the resource identifier of the topic, which is unique. To obtain the resource identifier, see <a href="#">Querying Topics</a> .

Parameter	Mandatory	Type	Description
name	Yes	String	Specifies the topic policy name. Only specified policy names are supported. For details, see <a href="#">Topic Attribute List</a> .

## Request Parameters

**Table 5-67** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

**Status code: 200**

**Table 5-68** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.

**Status code: 400**

**Table 5-69** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403**

**Table 5-70** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-71** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-72** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Deleting a specified topic policy

```
DELETE https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/{topic_urn}/attributes/access_policy
null
```

## Example Responses

**Status code: 200**

OK

```
{
  "request_id" : "6837531fd3f54550927b930180a706bf"
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

# 5.2 Subscriptions

## 5.2.1 Querying Subscriptions

### Function

This API is used to query the list of all subscriptions by page. The list is sorted by subscription adding time in ascending order. You can specify offset and limit. If no subscription has been added to the topic, an empty list is returned.

### Calling Method

For details, see [Calling APIs](#).

### URI

GET /v2/{project\_id}/notifications/subscriptions

**Table 5-73** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .

**Table 5-74** Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Specifies the offset. If the offset is an integer greater than 0 but less than the number of resources, all resources in excess of this offset will be queried. The default offset is 0. Default: <b>0</b>
limit	No	Integer	Specifies the maximum number of records in each query. The number ranges from 1 to 100 and is generally 10, 20, or 50. Specifies the number of resources returned on each page. The default number is 100. Default: <b>100</b>
protocol	No	String	Specifies the protocol name. The enumerated values are http, https, sms, email, functionstage, dms, and application.
status	No	Integer	Specifies the subscription status. 0: The subscription has not been confirmed. 1: The subscription has been confirmed. 2: Confirmation is not required. 3: The subscription was canceled. 4: The subscription was deleted.
endpoint	No	String	Specifies the subscription endpoint.
fuzzy_remark	No	String	Specifies the subscription remark for fuzzy match. The value can contain up to 128 bytes.

## Request Parameters

**Table 5-75** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

Status code: 200

**Table 5-76** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
subscription_count	Integer	Specifies the number of subscriptions.
subscriptions	Array of <a href="#">ListSubscriptionsItem</a> objects	Specifies the subscription structure.

**Table 5-77** ListSubscriptionsItem

Parameter	Type	Description
topic_urn	String	Specifies the resource identifier of the topic, which is unique.
protocol	String	Specifies the subscription protocol. (Different protocols indicate different types of endpoints to receive messages.) The following protocols are supported: default email: The endpoints are email addresses. sms: The endpoints are phone numbers. functionstage: FunctionGraph (function) transmission protocol. The endpoints are functions. http and https: The endpoints are URLs.

Parameter	Type	Description
subscription_url	String	Specifies the resource identifier of a subscription, which is unique.
owner	String	Specifies the project ID of the topic creator.
endpoint	String	Specifies the message receiving endpoint.
remark	String	Specifies the remarks.
status	Integer	0 indicates that the subscription is not confirmed. 1 indicates that the subscription is confirmed. 3 indicates that the subscription is canceled.
filter_policies	Array of <a href="#">SubscriptionsFilterPolicy</a> objects	Specifies the filter policy.

**Table 5-78** SubscriptionsFilterPolicy

Parameter	Type	Description
name	String	Specifies the filter policy name. <b>name</b> can contain 1 to 32 characters, including lowercase letters, digits, and underscores (.). <b>name cannot start or end with an underscore, nor contain consecutive underscores. name cannot start with <i>**smr**</i>.</b> Minimum: <b>1</b> Maximum: <b>32</b>
string_equals	Array of strings	Specifies the string array for exact match. An array can contain 1 to 10 strings. The array content must be unique. The string cannot be <b>null</b> or an empty string "". A string can contain 1 to 32 characters, including letters, digits, and underscores (_). Minimum: <b>1</b> Maximum: <b>32</b> Array Length: <b>1 - 10</b>

**Status code: 400**



**Table 5-79** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-80** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-81** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-82** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Querying subscriptions

```
GET https://{SMN_Endpoint}/v2/{project_id}/notifications/subscriptions?offset=0&limit=2
null
```

## Example Responses

**Status code: 200**

OK

```
{
  "request_id" : "6a63a18b8bab40ffb71ebd9cb80d0085",
  "subscription_count" : 2,
  "subscriptions" : [ {
    "topic_urn" : "urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1",
    "protocol" : "sms",
    "subscription_urn" :
    "urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1:2e778e84408e44058e6cbc6d3c377837",
    "owner" : "762bdb3251034f268af0e395c53ea09b",
    "endpoint" : "xxxxxxxx",
    "remark" : "",
    "status" : 0,
    "filter_policies" : [ {
      "name" : "alarm",
      "string_equals" : [ "os", "process" ]
    }, {
      "name" : "service",
      "string_equals" : [ "api", "db" ]
    } ]
  }, {
    "topic_urn" : "urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1",
    "protocol" : "email",
    "subscription_urn" :
    "urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1:a2d52a9f5c3b47f48c3fafb177a58796",
    "owner" : "762bdb3251034f268af0e395c53ea09b",
    "endpoint" : "xx@xx.com",
    "remark" : "",
    "status" : 0,
    "filter_policies" : [ {
      "name" : "alarm",
      "string_equals" : [ "os", "process" ]
    }, {
      "name" : "service",
      "string_equals" : [ "api", "db" ]
    } ]
  } ]
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.2.2 Querying Subscriptions of a Specified Topic

### Function

This API is used to query subscriptions to a specified topic by page. The list is sorted by subscription adding time in ascending order. You can specify offset and limit. If no subscription has been added to the topic, an empty list is returned.

### Calling Method

For details, see [Calling APIs](#).

### URI

GET /v2/{project\_id}/notifications/topics/{topic\_urn}/subscriptions

**Table 5-83** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
topic_urn	Yes	String	Specifies the resource identifier of the topic, which is unique. To obtain the resource identifier, see <a href="#">Querying Topics</a> .

**Table 5-84** Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Specifies the offset. If the offset is an integer greater than 0 but less than the number of resources, all resources in excess of this offset will be queried. The default offset is 0. Default: <b>0</b>

Parameter	Mandatory	Type	Description
limit	No	Integer	Specifies the maximum number of records in each query. The number ranges from 1 to 100 and is generally 10, 20, or 50. Specifies the number of resources returned on each page. The default number is 100. Default: <b>100</b>
fuzzy_remark	No	String	Specifies the subscription remark for fuzzy match. The value can contain up to 128 bytes.

## Request Parameters

**Table 5-85** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

**Status code: 200**

**Table 5-86** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
subscription_count	Integer	Specifies the number of subscriptions.
subscriptions	Array of <b>ListSubscriptionItem</b> objects	Specifies the subscription structure.

**Table 5-87** ListSubscriptionsItem

Parameter	Type	Description
topic_urn	String	Specifies the resource identifier of the topic, which is unique.
protocol	String	Specifies the subscription protocol. (Different protocols indicate different types of endpoints to receive messages.) The following protocols are supported: default email: The endpoints are email addresses. sms: The endpoints are phone numbers. functionstage: FunctionGraph (function) transmission protocol. The endpoints are functions. http and https: The endpoints are URLs.
subscription_urn	String	Specifies the resource identifier of a subscription, which is unique.
owner	String	Specifies the project ID of the topic creator.
endpoint	String	Specifies the message receiving endpoint.
remark	String	Specifies the remarks.
status	Integer	0 indicates that the subscription is not confirmed. 1 indicates that the subscription is confirmed. 3 indicates that the subscription is canceled.
filter_policies	Array of <a href="#">SubscriptionsFilterPolicy</a> objects	Specifies the filter policy.

**Table 5-88** SubscriptionsFilterPolicy

Parameter	Type	Description
name	String	Specifies the filter policy name. <b>name</b> can contain 1 to 32 characters, including lowercase letters, digits, and underscores (.). <b>name cannot start or end with an underscore, nor contain consecutive underscores. name cannot start with <i>**smr**</i>.</b> Minimum: <b>1</b> Maximum: <b>32</b>

Parameter	Type	Description
string_equals	Array of strings	Specifies the string array for exact match. An array can contain 1 to 10 strings. The array content must be unique. The string cannot be <b>null</b> or an empty string "". A string can contain 1 to 32 characters, including letters, digits, and underscores (_). Minimum: <b>1</b> Maximum: <b>32</b> Array Length: <b>1 - 10</b>

**Status code: 400****Table 5-89** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-90** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-91** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-92** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Example Requests**Querying subscriptions of the topic named **test\_topic\_v2**

```
GET https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/  
urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1/subscriptions?offset=0&limit=100  
  
null
```

**Example Responses****Status code: 200**

OK

```
{  
  "request_id" : "6a63a18b8bab40ffb71ebd9cb80d0085",  
  "subscription_count" : 2,  
  "subscriptions" : [ {  
    "topic_urn" : "urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1",  
    "protocol" : "sms",  
    "subscription_urn" :  
"urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1:2e778e84408e44058e6cbc6d3c377837"  
    ,  
    "owner" : "762bdb3251034f268af0e395c53ea09b",  
    "endpoint" : "xxxxxxxxxx",  
    "remark" : "",  
    "status" : 0,  
    "filter_policies" : [ {  
      "name" : "alarm",  
      "string_equals" : [ "os", "process" ]  
    }, {  
      "name" : "service",  
      "string_equals" : [ "api", "db" ]  
    } ]  
  }, {  
    "topic_urn" : "urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1",  
    "protocol" : "email",  
    "subscription_urn" :  
"urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1:a2d52a9f5c3b47f48c3fafb177a58796",  
    "owner" : "762bdb3251034f268af0e395c53ea09b",  
    "endpoint" : "xx@xx.com",  
    "remark" : "",  
    "status" : 0,  
    "filter_policies" : [ {  
      "name" : "alarm",  
      "string_equals" : [ "os", "process" ]  
    }, {  
      "name" : "service",  
      "string_equals" : [ "api", "db" ]  
    } ]  
  } ]  
}
```

```
}]  
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.2.3 Adding a Subscription

### Function

This API is used to add a subscription to a specified topic. If the status of the subscription is unconfirmed, a confirmation message is sent to the subscriber. After confirming the subscription, the subscriber can receive notification messages published to the topic. By default, 10,000 subscriptions can be added to a topic. However, in rare high-concurrency scenarios, extra subscriptions may be added successfully. The API is idempotent. If the added subscription already exists, a successful result and status code 200 are returned. Otherwise, the status code is 201.

### Calling Method

For details, see [Calling APIs](#).

### URI

POST /v2/{project\_id}/notifications/topics/{topic\_urn}/subscriptions

**Table 5-93** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .



Parameter	Mandatory	Type	Description
topic_urn	Yes	String	Specifies the resource identifier of the topic, which is unique. To obtain the resource identifier, see <a href="#">Querying Topics</a> .

## Request Parameters

**Table 5-94** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

**Table 5-95** Request body parameters

Parameter	Mandatory	Type	Description
protocol	Yes	String	<p>Specifies the subscription protocol. (Different protocols indicate different types of endpoints to receive messages.) The following protocols are supported:</p> <p>email: The endpoints are email addresses.</p> <p>sms: SMS transmission protocol. The endpoints are phone numbers.</p> <p>functionstage: FunctionGraph(function) transmission protocol. The endpoints are functions.</p> <p>functiongraph: FunctionGraph(workflow) transmission protocol. The endpoints are FunctionGraph workflows orchestrated by the FunctionGraph function.</p> <p>http and https: The endpoints are URLs.</p> <p>callnotify: The endpoints are phone numbers.</p> <p>wechat: WeChat group chatbot transmission protocol</p> <p>dingding: DingTalk group chatbot transmission protocol</p> <p>feishu: Lark group chatbot transmission protocol</p> <p>welink: WeLink group chatbot transmission protocol</p>

Parameter	Mandatory	Type	Description
endpoint	Yes	String	<p>Note:</p> <p>If you use the HTTP protocol, start the endpoint with <b>http://</b>.</p> <p>If you use the HTTPS protocol, start the endpoint with <b>https://</b>.</p> <p>If you use the email protocol, enter an email address.</p> <p>If you use the SMS protocol, enter a phone number.</p> <p>If you use the FunctionGraph (function) protocol, enter a function.</p> <p>If you use the FunctionGraph (workflow) protocol, enter a workflow.</p> <p>If you use the DMS protocol, enter a message queue.</p> <p>If you use the application protocol, enter a mobile device added to a platform application.</p> <p>If you use the voice notification protocol, enter a phone number.</p> <p>If you use the DingTalk chatbot protocol, enter the webhook URL of a custom DingTalk group chatbot or <b>openConversationId</b> of a group to which an enterprise DingTalk chatbot is added. When you add <b>openConversationId</b>, do not start the endpoint with <b>http://</b> or <b>https://</b>.</p> <p>If you use the WeCom chatbot protocol, enter the webhook URL of a WeCom group chatbot.</p> <p>If you use the Lark chatbot protocol, enter the webhook URL of a Lark group chatbot.</p>

Parameter	Mandatory	Type	Description
			If you use the WeLink protocol, enter a WeLink group number.
remark	No	String	Specifies the remarks. The remarks must be UTF-8-coded and can contain up to 128 bytes.
extension	No	<b>SubscriptionExtension</b> object	Specifies the extension information.

**Table 5-96** SubscriptionExtension

Parameter	Mandatory	Type	Description
client_id	No	String	Specifies the application ID. This field is mandatory when you set <b>protocol</b> to <b>welink</b> . Obtain the value from WeLink. Minimum: <b>1</b> Maximum: <b>64</b>
client_secret	No	String	Specifies the application secret. This field is mandatory when you set <b>protocol</b> to <b>welink</b> . Obtain the value from WeLink. Minimum: <b>1</b> Maximum: <b>64</b>
keyword	No	String	Specifies the keyword. When you set <b>protocol</b> to <b>feishu</b> , you must set either <b>keyword</b> or <b>sign_secret</b> . When you add a keyword for security verification on the Lark chatbot or a custom DingTalk chatbot, <b>keyword</b> must be one of the keywords you entered for the Lark chatbot or the custom DingTalk chatbot. Minimum: <b>0</b> Maximum: <b>20</b>

Parameter	Mandatory	Type	Description
sign_secret	No	String	Specifies the key. When you set <b>protocol</b> to <b>feishu</b> , you must set either this parameter or <b>keyword</b> . The value of this parameter must be the same as that you customized for the Lark chatbot or the custom DingTalk chatbot. For example, if you set only <b>key</b> for the Lark chatbot, enter the value of <b>key</b> . If you set only <b>keyword</b> for the Lark chatbot, skip this field. Minimum: <b>0</b> Maximum: <b>256</b>

## Response Parameters

**Status code: 201**

**Table 5-97** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
subscription_u rn	String	Specifies the resource identifier of a subscription, which is unique.

**Status code: 400**

**Table 5-98** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403**

**Table 5-99** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-100** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-101** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Adding a subscription to the topic named **test\_topic\_v1**

```
POST https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/  
urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1/subscriptions
```

```
{  
  "protocol": "email",  
  "endpoint": "xxx@xxx.com",  
  "remark": "O&M"  
}
```

## Example Responses

**Status code: 201**

OK

```
[ {
  "request_id" : "6a63a18b8bab40ffb71ebd9cb80d0085",
  "subscription_urn" :
  "urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1:2e778e84408e44058e6cbc6d3c377837"
} ]
```

## Status Codes

Status Code	Description
201	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.2.4 Deleting a Subscription

### Function

This API is used to delete a specified subscription.

### Calling Method

For details, see [Calling APIs](#).

### URI

DELETE /v2/{project\_id}/notifications/subscriptions/{subscription\_urn}

**Table 5-102** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .

Parameter	Mandatory	Type	Description
subscription_url	Yes	String	Specifies the resource identifier of the subscriber, which is unique. To obtain the resource identifier, see <a href="#">Query Subscriptions</a> .

## Request Parameters

**Table 5-103** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

**Status code: 200**

**Table 5-104** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.

**Status code: 400**

**Table 5-105** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403**



**Table 5-106** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-107** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-108** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Deleting a subscription with the URN

**urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test\_topic\_v1:2e778e84408e44058e6cbc6d3c377837**

```
DELETE https://{SMN_Endpoint}/v2/{project_id}/notifications/subscriptions/  
urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1:2e778e84408e44058e6cbc6d3c377837  
null
```

## Example Responses

**Status code: 200**

OK

```
{  
  "request_id" : "6a63a18b8bab40ffb71ebd9cb80d0085"  
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.2.5 Updating a Subscriber

### Function

This API is used to update the subscriber remarks.

### Calling Method

For details, see [Calling APIs](#).

### URI

PUT /v2/{project\_id}/notifications/topics/{topic\_urn}/subscriptions/  
{subscription\_urn}

**Table 5-109** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
topic_urn	Yes	String	Specifies the resource identifier of the topic, which is unique. To obtain the resource identifier, see <a href="#">Querying Topics</a> .

Parameter	Mandatory	Type	Description
subscription_u rn	Yes	String	Specifies the resource identifier of the subscriber, which is unique. To obtain the resource identifier, see <a href="#">Query Subscriptions</a> .

## Request Parameters

**Table 5-110** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

**Table 5-111** Request body parameters

Parameter	Mandatory	Type	Description
remark	Yes	String	Specifies the subscriber remarks. The subscriber remarks can contain up to 128 bytes. Minimum: <b>1</b> Maximum: <b>128</b>

## Response Parameters

**Status code: 200**

**Table 5-112** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the unique request ID.
subscription_u rn	String	Specifies the resource identifier of a subscription, which is unique.

**Status code: 400**

**Table 5-113** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-114** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-115** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-116** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Updating a subscriber

```
PUT https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/  
urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1/subscriptions/  
urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1:2e778e84408e44058e6cbc6d3c377837  
  
{  
  "remark" : "test remark"  
}
```

## Example Responses

**Status code: 200**

OK

```
{  
  "request_id" : "fdbabe38ead6482b8574f82a3d1168e9",  
  "subscription_urn" :  
  "urn:smn:regionId:762bdb3251034f268af0e395c53ea09b:test_topic_v1:2e778e84408e44058e6cbc6d3c377837"  
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.3 Templates

### 5.3.1 Querying Message Templates

#### Function

This API is used to query the template list by page. The list is sorted by template creation time in ascending order. You can specify offset and limit. If no template has been created, an empty list is returned. The parameters `message_template_name` and `protocol` are added.

#### Calling Method

For details, see [Calling APIs](#).

## URI

GET /v2/{project\_id}/notifications/message\_template

**Table 5-117** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .

**Table 5-118** Query Parameters

Parameter	Mandatory	Type	Description
offset	No	Integer	Specifies the offset. If the offset is an integer greater than 0 but less than the number of resources, all resources in excess of this offset will be queried. The default offset is 0. Default: <b>0</b>
limit	No	Integer	The number ranges from 1 to 100 and is generally 10, 20, or 50. Specifies the number of resources returned on each page. The default number is 100. Default: <b>100</b>
message_template_name	No	String	Specifies the template name. Enter 1 to 64 characters, and start with a letter or digit. Only letters, digits, hyphens (-), and underscores (_) are allowed.

Parameter	Mandatory	Type	Description
protocol	No	String	Specifies the protocol supported by the template. The following protocols are supported: default email sms functionstage dms http and https

## Request Parameters

**Table 5-119** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

**Status code: 200**

**Table 5-120** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
message_template_count	Integer	Specifies the number of returned templates.
message_templates	Array of <a href="#">MessageTemplate</a> objects	Specifies the Message_template structure array.

**Table 5-121** MessageTemplate

Parameter	Type	Description
message_template_id	String	Specifies the template ID.
message_template_name	String	Specifies the template name.
protocol	String	Specifies the protocol supported by the template. The following protocols are supported: email sms functionstage dms http and https
tag_names	Array of strings	Specifies the variable list.
create_time	String	Specifies when the template was created. The UTC time is in YYYY-MM-DDTHH:MM:SSZ format.
update_time	String	Specifies the last time when the template was updated. The UTC time is in YYYY-MM-DDTHH:MM:SSZ format.

**Status code: 400****Table 5-122** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-123** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.



Parameter	Type	Description
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-124** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-125** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Querying message templates

```
GET https://{SMN_Endpoint}/v2/{project_id}/notifications/message_template?  
offset=0&limit=2&message_template_name=test1&protocol=email
```

```
null
```

## Example Responses

**Status code: 200**

OK

```
{  
  "request_id" : "6a63a18b8bab40ffb71ebd9cb80d0085",  
  "message_template_count" : 3,  
  "message_templates" : [ {  
    "message_template_name" : "confirm_message",  
    "protocol" : "sms",  
    "update_time" : "2016-08-02T08:22:18Z",  
    "create_time" : "2016-08-02T08:22:18Z",
```

```
"tag_names" : [ "topic_urn" ],
"message_template_id" : "79227dfdf88d4e52a1820ca1eb411635"
}, {
"message_template_name" : "confirm_message",
"protocol" : "email",
"update_time" : "2016-08-02T08:22:19Z",
"create_time" : "2016-08-02T08:22:19Z",
"tag_names" : [ "topic_id" ],
"message_template_id" : "ecf63465804a4b10a0573980be78ffba"
}, {
"message_template_name" : "confirm_message",
"protocol" : "https",
"update_time" : "2016-08-02T08:22:20Z",
"create_time" : "2016-08-02T08:22:20Z",
"tag_names" : [ "topic_id" ],
"message_template_id" : "57ba8dcecd844878c5dd5815b65d10f"
}
}]
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.3.2 Creating a Message Template

### Function

This API is used to create a message template for quick message sending and reduced request data volume. By default, a user can create a maximum of 100 message templates. However, in rare high-concurrency scenarios, extra templates may be successfully created.

### Calling Method

For details, see [Calling APIs](#).

### URI

POST /v2/{project\_id}/notifications/message\_template

**Table 5-126** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .

## Request Parameters

**Table 5-127** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

**Table 5-128** Request body parameters

Parameter	Mandatory	Type	Description
message_template_name	Yes	String	Specifies the template name. Enter 1 to 64 characters, and start with a letter or digit. Only letters, digits, hyphens (-), and underscores (_) are allowed.
protocol	Yes	String	Specifies the protocol supported by the template. The following protocols are supported: default email sms functionstage dms http and https

Parameter	Mandatory	Type	Description
content	Yes	String	Specifies the template content, which supports plain text only. The template content cannot be left blank or larger than 256 KB.

## Response Parameters

### Status code: 201

Table 5-129 Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
message_template_id	String	Specifies the resource identifier of the template, which is unique.

### Status code: 400

Table 5-130 Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

### Status code: 403

Table 5-131 Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

### Status code: 404

**Table 5-132** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-133** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Creating an HTTPS message template with the name of **confirm\_message**

```
POST https://{SMN_Endpoint}/v2/{project_id}/notifications/message_template
{
  "message_template_name": "confirm_message",
  "protocol": "https",
  "content": "(1/2)You are invited to subscribe to topic({topic_id}). Click the following URL to confirm
subscription:(If you do not want to subscribe to this topic, ignore this message.)"
}
```

## Example Responses

**Status code: 201**

OK

```
{
  "request_id": "6a63a18b8bab40ffb71ebd9cb80d0085",
  "message_template_id": "57ba8dceccda844878c5dd5815b65d10f"
}
```

## Status Codes

Status Code	Description
201	OK
400	Bad Request

Status Code	Description
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.3.3 Querying Details About a Message Template

### Function

This API is used to query template details, including the template content.

### Calling Method

For details, see [Calling APIs](#).

### URI

GET /v2/{project\_id}/notifications/message\_template/{message\_template\_id}

**Table 5-134** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
message_template_id	Yes	String	Specifies the unique resource ID of a template. To obtain the ID, see <a href="#">Querying Message Templates</a> .

## Request Parameters

**Table 5-135** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

**Status code: 200****Table 5-136** Response body parameters

Parameter	Type	Description
message_template_id	String	Specifies the template ID.
message_template_name	String	Specifies the template name.
protocol	String	Specifies the protocol supported by the template. The following protocols are supported: default email sms functionstage dms http and https
tag_names	Array of strings	Specifies the variable list. The variable name will be quoted in braces ({} in the template. When you use a template to send messages, you can replace the variable with any content.
create_time	String	Specifies when the template was created. The UTC time is in YYYY-MM-DDTHH:MM:SSZ format.
update_time	String	Specifies the last time when the template was updated. The UTC time is in YYYY-MM-DDTHH:MM:SSZ format.

Parameter	Type	Description
content	String	Specifies the template content.
request_id	String	Specifies the request ID, which is unique.

## Example Requests

Querying details about a message template

```
GET https://{SMN_Endpoint}/v2/{project_id}/notifications/message_template/  
57ba8dcecd844878c5dd5815b65d10f  
  
null
```

## Example Responses

**Status code: 200**

OK

```
{  
  "message_template_id" : "57ba8dcecd844878c5dd5815b65d10f",  
  "message_template_name" : "confirm_message",  
  "protocol" : "https",  
  "tag_names" : [ "topic_id_id4" ],  
  "create_time" : "2016-08-02T08:22:20Z",  
  "update_time" : "2016-08-02T08:22:25Z",  
  "content" : "(1/24)You are invited to subscribe to topic({topic_id_id4}). Click the following URL to confirm  
subscription:(If you do not want to subscribe to this topic, ignore this message.)",  
  "request_id" : "ba79ca8f794f4f50985ce7b98a401b47"  
}
```

## Status Codes

Status Code	Description
200	OK

## Error Codes

See [Error Codes](#).

## 5.3.4 Modifying a Message Template

### Function

This API is used to modify the message template content.

### Calling Method

For details, see [Calling APIs](#).



## URI

PUT /v2/{project\_id}/notifications/message\_template/{message\_template\_id}

**Table 5-137** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
message_template_id	Yes	String	Specifies the unique resource ID of a template. To obtain the ID, see <a href="#">Querying Message Templates</a> .

## Request Parameters

**Table 5-138** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

**Table 5-139** Request body parameters

Parameter	Mandatory	Type	Description
content	Yes	String	Specifies the template content.

## Response Parameters

Status code: 200

**Table 5-140** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.

**Status code: 400****Table 5-141** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-142** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-143** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-144** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Modifying the content of a message template

```
PUT https://{SMN_Endpoint}/v2/{project_id}/notifications/message_template/  
b3ffa2cdda574168826316f0628f774f  
  
{  
  "content" : "(1/22)You are invited to subscribe to topic({topic_id_id1}). Click the following URL to confirm  
subscription:(If you do not want to subscribe to this topic, ignore this message.)"  
}
```

## Example Responses

Status code: 200

OK

```
{  
  "request_id" : "6a63a18b8bab40ffb71ebd9cb80d0085"  
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.3.5 Deleting a Message Template

### Function

This API is used to delete a message template. After you delete the template, you can no longer use it to publish messages.

### Calling Method

For details, see [Calling APIs](#).

### URI

DELETE /v2/{project\_id}/notifications/message\_template/{message\_template\_id}

**Table 5-145** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
message_template_id	Yes	String	Specifies the unique resource ID of a template. To obtain the ID, see <a href="#">Querying Message Templates</a> .

## Request Parameters

**Table 5-146** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

**Status code: 200**

**Table 5-147** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.

**Status code: 400**

**Table 5-148** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-149** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-150** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-151** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Deleting a message template

```
DELETE https://{SMN_Endpoint}/v2/{project_id}/notifications/message_template/  
b3ffa2cdda574168826316f0628f774e
```

```
null
```

## Example Responses

**Status code: 200**

OK

```
{  
  "request_id" : "6a63a18b8bab40ffb71ebd9cb80d0085"  
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

# 5.4 Message Publishing

## 5.4.1 Publishing a Message

### Function

This API is used to publish messages to a topic. After the message ID is returned, the message has been saved and is to be pushed to the subscribers of the topic. Three message formats are supported:

message

message\_structure

message\_template\_name

If the three formats are specified at the same time, they take effect in the following sequence: message\_structure > message\_template\_name > message

### Calling Method

For details, see [Calling APIs](#).

### URI

POST /v2/{project\_id}/notifications/topics/{topic\_urn}/publish

**Table 5-152** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
topic_urn	Yes	String	Specifies the resource identifier of the topic, which is unique. To obtain the resource identifier, see <a href="#">Querying Topics</a> .

## Request Parameters

**Table 5-153** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

**Table 5-154** Request body parameters

Parameter	Mandatory	Type	Description
subject	No	String	Specifies the message subject, which is used as the email subject when you publish email messages. The length of the subject cannot exceed 512 bytes.

Parameter	Mandatory	Type	Description
message	No	String	Specifies the message content. The message content must be UTF-8-coded and can be no more than 256 KB. If the endpoint is a phone number that exceeds 490 characters, SMN will cut it off. The SMS message cannot contain square brackets ([]).For application subscribers, messages must comply with format requirements of the mobile push platform. For details, see the format of the application message body. Otherwise, the mobile app will fail to receive messages. HMS, APNS, and APNS_SANDBOX mobile push platforms are supported.Note:Three message formats are supported:messagemessage_structurmessage_template_nameAt least one of them must be set. If they are set at the same time, the effective priority ismessage_structure > message_template_name > message



Parameter	Mandatory	Type	Description
message_structure	No	String	Specifies the message structure, which is a JSON string. The following protocols are supported: <b>email</b> , <b>sms</b> , <b>http</b> , <b>https</b> , <b>dms</b> , <b>functiongraph</b> , <b>functionstage</b> , <b>HMS</b> , <b>APNS</b> , <b>APNS_SANDBOX</b> , <b>dingding</b> , or <b>wechat</b> , <b>feishu</b> , or <b>welink</b> . For details about the message formats of the <b>HMS</b> , <b>APNS</b> , and <b>APNS_SANDBOX</b> protocols, see the format of the <b>application</b> message body. The <b>default</b> protocol is mandatory. If the system fails to match any other protocols, the message using the <b>default</b> protocol is sent. The <b>msgType</b> field must be specified for messages of the DingTalk chatbot, WeCom chatbot, Lark chatbot, or WeLink protocol. The DingTalk, WeCom, or Lark chatbot protocol support messages in <b>text</b> or <b>markdown</b> format. WeLink and WeLink (red version) chatbots support messages in <b>text</b> format. For the DingTalk chatbot protocol, SMN supports the @ group member function through the <b>at</b> fields. When you need to @ group members, set <b>isAtAll</b> to "true". You can enter the phone numbers of persons who need to be @ for the <b>atMobiles</b> field or enter the DingTalk user IDs of persons who need to be @ for the <b>atUserIds</b> field. When you use the <b>atMobiles</b> or <b>atUserIds</b> field, add @ before each phone number or user ID in the message content. For details about the display effect, see the official DingTalk document. Note: The following three message

Parameter	Mandatory	Type	Description
			<p>formats are supported: <code>message_structure</code> <code>message_template_name</code> <code>message</code>. At least one of them must be set. If they are set at the same time, the effective priority is <code>message_structure &gt; message_template_name &gt; message</code>.</p> <p>sequence: <code>message_structure &gt; message_template_name &gt; message</code></p> <p>HMS transparent push message { "hps": { "msg": { "type": 1, "body": { "key": "value" } } } }</p> <p>Huawei notification push message { "hps": { "msg": { "type": 3, "body": { "content": "Push message content", "title": "Push message content" }, "action": { "type": 1, "param": { "intent": "#Intent;compo=com.rvr/.Activity;S.W=U;end" } } }, "ext": { "biTag": "Trump", "icon": "http://upload.w.org/00/150pxsvg.png" } } }</p> <p>Apple platform message { "aps": { "alert": "hello world" } }</p>
message_template_name	No	String	<p>Specifies the message template name. To obtain the name, see <a href="#">Querying Message Templates</a>. Note: Three message formats are supported: <code>message_structure</code> <code>message_template_name</code> <code>message</code>. At least one of them must be set. If they are set at the same time, the effective priority is <code>message_structure &gt; message_template_name &gt; message</code>.</p>

Parameter	Mandatory	Type	Description
tags	No	Map<String,String>	Specifies the dictionary consisting of variable parameters and values. The value cannot be left blank. This parameter is mandatory when you use a message template to publish messages. The key in the dictionary is the parameter name in the message template and contains a maximum of 21 characters. The value in the dictionary is the value after the key in the message template is replaced. The value cannot exceed 1 KB.
time_to_live	No	String	Specifies the maximum retention period of a message in SMN. After the retention period expires, SMN does not send this message. Unit: second Default value: 3600s (one hour) The retention period must be a positive integer less than or equal to 86,400 (3600 x 24).
message_attributes	No	Array of <b>MessageAttribute</b> objects	Specifies the message attribute list. Array Length: <b>0 - 10</b>

**Table 5-155** MessageAttribute

Parameter	Mandatory	Type	Description
name	Yes	String	Specifies the attribute name. <b>name</b> can contain 1 to 32 characters, including only lowercase letters, digits, and underscores (_). <b>name</b> cannot start or end with an underscore, nor contain consecutive underscores. Minimum: <b>1</b> Maximum: <b>32</b>

Parameter	Mandatory	Type	Description
type	Yes	String	Specifies the attribute type. The value can be one of the following: <b>STRING</b> <b>STRING_ARRAY</b> <b>PROTOCOL</b> Enumeration values: <ul style="list-style-type: none"><li>• <b>STRING</b></li><li>• <b>STRING_ARRAY</b></li><li>• <b>PROTOCOL</b></li></ul>
value	Yes	Object	Specifies the attribute value. When you set <b>type</b> to <b>STRING</b> , <b>value</b> can contain 1 to 32 characters, including only letters, digits, and underscores (.). <i>When you set <b>type</b> to <b>STRING_ARRAY</b>, <b>value</b> is an array containing 1 to 10 strings. Each string in the array must be unique. Each string in the array must contain 1 to 32 characters, including only letters, digits, and underscores (.).</i> When you set <b>type</b> to <b>PROTOCOL</b> , <b>value</b> is a string array of supported protocol types.

## Response Parameters

Status code: 200

Table 5-156 Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
message_id	String	Specifies the message ID, which is unique.

Status code: 400

Table 5-157 Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.

Parameter	Type	Description
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-158** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-159** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 429****Table 5-160** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500**

**Table 5-161** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

- Publishing a message

```
POST https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/urn:smn:regionId:
f96188c7ccaf4ffba0c9aa149ab2bd57:test_create_topic_v2/publish
```

```
{
  "subject": "test message v2",
  "message": "Message test message v2",
  "time_to_live": "3600",
  "message_attributes": [ {
    "name": "smn_protocol",
    "type": "PROTOCOL",
    "value": [ "email", "sms" ]
  } ]
}
```

- Publishing messages using a message structure

```
POST https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/urn:smn:regionId:
f96188c7ccaf4ffba0c9aa149ab2bd57:test_create_topic_v2/publish
```

```
{
  "subject": "test message v2",
  "message_structure": "{\n  \"default\": \"xxx\\\", \n  \"APNS\": \"{\n    \"aps\": {\n      \"alert\": {\n        \"title\": \"\nxxx\\\", \"body\": \"xxx\\\"}}\n\",
  \"time_to_live\": \"3600\",
  \"message_attributes\": [ {
    \"name\": \"smn_protocol\",
    \"type\": \"PROTOCOL\",
    \"value\": [ \"email\", \"sms\" ]
  } ]
}
```

- Publishing messages using a template

```
POST https://{SMN_Endpoint}/v2/{project_id}/notifications/topics/urn:smn:regionId:
f96188c7ccaf4ffba0c9aa149ab2bd57:test_create_topic_v2/publish
```

```
{
  "subject": "test message template v2",
  "message_template_name": "confirm_message",
  "time_to_live": "3600",
  "tags": {
    "topic_urn": "topic_urn3331",
    "topic_id": "topic_id3332"
  },
  "message_attributes": [ {
    "name": "smn_protocol",
    "type": "PROTOCOL",
    "value": [ "email", "sms" ]
  } ]
}
```

## Example Responses

**Status code: 200**

OK

```
{  
  "request_id" : "6a63a18b8bab40ffb71ebd9cb80d0085",  
  "message_id" : "bf94b63a5dfb475994d3ac34664e24f2"  
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
429	Too Many Requests
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.5 Tags

### 5.5.1 Querying Resources by Tag

#### Function

This API is used to query resources by tag.

#### Calling Method

For details, see [Calling APIs](#).

#### URI

POST /v2/{project\_id}/{resource\_type}/resource\_instances/action

**Table 5-162** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
resource_type	Yes	String	Specifies the resource type. Possible values are: smn_topic: topic smn_sms: SMS smn_application: mobile push

## Request Parameters

**Table 5-163** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

**Table 5-164** Request body parameters

Parameter	Mandatory	Type	Description
tags	No	Array of <a href="#">ResourceTags</a> objects	A maximum of 10 tag keys are allowed in each query operation. Each tag key can have up to 10 tag values. The structure body is mandatory. The tag key cannot be left blank or be an empty string. Each tag key and tag values of one key must be unique. Resources identified by different keys are in AND relationship.



Parameter	Mandatory	Type	Description
tags_any	No	Array of <b>ResourceTags</b> objects	A maximum of 10 tag keys are allowed in each query operation. Each tag key can have up to 10 tag values. The structure body is mandatory. The tag key cannot be left blank or be an empty string. Each tag key and tag values of one key must be unique. Resources identified by different keys are in OR relationship.
not_tags	No	Array of <b>ResourceTags</b> objects	A maximum of 10 tag keys are allowed in each query operation. Each tag key can have up to 10 tag values. The structure body is mandatory. The tag key cannot be left blank or be an empty string. Each tag key and tag values of one key must be unique. Resources identified by different keys are in NAND relationship.
not_tags_any	No	Array of <b>ResourceTags</b> objects	A maximum of 10 tag keys are allowed in each query operation. Each tag key can have up to 10 tag values. The structure body is mandatory. The tag key cannot be left blank or be an empty string. Each tag key and tag values of one key must be unique. Resources identified by different keys are in NOR relationship.

Parameter	Mandatory	Type	Description
offset	No	String	Specifies the index position. The query starts from the next data record indexed by this parameter. You do not need to specify this parameter when you query resources on the first page. When you query resources on subsequent pages, set this parameter to the location returned in the response body for the previous query. If action is set to count, this parameter does not take effect. If you set action to filter, the offset value is 0 by default. The offset value cannot be a negative integer. Default: <b>0</b>
limit	No	String	Specifies the maximum number of resources to be queried. If action is set to count, this parameter does not take effect. If you set action to filter, the value of this parameter is 1000 by default. The maximum value of limit is 1000 and the minimum value is 1. Default: <b>1000</b>
action	Yes	String	Specifies the operation to be performed. The value can be filter (filtering) or count (querying the total number). filter indicates pagination query. count indicates that the total number of query results meeting the search criteria will be returned.
matches	No	Array of <b>TagMatch</b> objects	Specifies the key-value pair to be matched. The key can only be resource_name. The value will be exactly matched.

**Table 5-165** ResourceTags

Parameter	Mandatory	Type	Description
key	Yes	String	Specifies the tag key. <ul style="list-style-type: none"> <li>• A key can contain a maximum of 127 Unicode characters.</li> <li>• key must be specified.</li> </ul>
values	Yes	Array of strings	Specifies the tag values. <ul style="list-style-type: none"> <li>• Each tag contains a maximum of 10 values.</li> <li>• Values of the same tag must be unique.</li> <li>• It can contain a maximum of 255 Unicode characters.</li> <li>• If this parameter is left blank, any value can be used.</li> <li>• All values of a tag key are in the OR relationship.</li> </ul>

**Table 5-166** TagMatch

Parameter	Mandatory	Type	Description
key	Yes	String	Specifies the key field to be matched. key can only be resource_name. In such a case, value is the ECS name. <ul style="list-style-type: none"> <li>• The key must be unique, and the value is used for matching.</li> <li>• The key field is a fixed dictionary value.</li> <li>• key cannot be left blank.</li> </ul>

Parameter	Mandatory	Type	Description
value	Yes	String	Specifies the value. key can only be resource_name. In such a case, value is the ECS name. <ul style="list-style-type: none"> <li>It can contain a maximum of 255 Unicode characters.</li> <li>This field cannot be left blank.</li> </ul>

## Response Parameters

Status code: 200

**Table 5-167** Response body parameters

Parameter	Type	Description
resources	Array of <a href="#">TagResource</a> objects	Specifies the returned resource list.
total_count	Integer	Specifies the total number of records.

**Table 5-168** TagResource

Parameter	Type	Description
resource_id	String	Specifies the resource ID.
resource_detail	<a href="#">ResourceDetail</a> object	Specifies the resource details.
tags	Array of <a href="#">ResourceTag</a> objects	Specifies the list of tags.
resource_name	String	Specifies the resource name.

**Table 5-169** ResourceDetail

Parameter	Type	Description
enterprise_project_id	String	Specifies the enterprise project ID.

Parameter	Type	Description
detailId	String	Specifies the details ID.
topic_urn	String	Specifies the unique identifier of the topic.
display_name	String	Specifies the display name.

**Table 5-170** ResourceTag

Parameter	Type	Description
key	String	Specifies the key field to be matched. key can only be resource_name. In such a case, value is the ECS name. <ul style="list-style-type: none"><li>• The key must be unique, and the value is used for matching.</li><li>• The key field is a fixed dictionary value.</li><li>• key cannot be left blank.</li></ul>
value	String	Specifies the value. key can only be resource_name. In such a case, value is the ECS name. <ul style="list-style-type: none"><li>• It can contain a maximum of 255 Unicode characters.</li><li>• This field cannot be left blank.</li></ul>

**Status code: 400****Table 5-171** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-172** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.

Parameter	Type	Description
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404**

**Table 5-173** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500**

**Table 5-174** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

- Using tags to filter resources

POST https://{SMN\_Endpoint}/v2/{project\_id}/{resource\_type}/resource\_instances/action

```
{
  "offset": "100",
  "limit": "100",
  "action": "filter",
  "matches": [ {
    "key": "resource_name",
    "value": "resource1"
  } ],
  "not_tags": [ {
    "key": "key1",
    "values": [ "*"value1", "value2" ]
  }, {
    "key": "key2",
    "values": [ "*"value21", "value22" ]
  } ],
  "tags": [ {
    "key": "key1",
    "values": [ "*"value1", "value2" ]
  } ],
}
```

```

"tags_any" : [ {
  "key" : "key1",
  "values" : [ "value1", "value2" ]
}],
"not_tags_any" : [ {
  "key" : "key1",
  "values" : [ "value1", "value2" ]
}]
}

```

- Using tags to query the total number of resources

POST https://{SMN\_Endpoint}/v2/{project\_id}/{resource\_type}/resource\_instances/action

```

{
  "action" : "count",
  "not_tags" : [ {
    "key" : "key1",
    "values" : [ "value1", "*value2" ]
  } ],
  "tags" : [ {
    "key" : "key1",
    "values" : [ "value1", "value2" ]
  } ],
  "tags_any" : [ {
    "key" : "key1",
    "values" : [ "value1", "value2" ]
  } ],
  "not_tags_any" : [ {
    "key" : "key1",
    "values" : [ "value1", "value2" ]
  } ],
  "matches" : [ {
    "key" : "resource_name",
    "value" : "resource"
  } ]
}

```

## Example Responses

**Status code: 200**

OK

```

{
  "resources" : {
    "resource_detail" : {
      "topic_urn" : "urn:smn:regionId:f96188c7ccaf4ffba0c9aa149ab2bd57:resouce1",
      "display_name" : "testtest",
      "enterprise_project_id" : "0"
    },
    "resource_id" : "cffe4fc4c9a54219b60dbaf7b586e132",
    "resource_name" : "resouce1",
    "tags" : [ {
      "key" : "key1",
      "value" : "value1"
    } ]
  } ],
  "total_count" : 1000
}

```

## Status Codes

Status Code	Description
200	OK

Status Code	Description
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.5.2 Adding or Deleting Resource Tags in Batches

### Function

This API is used to add or delete tags in batches for a specified resource. You can add a maximum of 10 tags to a resource. The API is idempotent. When you are creating tags, if there are duplicate keys in the request body, an error is reported. If a to-be-created tag has the same key as an existing tag, the tag will be created and overwrite the existing one. During tag deletion, if some tags do not exist, the deletion is considered to be successful by default. The character set of the tags will not be checked.

### Calling Method

For details, see [Calling APIs](#).

### URI

POST /v2/{project\_id}/{resource\_type}/{resource\_id}/tags/action

**Table 5-175** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
resource_type	Yes	String	Specifies the resource type. Possible values are: smn_topic: topic smn_sms: SMS smn_application: mobile push



Parameter	Mandatory	Type	Description
resource_id	Yes	String	Specifies the resource ID. To obtain the value of resource_id, perform the following steps: When resource_type is set to smn_topic: Add X-SMN-RESOURCEID-TYPE=name in the request header and set the resource ID to the topic name. Call the GetResourceInstances API to obtain the resource ID. If you set resource_type to smn_sms, the resource ID is the signature ID, which can be obtained on the console.

## Request Parameters

**Table 5-176** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

**Table 5-177** Request body parameters

Parameter	Mandatory	Type	Description
tags	Yes	Array of <a href="#">ResourceTag</a> objects	Specifies the tag list. For details, see table 1. When you delete tags, the tag structure cannot be missing, and the key cannot be left blank or be an empty string. The system does not check the character set when deleting a tag.
action	Yes	String	Specifies the operation to be performed. The value can be create or delete only.

**Table 5-178** ResourceTag

Parameter	Mandatory	Type	Description
key	Yes	String	Specifies the key field to be matched. key can only be resource_name. In such a case, value is the ECS name. <ul style="list-style-type: none"> <li>The key must be unique, and the value is used for matching.</li> <li>The key field is a fixed dictionary value.</li> <li>key cannot be left blank.</li> </ul>
value	Yes	String	Specifies the value. key can only be resource_name. In such a case, value is the ECS name. <ul style="list-style-type: none"> <li>It can contain a maximum of 255 Unicode characters.</li> <li>This field cannot be left blank.</li> </ul>

## Response Parameters

**Status code: 400**

**Table 5-179** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403**

**Table 5-180** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.

Parameter	Type	Description
message	String	Describes the error message.

**Status code: 404**

**Table 5-181** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500**

**Table 5-182** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

- Batch adding tags to resources

POST https://{SMN\_Endpoint}/v2/{project\_id}/{resource\_type}/{resource\_id}/tags/action

```
{
  "action": "create",
  "tags": [ {
    "key": "key1",
    "value": "value1"
  }, {
    "key": "key",
    "value": "value3"
  } ]
}
```

- Batch deleting resource tags

POST https://{SMN\_Endpoint}/v2/{project\_id}/{resource\_type}/{resource\_id}/tags/action

```
{
  "action": "delete",
  "tags": [ {
    "key": "key1"
  }, {
    "key": "key2",
    "value": "value3"
  } ]
}
```

```
}]  
}
```

## Example Responses

None

## Status Codes

Status Code	Description
204	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.5.3 Querying Resource Tags

### Function

This API is used to query tags of a specified resource.

### Calling Method

For details, see [Calling APIs](#).

### URI

GET /v2/{project\_id}/{resource\_type}/{resource\_id}/tags

**Table 5-183** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .

Parameter	Mandatory	Type	Description
resource_type	Yes	String	Specifies the resource type. The type can be the following: smn_topic: topic smn_sms: SMS smn_application: mobile push
resource_id	Yes	String	Specifies the resource ID. To obtain the value of resource_id, perform the following steps:  When resource_type is set to smn_topic: Add X-SMN-RESOURCEID-TYPE=name in the request header and set the resource ID to the topic name. Call the GetResourceInstances API to obtain the resource ID. If you set resource_type to smn_sms, the resource ID is the signature ID, which can be obtained on the console.

## Request Parameters

Table 5-184 Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

Status code: 200

Table 5-185 Response body parameters

Parameter	Type	Description
tags	Array of <a href="#">ResourceTag</a> objects	Specifies resource tags.

**Table 5-186** ResourceTag

Parameter	Type	Description
key	String	Specifies the key field to be matched. key can only be resource_name. In such a case, value is the ECS name. <ul style="list-style-type: none"><li>• The key must be unique, and the value is used for matching.</li><li>• The key field is a fixed dictionary value.</li><li>• key cannot be left blank.</li></ul>
value	String	Specifies the value. key can only be resource_name. In such a case, value is the ECS name. <ul style="list-style-type: none"><li>• It can contain a maximum of 255 Unicode characters.</li><li>• This field cannot be left blank.</li></ul>

**Status code: 400****Table 5-187** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-188** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404**

**Table 5-189** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-190** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Querying resource tags

```
GET https://{SMN_Endpoint}/v2/{project_id}/{resource_type}/{resource_id}/tags
null
```

## Example Responses

**Status code: 200**

OK

```
{
  "tags": [ {
    "key": "key1",
    "value": "value1"
  }, {
    "key": "key2",
    "value": "value3"
  } ]
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request

Status Code	Description
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.5.4 Adding a Resource Tag

### Function

You can add a maximum of 10 tags to a resource. The API is idempotent. If a to-be-created tag has the same key as an existing tag, the tag will be created and overwrite the existing one.

### Calling Method

For details, see [Calling APIs](#).

### URI

POST /v2/{project\_id}/{resource\_type}/{resource\_id}/tags

**Table 5-191** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
resource_type	Yes	String	Specifies the resource type. Possible values are: smn_topic: topic smn_sms: SMS smn_application: mobile push



Parameter	Mandatory	Type	Description
resource_id	Yes	String	Specifies the resource ID. To obtain the value of resource_id, perform the following steps: When resource_type is set to smn_topic: Add X-SMN-RESOURCEID-TYPE=name in the request header and set the resource ID to the topic name. Call the GetResourceInstances API to obtain the resource ID. If you set resource_type to smn_sms, the resource ID is the signature ID, which can be obtained on the console.

## Request Parameters

**Table 5-192** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

**Table 5-193** Request body parameters

Parameter	Mandatory	Type	Description
tag	Yes	<a href="#">ResourceTag</a> object	Specifies the resource tag structure.

**Table 5-194** ResourceTag

Parameter	Mandatory	Type	Description
key	Yes	String	Specifies the key field to be matched. key can only be resource_name. In such a case, value is the ECS name. <ul style="list-style-type: none"><li>• The key must be unique, and the value is used for matching.</li><li>• The key field is a fixed dictionary value.</li><li>• key cannot be left blank.</li></ul>
value	Yes	String	Specifies the value. key can only be resource_name. In such a case, value is the ECS name. <ul style="list-style-type: none"><li>• It can contain a maximum of 255 Unicode characters.</li><li>• This field cannot be left blank.</li></ul>

## Response Parameters

**Status code: 400**

**Table 5-195** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403**

**Table 5-196** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.

Parameter	Type	Description
message	String	Describes the error message.

**Status code: 404****Table 5-197** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-198** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Adding a resource tag

```
POST https://{SMN_Endpoint}/v2/{project_id}/{resource_type}/{resource_id}/tags
```

```
{
  "tag": {
    "key": "DEV",
    "value": "DEV1"
  }
}
```

## Example Responses

None

## Status Codes

Status Code	Description
204	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.5.5 Querying Project Tags

### Function

This API is used to query all tags of a resource type in a specified region.

### Calling Method

For details, see [Calling APIs](#).

### URI

GET /v2/{project\_id}/{resource\_type}/tags

**Table 5-199** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
resource_type	Yes	String	Specifies the resource type. The type can be the following: smn_topic: topic smn_sms: SMS smn_application: mobile push

## Request Parameters

**Table 5-200** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

**Status code: 200**

**Table 5-201** Response body parameters

Parameter	Type	Description
tags	Array of <a href="#">ResourceTags</a> objects	Specifies resource tags.

**Table 5-202** ResourceTags

Parameter	Type	Description
key	String	Specifies the tag key. <ul style="list-style-type: none"><li>• A key can contain a maximum of 127 Unicode characters.</li><li>• key must be specified.</li></ul>
values	Array of strings	Specifies the tag values. <ul style="list-style-type: none"><li>• Each tag contains a maximum of 10 values.</li><li>• Values of the same tag must be unique.</li><li>• It can contain a maximum of 255 Unicode characters.</li><li>• If this parameter is left blank, any value can be used.</li><li>• All values of a tag key are in the OR relationship.</li></ul>

**Status code: 400**

**Table 5-203** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-204** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-205** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-206** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Querying project tags

```
GET https://{SMN_Endpoint}/v2/{project_id}/{resource_type}/tags
null
```

## Example Responses

**Status code: 200**

OK

```
{
  "tags": [ {
    "key": "key1",
    "values": [ "value1", "value2" ]
  }, {
    "key": "key2",
    "values": [ "value1", "value2" ]
  } ]
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.5.6 Deleting a Resource Tag

### Function

This API is used to delete resource tags. The API is idempotent. When deleting a tag, the system does not check its character set. The tag key cannot be left blank or be an empty string. If the key of the tag to be deleted does not exist, 404 will be returned.

### Calling Method

For details, see [Calling APIs](#).

### URI

```
DELETE /v2/{project_id}/{resource_type}/{resource_id}/tags/{key}
```

**Table 5-207** Path Parameters

Parameter	Mandatory	Type	Description
project_id	Yes	String	Specifies the project ID. For details about how to obtain the project ID, see <a href="#">Obtaining the Project ID</a> .
resource_type	Yes	String	Specifies the resource type. Possible values are: smn_topic: topic smn_sms: SMS smn_application: mobile push
resource_id	Yes	String	Specifies the resource ID. To obtain the value of resource_id, perform the following steps: When resource_type is set to smn_topic: Add X-SMN-RESOURCEID-TYPE=name in the request header and set the resource ID to the topic name. Call the GetResourceInstances API to obtain the resource ID. If you set resource_type to smn_sms, the resource ID is the signature ID, which can be obtained on the console.
key	Yes	String	Specifies the key value of the tag to be deleted.

## Request Parameters

**Table 5-208** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

**Status code: 400**



**Table 5-209** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-210** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-211** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-212** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

Deleting a resource tag

```
DELETE https://{SMN_Endpoint}/v2/{project_id}/{resource_type}/{resource_id}/tags/{key}
null
```

## Example Responses

None

## Status Codes

Status Code	Description
204	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

# 5.6 Version Querying

## 5.6.1 Querying All SMN API Versions

### Function

This API is used to list all SMN API versions.

### Calling Method

For details, see [Calling APIs](#).

### URI

GET /

## Request Parameters

**Table 5-213** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

## Response Parameters

**Status code: 200****Table 5-214** Response body parameters

Parameter	Type	Description
versions	Array of <a href="#">VersionItem</a> objects	Specifies the list of all versions.

**Table 5-215** VersionItem

Parameter	Type	Description
id	String	Specifies the version ID, for example, v2.
min_version	String	Specifies the microversion. If the API supports microversions, the system returns the supported minimum microversion. If no, the system returns an empty value.
status	String	Specifies the version status. CURRENT: The version is the primary version. SUPPORTED: The version is an earlier version, but it is still supported. DEPRECATED: The version is a deprecated version, which may be deleted later.
updated	String	Specifies the version release time, which must be a UTC time. For example, the release time of v2 is 2014-06-28T12:20:21Z.

Parameter	Type	Description
version	String	Specifies the microversion. If the API supports microversions, the system returns the supported minimum microversion. If no, the system returns an empty value.
links	Array of <a href="#">LinkItem</a> objects	Specifies the API URL.

**Table 5-216** LinkItem

Parameter	Type	Description
href	String	Specifies the corresponding shortcut link.
rel	String	Specifies the shortcut link marker name.

**Status code: 400****Table 5-217** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-218** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404**

**Table 5-219** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500**

**Table 5-220** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

## Example Requests

```
GET https://{SMN_Endpoint}/
null
```

## Example Responses

**Status code: 200**

OK

```
{
  "versions" : {
    "id" : "v2",
    "links" : [ {
      "href" : "https://127.0.0.1/v2",
      "rel" : "self"
    } ],
    "min_version" : "",
    "status" : "CURRENT",
    "updated" : "2018-09-19T00:00:00Z",
    "version" : ""
  }
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request

Status Code	Description
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

## 5.6.2 Querying the SMN API v2 Version

### Function

This API is used to query the version of SMN API v2.

### Calling Method

For details, see [Calling APIs](#).

### URI

GET /v2

### Request Parameters

**Table 5-221** Request header parameters

Parameter	Mandatory	Type	Description
X-Auth-Token	Yes	String	Specifies a user token. It can be obtained by calling an IAM API. The value of X-Subject-Token in the response header is the user token.

### Response Parameters

Status code: 200

**Table 5-222** Response body parameters

Parameter	Type	Description
version	<a href="#">VersionItem</a> object	Specifies the list of all v2 versions.

**Table 5-223** VersionItem

Parameter	Type	Description
id	String	Specifies the version ID, for example, v2.
min_version	String	Specifies the microversion. If the API supports microversions, the system returns the supported minimum microversion. If no, the system returns an empty value.
status	String	Specifies the version status. CURRENT: The version is the primary version. SUPPORTED: The version is an earlier version, but it is still supported. DEPRECATED: The version is a deprecated version, which may be deleted later.
updated	String	Specifies the version release time, which must be a UTC time. For example, the release time of v2 is 2014-06-28T12:20:21Z.
version	String	Specifies the microversion. If the API supports microversions, the system returns the supported minimum microversion. If no, the system returns an empty value.
links	Array of <a href="#">LinkItem</a> objects	Specifies the API URL.

**Table 5-224** LinkItem

Parameter	Type	Description
href	String	Specifies the corresponding shortcut link.
rel	String	Specifies the shortcut link marker name.

**Status code: 400**

**Table 5-225** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 403****Table 5-226** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 404****Table 5-227** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.

**Status code: 500****Table 5-228** Response body parameters

Parameter	Type	Description
request_id	String	Specifies the request ID, which is unique.
code	String	Specifies the error code.
message	String	Describes the error message.



## Example Requests

```
GET https://{SMN_Endpoint}/v2
null
```

## Example Responses

**Status code: 200**

OK

```
{
  "version" : {
    "id" : "v2",
    "links" : [ {
      "href" : "https://127.0.0.1/v2",
      "rel" : "self"
    } ],
    "min_version" : "",
    "status" : "CURRENT",
    "updated" : "2018-09-19T00:00:00Z",
    "version" : ""
  }
}
```

## Status Codes

Status Code	Description
200	OK
400	Bad Request
403	Unauthorized
404	Not Found
500	Internal Server Error

## Error Codes

See [Error Codes](#).

# 6 Public Parameters

## 6.1 General Request Return Code

### 6.1.1 Exception Response

- Parameter description

Parameter	Type	Description
request_id	String	Request ID
code	String	For details, see <a href="#">Error Codes</a> .
message	String	For details, see <a href="#">Error Codes</a> .

- Example

```
{
  "request_id": "aad0860d089c482b943971f802a6718e",
  "code": "SMN.0006",
  "message": "Topic not found."
}
```

### 6.1.2 Returned Value

- Normal

Returned Value	Description
200	The task is submitted successfully.
201	Resource creation succeeds.

- Abnormal

Returned Value	Description
400 Bad Request	Incorrect request parameters.
401 Unauthorized	Authentication failed.
403 Forbidden	No permission to access the requested resource.
404 Not Found	The requested resource does not exist.
500 Internal Server Error	The request fails because the server is abnormal.
501 Not Implemented	The request fails because the server does not support the requested function.
502 Bad Gateway	The request fails because the returned response is invalid.
503 Service Unavailable	The request fails because the system is abnormal.
504 Gateway Timeout	Gateway times out.

## 6.2 Error Codes

Status Code	Error Codes	Error Message	Description	Solution
200	SMN.0025	Template already exists.	The template already exists.	You cannot create the same template twice.
201	SMN.0121	An application with the same name but different properties already exists.	An application with the same name but different attributes already exists.	Enter a different application name.
201	SMN.0190	This endpoint already exists.	The endpoint already exists.	Enter another endpoint.
400	SMN.0002	Parameter: Name is invalid.	Invalid topic name.	Enter a valid topic name.

Status Code	Error Codes	Error Message	Description	Solution
400	SMN.0003	Parameter: DisplayName is invalid.	Invalid display name.	Enter a valid display name for the topic.
400	SMN.0005	Parameter: TopicUrn is invalid.	Invalid topic URN.	Enter a valid topic_urn value.
400	SMN.0011	Parameter: Protocol is invalid.	Invalid protocol.	Specify a correct protocol.
400	SMN.0012	Parameter: Endpoint is invalid.	Invalid endpoint.	Specify a valid endpoint.
400	SMN.0014	Parameter: SubscriptionUrn is invalid.	Invalid subscription URN.	Enter a valid subscription-urn value.
400	SMN.0015	Parameter: Offset or limit is invalid.	Invalid offset or limit value.	Enter valid offset and limit values.
400	SMN.0017	Parameter: Remark is invalid.	Invalid remark value.	Enter a valid remark value.
400	SMN.0019	Producer Exceptions.	Generator exception.	Contact technical support.
400	SMN.0021	MessageStructure is invalid.	Incorrect message structure.	Enter a valid message_structure value.
400	SMN.0024	Parameter: content is invalid.	Invalid content.	Enter a valid content value.
400	SMN.00290	SubscriberUrn is unavailable.	SubscriberUrn is unavailable.	Check whether the value of SubscriberUrn is correct.
400	SMN.0031	Parameter: template_id is invalid.	Invalid template ID.	Enter a valid template_id value.
400	SMN.0032	Parameter: message_template_name is invalid.	Invalid template name.	Enter a valid message_template_name value.

Status Code	Error Codes	Error Message	Description	Solution
400	SMN.0033	Parameter: push_policy is invalid.	Invalid push_policy value.	Enter a valid push_policy value.
400	SMN.0034	Parameter: subscription_auth_policy is invalid.	Invalid subscription_auth_policy value.	Enter a valid subscription_auth_policy value.
400	SMN.0035	Parameter: validation_policy is invalid.	Invalid validation_policy value.	Enter a valid validation_policy value.
400	SMN.0036	Parameter: xdomain_type is invalid.	Invalid xdomain_type value.	Enter a valid xdomain_type value.
400	SMN.0038	Parameter: tag is invalid.	Invalid tag value.	Enter a valid tag value.
400	SMN.0042	Parameter: Message_template_name is invalid.	Invalid template name.	Enter a valid message_template_name value.
400	SMN.0043	Parameter: subscription is invalid.	Invalid subscription.	Enter a valid subscription.
400	SMN.0044	Exceeded template limit.	Templates exceeded the maximum number allowed.	Each user can create no more than 100 message templates.
400	SMN.0046	Parameter: Attribute name is invalid.	Invalid attribute name.	Enter a valid attribute_name value.
400	SMN.0048	Parameter: Access policy is invalid.	Invalid access policy.	Enter a valid access_policy value.
400	SMN.0049	Parameter: Access policy version is invalid.	Invalid access policy version.	Enter a valid version of the access policy.
400	SMN.0050	Parameter: Access policy ID is invalid.	Invalid access policy ID.	Enter a valid access_policy id value.

Status Code	Error Codes	Error Message	Description	Solution
400	SMN.0051	Parameter: Access policy statement is invalid.	Invalid value for access_policy statement.	Enter a valid access_policy statement value.
400	SMN.0052	Parameter: Access policy statement ID is invalid.	Invalid value for access_policy statement id.	Enter a valid access_policy statement id value.
400	SMN.0053	Parameter: Access policy statement resource is invalid.	Invalid value for access_policy statement resource.	Enter a valid access_policy statement resource value.
400	SMN.0054	Parameter: Access policy statement effect is invalid.	Invalid value for access_policy statement effect.	Enter a valid access_policy statement effect value.
400	SMN.0055	Parameter: Access policy statement action is invalid.	Invalid value for access_policy statement action.	Enter a valid access_policy statement action value.
400	SMN.0056	Parameter: Access policy statement principle is invalid.	Invalid value for access_policy statement principle.	Enter a valid access_policy statement principle value.
400	SMN.0058	Parameter: Access policy statement condition is invalid.	Invalid value for access_policy statement condition.	Enter a valid access_policy statement condition value.
400	SMN.0059	Parameter: job_id is invalid.	Invalid job_id value.	Contact technical support.
400	SMN.0061	Parameter: Service name is invalid.	Invalid Service name value.	Contact technical support.
400	SMN.0062	Parameter: Show name is invalid.	Invalid Show name value.	Contact technical support.

Status Code	Error Codes	Error Message	Description	Solution
400	SMN.0066	Parameter: System parameter name is invalid.	Invalid System parameter name value.	Contact technical support.
400	SMN.0067	Parameter: System parameter value is invalid.	Invalid value for System parameter value.	Contact technical support.
400	SMN.0072	Parameter: Service is invalid.	Invalid service value.	Enter a valid service value.
400	SMN.0073	Parameter: Invalid action.	Invalid action value.	Enter a valid action value.
400	SMN.0074	Failed to add permission.	Failed to add permissions.	Contact technical support.
400	SMN.0077	Parameter: Status is invalid.	Invalid status value.	Enter a valid status value.
400	SMN.0080	The signId parameter is invalid.	Invalid sign-id value.	Enter a valid sign_id value.
400	SMN.0081	The signName parameter is invalid.	Invalid sign-name value.	Enter a valid sign_name value. It is a string of 2 to 8 characters containing only letters and digits.
400	SMN.0082	The length of the remark parameter value has reached the maximum allowed.	Remark too long	Enter a valid remark value that contains no more than 1500 bytes.
400	SMN.0087	The SMS message signature has not been approved.	SMS message signature not approved.	Enter an approved SMS message signature.

Status Code	Error Codes	Error Message	Description	Solution
400	SMN.0090	Invalid domain ID.	Invalid domain ID.	Enter a valid domain_id value.
400	SMN.0092	The kafka_id parameter is invalid.	Invalid Kafka ID.	Contact technical support.
400	SMN.0093	The address_list parameter is invalid.	Invalid address list.	Contact technical support.
400	SMN.0094	The type of queue parameter is invalid.	Invalid queue parameter type.	Contact technical support.
400	SMN.0095	The count of queue parameter is invalid.	Invalid queue parameter statistics.	Contact technical support.
400	SMN.0097	The names parameter is invalid.	Invalid names value.	Contact technical support.
400	SMN.0100	The eventType parameter is invalid.	Invalid event type.	Enter a valid event_type value.
400	SMN.0102	Parameter: message_id is invalid.	Invalid message ID.	Enter a valid message_id value.
400	SMN.0103	The start_time parameter value is invalid.	Invalid start time.	Enter a valid start_time value.
400	SMN.0104	The end_time parameter value is invalid.	Invalid end time.	Enter a valid end_time value.
400	SMN.0108	Parameter: Type is invalid.	Invalid type.	Enter a valid type.
400	SMN.0110	Parameter: Start date is invalid.	Invalid start date.	Enter a valid start_date value.



Status Code	Error Codes	Error Message	Description	Solution
400	SMN.0112	Parameter: End date is invalid.	Invalid end date.	Enter a valid end_date value.
400	SMN.0113	The start time and end time must be within the past 3 months.	The start time and end time must be within the past 3 months.	The start time and end time must be within the past 3 months.
400	SMN.0114	The end time must be later than the start time.	The end time must be later than the start time.	The end time must be later than the start time.
400	SMN.0115	Parameter: Application name is invalid.	Invalid application name.	Enter a valid application name.
400	SMN.0118	Wrong Certificate.	Certificate error.	Specify a valid certificate.
400	SMN.0123	Parameter: ApplicationUr n is invalid.	Invalid application URN.	Enter a valid application_urn value.
400	SMN.0124	Parameter: application attribute is invalid.	Invalid application_at tributes value.	Specify a valid application_attr ibutes value.
400	SMN.0126	ContentType is wrong.	Incorrect content type.	Contact technical support.
400	SMN.0129	Certificate type is wrong.	Incorrect certificate type.	Contact technical support.
400	SMN.0132	The value of the User_data parameter is invalid.	Invalid user_data value.	Enter a valid user_data value.
400	SMN.0133	The device token already exists.	Device token already exists.	You cannot create the same device token twice.
400	SMN.0134	The endpoint URN is invalid.	Invalid endpoint URN.	Enter a valid endpoint_urn value.

Status Code	Error Codes	Error Message	Description	Solution
400	SMN.0135	The endpoint does not exist.	The endpoint does not exist.	Specify a valid endpoint.
400	SMN.0136	The value of the enabled parameter is invalid.	Invalid enabled value.	Enter a valid enabled value.
400	SMN.0137	The application URN is invalid.	Invalid application URN.	Enter a valid application_urn value.
400	SMN.0140	The topic URN configured for the message sending failure event is invalid.	The topic URN configured for the message sending failure event is invalid.	Enter a valid topic_urn value.
400	SMN.0141	The topic configured for the message sending failure event does not exist.	The topic URN configured for the message sending failure event does not exist.	Enter a valid topic_urn value.
400	SMN.0142	The topic URN configured for the message sending success event is invalid.	Invalid topic URN.	Enter a valid topic_urn value.
400	SMN.0143	The topic configured for the message sending success event does not exist.	The topic URN configured for the message sending success event does not exist.	Enter a valid topic_urn value.

Status Code	Error Codes	Error Message	Description	Solution
400	SMN.0144	The topic URN configured for the response message event is invalid.	The topic URN configured for the response message event is invalid.	Enter a valid topic_urn value.
400	SMN.0145	The topic configured for the response message event does not exist.	The topic URN configured for the response message event does not exist.	Enter a valid topic_urn value.
400	SMN.0148	Parameter: user_id is invalid.	Invalid user ID.	Enter a valid user_id value.
400	SMN.0150	Complete real-name registration using your company's certificate.	Use your certificate to complete real-name registration.	Contact technical support.
400	SMN.0151	The message signature type cannot be promotional.	The signature cannot be a promotional message signature.	Specify a transactional SMS message signature.
400	SMN.0152	The number allocated to the SMS template has reached the maximum allowed.	SMS templates reached the maximum allowed number.	You can create no more than 100 SMS templates.
400	SMN.0155	Parameter: SmsTemplate Type is invalid.	Invalid SMS template type.	Enter a valid sms_template_type value.
400	SMN.0156	Parameter: SmsTemplate Name is invalid.	Invalid SMS template name.	Enter a valid sms_template_name value.

Status Code	Error Codes	Error Message	Description	Solution
400	SMN.0157	Parameter: SmsTemplate Content is invalid.	Invalid SMS template content.	Enter a valid sms_template_content value.
400	SMN.0159	The number of endpoints has reached the maximum allowed.	Endpoints reached the quota.	Enter no more than 1,000 phone numbers.
400	SMN.0160	Invalid endpoint.	Invalid endpoint.	Specify a valid endpoint.
400	SMN.0161	Invalid SMS template ID.	Invalid SMS template ID.	Enter a valid sms_template_id value.
400	SMN.0188	Invalid SMS template type.	Invalid SMS template type.	The template must be a promotional template.
400	SMN.0189	Failed to obtain the certificate required for reviewing the SMS message template function.	Failed to obtain the certificate required for viewing the SMS template.	Contact technical support.
400	SMN.0191	Parameter: Invalid enterprise name.	Invalid enterprise name.	Contact technical support.
400	SMN.0192	Parameter: Invalid enterprise certificate ID.	Invalid enterprise certificate.	Contact technical support.
400	SMN.0204	Promotional SMS messages must contain the way to unsubscribe in the end, for example, by replying "TD", or "T".	Promotional SMS messages must explain how recipients can unsubscribe, for example, by replying "unsubscribe".	Promotional SMS messages must explain how recipients can unsubscribe, for example, by replying "unsubscribe".

Status Code	Error Codes	Error Message	Description	Solution
400	SMN.0215	The SMS message signature ID does not match the signature name in the SMS message template content.	The SMS message signature ID does not match the signature name in the SMS template.	Specify a signature ID that matches the signature name in the template content.
400	SMN.0216	The template content does not include any valid SMS message signature.	No valid SMS message signature in the template content.	Enter a valid signature in the template content.
400	SMN.0217	The template content does not include any SMS message signature.	No SMS message signature in the template content.	The SMS template must contain an approved and available signature, for example, [xx mall].
400	SMN.0224	The SMS message template is invalid because the associated signature has been deleted.	The SMS template has expired due to the deletion of the associated signature.	Specify a valid sms_template_id value.
400	SMN.0227	The message contains sensitive words.	Sensitive words contained in the message content.	There were sensitive words in the message content. Modify the message content.
400	SMN.0230	Parameter: Invalid title.	Invalid title.	Enter a valid title.

Status Code	Error Codes	Error Message	Description	Solution
400	SMN.0261	Check whether your account balance is sufficient and top up your account if necessary.	Check the account balance and top up your account if necessary.	Check the account balance and top up your account if necessary.
403	SMN.0001	No permission to request resources.	No permissions for the requested resource.	Request the required permissions.
403	SMN.0004	Exceeded topic limit.	Topics exceeded the maximum number allowed.	You can create a maximum of 3,000 topics.
403	SMN.0007	Exceeded subscription limit.	Subscriptions exceeded the maximum allowed number.	You can add a maximum of 10,000 subscriptions to a topic.
403	SMN.0008	Parameter: Subject is invalid.	Invalid subject value.	Enter a valid subject value.
403	SMN.0009	Parameter: Message is invalid.	Invalid message.	Enter a valid message value.
403	SMN.0022	Parameter: token is invalid.	Invalid token value.	Specify a valid token.
403	SMN.00308	Policy doesn't allow {} to be performed.	Policy doesn't allow {} to be performed.	Check the SMN permission.
403	SMN.0047	Parameter: Value exceeds the maximum length.	value exceeds the maximum length.	Enter a valid value.

Status Code	Error Codes	Error Message	Description	Solution
403	SMN.0057	The number of SMS messages exceeds the limit.	SMS messages exceeded the maximum number allowed.	You can send no more than 60 SMS messages to a phone number within one hour and no more than 200 within 12 hours.
403	SMN.0065	The number of email messages exceeds the limit.	Email messages exceeded the maximum number allowed.	Contact technical support.
403	SMN.0069	Not authorized to subscribe internal endpoints.	Subscription endpoint not authorized.	Enter a correct HTTP/HTTPS endpoint.
403	SMN.0070	No permission to request resources. The role is op_restricted. Contact customer service.	Insufficient permissions to operate the current resource.	Check the account balance and top up your account if necessary. If the fault persists, contact customer service.
403	SMN.0071	No permission to request resources. Role is op_suspended .	Insufficient permissions to request the current resource. Your role is suspended.	Check whether your account has been frozen.
403	SMN.0075	Parameter: tags are too many.	Tags exceeded the maximum allowed number.	Enter no more than 90 non-repeated tags in a message template.

Status Code	Error Codes	Error Message	Description	Solution
403	SMN.0078	The maximum number of subscriptions has been reached.	Subscriptions reached the maximum allowed number.	Create a topic.
403	SMN.0083	Finish real-name authentication before continuing.	Complete real-name authentication.	Contact technical support.
403	SMN.0086	The number allocated to the SMS message signature has reached the maximum allowed.	SMS message signatures have reached quota.	You can create no more than 10 SMS message signatures.
403	SMN.0099	The SMN service has not been authorized to send messages to this queue.	SMN is not authorized to send messages to this queue.	Grant permissions to SMN in the queue policy.
403	SMN.0116	Platform do not support yet.	Unsupported platform.	Enter a supported platform.
403	SMN.0117	Certificate type is not supported.	Unsupported certificate type.	Enter a supported certificate type.
403	SMN.0119	PlatformPrinciple must be at most 8192 bytes long in UTF-8 encoding.	UTF-8 encoded platform_principle must not exceed 8192 bytes.	Enter a valid, UTF-8 encoded value for platform_principle that does not exceed 8192 bytes.



Status Code	Error Codes	Error Message	Description	Solution
403	SMN.0120	PlatformCredential must be at most 8192 bytes long in UTF-8 encoding.	UTF-8 encoded platform_credential must not exceed 8192 bytes.	Enter a valid, UTF-8 encoded value for platform_credential that does not exceed 8192 bytes.
403	SMN.0127	File is too large.	Excessive file size.	Contact technical support.
403	SMN.0128	Password is empty.	Password not specified.	Contact technical support.
403	SMN.0131	The value of the Token parameter is invalid.	Invalid token.	Specify a valid token.
403	SMN.0147	Only enterprise users who use the certificate images for authentication can create message signatures.	Only enterprise users who use certificates for identity authentication can create message signatures.	Contact technical support.
403	SMN.0153	Only enterprise users can create SMS message Template.	Only enterprise users can create SMS templates.	Complete enterprise authentication.
403	SMN.0154	Only enterprise users who use the certificate images for authentication can create sms message templates.	Only enterprise users who use certificates for identity authentication can create SMS templates.	Contact technical support.
403	SMN.0165	Parameter: tenant_token is invalid.	Invalid tenant token.	Specify a valid tenant_token value.

Status Code	Error Codes	Error Message	Description	Solution
403	SMN.0195	Complete enterprise real-name authentication first.	Complete real-name authentication.	Complete real-name authentication.
403	SMN.0228	Do not have permission to use this API. Contact customer service to apply for permission.	Insufficient permissions to use this API.	Contact technical support to apply for the permissions required to use this API.
404	SMN.0006	Topic not found.	Topic not found.	The topic does not exist. Create a topic.
404	SMN.0013	Subscription resource not found.	No subscription endpoint found.	Specify a valid subscription endpoint.
404	SMN.0027	Template not found.	Specified template not found.	Using an existing template.
404	SMN.0045	Attribute not found.	Attribute not found.	Specify a valid attribute.
404	SMN.0060	Job not found.	Failed to query the job.	Contact technical support.
404	SMN.0063	Cloud service not found.	Cloud service not found.	Contact technical support.
404	SMN.0068	System parameter not found.	System parameter not found.	Contact technical support.
404	SMN.0076	Default message template not found.	The message template using the default protocol does not exist.	Create a message template using the default protocol.

Status Code	Error Codes	Error Message	Description	Solution
404	SMN.0084	The SMS message signature could not be found.	SMS message signature not found.	Enter an approved SMS message signature.
404	SMN.0091	Default system message template not found.	The message template using the default protocol does not exist.	Create a system template using the default protocol.
404	SMN.0096	Kafka not found.	Failed to find Kafka.	Contact technical support.
404	SMN.0098	This queue does not exist.	The queue does not exist.	Specify a valid DMS queue.
404	SMN.0101	The graph does not exist in the functiongraph service.	The function does not exist in FunctionGraph.	Enter a valid FunctionGraph endpoint.
404	SMN.0109	Start date is not found.	start_date not found.	start_date must be specified.
404	SMN.0111	End date is not found.	end_date not found.	end_date must be specified.
404	SMN.0122	Application not found.	Application not found.	Enter a different application name.
404	SMN.0125	Endpoint does not exist.	The endpoint does not exist.	Specify a valid application endpoint.
404	SMN.0130	The application does not exist.	The cloud platform does not exist.	Enter a valid application_urn value.
404	SMN.0162	SMS template not found.	The SMS template does not exist.	Specify a valid SMS template.
404	SMN.0167	Phone number does not exist.	The mobile number does not exist.	Enter a valid phone number.

Status Code	Error Codes	Error Message	Description	Solution
404	SMN.0168	Email Address does not exist.	The e-mail address does not exist.	Enter a valid email address.
429	SMN.00359	Topic publishing exceeds the flow control limit, please try again later.	The number of messages published by a topic exceeds the traffic control limit.	Try again later.
429	SMN.00362	Topic publishing exceeds the global flow control limit, please try again later.	The number of messages published by a topic exceeds the global traffic control limit.	Try again later.
500	SMN.0016	Database Exceptions.	Database exception.	Contact technical support.
500	SMN.0018	Service internal error.	Internal service error.	Contact technical support.
500	SMN.0089	An error occurred in the BSS system. Try again later.	BSS error. Try again later.	Contact technical support.
500	SMN.0158	Failed to upload the file.	Failed to upload the file.	Contact technical support.

## 6.3 Obtaining a Project ID

A project ID is required for some URLs when an API is called. Therefore, you need to obtain a project ID in advance. The steps are as follows:

1. Obtain the token.

For details, see [Token Authentication](#).

2. Obtain a project ID.

The API for obtaining the project ID is **GET <https://iam.eu-west-0.myhuaweicloud.com/v3/projects>**.

Add **X-Auth-Token** to the request header and set its value to the token obtained in the preceding step.

The following is an example response. The value of **id** is the project ID to be obtained.

```
{
  "links": {},
  "projects": [
    {
      "is_domain": ,
      "description": "",
      "links": {},
      "enabled": true,
      "id": "", // Project ID
      "parent_id": "",
      "domain_id": "",
      "name": ""
    },
    ...
  ]
}
```

# A Appendix

---

## A.1 Topic Attribute List

Attribute Name	Function	Default Value
access_policy	Configures topic access policy, which is used to limit the access permission of other users.	Empty string
introduction	Configures the topic introduction, which is displayed in the email or SMS confirmation messages.	Empty string

# B Change History

---

Released On	Description
2022-07-08	This issue is the first official release.