Tag Management Service

FAQ

Issue 01

Date 2024-07-19





Copyright © Huawei Technologies Co., Ltd. 2024. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd. All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Security Declaration

Vulnerability

Huawei's regulations on product vulnerability management are subject to the *Vul. Response Process.* For details about this process, visit the following web page:

https://www.huawei.com/en/psirt/vul-response-process

For vulnerability information, enterprise customers can visit the following web page:

https://securitybulletin.huawei.com/enterprise/en/security-advisory

Contents

1 What Is the Difference Between Adding a Resource Tag and Creating a Key?	2
2 How Do I Start the ActiveX Plug-in When Using Internet Explorer 9 to Import Files?	
3 What Can I Do If I Failed to Import Tags?	
4 How Can I Rectify an Invalid Tag?	4

What Is the Difference Between Adding a Resource Tag and Creating a Key?

When you add a resource tag, if you set only the tag key, the value of the tag is empty value by default, and the tag will be associated with a resource after it is added. You can add tags in batches.

If you create a key, a column with the key as the header will be added to the resource tag list, and the value is set to Not Tagged by default. To attach tags with the key created to resources, add values for the key in the rows that contain the resources. If you do not add any values for the key, the key will not be associated with any resources.

The following picture shows a tag of a VPC with the key set to Owner and the value left empty. It also shows a created key, Usage.

Figure 1-1 Example



How Do I Start the ActiveX Plug-in When Using Internet Explorer 9 to Import Files?

Description

If you use Internet Explorer 9 to import files, you need to start the ActiveX plug-in.

Procedure

- 1. Click in the upper right corner of the browser.
- 2. Select Internet Options.
- 3. Click the **Security** tab in the displayed dialog box.
- 4. Click Internet.
- (Optional) Click **Default level**.
 If the security level is set to **Cutsom level**, reset it to **Default level**.
- 6. Move the security level slider to set the security level to **Medium**.
- 7. Click Apply.
- 8. Click Custom Level.
- 9. Set Initialize and script ActiveX controls not marked as safe for scripting to Prompt.
- 10. Click **OK**.

3 What Can I Do If I Failed to Import Tags?

You may have edited the tag template with Excel.

Tag import only support CSV files using UTF-8 encoding.

If you edit a CSV file with Excel for tag import, the tags will be garbled. To edit a CSV file, open it with notepad.

4 How Can I Rectify an Invalid Tag?

If an invalid tag appears, \bigcirc is displayed in the resource tag list, then you need to manually restore the invalid tag.

An invalid tag can be restored in either of the following situations:

- If the tag key is invalid, delete the tag and add a new tag that meets the requirements.
- If only the tag value is invalid, modify the tag value.

Procedure

- 1. Log in to the management console.
- 2. Under Management & Governance, select Tag Management Service.
- 3. Set the resource search criteria and click **Search**.
- 4. Click **Restore** in the resource tag list.
- 5. In the **Edit Tag** area, restore the invalid tag.
 - Invalid tag key
 - i. Locate the row containing the invalid tag key and click **Delete**.
 - ii. In the **Add Tag** area, enter a tag key and a tag value.
 - Invalid tag value

In the **Edit Tag** area, specify new values for tags.

6. Click OK.

The invalid tag has been restored.